

Lab 2 - Nonlinear Regression

Submitted by: Priyanshu Rawat

```
%% Given function
syms a x y
f(x) = log(a*x);
fprintf('Given function:\nf(x) = %s', f(x))
```

Given function:
 $f(x) = \log(a \cdot x)$

```
%% Error function
E = (y - log(a*x))^2;
fprintf('Error function:\nE = %s', E)
```

Error function:
 $E = (y - \log(a \cdot x))^2$

```
%% Taking derivative of the square of the error function w.r.t. `a`
dE = diff(E, a);
fprintf('Derivative of the error function:\ndE^2/da = %s', dE)
```

Derivative of the residual function:
 $dE^2/da = -(2 \cdot (y - \log(a \cdot x)))/a$

```
%% Using root finding approach to find `a`
fa = dE;
fprintf('Function to perform root finding:\nf(a) = %s', fa)
```

Function to perform root finding:
 $f(a) = -(2 \cdot (y - \log(a \cdot x)))/a$

```
%% Taking derivative of f(a)
dfa = diff(fa, a);
fprintf('Derivative of f(a):\ndf(a)/da = %s', dfa)
```

Derivative of f(a):
 $df(a)/da = 2/a^2 + (2 \cdot (y - \log(a \cdot x)))/a^2$

Nonlinear Regression fit: log-data-A

```
%% Loading log-data-A
data_A = importdata('log-data-A.txt');
Xa = data_A(:,1);
Ya = data_A(:,2);
```

Guess-1: Taking initial value of `a` = 1

```
%% Initial guess
a0 = 1;

%% Performing iterations
iterations = 0;
for n = [1:5000]
```

```

sum_fa = 0;
sum_dfa = 0;
for i = 1:length(Xa)
    sum_fa = sum_fa + (-(2*(Ya(i) - log(a0*Xa(i))))/a0);
    sum_dfa = sum_dfa + (2/a0^2 + (2*(Ya(i) - log(a0*Xa(i))))/a0^2);
end
an = a0 - (sum_fa/sum_dfa);
iterations = iterations+1;
if abs(an-a0) < 0.000001
    fprintf('Final value of `a` after convergence: %d', an);
    fprintf('Total number of iterations until convergence: %d', iterations);
    break
end
a0 = an;
end

```

Final value of `a` after convergence: 6.711359e+00
 Total number of iterations until convergence: 9

Guess-2: Taking initial value of `a` = 2

```

%% Initial guess
a0 = 2;

%% Performing iterations
iterations = 0;
for n = [1:5000]
    sum_fa = 0;
    sum_dfa = 0;
    for i = 1:length(Xa)
        sum_fa = sum_fa + (-(2*(Ya(i) - log(a0*Xa(i))))/a0);
        sum_dfa = sum_dfa + (2/a0^2 + (2*(Ya(i) - log(a0*Xa(i))))/a0^2);
    end
    an = a0 - (sum_fa/sum_dfa);
    iterations = iterations+1;
    if abs(an-a0) < 0.000001
        fprintf('Final value of `a` after convergence: %d', an);
        fprintf('Total number of iterations until convergence: %d', iterations);
        break
    end
    a0 = an;
end
end

```

Final value of `a` after convergence: 6.711359e+00
 Total number of iterations until convergence: 8

Guess-3: Taking initial value of `a` = 5

```

%% Initial guess
a0 = 5;

%% Performing iterations
iterations = 0;
for n = [1:5000]
    sum_fa = 0;
    sum_dfa = 0;

```

```

for i = 1:1:length(Xa)
    sum_fa = sum_fa + (-(2*(Ya(i) - log(a0*Xa(i))))/a0);
    sum_dfa = sum_dfa + (2/a0^2 + (2*(Ya(i) - log(a0*Xa(i))))/a0^2);
end
an = a0 - (sum_fa/sum_dfa);
iterations = iterations+1;
if abs(an-a0) < 0.000001
    fprintf('Final value of `a` after convergence: %d', an);
    fprintf('Total number of iterations until convergence: %d', iterations);
    break
end
a0 = an;
end

```

Final value of `a` after convergence: 6.711359e+00
 Total number of iterations until convergence: 5

Guess-4: Taking initial value of `a` = 8.5

```

%% Initial guess
a0 = 8.5;

%% Performing iterations
iterations = 0;
for n = [1:5000]
    sum_fa = 0;
    sum_dfa = 0;
    for i = 1:1:length(Xa)
        sum_fa = sum_fa + (-(2*(Ya(i) - log(a0*Xa(i))))/a0);
        sum_dfa = sum_dfa + (2/a0^2 + (2*(Ya(i) - log(a0*Xa(i))))/a0^2);
    end
    an = a0 - (sum_fa/sum_dfa);
    iterations = iterations+1;
    if abs(an-a0) < 0.000001
        fprintf('Final value of `a` after convergence: %d', an);
        fprintf('Total number of iterations until convergence: %d', iterations);
        break
    end
    a0 = an;
end
end

```

Final value of `a` after convergence: 6.711359e+00
 Total number of iterations until convergence: 6


Plotting the model and the data points in log-data-A

```

% Plotting the data points and the curve
figure
scatter(Xa,Ya, 10, 'filled')
hold on
plot(Xa, log(an*Xa), LineWidth=1.5)
title('Data-A vs Estimated Curve')
legend('Data-A', 'Estiamted Curve', Location='southeast')
xlabel('x-axis')
ylabel('y-axis')

```

hold off



Calculating the error using the error function 'E = (y - log(a*x))^2`

```
e=0;
for i = 1:1:length(Xa)
    e = e + (Ya(i) - log(an*Xa(i)))^2;
end
fprintf('Error in the given model for data-A is: %f', e)
```

Error in the given model for data-A is: 4.929149

Nonlinear Regression fit: log-data-B

```
%% Loading log-data-B
data_B = importdata('log-data-B.txt');
Xb = data_B(:,1);
Yb = data_B(:,2);
```

Guess-1: Taking initial value of `a` = 0.5

```
%% Initial guess
a0 = 0.5;

%% Performing iterations
iterations = 0;
for n = [1:5000]
    sum_fa = 0;
```

```

sum_dfa = 0;
for i = 1:1:length(Xb)
    sum_fa = sum_fa + (-(2*(Yb(i) - log(a0*Xb(i))))/a0);
    sum_dfa = sum_dfa + (2/a0^2 + (2*(Yb(i) - log(a0*Xb(i))))/a0^2);
end
an = a0 - (sum_fa/sum_dfa);
iterations = iterations+1;
if abs(an-a0) < 0.000001
    fprintf('Final value of `a` after convergence: %d', an);
    fprintf('Total number of iterations until convergence: %d', iterations);
    break
end
a0 = an;
end

```

Final value of `a` after convergence: 1.899612e+01
Total number of iterations until convergence: 12

Guess-2: Taking initial value of `a` = 1.2

```

%% Initial guess
a0 = 1.2;

%% Performing iterations
iterations = 0;
for n = [1:5000]
    sum_fa = 0;
    sum_dfa = 0;
    for i = 1:1:length(Xb)
        sum_fa = sum_fa + (-(2*(Yb(i) - log(a0*Xb(i))))/a0);
        sum_dfa = sum_dfa + (2/a0^2 + (2*(Yb(i) - log(a0*Xb(i))))/a0^2);
    end
    an = a0 - (sum_fa/sum_dfa);
    iterations = iterations+1;
    if abs(an-a0) < 0.000001
        fprintf('Final value of `a` after convergence: %d', an);
        fprintf('Total number of iterations until convergence: %d', iterations);
        break
    end
    a0 = an;
end

```

Final value of `a` after convergence: 1.899612e+01
Total number of iterations until convergence: 11

Guess-3: Taking initial value of `a` = 2.3

```

%% Initial guess
a0 = 2.3;

%% Performing iterations
iterations = 0;
for n = [1:5000]
    sum_fa = 0;
    sum_dfa = 0;
    for i = 1:1:length(Xb)

```

```

        sum_fa = sum_fa + (-(2*(Yb(i) - log(a0*Xb(i))))/a0);
        sum_dfa = sum_dfa + (2/a0^2 + (2*(Yb(i) - log(a0*Xb(i))))/a0^2);
    end
    an = a0 - (sum_fa/sum_dfa);
    iterations = iterations+1;
    if abs(an-a0) < 0.000001
        fprintf('Final value of `a` after convergence: %d', an);
        fprintf('Total number of iterations until convergence: %d', iterations);
        break
    end
    a0 = an;
end

```

Final value of `a` after convergence: 1.899612e+01
 Total number of iterations until convergence: 10

Guess-4: Taking initial value of `a` = 4.5

```

%% Initial guess
a0 = 4.5;

%% Performing iterations
iterations = 0;
for n = [1:5000]
    sum_fa = 0;
    sum_dfa = 0;
    for i = 1:length(Xb)
        sum_fa = sum_fa + (-(2*(Yb(i) - log(a0*Xb(i))))/a0);
        sum_dfa = sum_dfa + (2/a0^2 + (2*(Yb(i) - log(a0*Xb(i))))/a0^2);
    end
    an = a0 - (sum_fa/sum_dfa);
    iterations = iterations+1;
    if abs(an-a0) < 0.000001
        fprintf('Final value of `a` after convergence: %d', an);
        fprintf('Total number of iterations until convergence: %d', iterations);
        break
    end
    a0 = an;
end

```


Final value of `a` after convergence: 1.899612e+01
 Total number of iterations until convergence: 8

Plotting the model and the data points in log-data-B

```

figure
scatter(Xb,Yb, 10, 'filled')
hold on
plot(Xb, log(an*Xb), LineWidth=1.5)
title('Data-B vs Estimated Curve')
legend('Data-B', 'Estiamted Curve', Location='southeast')
xlabel('x-axis')
ylabel('y-axis')
hold off

```



Calculating the error using the error function 'E = (y - log(a*x))^2`

```
e=0;
for i = 1:length(Xb)
    e = e + (Yb(i) - log(an*Xb(i)))^2;
end
fprintf('Error in the given model for data-B is: %f', e)
```

Error in the given model for data-B is: 4.286344

Nonlinear Regression fit: log-data-C

```
%% Loading log-data-C
data_C = importdata('log-data-C.txt');
Xc = data_C(:,1);
Yc = data_C(:,2);
```

Guess-1: Taking initial value of `a` = 1.2

```
%% Initial guess
a0 = 1.2;

%% Performing iterations
iterations = 0;
for n = [1:5000]
    sum_fa = 0;
    sum_dfa = 0;
```

```

for i = 1:1:length(Xc)
    sum_fa = sum_fa + (-(2*(Yc(i) - log(a0*Xc(i))))/a0);
    sum_dfa = sum_dfa + (2/a0^2 + (2*(Yc(i) - log(a0*Xc(i))))/a0^2);
end
an = a0 - (sum_fa/sum_dfa);
iterations = iterations+1;
if abs(an-a0) < 0.000001
    fprintf('Final value of `a` after convergence: %d', an);
    fprintf('Total number of iterations until convergence: %d', iterations);
    break
end
a0 = an;
end

% Checking if the estimated `a` is a valid number
if isinteger(an) == false
    fprintf('`a` is not a valid number, try a different guess!')
end

```

`a` is not a valid number, try a different guess!

Guess-2: Taking initial value of `a` = 0.8

```

%% Initial guess
a0 = 0.8;

%% Performing iterations
iterations = 0;
for n = [1:5000]
    sum_fa = 0;
    sum_dfa = 0;
    for i = 1:1:length(Xc)
        sum_fa = sum_fa + (-(2*(Yc(i) - log(a0*Xc(i))))/a0);
        sum_dfa = sum_dfa + (2/a0^2 + (2*(Yc(i) - log(a0*Xc(i))))/a0^2);
    end
    an = a0 - (sum_fa/sum_dfa);
    iterations = iterations+1;
    if abs(an-a0) < 0.000001
        fprintf('Final value of `a` after convergence: %d', an);
        fprintf('Total number of iterations until convergence: %d', iterations);
        break
    end
    a0 = an;
end

% Checking if the estimated `a` is a valid number
if isinteger(an) == false
    fprintf('`a` is not a valid number, try a different guess!')
end

```

`a` is not a valid number, try a different guess!

Guess-3: Taking initial value of `a` = 0.3

```

%% Initial guess
a0 = 0.3;

```



```

%% Performing iterations
iterations = 0;
for n = [1:5000]
    sum_fa = 0;
    sum_dfa = 0;
    for i = 1:1:length(Xc)
        sum_fa = sum_fa + (-(2*(Yc(i) - log(a0*Xc(i))))/a0);
        sum_dfa = sum_dfa + (2/a0^2 + (2*(Yc(i) - log(a0*Xc(i))))/a0^2);
    end
    an = a0 - (sum_fa/sum_dfa);
    iterations = iterations+1;
    if abs(an-a0) < 0.000001
        fprintf('Final value of `a` after convergence: %d', an);
        fprintf('Total number of iterations until convergence: %d', iterations);
        break
    end
    a0 = an;
end

```

Final value of `a` after convergence: 2.899978e-01
 Total number of iterations until convergence: 4

Guess-4: Taking initial value of `a` = 0.15

```

%% Initial guess
a0 = 0.15;

%% Performing iterations
iterations = 0;
for n = [1:5000]
    sum_fa = 0;
    sum_dfa = 0;
    for i = 1:1:length(Xc)
        sum_fa = sum_fa + (-(2*(Yc(i) - log(a0*Xc(i))))/a0);
        sum_dfa = sum_dfa + (2/a0^2 + (2*(Yc(i) - log(a0*Xc(i))))/a0^2);
    end
    an = a0 - (sum_fa/sum_dfa);
    iterations = iterations+1;
    if abs(an-a0) < 0.000001
        fprintf('Final value of `a` after convergence: %d', an);
        fprintf('Total number of iterations until convergence: %d', iterations);
        break
    end
    a0 = an;
end

```

Final value of `a` after convergence: 2.899978e-01
 Total number of iterations until convergence: 6

Plotting the model and the data points in log-data-C

```


figure
scatter(Xc,Yc, 10, 'filled')
hold on
plot(Xc, log(an*Xc), LineWidth=1.5)

```

```

title('Data-C vs Estimated Curve')
legend('Data-C', 'Estiamted Curve', Location='southeast')
xlabel('x-axis')
ylabel('y-axis')
hold off

```



Calculating the error using the error function 'E = (y - log(a*x))^2`

```

e=0;
for i = 1:1:length(Xc)
    e = e + (Yc(i) - log(an*Xc(i)))^2;
end
fprintf('Error in the given model for data-C is: %f', e)

```

Error in the given model for data-C is: 3.814397