
Architectural Design

Objectives

- To introduce architectural design and to discuss its importance
- To explain the architectural design decisions that have to be made
- To introduce three complementary architectural styles covering organisation, decomposition and control
- To discuss reference architectures are used to communicate and compare architectures

Topics covered

- Architectural design decisions
- System organisation
- Decomposition styles
- Control styles
- Reference architectures

Software architecture

- The design process for identifying the sub-systems making up a system and the framework for sub-system control and communication is **architectural design**.
- The output of this design process is a description of the **software architecture**.

Architectural design

- An early stage of the system design process.
- Represents the link between specification and design processes.
- Often carried out in parallel with some specification activities.
- It involves identifying major system components and their communications.

Advantages of explicit architecture

- Stakeholder communication
 - Architecture may be used as a focus of discussion by system stakeholders.
- System analysis
 - Means that analysis of whether the system can meet its non-functional requirements is possible.
- Large-scale reuse
 - The architecture may be reusable across a range of systems.

Architecture and system characteristics

- Performance
 - Localise critical operations and minimise communications. Use large rather than fine-grain components.
- Security
 - Use a layered architecture with critical assets in the inner layers.
- Safety
 - Localise safety-critical features in a small number of sub-systems.
- Availability
 - Include redundant components and mechanisms for fault tolerance.
- Maintainability
 - Use fine-grain, replaceable components.


Architectural conflicts

- Using large-grain components improves performance but reduces maintainability.
- Introducing redundant data improves availability but makes security more difficult.
- Localising safety-related features usually means more communication so degraded performance.

System structuring

- Concerned with decomposing the system into interacting sub-systems.
- The architectural design is normally expressed as a block diagram presenting an overview of the system structure.
- More specific models showing how sub-systems share data, are distributed and interface with each other may also be developed.

Packing robot control system



Box and line diagrams

- Very abstract - they do not show the nature of component relationships nor the externally visible properties of the sub-systems.
- However, useful for communication with stakeholders and for project planning.

Architectural design decisions

- Architectural design is a creative process so the process differs depending on the type of system being developed.
- However, a number of common decisions span all design processes.

Architectural design decisions

- Is there a generic application architecture that can be used?
- How will the system be distributed?
- What architectural styles are appropriate?
- What approach will be used to structure the system?
- How will the system be decomposed into modules?
- What control strategy should be used?
- How will the architectural design be evaluated?
- How should the architecture be documented?

Architecture reuse

- Systems in the same domain often have similar architectures that reflect domain concepts.
- Application product lines are built around a core architecture with variants that satisfy particular customer requirements.
- Application architectures are covered in Chapter 13 and product lines in Chapter 18.

Architectural styles

- The architectural model of a system may conform to a generic architectural model or style.
- An awareness of these styles can simplify the problem of defining system architectures.
- However, most large systems are heterogeneous and do not follow a single architectural style.

Architectural models

- Used to document an architectural design.
- Static structural model that shows the major system components.
- Dynamic process model that shows the process structure of the system.
- Interface model that defines sub-system interfaces.
- Relationships model such as a data-flow model that shows sub-system relationships.
- Distribution model that shows how sub-systems are distributed across computers.


System organisation

- Reflects the basic strategy that is used to structure a system.
- Three organisational styles are widely used:
 - A shared data repository style;
 - A shared services and servers style;
 - An abstract machine or layered style.

The repository model

- Sub-systems must exchange data. This may be done in two ways:
 - Shared data is held in a central database or repository and may be accessed by all sub-systems;
 - Each sub-system maintains its own database and passes data explicitly to other sub-systems.
- When large amounts of data are to be shared, the repository model of sharing is most commonly used.

CASE toolset architecture




Repository model characteristics

- Advantages
 - Efficient way to share large amounts of data;
 - Sub-systems need not be concerned with how data is produced Centralised management e.g. backup, security, etc.
 - Sharing model is published as the repository schema.
- Disadvantages
 - Sub-systems must agree on a repository data model. Inevitably a compromise;
 - Data evolution is difficult and expensive;
 - No scope for specific management policies;
 - Difficult to distribute efficiently.

Client-server model

- Distributed system model which shows how data and processing is distributed across a range of components.
- Set of stand-alone servers which provide specific services such as printing, data management, etc.
- Set of clients which call on these services.
- Network which allows clients to access servers.

Film and picture library




Client-server characteristics

- Advantages
 - Distribution of data is straightforward;
 - Makes effective use of networked systems. May require cheaper hardware;
 - Easy to add new servers or upgrade existing servers.
- Disadvantages
 - No shared data model so sub-systems use different data organisation. Data interchange may be inefficient;
 - Redundant management in each server;
 - No central register of names and services - it may be hard to find out what servers and services are available.

Abstract machine (layered) model

- Used to model the interfacing of sub-systems.
- Organises the system into a set of layers (or abstract machines) each of which provide a set of services.
- Supports the incremental development of sub-systems in different layers. When a layer interface changes, only the adjacent layer is affected.
- However, often artificial to structure systems in this way.

Version management system



Modular decomposition styles

- Styles of decomposing sub-systems into modules.
- No rigid distinction between system organisation and modular decomposition.

Sub-systems and modules

- A sub-system is a system in its own right whose operation is independent of the services provided by other sub-systems.
- A module is a system component that provides services to other components but would not normally be considered as a separate system.


Modular decomposition

- Another structural level where sub-systems are decomposed into modules.
- Two modular decomposition models covered
 - An object model where the system is decomposed into interacting object;
 - A pipeline or data-flow model where the system is decomposed into functional modules which transform inputs to outputs.
- If possible, decisions about concurrency should be delayed until modules are implemented.

Object models

- Structure the system into a set of loosely coupled objects with well-defined interfaces.
- Object-oriented decomposition is concerned with identifying object classes, their attributes and operations.
- When implemented, objects are created from these classes and some control model used to coordinate object operations.

Invoice processing system




Object model advantages

- Objects are loosely coupled so their implementation can be modified without affecting other objects.
- The objects may reflect real-world entities.
- OO implementation languages are widely used.
- However, object interface changes may cause problems and complex entities may be hard to represent as objects.

Function-oriented pipelining

- Functional transformations process their inputs to produce outputs.
- May be referred to as a pipe and filter model (as in UNIX shell).
- Variants of this approach are very common. When transformations are sequential, this is a batch sequential model which is extensively used in data processing systems.
- Not really suitable for interactive systems.

Invoice processing system



Pipeline model advantages

- Supports transformation reuse.
- Intuitive organisation for stakeholder communication.
- Easy to add new transformations.
- Relatively simple to implement as either a concurrent or sequential system.
- However, requires a common format for data transfer along the pipeline and difficult to support event-based interaction.


Control styles

- Are concerned with the control flow between sub-systems. Distinct from the system decomposition model.
- Centralised control
 - One sub-system has overall responsibility for control and starts and stops other sub-systems.
- Event-based control
 - Each sub-system can respond to externally generated events from other sub-systems or the system's environment.


Centralised control

- A control sub-system takes responsibility for managing the execution of other sub-systems.
- Call-return model
 - Top-down subroutine model where control starts at the top of a subroutine hierarchy and moves downwards. Applicable to sequential systems.
- Manager model
 - Applicable to concurrent systems. One system component controls the stopping, starting and coordination of other system processes. Can be implemented in sequential systems as a case statement.

Call-return model



Real-time system control




Event-driven systems

- Driven by externally generated events where the timing of the event is outwith the control of the sub-systems which process the event.
- Two principal event-driven models
 - Broadcast models. An event is broadcast to all sub-systems. Any sub-system which can handle the event may do so;
 - Interrupt-driven models. Used in real-time systems where interrupts are detected by an interrupt handler and passed to some other component for processing.
- Other event driven models include spreadsheets and production systems.

Broadcast model

- Effective in integrating sub-systems on different computers in a network.
- Sub-systems register an interest in specific events. When these occur, control is transferred to the sub-system which can handle the event.
- Control policy is not embedded in the event and message handler. Sub-systems decide on events of interest to them.
- However, sub-systems don't know if or when an event will be handled.


Selective broadcasting



Interrupt-driven systems

- Used in real-time systems where fast response to an event is essential.
- There are known interrupt types with a handler defined for each type.
- Each type is associated with a memory location and a hardware switch causes transfer to its handler.
- Allows fast response but complex to program and difficult to validate.

Interrupt-driven control




Reference architectures

- Architectural models may be specific to some application domain.
- Two types of domain-specific model
 - Generic models which are abstractions from a number of real systems and which encapsulate the principal characteristics of these systems. Covered in Chapter 13.
 - Reference models which are more abstract, idealised model. Provide a means of information about that class of system and of comparing different architectures.
- Generic models are usually bottom-up models; Reference models are top-down models.

Reference architectures

- Reference models are derived from a study of the application domain rather than from existing systems.
- May be used as a basis for system implementation or to compare different systems. It acts as a standard against which systems can be evaluated.
- OSI model is a layered model for communication systems.


OSI reference model



Case reference model

- Data repository services
 - Storage and management of data items.
- Data integration services
 - Managing groups of entities.
- Task management services
 - Definition and enaction of process models.
- Messaging services
 - Tool-tool and tool-environment communication.
- User interface services
 - User interface development.

The ECMA reference model



Key points

- The software architecture is the fundamental framework for structuring the system.
- Architectural design decisions include decisions on the application architecture, the distribution and the architectural styles to be used.
- Different architectural models such as a structural model, a control model and a decomposition model may be developed.
- System organisational models include repository models, client-server models and abstract machine models.

Key points

- Modular decomposition models include object models and pipelining models.
- Control models include centralised control and event-driven models.
- Reference architectures may be used to communicate domain-specific architectures and to assess and compare architectural designs.

Architectural models

- Different architectural models may be produced during the design process
- Each model presents different perspectives on the architecture

Architecture attributes

- Performance
 - Localise operations to minimise sub-system communication
- Security
 - Use a layered architecture with critical assets in inner layers
- Safety
 - Isolate safety-critical components
- Availability
 - Include redundant components in the architecture
- Maintainability
 - Use fine-grain, self-contained components

Object-oriented Design

Objectives

- To explain how a software design may be represented as a set of interacting objects that manage their own state and operations
- To describe the activities in the object-oriented design process
- To introduce various models that can be used to describe an object-oriented design
- To show how the UML may be used to represent these models

Topics covered

- Objects and object classes
- An object-oriented design process
- Design evolution

Object-oriented development

- Object-oriented analysis, design and programming are related but distinct.
- OOA is concerned with developing an object model of the application domain.
- OOD is concerned with developing an object-oriented system model to implement requirements.
- OOP is concerned with realising an OOD using an OO programming language such as Java or C++.

Characteristics of OOD

- Objects are abstractions of real-world or system entities and manage themselves.
- Objects are independent and encapsulate state and representation information.
- System functionality is expressed in terms of object services.
- Shared data areas are eliminated. Objects communicate by message passing.
- Objects may be distributed and may execute sequentially or in parallel.

Interacting objects



Advantages of OOD

- Easier maintenance. Objects may be understood as stand-alone entities.
- Objects are potentially reusable components.
- For some systems, there may be an obvious mapping from real world entities to system objects.

Objects and object classes

- Objects are entities in a software system which represent instances of real-world and system entities.
- Object classes are templates for objects. They may be used to create objects.
- Object classes may inherit attributes and services from other object classes.

Objects and object classes


*An **object** is an entity that has a state and a defined set of operations which operate on that state. The state is represented as a set of object attributes. The operations associated with the object provide services to other objects (clients) which request these services when some computation is required.*

*Objects are created according to some **object class** definition. An object class definition serves as a template for objects. It includes declarations of all the attributes and services which should be associated with an object of that class.*

The Unified Modeling Language

- Several different notations for describing object-oriented designs were proposed in the 1980s and 1990s.
- The Unified Modeling Language is an integration of these notations.
- It describes notations for a number of different models that may be produced during OO analysis and design.
- It is now a *de facto* standard for OO modelling.

Employee object class (UML)



Object communication

- Conceptually, objects communicate by message passing.
- Messages
 - The name of the service requested by the calling object;
 - Copies of the information required to execute the service and the name of a holder for the result of the service.
- In practice, messages are often implemented by procedure calls
 - Name = procedure name;
 - Information = parameter list.

Message examples

```
// Call a method associated with a buffer  
// object that returns the next value  
// in the buffer
```

```
v = circularBuffer.Get () ;
```


```
// Call the method associated with a  
// thermostat object that sets the  
// temperature to be maintained
```

```
thermostat.setTemp (20) ;
```

Generalisation and inheritance

- Objects are members of classes that define attribute types and operations.
- Classes may be arranged in a class hierarchy where one class (a super-class) is a generalisation of one or more other classes (sub-classes).
- A sub-class inherits the attributes and operations from its super class and may add new methods or attributes of its own.
- Generalisation in the UML is implemented as inheritance in OO programming languages.

A generalisation hierarchy



Advantages of inheritance

- It is an abstraction mechanism which may be used to classify entities.
- It is a reuse mechanism at both the design and the programming level.
- The inheritance graph is a source of organisational knowledge about domains and systems.


Problems with inheritance

- Object classes are not self-contained. they cannot be understood without reference to their super-classes.
- Designers have a tendency to reuse the inheritance graph created during analysis. Can lead to significant inefficiency.
- The inheritance graphs of analysis, design and implementation have different functions and should be separately maintained.

UML associations

- Objects and object classes participate in relationships with other objects and object classes.
- In the UML, a generalised relationship is indicated by an association.
- Associations may be annotated with information that describes the association.
- Associations are general but may indicate that an attribute of an object is an associated object or that a method relies on an associated object.

An association model



Concurrent objects

- The nature of objects as self-contained entities make them suitable for concurrent implementation.
- The message-passing model of object communication can be implemented directly if objects are running on separate processors in a distributed system.

Servers and active objects

- Servers.
 - The object is implemented as a parallel process (server) with entry points corresponding to object operations. If no calls are made to it, the object suspends itself and waits for further requests for service.
- Active objects
 - Objects are implemented as parallel processes and the internal object state may be changed by the object itself and not simply by external calls.

Active transponder object

- Active objects may have their attributes modified by operations but may also update them autonomously using internal operations.
- A **Transponder** object broadcasts an aircraft's position. The position may be updated using a satellite positioning system. The object periodically update the position by triangulation from satellites.

An active transponder object

```
class Transponder extends Thread {  
  
    Position currentPosition ;  
    Coords c1, c2 ;  
    Satellite sat1, sat2 ;  
    Navigator theNavigator ;  
  
    public Position givePosition ()  
    {  
        return currentPosition ;  
    }  
  
    public void run ()  
    {  
        while (true)  
        {  
            c1 = sat1.position () ;  
            c2 = sat2.position () ;  
            currentPosition = theNavigator.compute (c1, c2) ;  
        }  
    }  
  
} //Transponder
```

Java threads

- Threads in Java are a simple construct for implementing concurrent objects.
- Threads must include a method called `run()` and this is started up by the Java run-time system.
- Active objects typically include an infinite loop so that they are always carrying out the computation.

An object-oriented design process

- Structured design processes involve developing a number of different system models.
- They require a lot of effort for development and maintenance of these models and, for small systems, this may not be cost-effective.
- However, for large systems developed by different groups design models are an essential communication mechanism.

Process stages

- Highlights key activities without being tied to any proprietary process such as the RUP.
 - Define the context and modes of use of the system;
 - Design the system architecture;
 - Identify the principal system objects;
 - Develop design models;
 - Specify object interfaces.

Weather system description


A **weather mapping system** is required to generate weather maps on a regular basis using data collected from remote, unattended weather stations and other data sources such as weather observers, balloons and satellites. Weather stations transmit their data to the area computer in response to a request from that machine.

The area computer system validates the collected data and integrates it with the data from different sources. The integrated data is archived and, using data from this archive and a digitised map database a set of local weather maps is created. Maps may be printed for distribution on a special-purpose map printer or may be displayed in a number of different formats.


System context and models of use

- Develop an understanding of the relationships between the software being designed and its external environment
- System context
 - A static model that describes other systems in the environment. Use a subsystem model to show other systems. Following slide shows the systems around the weather station system.
- Model of system use
 - A dynamic model that describes how the system interacts with its environment. Use use-cases to show interactions

Layered architecture




Subsystems in the weather mapping system



Use-case models

- Use-case models are used to represent each interaction with the system.
- A use-case model shows the system features as ellipses and the interacting entity as a stick figure.

Use-cases for the weather station



Use-case description

System	Weather station
Use-case	Report
Actors	Weather data collection system, Weather station
Data	The weather station sends a summary of the weather data that has been collected from the instruments in the collection period to the weather data collection system. The data sent are the maximum minimum and average ground and air temperatures, the maximum, minimum and average air pressures, the maximum, minimum and average wind speeds, the total rainfall and the wind direction as sampled at 5 minute intervals.
Stimulus	The weather data collection system establishes a modem link with the weather station and requests transmission of the data.
Response	The summarised data is sent to the weather data collection system
Comments	Weather stations are usually asked to report once per hour but this frequency may differ from one station to the other and may be modified in future.

Architectural design

- Once interactions between the system and its environment have been understood, you use this information for designing the system architecture.
- A layered architecture as discussed in Chapter 11 is appropriate for the weather station
 - Interface layer for handling communications;
 - Data collection layer for managing instruments;
 - Instruments layer for collecting data.
- There should normally be no more than 7 entities in an architectural model.

Weather station architecture



Object identification

- Identifying objects (or object classes) is the most difficult part of object oriented design.
- There is no 'magic formula' for object identification. It relies on the skill, experience and domain knowledge of system designers.
- Object identification is an iterative process. You are unlikely to get it right first time.

Approaches to identification

- Use a grammatical approach based on a natural language description of the system (used in Hood OOD method).
- Base the identification on tangible things in the application domain.
- Use a behavioural approach and identify objects based on what participates in what behaviour.
- Use a scenario-based analysis. The objects, attributes and methods in each scenario are identified.

Weather station description

A **weather station** is a package of software controlled instruments which collects data, performs some data processing and transmits this data for further processing. The instruments include air and ground thermometers, an anemometer, a wind vane, a barometer and a rain gauge. Data is collected periodically.

When a command is issued to transmit the weather data, the weather station processes and summarises the collected data. The summarised data is transmitted to the mapping computer when a request is received.

Weather station object classes

- Ground thermometer, Anemometer, Barometer
 - Application domain objects that are 'hardware' objects related to the instruments in the system.
- Weather station
 - The basic interface of the weather station to its environment. It therefore reflects the interactions identified in the use-case model.
- Weather data
 - Encapsulates the summarised data from the instruments.

Weather station object classes



Further objects and object refinement

- Use domain knowledge to identify more objects and operations
 - Weather stations should have a unique identifier;
 - Weather stations are remotely situated so instrument failures have to be reported automatically. Therefore attributes and operations for self-checking are required.
- Active or passive objects
 - In this case, objects are passive and collect data on request rather than autonomously. This introduces flexibility at the expense of controller processing time.

Design models

- Design models show the objects and object classes and relationships between these entities.
- Static models describe the static structure of the system in terms of object classes and relationships.
- Dynamic models describe the dynamic interactions between objects.


Examples of design models

- Sub-system models that show logical groupings of objects into coherent subsystems.
- Sequence models that show the sequence of object interactions.
- State machine models that show how individual objects change their state in response to events.
- Other models include use-case models, aggregation models, generalisation models, etc.

Subsystem models

- Shows how the design is organised into logically related groups of objects.
- In the UML, these are shown using packages - an encapsulation construct. This is a logical model. The actual organisation of objects in the system may be different.


Weather station subsystems



Sequence models

- Sequence models show the sequence of object interactions that take place
 - Objects are arranged horizontally across the top;
 - Time is represented vertically so models are read top to bottom;
 - Interactions are represented by labelled arrows, Different styles of arrow represent different types of interaction;
 - A thin rectangle in an object lifeline represents the time when the object is the controlling object in the system.


Data collection sequence



Statecharts

- Show how objects respond to different service requests and the state transitions triggered by these requests
 - If object state is Shutdown then it responds to a Startup() message;
 - In the waiting state the object is waiting for further messages;
 - If reportWeather () then system moves to summarising state;
 - If calibrate () the system moves to a calibrating state;
 - A collecting state is entered when a clock signal is received.

Weather station state diagram



Object interface specification

- Object interfaces have to be specified so that the objects and other components can be designed in parallel.
- Designers should avoid designing the interface representation but should hide this in the object itself.
- Objects may have several interfaces which are viewpoints on the methods provided.
- The UML uses class diagrams for interface specification but Java may also be used.

Weather station interface

```
interface WeatherStation {  
  
    public void WeatherStation () ;  
  
    public void startup () ;  
    public void startup (Instrument i) ;  
  
    public void shutdown () ;  
    public void shutdown (Instrument i) ;  
  
    public void reportWeather () ;  
  
    public void test () ;  
    public void test ( Instrument i ) ;  
  
    public void calibrate ( Instrument i) ;  
  
    public int getID () ;  
  
} //WeatherStation
```


Design evolution

- Hiding information inside objects means that changes made to an object do not affect other objects in an unpredictable way.
- Assume pollution monitoring facilities are to be added to weather stations. These sample the air and compute the amount of different pollutants in the atmosphere.
- Pollution readings are transmitted with weather data.

Changes required

- Add an object class called **Air quality** as part of **WeatherStation**.
- Add an operation **reportAirQuality** to **WeatherStation**. Modify the control software to collect pollution readings.
- Add objects representing pollution monitoring instruments.

Pollution monitoring



Key points

- OOD is an approach to design so that design components have their own private state and operations.
- Objects should have constructor and inspection operations. They provide services to other objects.
- Objects may be implemented sequentially or concurrently.
- The Unified Modeling Language provides different notations for defining different object models.

Key points

- A range of different models may be produced during an object-oriented design process. These include static and dynamic system models.
- Object interfaces should be defined precisely using e.g. a programming language like Java.
- Object-oriented design potentially simplifies system evolution.