LAB SESSION-8

COURSE:- Computer Networks Lab

Course Code:- BCSE308P

Faculty:- Anita X

Name:- Priyanshu Soni


Reg. No.:- 21BRS1629

Implementing DNS using TCP socket programming

Code:

```
Client: -
import iava.io.*;
import java.net.*;
public class DNSClient {
  public static void main(String[] args) throws IOException {
     Socket socket = new Socket("localhost", 5000);
     PrintWriter out = new PrintWriter(socket.getOutputStream(), true);
     out.println("google.com");
     BufferedReader in = new BufferedReader(new
InputStreamReader(socket.getInputStream()));
     String ipAddress = in.readLine();
     System.out.println("IP address: " + ipAddress);
     socket.close();
  }
}
 Server:-
import java.io.*;
import java.net.*;
public class DNSServer {
    public static void main(String[] args) throws IOException {
        File file = new File("ip_addresses.txt");
        BufferedReader br = new BufferedReader(new FileReader(file));
        ServerSocket serverSocket = new ServerSocket(5000);
        System.out.println("DNS server started. Listening on port 5000...");
        while (true) {
            Socket clientSocket = serverSocket.accept();
            System.out.println("Connection established with client " +
clientSocket.getInetAddress());
            BufferedReader in = new BufferedReader(new
InputStreamReader(clientSocket.getInputStream()));
            String domainName = in.readLine();
            System.out.println("Received request for domain: " + domainName);
            String ipAddress = "";
            String line;
            while ((line = br.readLine()) != null) {
                if (line.startsWith(domainName)) {
                     ipAddress = line.substring(domainName.length() + 1);
                     break;
                }
            PrintWriter out = new PrintWriter(clientSocket.getOutputStream(),
true);
            out.println(ipAddress);
            clientSocket.close();
        }
    }
}
```

Contents of Ip_addresses.txt:-



Input: -

Google.com

Output: -

Server:

PS D:\3RD YEAR\NETWORKS LAB\lab-8\\tcp> & 'C:\Program Files\Java\jdk-17.0.1\\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessage -cp' 'C:\Users\THE_EXOTIC_ONE\AppData\Roaming\Code\User\workspaceStorage\e6b72aad680f629cc97cdfbfbe6ebddc\redhat.java\jdt_ws\tcp_c74518 in' 'DNSServer'

DNS server started. Listening on port 5000... Connection established with client /127.0.0.1 Received request for domain: google.com

Client:

PS D:\3RD YEAR\NETWORKS LAB\lab-8\la

IP address: 172.217.6.110

PS D:\3RD YEAR\NETWORKS LAB\lab-8\lab-8\tcp>

Implementing DNS using UDP socket programming.

Code:-

}

```
Client:
import java.io.*;
import java.net.*;
public class DNSClient {
    public static void main(String[] args) throws IOException {
        DatagramSocket socket = new DatagramSocket();
        InetAddress serverAddress = InetAddress.getByName("localhost");
        String domainName = "google.com";
        byte[] buffer = domainName.getBytes();
        DatagramPacket requestPacket = new DatagramPacket(buffer, buffer.length,
serverAddress, 5000);
        socket.send(requestPacket);
        byte[] responseBuffer = new byte[1024];
        DatagramPacket responsePacket = new DatagramPacket(responseBuffer,
responseBuffer.length);
        socket.receive(responsePacket);
        String ipAddress = new String(responsePacket.getData(), 0,
responsePacket.getLength());
        System.out.println("IP address: " + ipAddress);
        socket.close();
    }
}
 Server:
import java.io.*;
import java.net.*;
public class DNSServer {
    public static void main(String[] args) throws IOException {
        File file = new File("ip_addresses1.txt");
        BufferedReader br = new BufferedReader(new FileReader(file));
        DatagramSocket socket = new DatagramSocket(5000);
        System.out.println("DNS server started. Listening on port 5000...");
        while (true) {
            byte[] buffer = new byte[1024];
            DatagramPacket requestPacket = new DatagramPacket(buffer,
buffer.length);
            socket.receive(requestPacket);
            InetAddress clientAddress = requestPacket.getAddress();
            int clientPort = requestPacket.getPort();
            String domainName = new String(requestPacket.getData(), 0,
requestPacket.getLength());
            System.out.println("Received request for domain: " + domainName);
            String ipAddress = "";
            String line;
            while ((line = br.readLine()) != null) {
                if (line.startsWith(domainName)) {
                    ipAddress = line.substring(domainName.length() + 1);
                    break;
```

Contents of io_addresses1.txt file



Input:

google.com

Output:

Server:

```
PS D:\3RD YEAR\NETWORKS LAB\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-8\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\lab-9\la
```

Client:

```
PS D:\3RD YEAR\NETWORKS LAB\lab-8\lab-8\udp> & 'C:\Program Files\Java\jdk-17.0.1\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\THE_EXOTIC_ONE\AppData\Roaming\Code\User\workspaceStorage\639e6d9447d2623a87b2dbbb22ddb24e\redhat.java\jdt_ws\udp_c7451c94\bin' 'DNSclient'
IP address: 172.217.6.110
PS D:\3RD YEAR\NETWORKS LAB\lab-8\lab-8\udp>
```