

Implement Client Script & UI Policy (Incident)

2. Requirements

Functional Requirements

- Create an active Incident UI Policy named High Impact Control.
- Trigger the policy when Impact is 1 – High.
- Make Assignment group mandatory under the UI Policy Action.
- Enable Reverse if false.
- Create an Urgency UI Policy Action that makes Urgency read-only when Impact is High.
- Create an onChange Client Script on Incident/Impact that sets Urgency to High when Impact is 1.
- Create an onSubmit Client Script that prevents saving a High Impact Incident when Assigned To is empty.
- Create an onCellEdit Client Script that blocks direct State changes from the Incident list.
- Allow form-based State updates.
- Test both positive and reverse-condition behavior.

Business Rules Represented

For High Impact incidents, the documented configuration requires appropriate assignment information, automatically sets Urgency to High, makes Urgency read-only, and prevents saving when Assigned To is empty. Direct list editing of State is blocked.

Acceptance Conditions

- High Impact + empty Assigned To → save is prevented and an error is shown.
- High Impact + Assigned To populated → save succeeds.
- Changing Impact from High to Medium reverses the mandatory/read-only behavior.
- Direct State list edit → blocked.
- State change from the Incident form → allowed.

Source basis: supplied 18-page Project 3 PDF. Unsupported project metadata, screenshots, execution results, and dates are not fabricated.