Priyasakhi

Incinerators (Burning machines)



General Technical Specifications for Incinerators

- MS epoxy (rust/weather proof) powder coated body,
- Advance fully automated, Electrically Operated,
- Smell free burning process, flexible, stretchable aluminum or CI pipe for exhaust upto 3 Mtr.
- Wall Mountable, Front manual loading for the safety of users
- Magnetic closing door, smoke leakage proof with dual chamber
- Easily cleanable ash tray for residue ash collection for the collection of 150 gms or more.
- Auto cut of relay for over heat protection, Auto power off for Power saving,
- Ceramic wool insulation for power (shock proof) and thermal safety
- Burns pads and give less than 1 gm ash
- User friendly push button with proper usage instruction
- Power: 1200 Watt / 230V /50Hz
- Spiral coil with thermal sensors, All accessories used in m/c carry ISI marked or certified
- 1 year Warranty for all kind of manufacturing defects
- Graphic sticker display with every machine for easy understanding to user. (optional)
- Voice Instructions for users in any language (Optional)

Models

| Sanitary Napkin – Incinerators (Burning Machine) | | | | | |
|--|------------|-------------|-------------|-------------|-------------|
| Model & Specifications | DIS 10 | DIS 25 | DIS 50 | DIS 50 E | DIS 50XE |
| Burning Capacity At a time | 5 | 15-20 | 25-35 | 15-20 | 15-20 |
| Burning Capacity Full day | 25-30 | 150=200 | 300-350 | 200-250 | 200-250 |
| Time taking to burn one napkin (Mnt) | 15 | 10 | 5 | 5 | 5 |
| Dimensions (L x W x H) in mm | | 450x270x250 | 600x270x250 | 600x270x250 | 600x270x250 |
| Net Weight Approx | | 14.0 | 18.0 | 21.0 | 24.0 |
| Ceramic Coil Capacity in Watts | 400 | 750 | 1000 | 1000 | 1000 |
| Power Requirement | 230V, 50Hz | 230V, 50Hz | 230V, 50Hz | 230V, 50Hz | 230V, 50Hz |
| Power Consumption per Day | 0.02 Unit | 0.04 Unit | 0.06 Unit | 0.07 Unit | 0.08 Unit |
| Temperature Display | Yes | Yes | Yes | Yes | Yes |
| Timer Controller | Yes | Yes | Yes | Yes | Yes |
| Temperature Controller | Yes | Yes | Yes | Yes | Yes |
| Ceramic Insulation for safety | Yes | Yes | Yes | Yes | Yes |
| Exhaust Blower | | | | Yes | Yes |
| Smoke Filter for suspected Particles | | | | | Yes |
| Smoke Exhaust Pipe availability (3 Mtr) | Yes | Yes | Yes | Yes | Yes |
| Wall Mountable | Yes | Yes | Yes | Yes | Yes |
| Any brand Pads can be used | Yes | Yes | Yes | Yes | Yes |
| Can Machine used 7 / 24 / 365 | Yes | Yes | Yes | Yes | Yes |
| Auto Power off after burning | Yes | Yes | Yes | Yes | Yes |
| Manufacturing Warranty for Parts | 1 Year | 1 Year | 1 Year | 1 Year | 1 Year |
| Service support & Parts Supply (atleast) | 5 Year | 5 Year | 5 Year | 5 Year | 5 Year |
| Free Visiting of engineer | 1 | 1 | 2 | 2 | 2 |
| Installation Charges included | No | No | No | No | No |
| Whether Visiting calls will be Charged | Yes | Yes | Yes | Yes | Yes |
| GST / Transportation Included | No | No | No | No | No |
| Best Opted machine | Home | Affordable | | Expensive | |

Accessories

- Heater coil 450W, 750W,
- Temperature Display
- Temperature Controller
- Timer Controller
- Temperature Sensor
- Switches
- DC Relay
- SMP
- LED bulbs