

Experiment – 18

High Level Programming Extensions – Cursors

```
mysql> CREATE TABLE StudentResult (  
-> StudentID INT,  
-> StudentName VARCHAR(50),  
-> Grade VARCHAR(10)  
-> );  
Query OK, 0 rows affected (0.08 sec)
```

```
mysql>  
mysql> DELIMITER ;  
mysql> SELECT StudentID, StudentName, Marks, GetGrade(Marks) AS Grade  
-> FROM Student;  
  
+-----+-----+-----+-----+  
| StudentID | StudentName | Marks | Grade |  
+-----+-----+-----+-----+  
| 101 | Indhu | 85 | A |  
| 102 | Meghana | 78 | B |  
| 103 | Shalini | 92 | A+ |  
| 104 | Teju | 67 | C |  
+-----+-----+-----+-----+  
4 rows in set (0.05 sec)
```

```
mysql> DELIMITER //  
mysql>  
mysql> CREATE FUNCTION AddBonus(marks INT)  
-> RETURNS INT  
-> DETERMINISTIC  
-> BEGIN  
-> RETURN marks + 10;  
-> END //  
Query OK, 0 rows affected (0.06 sec)
```

```
mysql>  
mysql> DELIMITER ;  
mysql> SELECT StudentName, Marks, AddBonus(Marks) AS FinalMarks  
-> FROM Student;  
  
+-----+-----+-----+  
| StudentName | Marks | FinalMarks |  
+-----+-----+-----+  
| Indhu | 85 | 95 |  
| Meghana | 78 | 88 |  
| Shalini | 92 | 102 |  
| Teju | 67 | 77 |  
+-----+-----+-----+  
4 rows in set (0.00 sec)
```

```
mysql>
mysql> DELIMITER ;
mysql> CALL ProcessStudents();
Query OK, 0 rows affected (0.07 sec)
```

```
mysql> SELECT * FROM StudentResult;
```

StudentID	StudentName	Grade
101	Indhu	F
102	Meghana	F
103	Shalini	F
104	Teju	F

```
4 rows in set (0.00 sec)
```