

EXPERIMENT – 15

Simple programming using CASE and LOOP

CASE & LOOP:

```
mysql> -- EXPERIMENT 15: CASE and LOOP
mysql> DELIMITER //
mysql> CREATE PROCEDURE GradeCase(IN input_marks INT)
  -> BEGIN
  ->     DECLARE grade_result VARCHAR(10);
  ->     CASE
  ->         WHEN input_marks >= 90 THEN SET grade_result = 'A+';
  ->         WHEN input_marks >= 75 THEN SET grade_result = 'A';
  ->         WHEN input_marks >= 60 THEN SET grade_result = 'B';
  ->         ELSE SET grade_result = 'C';
  ->     END CASE;
  ->     SELECT input_marks AS marks, grade_result AS grade;
  -> END //
Query OK, 0 rows affected (0.01 sec)

mysql> DELIMITER ;
mysql> CALL GradeCase(85);
+-----+-----+
| marks | grade |
+-----+-----+
|    85 | A     |
+-----+-----+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> DELIMITER //
mysql> CREATE PROCEDURE PrintLoop()
  -> BEGIN
  ->     DECLARE i INT DEFAULT 1;
  ->     my_loop: LOOP
  ->         IF i > 5 THEN
  ->             LEAVE my_loop;
  ->         END IF;
  ->         SELECT i AS loop_counter;
  ->         SET i = i + 1;
  ->     END LOOP my_loop;
  -> END //
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> DELIMITER ;
mysql> CALL PrintLoop();
+-----+
| loop_counter |
+-----+
|           1 |
+-----+
1 row in set (0.00 sec)

+-----+
| loop_counter |
+-----+
|           2 |
+-----+
1 row in set (0.00 sec)

+-----+
| loop_counter |
+-----+
|           3 |
+-----+
1 row in set (0.00 sec)

+-----+
| loop_counter |
+-----+
|           4 |
+-----+
1 row in set (0.00 sec)

+-----+
| loop_counter |
+-----+
|           5 |
+-----+
1 row in set (0.01 sec)

Query OK, 0 rows affected (0.01 sec)
```

