SIMATS ENGINEERING
ASSESSMENT TOOL 3

COURSE NAME: Artificial Intelligence **COURSE CODE: CSA1707**

COURSE OUTCOME COVERED

CO3: *Analyze knowledge representation and reasoning using propositional logic, FOL, inference, resolution, chaining methods, knowledge representation to perform logical reasoning for drawing valid conclusions and decision making. (BL4)*

Assessment Tool Weightage: 50%

Time Duration: 30 Minutes

QUESTIONS: 30 **Total Marks:30**

Annexure A

MCQ

Code of Conduct:

I ***S. Lakshmi Priya (192524284)*** *(Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment. I understand that any violation of academic integrity rules will result in disciplinary action.*

Signature of the student: *S. Lakshmi Priya*

Annexure A

Circle the most appropriate option for each question.

Q1. Which of the following best describes a Logical Agent in AI?

a) An agent that reacts randomly to the environment

b) An agent that uses a knowledge base and logical inference to decide actions

c) An agent that only follows pre-defined scripts

d) An agent that learns from rewards

Answer: b) An agent that uses a knowledge base and logical inference to decide actions

Q2. In Propositional Logic, 'P → Q' is logically equivalent to:

a) P ∧ ¬Q

b) ¬P ∨ Q

c) ¬Q → ¬P only

d) Both b and c

Answer: d) Both b and c

Q3. Conjunctive Normal Form (CNF) requires the formula to be expressed as:

a) A disjunction of conjunctions

b) A conjunction of disjunctions (clauses)

c) A conjunction of literals only

d) A sequence of implications

Answer: b) A conjunction of disjunctions (clauses)

Q4. In FOL, the sentence ∀x: Student(x) → Passes(x) means:

a) Some students pass

b) Every entity that is a student passes

c) If something passes, it is a student

d) There exists at least one student who passes

Answer: b) Every entity that is a student passes

Q5. Unification in FOL is the process of finding substitutions that:

a) Convert clauses to CNF

b) Make two logical expressions syntactically identical

c) Prove a goal using backward chaining

d) Derive facts using Modus Ponens

Answer: b) Make two logical expressions syntactically identical

Q6. In the Resolution algorithm, deriving the empty clause □ indicates:

a) The knowledge base is consistent

b) The negated goal is satisfiable

c) A contradiction — the original goal is proven

d) More clauses need to be added

Answer: c) A contradiction — the original goal is proven

Q7. Forward Chaining is best described as a _____ strategy.

a) Goal-driven / top-down

b) Data-driven / bottom-up

c) Heuristic-based depth-first

d) Probabilistic inference

Answer: b) Data-driven / bottom-up

Q8. Backward Chaining begins reasoning from:

a) All known facts toward a conclusion

b) The goal and works backward to verify supporting facts

c) A random clause in the knowledge base

d) The resolution refutation tree

Answer: b) The goal and works backward to verify supporting facts

Q9. Which step is NOT part of converting a sentence to CNF?

a) Eliminate biconditionals (↔)

b) Move negations inward using De Morgan's laws

c) Apply Skolemization to remove existential quantifiers

d) Distribute AND over OR

Answer: d) Distribute AND over OR

Q10. Knowledge Engineering in FOL involves:

a) Training a neural network on domain-specific data

b) Defining domain concepts, relations, and axioms formally in FOL

c) Writing heuristic search strategies

d) Encoding reward functions for reinforcement learning

Answer: b) Defining domain concepts, relations, and axioms formally in FOL

Q11. Modus Ponens states: If $P \rightarrow Q$ is known and P is true, then:

a) $\neg Q$ is true

b) Q must be true

c) P is uncertain

d) The KB is inconsistent

Answer: b) Q must be true

Q12. The Most General Unifier (MGU) is the substitution that:

a) Is the most specific possible match

b) Makes two terms identical with minimal variable binding

c) Eliminates all variables from a clause

d) Applies resolution to produce CNF

Answer: b) Makes two terms identical with minimal variable binding

Q13. Which inference method is more appropriate when a specific goal is known?

a) Forward Chaining
c) Backward Chaining
b) Truth Table method
d) A* search

Answer: c) Backward Chaining

Q14. Propositional Logic differs from First Order Logic because it:

a) Supports probabilistic reasoning
c) Is always more expressive
b) Cannot represent objects, relations, or quantifiers — only truth values of atomic propositions
d) Handles uncertainty better

Answer: b) Cannot represent objects, relations, or quantifiers — only truth values of atomic propositions

Q15. Resolution Refutation proves a goal G by:

a) Directly deriving G from the KB using forward chaining
c) Checking G in the truth table
b) Adding ¬G to the KB and deriving a contradiction (empty clause □)
d) Applying Modus Tollens repeatedly

Answer: b) Adding ¬G to the KB and deriving a contradiction (empty clause □)

Q16. Learning from observation in AI refers to:

a) An agent receiving numerical rewards from the environment
c) Acquiring knowledge by following explicit symbolic rules
b) Improving performance by examining examples or experience from the environment
d) Memorizing a fixed dataset without generalization

Answer: b) Improving performance by examining examples or experience from the environment

Q17. Inductive learning is best described as:

a) Deriving specific conclusions from general rules

b) Generalizing a hypothesis from specific training examples

c) Memorizing training data exactly

d) Applying search algorithms to find optimal policies

Answer: b) Generalizing a hypothesis from specific training examples

Q18. In a Decision Tree, what does each internal node represent?

a) A class label / output decision

b) A probability distribution over outcomes

c) A test on an attribute / feature

d) A training data sample

Answer: c) A test on an attribute / feature

Q19. Explanation-Based Learning (EBL) differs from inductive learning because it:

a) Requires large amounts of training data to generalize

b) Learns only from numeric data using regression

c) Uses prior domain knowledge to explain and generalize a single example

d) Applies unsupervised clustering to find hidden patterns

Answer: c) Uses prior domain knowledge to explain and generalize a single example

Q20. In statistical learning, a Naive Bayes classifier assumes:

a) All features are conditionally dependent on each other given the class

b) The data must follow a uniform distribution

c) All features are conditionally independent given the class label

d) Labels are determined by a reward function

Answer: c) All features are conditionally independent given the class label

Q21. Learning with complete data (no hidden variables) in a Bayesian network involves:

a) Using the EM algorithm to estimate missing values

b) Training a deep neural network with dropout regularization

c) Directly computing maximum likelihood estimates from observed data

d) Applying reinforcement signals to update weights

Answer: c) Directly computing maximum likelihood estimates from observed data

Q22. The Expectation-Maximization (EM) algorithm is used when:

a) Training data is fully labeled and no variables are hidden

b) An agent explores an unknown environment using trial and error

c) The dataset contains hidden (latent) variables that cannot be directly observed

d) Backpropagation fails to converge in a neural network

Answer: c) The dataset contains hidden (latent) variables that cannot be directly observed

Q23. In a Neural Network, the activation function serves to:

a) Initialize the weights of each neuron to zero

b) Normalize the input dataset before training

c) Introduce non-linearity to enable learning of complex patterns

d) Store previously learned examples in memory

Answer: c) Introduce non-linearity to enable learning of complex patterns

Q24. Which of the following correctly describes backpropagation in a neural network?

a) Weights are updated in the forward pass using input gradients

b) Outputs of each layer are stored and reused in later epochs

c) The error is propagated backward from output to input layers to adjust weights

d) A separate model is trained for each hidden layer independently

Answer: c) The error is propagated backward from output to input layers to adjust weights

Q25. A Support Vector Machine (SVM) — a type of kernel machine — classifies data by:

a) Minimizing the number of training examples used

b) Grouping similar data points into clusters using centroids

c) Finding the maximum-margin hyperplane that separates classes

d) Updating weights using Q-values from an environment

Answer: c) Finding the maximum-margin hyperplane that separates classes

Q26. The kernel trick in kernel machines (SVMs) allows:

a) Reducing the number of support vectors needed

b) Accelerating gradient descent convergence

c) Operating in a high-dimensional feature space without explicitly computing coordinates

d) Replacing hidden layers in a deep neural network

Answer: c) Operating in a high-dimensional feature space without explicitly computing coordinates

Q27. In Reinforcement Learning, the agent aims to maximize:

a) Classification accuracy on a fixed test set

b) The number of features selected from the training data

c) Cumulative reward received over time through interaction with the environment

d) The size of the neural network hidden layer

Answer: c) Cumulative reward received over time through interaction with the environment

Q28. The Q-Learning algorithm in Reinforcement Learning is classified as:

a) A supervised learning algorithm requiring labeled datasets

b) An unsupervised clustering technique using centroids

c) A model-free, off-policy temporal difference learning method

d) A decision-tree-based ensemble classifier

Answer: c) A model-free, off-policy temporal difference learning method

Q29. Overfitting in machine learning occurs when:

a) The model performs poorly on both training and test data

b) The learning rate is set too low during gradient descent

c) The model fits training data too closely and generalizes poorly to new data

d) The training set has more features than training examples

Answer: c) The model fits training data too closely and generalizes poorly to new data

Q30. Which of the following best distinguishes Reinforcement Learning from Supervised Learning?

a) RL uses labeled input-output pairs; SL uses reward signals

b) Both RL and SL require explicit reward functions

c) RL learns via trial-and-error with reward feedback; SL learns from labeled examples

d) RL is always faster to converge than SL on any dataset

Answer: c) RL learns via trial-and-error with reward feedback; SL learns from labeled examples

RUBRICS FOR CALCULATION

Criteria	Weightage (%)	Level 4 (Exemplary)	Level 3 (Proficient)	Level 2 (Developing)	Level 1 (Beginning)
Conceptual Understanding	30%	Demonstrates thorough understanding; answers all questions accurately	Shows good understanding with few errors	Partial understanding; several incorrect responses	Lacks understanding; majority of answers incorrect
Accuracy of Answers	25%	All answers are correct	Most answers are correct with minor mistakes	Some correct answers; frequent errors	Mostly incorrect answers
Application of Knowledge	20%	Correctly applies concepts to problem-based questions	Applies concepts with minor errors	Limited ability to apply concepts	Unable to apply concepts
Time Management	15%	Completes quiz well within time efficiently	Completes on time with minor delays	Requires extra time or rushes through questions	Unable to complete within given time
Question Interpretation	10%	Interprets all questions correctly and responds appropriately	Misinterprets a few questions	Often misinterprets questions	Unable to understand questions