

Input Function in Python



Outcomes of this Lecture

What is static initialization?

What is the use of dynamic initialization?

What is the return type of input() function?

How to store int values using input()

How to convert other number system values to decimal using input()





Static initialization

- Assigning the value to a variable is called initialization.
- Ex: `num=10;`
- Assigning the value(s) for the variable (s) **within the source code** (program) is called, static initialization.



Dynamic initialization

- Assigning the value(s) for the variable (s) **at runtime of a** program (Dynamically) is called, dynamic initialization.
- With help of it, we can receive the **input form the keyboard** while executing the program.



Input()

- Data given to the program is called input to the program.
- When developer wants to take input from the user at some point in the program, input() function can be used in python.
- To receive the data dynamically into program we use **“input()”** method in python.



Input() contd..

- Syntax: **input("Prompt String")**
- Ex: **input("enter your name");**
- Prompt string is optional.
- Ex: **input()**



Input() contd..

- The **return type** of the input() method is **string**.
- Even though you enter any other type data it returns it in string form.
- If you want to convert that input into any other datatype, we need to convert it explicitly (Type Conversion).
- To convert into integer type we use **int()** and to float type we use **float()**.

Check your knowledge

What is static initialization?

What is the use of dynamic initialization?

What is the return type of input() function?

How to store int values using input()

How to convert other number system values to decimal using input()

