



C Programming Video Tutorials

C Programming Tutorial

C - Home

C - Overview

C - Environment Setup

C - Program Structure

C - Basic Syntax

C - Data Types

C - Variables

C - Constants

C - Storage Classes

C - Operators

C - Decision Making

C - Loops

C - Functions

C - Scope Rules

C - Arrays

C - Pointers

C - Strings

C - Structures

[C - Unions](#)[C - Bit Fields](#)[C - Typedef](#)[C - Input & Output](#)[C - File I/O](#)[C - Preprocessors](#)[C - Header Files](#)[C - Type Casting](#)[C - Error Handling](#)[C - Recursion](#)[C - Variable Arguments](#)[C - Memory Management](#)[C - Command Line Arguments](#)[C Programming Resources](#)[C - Questions & Answers](#)[C - Quick Guide](#)[C - Useful Resources](#)[C - Discussion](#)

C - typedef

[Live Demo](#)

Advertisements



Select your business
size to get started.

Less than 2

20 people

[⬅ Previous Page](#)[Next Page ➡](#)

The C programming language provides a keyword called **typedef**, which you can use to give a type a new name. Following is an example to define a term **BYTE** for one-byte numbers –

```
typedef unsigned char BYTE;
```

After this type definition, the identifier `BYTE` can be used as an abbreviation for the type **unsigned char**, for example..

```
BYTE b1, b2;
```

By convention, uppercase letters are used for these definitions to remind the user that the type name is really a symbolic abbreviation, but you can use lowercase, as follows –

```
typedef unsigned char byte;
```

You can use **typedef** to give a name to your user defined data types as well. For example, you can use typedef with structure to define a new data type and then use that data type to define structure variables directly as follows –

```
#include <stdio.h>
#include <string.h>

typedef struct Books {
    char title[50];
    char author[50];
    char subject[100];
    int book_id;
} Book;

int main( ) {

    Book book;

    strcpy( book.title, "C Programming");
    strcpy( book.author, "Nuha Ali");
    strcpy( book.subject, "C Programming Tutorial");
    book.book_id = 6495407;

    printf( "Book title : %s\n", book.title);
    printf( "Book author : %s\n", book.author);
    printf( "Book subject : %s\n", book.subject);
    printf( "Book book_id : %d\n", book.book_id);

    return 0;
}
```

When the above code is compiled and executed, it produces the following result –

```
Book title : C Programming
Book author : Nuha Ali
Book subject : C Programming Tutorial
Book book_id : 6495407
```

typedef vs #define

#define is a C-directive which is also used to define the aliases for various data types similar to **typedef** but with the following differences –

typedef is limited to giving symbolic names to types only where as **#define** can be used to define alias for values as well, q., you can define 1 as ONE etc.

typedef interpretation is performed by the compiler whereas **#define** statements are processed by the pre-processor.

The following example shows how to use #define in a program –

```
#include <stdio.h>

#define TRUE  1
#define FALSE 0

int main( ) {
    printf( "Value of TRUE : %d\n", TRUE);
    printf( "Value of FALSE : %d\n", FALSE);

    return 0;
}
```

When the above code is compiled and executed, it produces the following result –

```
Value of TRUE : 1
Value of FALSE : 0
```

⏪ Previous Page

Next Page ⏩

Advertisements





[FAQ's](#) [Cookies Policy](#) [Contact](#)

© Copyright 2018. All Rights Reserved.

Enter email for newslett

go