

# GeeksforGeeks

A computer science portal for geeks

[Courses](#)[Login](#)[Write an Article](#)

int (1 sign bit  
+ 31 data  
bits)  
keyword in C

Program  
error signals

Why array  
index starts  
from zero ?

TCP Server-  
Client  
implementation  
in C

How to  
return  
multiple  
values from  
a function in  
C or C++?

Dynamic  
Memory  
Allocation in  
C using  
malloc(),  
calloc(),  
free() and  
realloc()

Commonly

Asked C  
Programming  
Interview  
Questions |  
Set 3

Applications  
of Pointers in  
C/C++

Pre-  
increment  
and Post-  
increment in  
C/C++

Sum of array  
Elements  
without  
using loops  
and  
recursion

"static const"  
vs "#define"  
vs "enum"

Comments  
in C/C++

How will you  
print  
numbers  
from 1 to  
100 without  
using loop? |  
Set-2

How to find  
Segmentation  
Error in C &  
C++ ? (Using

GDB)

Why strcpy  
and strncpy  
are not safe  
to use?

time()  
function in C

Loader in  
C/C++

GDB (Step by  
Step  
Introduction)

Communication  
between two  
process  
using signals  
in C

tolower()  
function in C

Passing  
Reference to  
a Pointer in  
C++

Difference  
between  
const int\*,  
const int \*  
const, and  
int const \*

How does a  
C program  
executes?

How to avoid  
Structure  
Padding in  
C?

Difference  
between Call  
by Value and  
Call by  
Reference

strrev()  
function in C

Interesting  
facts about  
C Language

Difference  
between  
fundamental  
data types  
and derived  
data types

C++:  
Methods of  
code  
shortening in  
competitive  
programming

Inline  
function in C



## Segmentation Fault (SIGSEGV) vs Bus Error (SIGBUS)

**Segmentation fault(SIGSEGV)** and **Bus error(SIGBUS)** are signals generated when serious program error is detected by the operating system and there is no way the program could continue to execute because of these errors.

**1) Segmentation Fault** (also known as SIGSEGV and is usually signal 11) occur when the program tries to write/read outside the memory allocated for it or when writing memory which can only be read. In other words when the program tries to access the memory to which it doesn't have access to. SIGSEGV is abbreviation for "Segmentation Violation".

Few cases where SIGSEGV signal generated are as follows,

- > Using uninitialized pointer
- > De-referencing a NULL pointer
- > Trying to access memory that the program doesn't own (eg. trying to access an array element out of array bounds).
- > Trying to access memory which is already de-allocated (trying to use dangling pointers).

Please refer [this](#) article for examples.

**2) Bus Error** (also known as SIGBUS and is usually signal 10) occur when a process is trying to access memory that the CPU cannot physically address. In other words the memory tried to access by the program is not a valid memory address. It caused due to alignment issues with the CPU (eg. trying to read a long from an address which isn't a multiple of 4). SIGBUS is abbreviation for "Bus Error".

SIGBUS signal occurs in below cases,





- > Program instructs the CPU to read or write a specific physical memory address

which is not valid / Requested physical address is unrecognized by the whole computer system.

-> Unaligned access of memory (For example, if multi-byte accesses must be 16 bit-aligned, addresses (given in bytes) at 0, 2, 4, 6, and so on would be considered aligned and therefore accessible, while addresses 1, 3, 5, and so on would be considered unaligned.)

**The main difference** between Segmentation Fault and Bus Error is that Segmentation Fault indicates an invalid access to a valid memory, while Bus Error indicates an access to an invalid address.

Below is an example of Bus Error taken from [wikipedia](#).



```
// C program to demonstrate Bus Error
#include <stdlib.h>

int main(int argc, char **argv)
{
    #if defined(__GNUC__)
    # if defined(__i386__)
        /* Enable Alignment Checking on x86 */
        __asm__("pushf\norl $0x40000, (%esp)\npopf");
    # elif defined(__x86_64__)
        /* Enable Alignment Checking on x86_64 */
        __asm__("pushf\norl $0x40000, (%rsp)\npopf");
    # endif
    #endif

    /* malloc() always provides aligned memory */
    char *cptr = malloc(sizeof(int) + 1);

    /* Increment the pointer by one, making it
       misaligned */
    int *iptr = (int *) ++cptr;

    /* Dereference it as an int pointer, causing
       an unaligned access */
    *iptr = 42;

    /* Following accesses will also result in
       sigbus error.
       short *sptr;
       int    i;

       sptr = (short *)&i;

       // For all odd value increments, it will
       // result in sigbus.
       sptr = (short *)(((char *)sptr) + 1);
       *sptr = 100;    */

    return 0;
}
```

Output :

Bad memory access (SIGBUS)

This article is contributed by **Prashanth Pangera**. If you like GeeksforGeeks and would like to contribute, you can also write an article using [contribute.geeksforgeeks.org](https://contribute.geeksforgeeks.org) or mail your article to [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org). See your article appearing on the

GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

## Recommended Posts:

[Core Dump \(Segmentation fault\) in C/C++](#)

[How to find Segmentation Error in C & C++ ? \(Using GDB\)](#)

[Memory Segmentation in 8086 Microprocessor](#)

[Else without IF and L-Value Required Error in C](#)

[Program error signals](#)

[Error Handling in C programs](#)

[Dividing a Large file into Separate Modules in C/C++, Java and Python](#)

[C program to store Student records as Structures and Sort them by Name](#)

[Similarities and Differences between Ruby and C language](#)

[Program to copy the contents of one array into another in the reverse order](#)

[Interesting facts about C Language](#)

[Program to Reverse a String using Pointers](#)

[Difference between Structure and Array in C](#)

[Structured Programming Approach with Advantages and Disadvantages](#)

**Article Tags :** [C](#) [C-Pointers](#) [system-programming](#)

**Practice Tags :** [C](#)



1

☐ To-do ☐ Done

1

Based on 2 vote(s)



[Feedback](#)[Add Notes](#)[Improve Article](#)

Please write to us at [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org) to report any issue with the above content.

Writing code in comment? Please use [ide.geeksforgeeks.org](https://ide.geeksforgeeks.org), generate link and share the link here.

[Load Comments](#)[Share this post!](#)

GeeksforGeeks  
A computer science portal for geeks

710-B, Advant Navis Business Park,  
Sector-142, Noida, Uttar Pradesh - 201305  
[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)

**COMPANY**

About Us  
Careers  
Privacy Policy  
Contact Us

**LEARN**

Algorithms  
Data Structures  
Languages  
CS Subjects  
Video Tutorials

**PRACTICE**

Company-wise  
Topic-wise  
Contests  
Subjective Questions

**CONTRIBUTE**

Write an Article  
Write Interview  
Experience  
Internships  
Videos

@geeksforgeeks, Some rights reserved