

Advantages of vector over array in C++

Difficulty Level : Medium ● Last Updated : 30 Oct, 2018

We have already discussed [arrays](#) and [vectors](#). In this post, we will discuss advantages of vector over normal array.

Advantages of Vector over arrays :

1. Vector is **template class** and is **C++ only construct** whereas arrays are **built-in language construct** and present in both C and C++.
2. Vector are implemented as **dynamic arrays with list interface** whereas arrays can be implemented as **statically or dynamically** with **primitive data type** interface.

```
#include <bits/stdc++.h>
using namespace std;

int main()
{
    int array[100]; // Static Implementation
    int* arr = new int[100]; // Dynamic Implementation
    vector<int> v; // Vector's Implementation
    return 0;
}
```

3. **Size of arrays are fixed** whereas the **vectors are resizable** i.e they can grow and shrink as vectors are allocated on heap memory.

```
#include <bits/stdc++.h>
using namespace std;

int main()
{
    int array[100]; // Static Implementation

    cout << "Size of Array " << sizeof(array) / sizeof(array[0]) << "\n";

    vector<int> v; // Vector's Implementation

    // Inserting Values in Vector
```

```

    v.push_back(3);
    v.push_back(4);
    v.push_back(5);

    cout << "Size of vector Before Removal=" << v.size() << "\n";

    // Output Values of vector
    for (auto it : v)
        cout << it << " ";

    v.erase(v.begin() + 2); // Remove 3rd element

    cout << "\nSize of vector After removal=" << v.size() << "\n";

    // Output Values of vector
    for (auto it : v)
        cout << it << " ";

    return 0;
}

```

Output:

```

Size of Array 100
Size of vector Before Removal=5
1 2 3 4 5
Size of vector After removal=4
1 2 4 5

```

4. Arrays **have to be deallocated explicitly** if defined dynamically whereas vectors are **automatically de-allocated** from heap memory.

```

#include <bits/stdc++.h>
using namespace std;

int main()
{
    int* arr = new int[100]; // Dynamic Implementation
    delete[] arr; // array Explicitly deallocated

    vector<int> v; // Automatic deallocation when variable goes out of scop
    return 0;
}

```

5. Size of array **cannot be determined** if **dynamically allocated** whereas Size of the vector can be determined in **O(1) time**.
6. When arrays are passed to a function, a **separate parameter for size is also passed** whereas in case of passing a vector to a function, there is no such need as **vector maintains variables which keeps track of size of container at all**

```

#include <bits/stdc++.h>
using namespace std;

int main()
{
    int* arr = new int[100]; // Dynamic Implementation

    cout << "Size of array= ";
    cout << sizeof(arr) / sizeof(*arr) << "\n"; // Pointer cannot be used to
    // block pointed by it
    return 0;
}

```

Output:

Size of array= 2

7. When array becomes full and new elements are inserted; **no reallocation is done implicitly** whereas When vector becomes larger than its capacity, reallocation is done implicitly.
8. **Arrays cannot be returned unless dynamically allocated from a function** whereas **vectors can be returned from a function**.

```

// Program to demonstrate arrays cannot be returned
#include <bits/stdc++.h>
using namespace std;

int* getValues()
{
    int arr[10]; // Array defined locally
    for (int i = 0; i < 10; i++) // Putting Values in array
        arr[i] = i + 1;

    return arr; // returning pointer to array
}

// main function
int main()
{
    int* array; // pointer of int type

    array = getValues(); // Call function to get arr

    for (int i = 0; i < 10; i++) { // Printing Values
        cout << "*(array + " << i << " ) : ";
        cout << *(array + i) << endl;
    }

    return 0;
}

```

Output:

warning: address of local variable 'arr' returned [-Wreturn-local-ad
Segmentation Fault (SIGSEGV)

```
// Program to demonstrate vector can be returned
#include <bits/stdc++.h>
using namespace std;

// Function returning vector
vector<int> getValues()
{
    vector<int> v; // Vector defined locally
    for (int i = 0; i < 10; i++) // Inserting values in Vector
        v.push_back(i + 1);

    return v; // returning pointer to array
}

// main function
int main()
{
    vector<int> get;

    get = getValues(); // Call function to get v

    // Output Values of vector
    for (auto it : get)
        cout << it << " ";

    return 0;
}
```

1 2 3 4 5 6 7 8 9 10

9. Arrays cannot be copied or assigned directly whereas Vectors can be copied or assigned directly.

```
#include <bits/stdc++.h>
using namespace std;

// main function
int main()
{
    vector<int> v; // Vector defined locally
    for (int i = 0; i < 10; i++)
        v.push_back(i + 1);

    vector<int> get;

    get = v; // Copying vector v into vector get

    cout << "vector get:\n";
    for (auto it : get)
        cout << it << " ";

    int arr[10];
    for (int i = 0; i < 10; i++) // Putting Values in array
        arr[i] = i + 1;

    int copyArr[10];

    copyArr = arr; // Error

    return 0;
}
```

Output:

vector get:
1 2 3 4 5 6 7 8 9 10

error: invalid array assignment
copyArr=arr;

Like 0

[Previous](#)

[Python | Count the Number of matching characters in a pair of string](#)

[Next](#)

[Java AWT | MouseInfo and PointerInfo](#)

RECOMMENDED ARTICLES

Page : [1](#) [2](#) [3](#)

01 [vector::front\(\) and vector::back\(\) in C++ STL](#)
22, Dec 17

05 [vector :: cbegin\(\) and vector :: cend\(\) in C++ STL](#)
01, May 18

02 [vector::push_back\(\) and vector::pop_back\(\) in C++ STL](#)
22, Dec 17

06 [How to flatten a Vector of Vectors or 2D Vector in C++](#)
07, Apr 20

03 [vector::operator= and vector::operator\[\] in C++ STL](#)
09, Jan 18

07 [vector::empty\(\) and vector::size\(\) in C++ STL](#)
22, Dec 17

04 [vector::crend\(\) & vector::crbegin\(\) with example](#)
17, Jan 18

08 [vector::begin\(\) and vector::end\(\) in C++ STL](#)
22, Jan 18

Article Contributed By :



Abhishek rajput

@Abhishek rajput

Vote for difficulty

Current difficulty : [Medium](#)

Easy

Normal

Medium

Hard

Expert

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

Improved By : [nikhil_jsk](#)

Article Tags : [cpp-array](#), [cpp-vector](#), [Arrays](#), [Data Structures](#), [Difference Between](#)

Practice Tags : [Data Structures](#), [Arrays](#)

Improve Article

Report Issue

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments



5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company

[About Us](#)
[Careers](#)
[Privacy Policy](#)
[Contact Us](#)
[Copyright Policy](#)

Practice

[Courses](#)
[Company-wise](#)
[Topic-wise](#)
[How to begin?](#)

Learn

[Algorithms](#)
[Data Structures](#)
[Languages](#)
[CS Subjects](#)
[Video Tutorials](#)

Contribute

[Write an Article](#)
[Write Interview Experience](#)
[Internships](#)
[Videos](#)

@geeksforgeeks , Some rights reserved