

# GeeksforGeeks

A computer science portal for geeks

[Practice](#)[Login](#)[Write an Article](#)

unordered\_set  
in C++ STL

unordered\_map  
in C++ STL

Sorting a  
vector in C++

vector  
insert()  
function in  
C++ STL

string find in  
C++

map insert()  
in C++ STL

swap() in  
C++

map find()  
function in  
C++ STL

set find()  
function in  
C++ STL

Check if a  
given graph  
is Bipartite



using DFS

vector ::  
assign() in  
C++ STL

Pre-  
increment  
and Post-  
increment in  
C/C++

static\_cast in  
C++ | Type  
Casting  
operators

map count()  
function in  
C++ STL

Sum of array  
Elements  
without  
using loops  
and  
recursion

set insert()  
function in  
C++ STL

How to  
return  
multiple  
values from  
a function in  
C or C++?

std::any  
Class in C++



vector  
rbegin() and  
rend()  
function in  
C++ STL

Applications  
of Pointers in  
C/C++

map erase()  
function in  
C++ STL

Memory leak  
in C++ and  
How to avoid  
it?

STL Priority  
Queue for  
Structure or  
Class

Loader in  
C/C++

vector  
emplace()  
function in  
C++ STL

list erase()  
function in  
C++ STL

Types of  
Operator  
Overloading  
in C++



Check if X  
can give  
change to  
every person  
in the Queue

set  
lower\_bound()  
function in  
C++ STL

multimap  
insert() in  
C++ STL



## Map in C++ Standard Template Library (STL)

Maps are associative containers that store elements in a mapped fashion. Each element has a key value and a mapped value. No two mapped values can have same key values.

Some basic functions associated with Map:

**begin()** – Returns an iterator to the first element in the map

**end()** – Returns an iterator to the theoretical element that follows last element in the map

**size()** – Returns the number of elements in the map

**max\_size()** – Returns the maximum number of elements that the map can hold

**empty()** – Returns whether the map is empty

**pair insert(keyvalue, mapvalue)** – Adds a new element to the map

**erase(iterator position)** – Removes the element at the position pointed by the iterator







`erase(const g)` – Removes the key value 'g' from the map

`clear()` – Removes all the elements from the map

#### Content Delivery Network - Redefining CDN at the

Security is built-in, not bolted on. Deliver content with peace of m



```

#include <iostream>
#include <iterator>
#include <map>

using namespace std;

int main()
{
    // empty map container
    map<int, int> gquiz1;

    // insert elements in random order
    gquiz1.insert(pair<int, int>(1, 40));
    gquiz1.insert(pair<int, int>(2, 30));
    gquiz1.insert(pair<int, int>(3, 60));
    gquiz1.insert(pair<int, int>(4, 20));
    gquiz1.insert(pair<int, int>(5, 50));
    gquiz1.insert(pair<int, int>(6, 50));
    gquiz1.insert(pair<int, int>(7, 10));

    // printing map gquiz1
    map<int, int>::iterator itr;
    cout << "\nThe map gquiz1 is : \n";
    cout << "\tKEY\tELEMENT\n";
    for (itr = gquiz1.begin(); itr != gquiz1.end(); ++itr) {
        cout << '\t' << itr->first
            << '\t' << itr->second << '\n';
    }
    cout << endl;

    // assigning the elements from gquiz1 to gquiz2
    map<int, int> gquiz2(gquiz1.begin(), gquiz1.end());

    // print all elements of the map gquiz2
    cout << "\nThe map gquiz2 after"
        << " assign from gquiz1 is : \n";
    cout << "\tKEY\tELEMENT\n";
    for (itr = gquiz2.begin(); itr != gquiz2.end(); ++itr) {
        cout << '\t' << itr->first
            << '\t' << itr->second << '\n';
    }
    cout << endl;

    // remove all elements up to
    // element with key=3 in gquiz2
    cout << "\ngquiz2 after removal of"
        << " elements less than key=3 : \n";
    cout << "\tKEY\tELEMENT\n";
    gquiz2.erase(gquiz2.begin(), gquiz2.find(3));
    for (itr = gquiz2.begin(); itr != gquiz2.end(); ++itr)
        cout << '\t' << itr->first
            << '\t' << itr->second << '\n';
}

```

**Output:**

The map gquiz1 is :

KEY	ELEMENT
1	40
2	30
3	60
4	20
5	50
6	50
7	10

The map gquiz2 after assign from gquiz1 is :

KEY	ELEMENT
1	40
2	30
3	60
4	20
5	50
6	50
7	10

gquiz2 after removal of elements less than key=3 :

KEY	ELEMENT
3	60
4	20
5	50
6	50
7	10

gquiz2.erase(4) : 1 removed

KEY	ELEMENT
3	60
5	50
6	50
7	10



<code>gquiz1.lower_bound(5) :</code>	<code>KEY = 5</code>	<code>ELEMENT = 50</code>
<code>gquiz1.upper_bound(5) :</code>	<code>KEY = 6</code>	<code>ELEMENT = 50</code>

### List of all functions of Map:


- **map insert() in C++ STL** – Insert elements with a particular key in the map container. .
- **map count() function in C++ STL** – Returns the number of matches to element with key value 'g' in the map.
- **map equal\_range() in C++ STL** – Returns an iterator of pairs. The pair refers to the bounds of a range that includes all the elements in the container which have a key equivalent to k.
- **map erase() function in C++ STL** – Used to erase element from the container.
- **map rend() function in C++ STL** – Returns a reverse iterator pointing to the theoretical element right before the first key-value pair in the map(which is considered its reverse end).
- **map rbegin() function in C++ STL** – Returns a reverse iterator which points to the last element of the map.
- **map find() function in C++ STL** – Returns an iterator to the element with key value 'g' in the map if found, else returns the iterator to end.
- **map crbegin() and crend() function in C++ STL** – **crbegin()** returns a constant reverse iterator referring to the last element in the map container. **crend()** returns a constant reverse iterator pointing to the theoretical element before the first element in the map.
- **map cbegin() and cend() function in C++ STL** – **cbegin()** returns a constant iterator referring to the first element in the map container. **cend()** returns a constant iterator pointing to the theoretical element that follows last element in the multimap.
- **map emplace() in C++ STL** – Inserts the key and its element in the map container.
- **map max\_size() in C++ STL** – Returns the maximum number of elements a map container can hold.
- **map upper\_bound() function in C++ STL** – Returns an iterator to the first element that is equivalent to mapped value with key value 'g' or definitely will go after the element with key value 'g' in the map
- **map operator= in C++ STL** – Assigns contents of a container to a different container, replacing its current content.
- **map lower\_bound() function in C++ STL** – Returns an iterator to the first element that is equivalent to mapped value with key value 'g' or definitely will not go before



the element with key value 'g' in the map.

- **map::emplace\_hint()** function in C++ STL – Inserts the key and its element in the map container with a given hint.
- **map::value\_comp()** in C++ STL – Returns the object that determines how the elements in the map are ordered ('<' by default).
- **map::key\_comp()** function in C++ STL – Returns the object that determines how the elements in the map are ordered ('<' by default).
- **map::size()** in C++ STL – Returns the number of elements in the map.
- **map::empty()** in C++ STL – Returns whether the map is empty.
- **map::begin()** and **end()** in C++ STL – **begin()** returns an iterator to the first element in the map. **end()** returns an iterator to the theoretical element that follows last element in the map
- **map::operator[]** in C++ STL – This operator is used to reference the element present at position given inside the operator.
- **map::clear()** in C++ STL – Removes all the elements from the map.
- **map::at()** and **map::swap()** in C++ STL – **at()** function is used to return the reference to the element associated with the key k. **swap()** function is used to exchange the contents of two maps but the maps must be of same type, although sizes may differ.

### Recent articles on Map



Please write comments if you find anything incorrect, or you want to share more infor-

mation about the topic discussed above




## Recommended Posts:

The C++ Standard Template Library (STL)  
Set in C++ Standard Template Library (STL)  
Multimap in C++ Standard Template Library (STL)  
List in C++ Standard Template Library (STL)  
Sort in C++ Standard Template Library (STL)  
Multiset in C++ Standard Template Library (STL)  
Pair in C++ Standard Template Library (STL)  
Deque in C++ Standard Template Library (STL)  
Queue in Standard Template Library (STL)  
Priority Queue in C++ Standard Template Library (STL)  
Binary Search in C++ Standard Template Library (STL)  
<algorithms> library in C++ STL  
snprintf() in C library  
<strings> library in C++ STL  
<numeric> library in C++ STL

Content Delivery Network - Total Security. Total Contr

Defend, accelerate, and innovate your websites, applications, AP

 cloudpath.com/cdn

**Article Tags :** C++ cpp-containers-library cpp-map STL

**Practice Tags :** STL CPP



3



**2.8**☐ To-do ☐ DoneBased on **42** vote(s)

Feedback

Add Notes

Improve Article

Please write to us at [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org) to report any issue with the above content.

Writing code in comment? Please use [ide.geeksforgeeks.org](https://ide.geeksforgeeks.org), generate link and share the link here.

Load Comments

Share this post!

GeeksforGeeks  
A computer science portal for geeks

710-B, Advant Navis Business Park,  
Sector-142, Noida, Uttar Pradesh - 201305  
[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)

**COMPANY**

About Us  
Careers  
Privacy Policy  
Contact Us

**LEARN**

Algorithms  
Data Structures  
Languages  
CS Subjects  
Video Tutorials

**PRACTICE**

Company-wise  
Topic-wise  
Contests  
Subjective Questions

**CONTRIBUTE**

Write an Article  
Write Interview  
Experience  
Internships  
Videos

@geeksforgeeks, Some rights reserved

