

# GeeksforGeeks

A computer science portal for geeks

[Courses](#)[Login](#)[Write an Article](#)

Sorting a  
vector in C++

string find in  
C++

Why array  
index starts  
from zero ?

Check if a  
given graph  
is Bipartite  
using DFS

How to  
return  
multiple  
values from  
a function in  
C or C++?

Applications  
of Pointers in  
C/C++

Pre-  
increment  
and Post-  
increment in  
C/C++

static\_cast in  
C++ | Type

Casting  
operators

Sum of array  
Elements  
without  
using loops  
and  
recursion

"static const"  
vs "#define"  
vs "enum"

How to find  
Segmentation  
Error in C &  
C++ ? (Using  
GDB)

Why strcpy  
and strncpy  
are not safe  
to use?

Memory leak  
in C++ and  
How to avoid  
it?

Loader in  
C/C++

Type  
Conversion  
in C++

GDB (Step by  
Step  
Introduction)

Modulus

function in  
C++ STL

Some useful  
C++ tricks  
for beginners  
in  
Competitive  
Programming

Interesting  
Facts about  
C++

Passing  
Reference to  
a Pointer in  
C++

Difference  
between Call  
by Value and  
Call by  
Reference

Difference  
between  
fundamental  
data types  
and derived  
data types

Types of  
Operator  
Overloading  
in C++

list insert() in  
C++ STL

std::any

Class in C++

C++:  
Methods of  
code  
shortening in  
competitive  
programming

Split a string  
in equal  
parts such  
that all parts  
are  
palindromes

Amadeus  
Labs R & D |  
On Campus  
(freshers) |  
Full  
time+Internship

#pragma  
Directive in  
C/C++

Measure  
execution  
time with  
high  
precision in  
C/C++







## Multimap in C++ Standard Template Library (STL)

Multimap is similar to `map` with an addition that multiple elements can have same keys. Rather than each element being unique, the key value and mapped value pair has to be unique in this case.

**Some Basic Functions associated with multimap:**

- **begin()** – Returns an iterator to the first element in the multimap
- **end()** – Returns an iterator to the theoretical element that follows last element in the multimap
- **size()** – Returns the number of elements in the multimap
- **max\_size()** – Returns the maximum number of elements that the multimap can hold
- **empty()** – Returns whether the multimap is empty
- **pair<int,int> insert(keyvalue,multimapvalue)** – Adds a new element to the multimap

### C++ implementation to illustrate above functions



```
#include <iostream>
#include <map>
#include <iterator>

using namespace std;

int main()
{
    multimap <int, int> gquiz1;           // empty multimap contain

    // insert elements in random order
    gquiz1.insert(pair <int, int> (1, 40));
    gquiz1.insert(pair <int, int> (2, 30));
    gquiz1.insert(pair <int, int> (3, 60));
    gquiz1.insert(pair <int, int> (4, 20));
    gquiz1.insert(pair <int, int> (5, 50));
    gquiz1.insert(pair <int, int> (6, 50));
    gquiz1.insert(pair <int, int> (6, 10));

    // printing multimap gquiz1
    multimap <int, int> :: iterator itr;
    cout << "\nThe multimap gquiz1 is : \n";
    cout << "\tKEY\tELEMENT\n";
    for (itr = gquiz1.begin(); itr != gquiz1.end(); ++itr)
    {
        cout << '\t' << itr->first
              << '\t' << itr->second << '\n';
    }
    cout << endl;

    // assigning the elements from gquiz1 to gquiz2
    multimap <int, int> gquiz2(gquiz1.begin(),gquiz1.end());

    // print all elements of the multimap gquiz2
    cout << "\nThe multimap gquiz2 after assign from gquiz1 is : \n";
    cout << "\tKEY\tELEMENT\n";
    for (itr = gquiz2.begin(); itr != gquiz2.end(); ++itr)
    {
        cout << '\t' << itr->first
              << '\t' << itr->second << '\n';
    }
    cout << endl;

    // remove all elements up to element with value 30 in gquiz2
    cout << "\ngquiz2 after removal of elements less than key=3 : \n";
    cout << "\tKEY\tELEMENT\n";
    gquiz2.erase(gquiz2.begin(), gquiz2.find(3));
    for (itr = gquiz2.begin(); itr != gquiz2.end(); ++itr)
    {
        cout << '\t' << itr->first
              << '\t' << itr->second << '\n';
    }

    // remove all elements with key = 4
```

Output:

The multimap gquiz1 is :

KEY	ELEMENT
1	40
2	30
3	60
4	20
5	50
6	50
6	10

The multimap gquiz2 after assign from gquiz1 is :

KEY	ELEMENT
1	40
2	30
3	60
4	20
5	50
6	50
6	10

gquiz2 after removal of elements less than key=3 :

KEY	ELEMENT
3	60
4	20
5	50
6	50
6	10

gquiz2.erase(4) : 1 removed

KEY	ELEMENT
3	60
5	50
6	50
6	10

gquiz1.lower\_bound(5) :      KEY = 5              ELEMENT = 50

gquiz1.upper\_bound(5) :      KEY = 6              ELEMENT = 50



### List of Functions of Multimap:

- **multimap::operator=** in C++ STL – It is used to assign new contents to the container by replacing the existing contents.
- **multimap::crbegin()** and **multimap::crend()** in C++ STL – **crbegin()** returns a constant reverse iterator referring to the last element in the multimap container. **crend()** returns a constant reverse iterator pointing to the theoretical element before the first element in the multimap.
- **multimap::emplace\_hint()** in C++ STL – Inserts the key and its element in the multimap container with a given hint.
- **multimap clear()** function in C++ STL – Removes all the elements from the multimap.
- **multimap empty()** function in C++ STL – Returns whether the multimap is empty.
- **multimap maxsize()** in C++ STL – Returns the maximum number of elements a multimap container can hold.
- **multimap value\_comp()** function in C++ STL – Returns the object that determines how the elements in the multimap are ordered ('<' by default)
- **multimap rend** in C++ STL – Returns a reverse iterator pointing to the theoretical element preceding to the first element of the multimap container.
- **multimap::cbegin()** and **multimap::cend()** in C++ STL – **cbegin()** returns a constant iterator referring to the first element in the multimap container. **cend()** returns a constant iterator pointing to the theoretical element that follows last element in the multimap.
- **multimap::swap()** in C++ STL – Swap the contents of one multimap with another multimap of same type and size.
- **multimap rbegin** in C++ STL – Returns an iterator pointing to the last element of the container.
- **multimap size()** function in C++ STL – Returns the number of elements in the multimap container.
- **multimap::emplace()** in C++ STL – Inserts the key and its element in the multimap container.
- **multimap::begin()** and **multimap::end()** in C++ STL – **begin()** returns an iterator referring to the first element in the multimap container. **end()** returns an iterator to the theoretical element that follows last element in the multimap.
- **multimap upper\_bound()** function in C++ STL – Returns an iterator to the first element that is equivalent to multimapped value with key value 'g' or definitely will go after the element with key value 'g' in the multimap.
- **multimap::count()** in C++ STL – Returns the number of matches to element with key value 'g' in the multimap.

- [multimap::erase\(\) in C++ STL](#) – Removes the key value from the multimap.
- [multimap::find\(\) in C++ STL](#) – Returns an iterator to the element with key value 'g' in the multimap if found, else returns the iterator to end.
- [multimap equal\\_range\(\) in C++ STL](#) – Returns an iterator of pairs. The pair refers to the bounds of a range that includes all the elements in the container which have a key equivalent to k.
- [multimap insert\(\) in C++ STL](#) – Used to insert elements in the multimap container.
- [multimap lower\\_bound\(\) function in C++ STL](#) – Returns an iterator to the first element that is equivalent to multimapped value with key value 'g' or definitely will not go before the element with key value 'g' in the multimap.
- [multimap key\\_comp\(\) in C++ STL](#) – Returns the object that determines how the elements in the multimap are ordered ('<' by default).

### Recent articles on Multimap

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

### Recommended Posts:

[Set in C++ Standard Template Library \(STL\)](#)  
[The C++ Standard Template Library \(STL\)](#)  
[Map in C++ Standard Template Library \(STL\)](#)  
[List in C++ Standard Template Library \(STL\)](#)  
[Sort in C++ Standard Template Library \(STL\)](#)  
[Multiset in C++ Standard Template Library \(STL\)](#)  
[Queue in Standard Template Library \(STL\)](#)  
[Deque in C++ Standard Template Library \(STL\)](#)  
[Pair in C++ Standard Template Library \(STL\)](#)  
[Priority Queue in C++ Standard Template Library \(STL\)](#)  
[Binary Search in C++ Standard Template Library \(STL\)](#)  
[multimap::cbegin\(\) and multimap::crend\(\) in C++ STL](#)  
[multimap::cbegin\(\) and multimap::cend\(\) in C++ STL](#)  
[multimap::begin\(\) and multimap::end\(\) in C++ STL](#)  
[multimap insert\(\) in C++ STL](#)



**Article Tags :** C++ cpp-containers-library cpp-multimap cpp-multimap-functions STL

**Practice Tags :** STL CPP



Be the First to upvote.

☐ To-do ☐ Done

**2.2**

Based on **10** vote(s)

Feedback

Add Notes

Improve Article

Please write to us at [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org) to report any issue with the above content.

Writing code in comment? Please use [ide.geeksforgeeks.org](https://ide.geeksforgeeks.org), generate link and share the link here.

Load Comments

Share this post!

GeeksforGeeks  
A computer science portal for geeks

710-B, Advant Navis Business Park,  
Sector-142, Noida, Uttar Pradesh - 201305  
[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)

#### COMPANY

About Us  
Careers  
Privacy Policy  
Contact Us

#### LEARN

Algorithms  
Data Structures  
Languages  
CS Subjects  
Video Tutorials

#### PRACTICE

Company-wise  
Topic-wise  
Contests  
Subjective Questions

#### CONTRIBUTE

Write an Article  
Write Interview  
Experience  
Internships  
Videos

@geeksforgeeks, Some rights reserved