

Introduction to Deep Learning and Caffe

HE Shuncheng
hsc12@outlook.com

Tsinghua-Seagate Future Robotics Club
Association of Science and Technology of Automation

November 2, 2015

Contents

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com

Classification Task

Classification Task

Structure of ANN

Structure of ANN

CNN for Image
Classification

CNN for Image Classification

Caffe for CNN

Caffe for CNN

Using Caffe - An
Example

Using Caffe - An Example

Binary Classification

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com

Classification Task

Structure of ANN

CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example



Figure 1: a cat?




Figure 2: a dog?

Binary Classification: Given input data x (e.g. a picture), the output of a binary classifier $y = f(x)$ is one label retrieved from a set of two labels $y \in \{\pm 1\}$.

Linear Classifier

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com


Classification Task

Structure of ANN

CNN for Image
Classification


Caffe for CNN

Using Caffe - An
Example



Data set $\mathcal{D} = \{(x_1^{(1)}, x_2^{(1)}), \dots, (x_1^{(n)}, x_2^{(n)})\}$
A linear binary classifier is a
hyperplane $w^T x = b$
 $f(x) = \text{sgn}(w^T x - b)$

Performance of Linear Classifier



True Positive:

$$y = +1, f(x) = +1$$

True Negative:

$$y = -1, f(x) = -1$$

False Positive:

$$y = -1, f(x) = +1$$

False Negative:

$$y = +1, f(x) = -1$$

Accuracy:


$$\frac{TP+TN}{n}$$

Error Rate:


$$\frac{FP+FN}{n}$$

A good classifier: **minizing** the error rate

Basic Concepts



Training Set
Test Set
Training Error
Generalization Error
Overfitting
Loss Function



Overfitting

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com


Classification Task

Structure of ANN


CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example



Perceptron



Perceptron

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com


Classification Task

Structure of ANN

CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example




Training Algorithm

Define a loss function:

$$E(w) = \frac{1}{2} \sum_{d \in \mathcal{D}} (t_d - o_d)^2$$

How to reduce loss?



Gradient Descent

Gradient w.r.t. w

$$\nabla E(w) = \left(\frac{\partial E}{\partial w_0}, \frac{\partial E}{\partial w_1}, \dots, \frac{\partial E}{\partial w_n} \right)^T$$

in where

$$\frac{\partial E}{\partial w_i} = \sum_{d \in \mathcal{D}} (t_d - o_d)(-x_i^{(d)})$$

for every iteration (η denotes learning rate)

$$w_i \leftarrow w_i + \Delta w_i$$

$$\Delta w_i = -\eta \frac{\partial E}{\partial w_i} = \eta \sum_{d \in \mathcal{D}} (t_d - o_d) x_i^{(d)}$$


$$\forall i \in [n]$$

Artificial Neural Network

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com

Structure of ANN



$$x^{l+1} = h(W^{T+1}x^l)$$

h is a non-linear function.

Classification Task

Structure of ANN


CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example

Sigmoid Function

$$h(x) = \frac{1}{1 + e^{-x}}$$



- ▶ 1. continuous
- ▶ 2. map $[-\infty, +\infty]$ to $[0, 1]$
- ▶ 3. nonlinearity
- ▶ 4. $h'(x)$ is easy to calculate

$$h'(x) = h(x)(1 - h(x))$$

Back Propagation and Delta Rule

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com

Classification Task

Structure of ANN

CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example

Please refer to [this page](#)

Mathematical model of ANN

$$x^l = f(u^l), u^l = (W^{l-1})^T x^{l-1} + b^l$$

where l denotes the current layer with the output layer designated to be layer L and the input layer designated to be layer 1. Function $f(\cdot)$ is a nonlinear function (i.e. sigmoid or hyperbolic tangent).

Define loss function as

$$E(x^L, t)$$

where x^L is the network output and t is the target output.

Back Propagation and Delta Rule

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com

Classification Task

Structure of ANN

CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example

Expand the loss function

$$E(x^L, t) = E(f((W^{L-1})^T x^{L-1}), t)$$

Using chain rule, we can write the derivatives w.r.t. W^{L-1}

$$\frac{\partial E}{\partial W^{L-1}} = x^{L-1} (f'(u^L) \star \frac{\partial E}{\partial x^L})^T$$

where \star denotes elementwise multiplication, and if we define

$$\delta^L = f'(u^L) \star \frac{\partial E}{\partial x^L}$$

we get

$$\frac{\partial E}{\partial W^{L-1}} = x^{L-1} (\delta^L)^T$$

Back Propagation and Delta Rule

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com

Classification Task

Structure of ANN

CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example

If we calculate the δ term recursively

$$\delta^l = f'(u^l) \star ((W^l)^T \delta^{l+1}), l = L - 1, \dots, 2$$

it is easy to write

$$\frac{\partial E}{\partial W^l} = x^l (\delta^{l+1})^T, l = L - 2, \dots, 1$$

Network Structure




Figure 3: structure of convolutional neural network

- ▶ Convolution Layer
- ▶ Pooling Layer (Subsampling)
- ▶ Full-connected Layer (Inner-product)
- ▶ ReLU Layer
- ▶ Softmax Layer

Convolution Layer

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com

Classification Task


Structure of ANN

CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example


kernel size= 3×3



$$g_{ij} = \sum_{s=i}^{i+2} \sum_{t=j}^{j+2} h_{st} k_{st}$$


Convolution Layer

stride=1



$$g_{ij} = \sum_{s=i}^{i+2} \sum_{t=j}^{j+2} h_{st} k_{st}$$

Pooling Layer



$$g_{ij} = \max\{h_{2i,2j}, h_{2i+1,2j}, h_{2i,2j+1}, h_{2i+1,2j+1}\}$$

No free parameter in pooling layer.

Inner-product

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com

Classification Task

Structure of ANN

CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example

Known as full-connected layer. Weights are designated from every input to every output, namely

$$y = W^T x$$

Rectified Linear Unit

A rectifier

$$y = \max\{0, x\}$$


A rectified linear unit

$$y = \ln(1 + e^x)$$

with its derivative w.r.t. x

$$\frac{dy}{dx} = \frac{1}{1 + e^{-x}}$$

ReLU improves efficiency of calculating.



Derived from softmax regression, extension of logistic regression for multi-label classification.

$$y_i = \frac{e^{x_i}}{\sum_{k=1}^n e^{x_k}}, \forall i \in [n]$$

Outputs of softmax layer are probabilities of each label.

MNIST Database

MNIST: Mixed National Institute of Standards and Technology



Figure 4: Handwritten Digits

10 distinguishing classes

LeNet Review




Figure 5: LeNet for MNIST

- ▶ input: a picture (size 28×28)
- ▶ conv1: 4 kernels (size 5×5)
- ▶ pool1: max pooling (size 2×2)
- ▶ conv2: 3 kernels (size 5×5)
- ▶ pool2: max pooling (size 2×2)
- ▶ ip: full-connected ($192 \rightarrow 10$)
- ▶ softmax: 10 inputs, 10 prob outputs

Caffe Tutorial

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com

Classification Task

Structure of ANN

CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example

For more information please refer to [this page](#).

Key words:

- ▶ Nets, Layers and Blobs
- ▶ Forward / Backward
- ▶ Loss
- ▶ Solver
- ▶ Layer Catalogue
- ▶ Interfaces
- ▶ Data

Nets, Layers and Blobs

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com


Classification Task

Structure of ANN

CNN for Image
Classification


Caffe for CNN

Using Caffe - An
Example



Example: Softmax Regression

Forward / Backward



Softmax:

$$y_i(x) = \frac{e^{x_i}}{\sum_{k=1}^n e^{x_k}}, \forall i \in [n]$$

Softmax loss function:

let label j be groundtruth, therefore

$$L = -\ln(y_j(x)) = -\ln\left(\frac{e^{x_j}}{\sum_{k=1}^n e^{x_k}}\right) = \ln\left(\sum_{k=1}^n e^{x_k}\right) - x_j$$

$$\frac{\partial L}{\partial x_i} = y_i(x) - \delta_{ij}$$

where $\delta_{ij} = 1$ iff $i = j$, and $\delta_{ij} = 0$ otherwise.

Classification Task

Structure of ANN

CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example

SGD (Stochastic Gradient Descent)

$$\begin{aligned}w_{t+1} &= w_t + \Delta w_t \\ \Delta w_{t+1} &= \mu \Delta w_t - \alpha \frac{\partial L}{\partial w_t}\end{aligned}$$

α : learning rate

μ : momentum

Solver parameters (i.e.):

- ▶ basic learning rate: $\alpha = 0.01$
- ▶ learning rate policy: step (reduce learning rate according to step size)
- ▶ step size: 100000
- ▶ gamma: 0.1 (multiply learning rate with factor 0.1 after step size)
- ▶ momentum: $\mu = 0.9$
- ▶ max iteration: 350000 (stop at iteration 350000)

Layer Catalogue

Please refer to [this page](#).

Vision layer:

- ▶ convolution
- ▶ pooling

Loss layer:

- ▶ softmax loss
- ▶ Euclidean loss
- ▶ cross-entropy

Activation layer:

- ▶ sigmoid
- ▶ ReLU
- ▶ hyperbolic tangent

Layer Catalogue

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com

Classification Task

Structure of ANN

CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example

Data layer:

- ▶ database
- ▶ in-memory
- ▶ HDF5 input
- ▶ HDF5 output

Common layer:

- ▶ inner product
- ▶ splitting
- ▶ flatening
- ▶ reshape
- ▶ concatenation

Installation

Prerequisites:

protobuf, CUDA, OpenBLAS, Boost, OpenCV, Imdb, leveldb, cuDNN(optional), Python(optional), numpy(optional), MATLAB(optional)

Install:

```
git clone git://github.com/BVLC/caffe  
/your/own/caffe/folder
```

Go to Caffe root folder

```
cp Makefile.config.example Makefile.config  
make all  
make test  
make runtest
```

Hardware:

K40, K20, Titan for ImageNet scale
GTX series or GPU-equipped MacBook Pro for small datasets

LeNet Example

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com

Classification Task

Structure of ANN

CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example

LeNet Structure

1. Protobuf Protocol

2. Run!

How to be Professional?

Introduction to
Deep Learning and
Caffe

HE Shuncheng
hsc12@outlook.com

Classification Task

Structure of ANN

CNN for Image
Classification

Caffe for CNN

Using Caffe - An
Example

1. Figure out theoretical keypoints (read papers)
2. Read Caffe source code
3. Be proficient at programming and debugging skills
4. Take advantage of search engine and community
5. Do it through this pipeline:
 - ▶ Experiment design
 - ▶ Data preparation (build database with tools)
 - ▶ Model selection (including network and solver)
 - ▶ Training
 - ▶ Analysis and comparison