

NAME :- Pranav Shetty

Roll no :- 53

```
#include<stdio.h>

#include<graphics.h>

int main()
{
    long x,y,x_center,y_center;

    long a_sqr,b_sqr,fx,fy,d,a,b,tmp1,tmp2;
    int g_driver=DETECT,g_mode;

    initgraph(&g_driver,&g_mode,"");
    prin ("*MID POINT ELLIPSE*");
    prin ("\n Enter coordinate x = ");
    scanf("%ld",&x_center);
    printf(" Enter coordinate y = ");
    scanf("%ld",&y_center);
    printf("\n Now Enter constants a =");
    scanf("%ld",&a,&b);
    printf(" Now Enter constants b =");
    scanf("%ld",&b);

    x=0;
    y=b;

    a_sqr=a*a;
    b_sqr=b*b;
    fx=2*b_sqr*x;
    fy=2*a_sqr*y;

    d=b_sqr-(a_sqr*b) + (a_sqr*0.25);
```

```

do
{

putpixel(x_center+x,y_center+y,1);
putpixel(x_center-x,y_center-y,1);
putpixel(x_center+x,y_center-y,1);
putpixel(x_center-x,y_center+y,1);
if(d<0)
{
d=d+fx+b_sqr;
}
else
{
y=y-1;
d=d+fx+-fy+b_sqr;
fy=fy-(2*a_sqr);
}
x=x+1;
fx=fx+(2*b_sqr);
delay(10);
}
while(fx<fy);    tmp1=(x+0.5)*(x+0.5);
tmp2=(y-1)*(y-1);
d=b_sqr*tmp1+a_sqr*tmp2-(a_sqr*b_sqr);

do
{

putpixel(x_center+x,y_center+y,1);

```

```

putpixel(x_center-x,y_center-y,1);
putpixel(x_center+x,y_center-y,1);
putpixel(x_center-x,y_center+y,1);

        if(d>=0)
            d=d-fy+a_sqr;
        else
        {
            x=x+1;
            d=d+fx-fy+a_sqr;
            fx=fx+(2*b_sqr);
        }
        y=y-1;
        fy=fy-(2*a_sqr);
    }
    while (y>0);
getch();
closegraph();
}

```

MID POINT ELLIPSE

Enter coordinate $x = 200$

Enter coordinate $y = 150$

Now Enter constants $a = 100$

Now Enter constants $b = 50$

