Index

A.O. Smith Engineered Storage Products Co., T-1 to T-8
ABB Lummus Crest, C-14
abrasives, A-1 to A-8
  bond of, A-5 to A-7
  characteristics of, A-4, 4
  computer numerical control (CNC) and, A-1 to A-3
  friability of, A-3 to A-4, A-6
  grade or hardness of, A-5 to A-7
  grain size of, A-6
  grinding wheels and, A-3 to A-7
  grit size of, A-5 to A-6
  material data safety sheet for, A-8
  packaging of, A-7 to A-8
  peening processes, A-7 to A-9
  physical characteristics of, A-2
  pumping fluids containing, P-274
  selection of, A-5 to A-7
  "stations" of, A-5
  structure or bulk density of, A-5
absolute pressure switches, C-383
absolute separators vertical, S-16 to S-19
absorbers
  in air pollution control and, A-83, A-96 to A-97
  of sound, A-11
absorptive linings in soundproofing panels, A-33 to A-37
absorptivity, M-10
Abtech Scientific Inc., P-6
acceleration
  braking properties and, C-347 to C-350
  in electric motors and, E-3 to E-5, E-12, E-24, E-29
  in fans, F-3
  vibrational analysis (VA) and, C-265, C-287, C-305, C-311
accelerometers, C-269, C-324
accident management, A-9
accreditation, ASME, Sp-25 to Sp-28, Sp-34
accuracy in degrees, thermometers, M-2
acetaldehyde, P-10 to P-32, P-40 to P-57, V-15
acetic acid, V-15
acetic anhydride, V-15
acetone, C-72, C-418, P-10 to P-31, P-40 to P-57, V-15
acetonitrile, P-10 to P-31, P-40 to P-57
acetylene, C-415
acid rain, A-9 to A-13, P-60 to P-62
acid treatment, R-5
acids, in lubricating oil, L-25
acoustic enclosures, turbine (*See* soundproofing and noise control), A-10 to A-37
acoustic performance, A-37
acoustics, in reciprocating (labyrinthine) compressors, C-116
acrolein, C-415
acrylamide, P-32
acrylic acid, P-10 to P-31, P-40 to P-57
acrylic baking enamel tank exterior coating, T-5
acrylic urethane tank exterior coating, T-5
acrylonitrile, P-10 to P-32, P-40 to P-57, V-15
activated carbon, R-6
activated diffusion healing (ADH), M-32
active vs. reactive sound fields, A-20
actual deposits, R-6
actuation values, switches, C-377
actuators, A-37 to A-47
  electrically controllable servo meter for, A-42
  electrohydraulic, A-37 to A-47, F-31
  in fuel system control, F-30 to F-34
  hydraulic amplification in, A-41
  hysteresis in, A-41
  magnetic bearings using, B-5 to B-9
  proportional and dynamic conversion of electrical control signals, A-40
  Turcon CTo electrohydraulic actuator, A-47
acylamide, P-10 to P-31, P-40 to P-57
AD CARB, carbon–graphite mix products, C-8 to C-13
additives, petroleum processing, R-5 to R-6
adhesives, A-1
adiabatic expansion factor in, M-25
adipate, P-10 to P-31, P-40 to P-57
adjustable frequency electric motors, E-10 to E-15
adsorption, R-6
Advanced Carbon Products, C-8 to C-13
advanced pattern groove (APG) seals, S-3 to S-4
aerfoils (*See* metallurgy; turbines)
aerobic bacteria, R-7
aeroderivative fuel regulator for gas turbine, C-354 to C-358
aerosols, chlorofluorocarbons (CFCs) in, O-17 to O-18
AGFA, P-3 to P-7
aggregate, A-1
agitators, A-38, D-4
agriculture and agricultural product processing (*See also* food industry), A-48 to A-49, C-34, Sp-1 to Sp-3
  coolers for dairies/dairy products, C-412 to C-413, C-420
  crystallizers (*See* crystallizers)
  ejectors, E-2 to E-3
  environmental accountability, E-40 to E-49
  feeding management (livestock), E-44
  irradiation in, I-1 to I-5
  ISO VILJA technology in, E-46, E-48
  pollutants of, P-12
air blowing, R-7
air conditioning (*See also* refrigerants)
  development of, R-14 to R-15
  glycol as coolant in, C-413
  heat pump and, H-4
  R-22 refrigerant in, R-11 to R-13
  refrigerants and for, R-11 to R-13
  sizing of, C-422 to C-423
air density, fans, F-1, F-3
air entrained cement, C-22 to C-23, C-28
air filtration, A-49 to A-83
  bleed extraction systems for, A-51 to A-52
  bypass door for, A-53, A-59 to A-60, A-76
  cartridge type filter in, A-54, A-58
  chimneys and, cleaning of, C-78
  coalescer panels for, A-52 to A-53
  compressor damage in, A-75
  corrosion in, A-55 to A-59, A-64 to A-69, A-71 to A-79
  design suitability of, A-55 to A-61
  drains and drain valve in, A-56, A-62 to A-63
  dust vs., A-51 to A-52, A-56, A-66, A-70, A-74 to A-76
  dynamic water eliminator (Hydra) filters in, A-81
  erosion in, A-75 to A-78
  filter designs for, A-74
  filter elements for, A-53
  filter materials in, A-61, A-79 to A-81
  filter specifications for, offshore environment, A-77 to A-79
  flare carbon vs., A-74 to A-75
  fouling in, A-55 to A-57, A-76 to A-78
  future developments in, A-81
  high efficiency (Hercules) filters in, A-81 to A-82
  high volume flow in, A-81
  high vs. low velocity systems, A-74
  housing for, A-53 to A-54, A-58 to A-61, A-70
  huff and puff design in, A-49 to A-50
  humidity vs., A-51 to A-53, A-57, A-74
  icing conditions vs., A-49 to A-50
  insect ingestion in, A-49, A-51, A-66
  low pressure loss in, A-81 to A-83
  maritime use of, A-61
  materials used in, A-58
  National Gas Turbine Establishment (NGTE), A-69
  new designs for, A-61 to A-66
  offshore or coastal environments vs., A-57, A-66 to A-84
  oil fume ingestion in, A-49
  operational experiences with, A-53 to A-61
  particle fusion in, A-78
  pollutant ingestion and build up in, A-49
  pulse jet–type, A-49
  rainfall vs., A-50 to A-63
  salt corrosion in, A-57, A-61 to A-64, A-69 to A-74
  sand ingestion in, A-49
  silencer outlet of, A-64

specifications for, A-83
spin tubes in, A-57
stainless steel housing in, A-58, A-60, A-62 to A-63, A-71 to A-72
tropical environments and, A-50 to A-74
turbine damage in, A-58
vane separators for, A-63, A-74
water eliminator for, A-82 to A-83
weather louvers for, A-56, A-61, A-74
weatherhoods for, A-55 to A-56, A-60
air horsepower (ahp), fans, F-5
air inlet manifolds, compressors and, paint and corrosion damage in, T-74 to T-75
air movement studies, in explosion hazard assessment, E-68, E-71
air plasma coatings, M-35
air pollution control, A-83 to A-101, E-52, P-57 to P-60
absorbers for, A-83, A-96 to A-97
accidents/incidents and, E-46
blocking of catalyst vs., A-96
carbon dioxide (CO_2) (*See also* carbon dioxide)
carbon monoxide and, C-62 to C-64
Catpac TCR system in, A-100 to A-101
cement kilns and, C-22, C-28 to C-34
chemisorption in, A-96, A-98
chimneys and, cleaning of, C-78
chlorofluorocarbons (CFCs) in, C-413
combined unit systems for, A-83, A-99 to A-101
condensers and, C-233
continuous emissions monitoring (CEM) in, C-34
DeNox systems, A-90, A-93, A-100
dense phase technology in, A-98
DEPAC system for, A-98 to A-99
dioxins and, A-96 to A-97
electrostatic precipitators and, A-83 to A-85
end product handling and, A-83, A-97 to A-98
environmental accountability, E-40 to E-49
fabric filters in, A-83, A-85 to A-86
Filpac TCR system in, A-100 to A-101
Filsorption system for, A-96 to A-97, A-100 to A-101
filter product ranges in, A-87 to A-88
filters in, A-96, A-98
flue gas desulfurization (FGD) in, A-83, A-86, A-89 to A-90
fly ash handling and, A-97 to A-98
heavy metals and, A-96 to A-97
IEA Greenhouse Gas Implementing Agreement, C-14
lime/limestone FGD in, A-90
nitrous oxide (NO_x) (*See* nitrogen oxides)
ozone, O-4 to O-26
poisoning of catalyst vs., A-96
power production and, P-72
seawater FGD in, A-90, A-92
selective catalytic reduction (SCR) in, A-83, A-90, A-93 to A-96
sintering of catalyst vs., A-96
sulfur dioxide (SO_x) in, A-83, P-60 to P-62
TCR, A-99 to A-100
wet/dry FGD in, A-89 to A-91, A-100
Wetpac TCR system in, A-100 to A-101
air purification, sterilization, A-101 to A-102
air separation unit (ASU), C-17
air vessel control, in hydrodynamic brakes, with capacitative heat storage, B-19
air washing, air purification using, A-102
airfoils (*See also* metallurgy), control of, C-336
AKZO Pharma, D-12
aldrin, V-15
alkalis, in lubricating oil, L-25
alkylation, in petroleum industry, R-4
AlliedSignal, P-4
alloys, M-39, M-42 to M-43
alphatron gauges, M-22
Alstom Corporation, A-95, C-14, C-78 to C-84, G-5 to G-20, L-8 to L-10, P-4, P-73
Altair Filters International Ltd., A-10 to A-37, A-50 to A-83, S-29 to S-38
altered refinery, R-7
alternative fuels, F-37
alternators, synchronous clutches and, P-107, P-112
aluminum and aluminum alloys, P-10 to P-31, P-40 to P-57, M-40, M-42
aluminum oxide, A-4, A-6, C-25, P-10 to P-31, P-40 to P-57
ambient air pressure (Po), gas turbines and, T-55 to T-58
ambient air pressure (Pt), gas turbines and, T-58
ambient air quality objective, ozone and, O-9 to O-10
American Gear Manufacturers Association (AGMA), P-75
American National Standards Institute (ANSI)
explosion hazard assessment, E-87
generators and turbogenerators design, G-1
American Petroleum Instate (API), R-8
explosion hazard assessment, E-86
specifications, Sp-3
American Public Health Association (APHA), R-8
American Society for Testing and Materials (ASTM), M-12
cement, C-22 to C-28
American Society of Heating, Refrigeration, Air Conditioning Engineers (ASHRAE), R-11
American Society of Mechanical Engineers (ASME), A-1, M-12
ASME (*See* American Society of Mechanical Engineers), A-1
accreditation packages, Sp-25 to Sp-28
boiler code on CD-ROM from, Sp-32
boiler/pressure vessel codes, Sp-24
certification programs of, Sp-30 to Sp-31
electronic stress tables from, Sp-33
elevator and escalator CD-ROM from, Sp-31 to Sp-32
Information Handling Services (IHS) of, Sp-32
ISO 9000 registration program, Sp-29
Power Test Codes, M-12
Power Test Codes for flow measurement, M-26 to M-29
Power Test Codes for pressure measurement, M-15
pressure vessel codes on CD-ROM from, Sp-32
RA search online service of, Sp-33
specifications, Sp-3
Worldwide Standard Service of, Sp-32
American Standards Association, A-3
amines, C-43, C-58
ammonia, C-33, C-418, P-10 to P-31, P-40 to P-57, V-15 to V-16
as refrigerant, R-13 to R-18
ammonia bisulfate formation (ammonia slip), C-33
ammonium nitrate, P-10 to P-31, P-40 to P-57
ammonium sulfate, P-10 to P-31, P-40 to P-57
ammonium thiosulfate, C-72
amplitude, in vibrational analysis (VA), C-263, C-268 to C-272, C-280 to C-282, C-302, C-315 to C-317
aniline, P-10 to P-31, P-40 to P-57
annulus, hydrodynamic power transmission and, P-123 to P-127
anodes, sacrificial anodes vs., C-247
anthracene, C-68, P-10 to P-31, P-40 to P-57
anthraquinone, C-68
anti-icing additives, R-8
antifreeze, C-408 to C-412
antifungals, freeze dry production of, D-17
anti-knock compounds, R-8
anti-nodes, vibrational analysis (VA), in plots of, C-276
antimony, P-10 to P-31, P-40 to P-57
antinutritive factors, E-43
antioxidants, R-8
antistatic coatings, P-3
antisurge control/valves, C-359 to C-368
in turbocompressors, C-332 to C-335
API 610 CAP 8 type process pumps, P-285 to P-292
API 610 CVA8 overhung vertical pumps, P-292 to P-296
API 610 double suction pumps, P-296 to P-299
API 610 rigid or flexible coupled pumps, P-296
apparent viscosity, P-272
aqueous corrosion, M-40
aquifers suitable for disposal of CO_2, C-14, C-21
ARCO Chemical, C-42 to C-62, D-7 to D-8
argon, C-95
ArLon 6100 interior tank coating, T-4
Armstrong Engineering Association, C-62 to C-77, H-6 to H-23
arsenic, P-10 to P-32, P-40 to P-57
as-low-as-reasonably-practicable (ALARP) risks and, E-80
ASARCO Inc., P-4
asbestos, P-10 to P-32, P-40 to P-57
ASC MC antisurge controller, C-361 to C-368
Asea Brown Boveri, P-73
asphaltum, in lubricating oil, L-25
AssiDomän forestry management case study in, F-13 to F-21, E-50 to E-56, P-204 to P-205
atmospheric conditions vs. power degradation, in gas turbines, T-65 to T-67
atmospheric distillation, in petroleum industry, R-2
attenuation of sound, A-33 to A-37
attractive electromagnetic suspension, in bearings, B-5
auditing, E-43
operational optimization, life cycle assessment and, L-19 to L-21
authorized deposits, R-8
authorized inspection, Sp-4
autoclaving, M-34
automotive lifting devices, Sp-4
autrients, C-78
Avon Aeroderivative gas generator, Rolls Royce, M-32
Avon Mk. 1535 turbine cooling air, M-34
axial balance, in pumps and, P-243 to P-247, P-275 to P-276
axial compressors (*See also* compressors; turbocompressors), C-136 to C-165
adjustable stator blade design (VARAX), C-140, C-337 to C-338
adjusting cylinder in, C-162
applications for, C-137, C-139
axial thrust bearings in, C-163 to C-164
bearing pedestals in, C-155 to C-160
bearings in, C-163 to C-164
blade carrier in, C-160
blades in, C-160 to C-162
casing inserts in, C-160
casings in, C-155 to C-160
control systems in, C-161
cross section view (VARAX), C-159
cross sectional view of, C-141
discharge temperature in, C-156
features of, C-156

fixed stator blade design (FIXAX), C-140, C-153, C-157
gas turbines and, T-47 to T-48
horizontally split casing design, C-142
humidity vs. molecular mass of wet gas in, C-156
intercooler in, C-340
journal bearings in, C-163
longitudinal view (VARAX), C-159
oil supply system for, C-339, C-341, C-343
operating range for, C-153 to C-155
performance data for, C-154 to C-158
remote setting of reference values in, C-161 to C-162
rotors in, C-160
seals in, C-342
servomotors in, C-161 to C-162
shaft seals in, C-162 to C-163
size vs. performance of, C-154 to C-158
solid coupling in, C-164 to C-165
stator blade settings/control, C-153 to C-155, C-162
suction volume of, C-140, C-142
type designations for, C-153
variable stator blade design (VARAX), C-153, C-157 to C-159
vertically split casing design, C-143 to C-144
axial flow, in gas turbines, T-51 to T-53
axial piston, in pumps, P-260 to P-264
axial thrust bearings (*See also* thrust bearings)
in axial compressors, C-163 to C-164
in centrifugal compressors, C-178 to C-181
in isotherm turbocompressors, C-200 to C-202
axial tilting pad bearings, in high speed gears, P-104 to P-107
axis of control, in magnetic bearings, B-6
azeotrope refrigerant mixtures, R-11

back-pressure steam turbines, T-96 to T-98
back-to-back high speed gear test bed, P-99 to P-101
background noise measurement, A-20 to A-21
backmixing, in chemical reactors, R-1
baffles, solids concentration in riser using, computational fluid dynamics, C-2
balancing (*See also* condition monitoring), B-1, C-288 to C-291
causes of imbalance and, C-288 to C-291
centrifugal pumps and, P-243 to P-247
damping and, C-316 to C-318
generators and turbogenerators, G-11
influence coefficients in, C-325 to C-327
misalignment and, C-290 to C-291
modal balancing in, C-327 to C-328
onspeed, for rotors, B-1
process of, C-289 to C-290
rotary pumps, P-275 to P-276
strobe lights for, C-278 to C-280
subsynchronrous frequency orders and, C-291 to C-294
vibrational analysis (VA) and, C-278 to C-280, C-288 to C-291, C-325 to C-328
ball bearings, B-1 to B-2
balling machines, B-28
barometers, C-329, M-18
barrier coatings, F-15, F-21 to F-23
BASF/Varta, P-4
batch reactors, R-1
batteries (*See* cells)
Bayer AG, P-3 to P-4
bayonet type electric heater, H-13
bayonet type vaporizers, V-7 to V-12
bearings (*See also* axial thrust bearings; journal bearings; lubrication; magnetic bearings), B-1 to B-11
attractive electromagnetic suspension in, B-5
in axial compressors, C-155 to C-160, C-163 to C-164
axial thrust, C-163 to C-164, C-178 to C-181, C-201 to C-202
ball, B-1 to B-2
carbon-graphite mix products and, C-10, C-13
in centrifugal compressors, C-176 to C-178
in electric motors, E-16
in generators and turbogenerators, G-7 to G-9, G-15
in high speed gears and, P-101 to P-107
in isotherm turbocompressors, C-211, C-214
journal type (*See* journal bearings)
magnetic type (*See* magnetic bearings)
needle, B-1 to B-2
noncontacting technology in, magnetic type bearings, B-5
radial magnetic type, B-6 to B-7
in reciprocating (labyrinthine) compressors, C-86, C-92
roller, B-1 to B-2
rolling contact type, B-1 to B-2
sliding contact type, B-2 to B-5
stator and rotor in, magnetic, B-5
in steam turbines, T-78
temperature monitoring for, C-261
three lobe journal type, B-3
thrust type (*See* thrust bearings)
tilting pad journal type, B-4, L-25
in worm gears, P-94
Belleville washer negative spring rate sensor in, C-386 to C-387
bellows gauges, M-21
bellows type sensors, C-386
belt drives, D-3
bending stiffness of panels vs. soundproofing quality, A-29 to A-31
benzene, C-72, C-418, P-10 to P-31, P-33, P-40 to P-57, V-15
benzene hexachloride, C-68
benzoic acid, C-68
benzoyl peroxide, P-10 to P-31, P-40 to P-57
benzyl chloride, P-10 to P-31, P-40 to P-57
Bernoulli's theorem, P-222
best practical treatment (BPT), R-8
betaine, E-43
beverage industries pollutants, P-15, P-29
bimetallic sensors, C-377
bimetallic thermometers, M-8 to M-9
bioabsorbable polymers, freeze dry production of, D-17
bioassay, R-9 to R-10
biochemical oxygen demand (BOD), P-69, R-8
bioconversion, E-43
biodegradation of plastics, P-2 to P-3
biodistegrable plastics, P-2
biofilter, E-43
biological diversity, E-50
biological engineering, A-49
biological oxygen demand (BOD), E-43
biomass fuels, P-205 to P-214
coal co-gasification, CO_2 removal and, C-17 to C-18
cost vs. energy efficiency for, C-18 to C-20
gasification and reformation of natural gas in series in, C-18
biomass gasifier (BIG), P-208 to P-210
Bioplastics Inc., P-2
bioremediation, A-49
biosensors, conductive polymers in, P-6
biotechnology, E-44
biotopes, F-13
biphenyl, P-10 to P-31, P-40 to P-57
bipolar junction transistors (BJT), E-29
Bis(2-ethylhexyl) adipate, P-10 to P-31, P-40 to P-57
Bis(2-ehtylhexyl) phthalate, P-10 to P-31, P-33, P-40 to P-57
bisphenol, C-68, V-15
black liquor gasifier (BLG), P-209
black liquor processing, E-51 to E-52, P-205 to P-214
blade carrier, in axial compressors, C-160
blade tip grinders, A-1
blades (*See also* fans; metallurgy)
in axial compressors, C-160 to C-162
cracks in, L-16
in fans, F-1 to F-3
in hydrodynamic power transmission, P-123 to P-127, P-138
in isotherm turbocompressors, C-211 to C-215
material selection for, M-41
root disc serration configuration in, L-16
in steam turbines and, T-76, T-88 to T-90
vibrational analysis (VA) and, C-294
Blasberg Oberflae-chentechnik, P-4
blast furnace gas, F-37
blending
gravity, in tanks, T-4 to T-8
in petroleum industry, R-2, R-5 to R-6
blocking of catalyst, in air pollution control, A-96
blowdown, R-8
blowers
rotary piston, C-232
rotating positive displacement compressors and, C-228 to C-232
synchronous clutches and, P-107
Bode plots, in vibrational analysis (VA), C-270, C-272 to C-280
boilers (*See also* pressure vessels; turbines, steam), B-11, S-38, Sp-4
ASME accreditation packages for, Sp-25 to Sp-28
ASME CD-ROM for, Sp-32
books of interest on, Sp-37 to Sp-38
centrifugal pumps and, P-242
dryness of steam produced by, T-111
hydrodynamic power transmission and, in pumps, P-152 to P-164
International Code for, Sp-24
ISO 9000 registration program, Sp-29
steam separators for, T-108 to T-112
Tomlinson, in pulp and paper mill, P-210
bond of abrasives, A-5 to A-7
booster, in ultrasonic cleaners, U-3
borescopes, B-11
Bourdon tube sensors, C-383, M-8, M-21, P-224
brakes, hydrodynamic, B-11 to B-23
advantages of, B-14
air vessel control in, with capacitative heat storage, B-19
applications for, B-13 to B-14, B-23 to B-28
braking power in, B-16, B-20 to B-21
braking torque in, B-16, B-20 to B-21
closed vs. open circuit, B-12 to B-13
components of, B-15 to B-16
control and energy dissipation in, B-12 to B-13
control characteristic curves for, B-23 to B-24
controls and control schematics for, B-16 to B-19
dimensions and technical data, single and double flow models, B-22 to B-23
heat exchanger control in, B-17
high speed and acceleration, in gas turbines, C-347 to C-350
models of, Voith Corp., B-14 to B-16
non-self-supporting, B-14 to B-16

operation of, B-11 to B-12
performance characteristics of, graphs for, B-16, B-20 to B-21
pump control in, B-17 to B-19
schematic of, B-25
self-supporting, B-15 to B-16
speed vs. braking torque/power, B-20 to B-21
through flow control in, B-18
VHBI, B-14 to B-16, B-25 to B-28
VHBK, B-27
VHBM, B-14 to B-16
brass, in condensers, C-245
brazing, M-31 to M-32
breakdown rpm region, in electric motors, E-24 to E-25
breather drains, in electric motors and, E-18
brick lined process equipment, B-23
Bridgestone Corp., P-4
briquette machine, A-48, B-28
Bristol Meyers Co., D-17
bromine, V-16
Brunei Shell petroleum Fairly 4 platform, A-73
brushes
carbon-graphite mix products for, C-13
generators and turbogenerators, G-16
brushless excitation, generators, G-12 to G-16
building materials industry, pollutants, P-30
bulb and capillary sensors, C-378 to C-379
Buna-N shaft seal, electric motors, E-17
burners, biomass fuel fed, from pulp and paper mill, P-210
business service industries pollutants, P-31
butadiene, C-415, P-10 to P-31, P-33, P-40 to P-57, V-15
butane cyclopropane, C-418
butane, F-41, V-15, V-17
butanol, V-16
butene, V-16
butterfly valves, C-392
butyl alcohols, P-10 to P-31, P-40 to P-57
butyl benzyl phthalate, P-10 to P-31, P-40 to P-57
butyl cresol, C-68
butylamine, V-16
butylene, V-15
butyric acid, C-68
bypass doors, in air filtration systems, A-53, A-59 to A-60, A-76

C.I acid green 3, P-10 to P-31, P-40 to P-57
cadmium, P-10 to P-31, P-34, P-40 to P-57
calcium carbonate, C-14
calcium cyanamide, P-10 to P-31, P-40 to P-57
calcium nitrate, C-68, C-72
calcium oxide (CaO), C-28
calcium sulfate, C-25
calibration
of pressure measurement devices, M-16
of temperature measuring instruments, M-11 to M-12
Cambridge Display Technology (CDT), P-5
Campbell diagrams, in vibrational analysis (VA), C-323 to C-326
Canadian Petroleum Products Insatiate (CPPI), R-8
Canadian studies in pollution, pollution control, P-8 to P-72
CAP 8 type process pumps (API 610), P-285 to P-292
capacitance method, in level sensing, C-388
capacity (cfm), in fans, F-1, F-3
capacity of flow, in flow measurement, M-24 to M-25
caprolactum, C-68
carbon dioxide (CO_2), C-13 to C-21, C-95, E-36, F-18, V-16
aquifers suitable for disposal of, C-14, C-21
biomass gasification and reformation of natural gas in series in, C-18
capture of, from gas turbine base power plants, C-14 to C-16
cement production and, C-29 to C-30
coal and biomass co-gasification in, C-17 to C-18
cost vs. energy efficiency in, C-18 to C-22
energy efficiencies vs. costs, C-18 to C-20
global warming, greenhouse gases and, C-13
ground injection project (Sweden) for, C-14 to C-21
IEA Greenhouse Gas Implementing Agreement, C-14
integrated gasification combined cycle (IGCC) and, C-14 to C-16
limiting emissions of, C-14
liquefaction of, for dry cleaning products, C-13
liquid phase methanol synthesis (LPMeOH) in, C-17 to C-18
methanol, power, heating, neutral co-production of, C-16 to C-17
monoethanol amine (MEA) solvent in, C-15
natural gas combined cycle (NGCC) and, C-14 to C-16
power production and, P-72
as refrigerant, R-13 to R-18
Selexol process for, C-15 to C-17
solidification of, C-14
syngas production in, C-17 to C-18
technology and cost options for, C-14 to C-21
transport and disposal of, C-20
carbon disulfide, P-10 to P-31, P-40 to P-57
carbon-graphite mix products, C-7 to C-13
applications for, example of, C-11 to C-12
bearing design for, C-10, C-13
chemical resistance of, C-9
close in tolerance of, C-10
coefficient of friction in, C-9
coefficient of thermal expansion in, C-9
design factors for, C-9 to C-11
electrical contacts and, C-13
environmental factors and, C-9
filters using, C-13
interference fit for, C-9
load bearing capacity of, C-9
material classification for, C-9
mating materials for, C-9
mechanical strength of, C-9
oxidization resistance in, C-9
products made from, C-13
properties of, C-8
running clearance for, C-10
seals using, C-12 to C-13
self-lubricating properties of, C-8
specialty products using, C-13
temperature parameters for, C-9
tolerances for, C-10
carbon monoxide (CO), C-15, E-38, P-62 to P-64
carbon tetrachloride, P-10 to P-31, P-34, P-40 to P-57, V-15
carcinogens, C-38, M-32
cardboard (*See* packaging; paper products and packaging)
cartons, paper, F-24
cartridge filters, F-6 to F-8
in air filtration systems, A-54, A-58
cascade diagrams, in vibrational analysis (VA), C-272 to C-273
casings
in axial compressors and, C-155 to C-160
in centrifugal compressors, C-170 to C-175
in isotherm turbocompressors, C-205 to C-206, C-210 to C-211
in rotary pumps, P-276
in steam turbines and, T-76
castings (*See also* metallurgy), M-43
catalyst, R-8
catalysts, fluidized beds, F-12
catalytic cracking, petroleum industry, P-2 to P-3
catalytic reactors, R-1
CATAPOL project, C-5, C-7
Catpac TCR system, air pollution control and, A-100 to A-101
caustic soda, C-43, C-58
cavitation, C-264, C-328, P-232
cells, chemical, C-22, P-4
Celsius temperature conversion, M-12
cement, Portland; and kilns, C-22 to C-34
additions to, C-24, C-28
air entrained, C-22 to C-23, C-28
American Society for Testing and Materials (ASTM) specs for, C-22 to C-28
carbon dioxide (CO_2) emission, C-34
CCME (Canada) National Emission Guidelines for kilns and, C-28 to C-34
certification of, by manufacturer, C-28
chemical requirements of, C-25 to C-26
clinkering process in, C-29 to C-30
combustion and operation modification (COM) to reduce emissions from, C-32
continuous emissions monitoring (CEM) in, C-34
definition of, C-23, C-29
energy consumption in production of, C-29 to C-30
hazardous wastes used in, C-33
inspection of, C-26
kilns for, environmental impact of, C-22, C-28 to C-34
low NO_x burners (LNBs) to reduce emission from, C-32 to C-33
manufacturer's statement for, C-27
measurement of emissions from, vs. costs, C-34
nitrogen oxide (NO_x) and, C-29 to C-31
ordering information for, C-23
packaging and package marking for, C-27 to C-28
physical properties of, C-24, C-29 to C-30
production of, C-28 to C-34
rejection of, C-26
sampling of, C-24
selective noncatalytic reduction (SNCR) to reduce emission from, C-33
setting time for, C-24
staged air combustion to reduce emission from, C-32
storage of, C-28
sulfur dioxide (SO_2) emission from, C-34
testing of, C-24
types and classification of, C-22 to C-23
centrifugal compressors (*See also* compressors; turbocompressors), C-81, C-136, C-165 to C-190
adaptability to application demands in, C-167 to C-170
applications for, C-182 to C-190
axial thrust bearings in, C-178 to C-181
axial thrust in, C-176 to C-178
barrel type design, C-171 to C-174
bearings in, C-176 to C-178
building block system in, C-170 to C-171
casing in, C-170 to C-175
drainage system in, C-181 to C-182
drive for, C-188
features of, C-170 to C-190
flow conditions and, C-167 to C-168
fluid injection devices in, C-182
horizontally split casing design in, C-166 to C-170, C-172
impellers in, C-172, C-174 to C-177, C-186
inlet guide vane assembly in, C-181
journal bearings in, C-178 to C-181

magnetic bearings and, C-185 to C-186, C-189 to C-190
materials used in, C-182 to C-183
motor for, C-187 to C-190
pressure range for, C-168 to C-170
process conditions for, C-168
retrofit design modification for gas pipeline station, C-182 to C-186
rotor in, C-189 to C-190
selection chart for, C-168
series designations for, C-169
shaft seal in, C-180
size vs. performance in, C-167 to C-170
solid coupling in, C-176 to C-178
testing of, C-188 to C-189
type range of, C-166 to C-170
vertically split casing design in, C-168 to C-170
centrifugal gas exhausters, E-56 to E-57
centrifugal pumps, P-218 to P-259
applications for, P-218 to P-219, P-241 to P-255
axial balance in, P-243 to P-247
Bernoulli's theorem and, P-222
boiler feed, P-242
Bourdon tube to measure flow in, P-224
cavitation in, P-232
characteristic curves of performance for, P-228
condensate, NPSH and, P-236 to P-237, P-243
continuity equation in, P-221 to P-224
double volute, P-247 to P-248
friction loss in, P-222
head in, P-222, P-224 to P-228
hot water, NPSH and, P-236
Hydraulic Institute Standards for, P-231
hydraulic pressure, P-242 to P-243
hydraulics of, P-221 to P-241
impellers in, P-219, P-226 to P-228
installation of, P-257 to P-258
kinetic head in, P-222
materials selection, by liquids to be pumped, P-241
minimum flow through, P-237 to P-240
nonclogging, P-243
operation of, P-257 to P-258
parallel operations for, P-228 to P-230
performance analysis of, P-226 to P-228
piping for, P-257
potential head in, P-222
power/horsepower requirement calculation for, P-225 to P-226
pressure head in, P-221 to P-224
priming of, P-257
recirculation connection for, P-240 to P-241
seals in, P-250 to P-254
series operations for, P-228 to P-230
single stage, double suction type, P-241 to P-242
specific speed of, P-219 to P-221
static head in, P-221 to P-224
stuffing boxes for, P-248 to P-254
suction head in, net positive (NPSH), P-232 to P-237, P-257
suction head in, P-222
suction lift in, P-222
temperature rise in, P-237 to P-240
temperature vs. efficiency in, P-254 to P-255
total discharge head in, P-223 to P-224
total head in, P-222
troubleshooting, P-258 to P-259
valves in, P-257
velocity head in, P-221 to P-224
vibration limits for, P-255 to P-258
viscous liquids and, P-230 to P-232
warmup procedures for, P-254
centrifuges, A-48, C-34 to C-38
ceramic abrasive, A-4
ceramics, A-2, C-38
CERCLA, propylene glycol and, C-412 to C-413
certification, Sp-14, Sp-30 to Sp-31, Sp-34
chains, Sp-4
characteristic curves of performance, pump, P-228
check valves, C-392
Chem Systems/Air Products, C-17 to C-18
chemical cleaning, C-38, T-67
chemical complex (petrochemicals), chemical plant, C-38 to C-41
chemical engineering, Sp-1 to Sp-3
Chemical Manufacturers Association (CMA) guidelines, C-61
chemical oxygen demand (COD), R-8
chemical reactors, R-1
chemical treating, R-5
chemicals (*See also* hazardous materials; pollutants; toxic chemicals), C-41 to C-42, Sp-1 to Sp-3
inorganic, C-64
pollutants and, P-25 to P-26
toxic, handling of, C-42 to C-62
transport of, T-40 to T-41
chemisorption, in air pollution control, A-96, A-98
CHEMTREC information service, telephone number, C-61
chillers
for agricultural and food products, A-48
crystallizers as (*See also* crystallizers), C-62
chimneys (*See also* stacks), C-78
chlordane, P-7
chlorine dioxide, P-10 to P-31, P-40 to P-57, V-15
chlorine, C-86, P-10 to P-31, P-40 to P-57, V-15 to V-16
chlormethane, P-11 to P-31, P-40 to P-57
chloroacetic acid, P-11 to P-31, P-40 to P-57
chlorobenezene, C-68, C-72, V-15
chloroethane, P-11 to P-31, P-40 to P-57
chlorofluorcarbons (CFCS) (*See also* ozone; refrigerants), C-13 to C-14, R-10 to R-11, R-14 to R-15
aerosols using, O-17 to O-18
coatings containing, O-14, O-16 to O-26
cost of replacing use of, O-16 to O-22
foams containing, O-14, O-16 to O-26
insulation containing, O-14, O-16 to O-26
ozone and depletion and, C-13 to C-14
packaging containing, O-14, O-16 to O-26
refrigerants containing, O-14, O-16 to O-26
solvents containing, O-14, O-16 to O-26
sterilants containing, O-14, O-16 to O-26
chloroform, P-11 to P-31, P-34, P-40 to P-57
chloromethanes, V-15
chromium, P-11 to P-31, P-34, P-40 to P-57
circular pitch, worm gears, P-84
civil engineering, Sp-1 to Sp-3
Clarkson Co. (knife gate valve), C-402 to C-403
Clean Air Act, propylene glycol and, C-412 to C-413
cleaning, in metallurgy and, M-32, M-34
cleanliness factor, C-243 to C-244
clutch type couplings, C-347
clutches, synchronous clutch couplings (*See also* power transmission), P-107 to P-115
coal
biomass co-gasification, CO_2 removal and, C-17 to C-18
cost vs. energy efficiency for, C-18 to C-20
coal gas, F-37
coal powered energy plants, integrated gasification combined cycle (IGCC), CO_2 removal and, C-14 to C-16
coalescer panels, in air filtration systems, A-52 to A-53
coating processes, computational fluid dynamics to model, C-7
coatings (*See also* metallurgy), M-31, M-34 to M-35
anticorrosion, C-442
chlorofluorocarbons in, O-14, O-16 to O-26
tank exteriors, T-5 to T-8
tank interior, for potable water, T-9 to T-13
tank interiors, T-4 to T-8
cobalt and cobalt alloys, M-41 to M-42, P-11 to P-31, P-40 to P-57
abrasives and, A-2
codes, commonly used, Sp-1 to Sp-3
codes, life cycle assessment (LCA), L-19
coding systems, color coding in, C-81
coefficient of discharge, flow measurement, M-24
coefficient of friction, worm gears and, P-86 to P-88
coefficient of performance (COP), refrigerants and, R-18
cogeneration, C-78 to C-84
life cycle assessment (LCA) and, L-17 to L-18
synchronous clutches and, P-107 to P-108, P-114 to P-115
coil type stab electric heater, H-14
"coincidence frequency," A-27, A-30
coke oven gas, F-37
coking processes, in petroleum industry, R-4
cold-to-cold expansion joints, E-58 to E-59
color coding, C-81
columns (*See also* towers and columns), T-40
combined cycle applications, C-78, P-107
combined cycle gas turbine (CCGT) plants, explosion hazard assessment for, E-67, E-70 to E-71, E-74, E-81 to E-85
combined flow coefficient, flow measurement, M-24
combined heat and power (CHP) plants, P-208, P-210
explosion hazard assessment for, E-67, E-70 to E-71, E-81 to E-85
combined unit systems, in air pollution control and, A-83, A-99 to A-101
combining processes, in petroleum industry, R-4
combustion, computational fluid dynamics to model, C-1 to C-7
combustion cans, material selection for, M-40 to M-41
combustion chamber, in gas turbines, T-49 to T-51
combustors (*See* turbines)
communication industries pollutants, P-29
commutators, carbon-graphite mix products and, C-13
comparators, optical, A-2
complex vibration, in vibrational analysis (VA), C-263
compounds, M-39
compressible fluid, in flow measurement, M-28 to M-29
compression, air purification using, A-102
compressors (*See also* axial compressors; centrifugal compressors; integrally geared compressors; isotherm compressors; reciprocating or laby compressors; rotating positive displacement compressors; turbocompressors), C-81 to C-232, C-264, Sp-5
air filtration systems and, A-75
air inlet manifolds, paint and corrosion damage in, T-74 to T-75
antisurge control in, C-359 to C-368
applications for, C-138

atmospheric conditions vs. power degradation in, T-65 to T-67
axial (*See* axial compressors)
axial inlet design, C-148
centrifugal (*See* centrifugal compressors)
chemical cleaners for, T-67
cleaning or washing of, T-59 to T-75
cleaning/washing equipment and procedures for, T-71 to T-75
control systems for, C-136
corrosion and corrosion inhibitors in, T-74 to T-75
debris in, A-59
detergent cleaning of, T-70
expanders (turboexpanders) using, C-151 to C-152
foaming cleaners for, T-67 to T-68
fouling of, T-63 to T-65, T-67
gas turbines and, T-47
horizontally split casing design in, C-142, C-166 to C-170
hot vs. cold water cleaning of, T-73 to T-74
integrally geared (*See* integrally geared compressors)
isotherm turbo (*See* isotherm turbocompressors)
offline cleaning of, T-67, T-70 to T-71, T-73 to T-74
online cleaning of, T-67, T-70 to T-73
reciprocating or labyrinthine (laby) (*See also* reciprocating or labyrinthine compressors)
rinsing after cleaning of, T-68
rotating positive displacement (*See* rotating positive displacement compressors)
rotors in, M-40
screw (*See* rotating positive displacement compressors)
single stage design, C-147 to C-148
stall in, T-48 to T-49
subsynchronrous frequency vibration, C-291 to C-294
surging in, T-48 to T-49
TURBAIR vacuum blowers using, C-149 to C-150
turbo- (*See* turbocompressors)
turbochargers and, T-112 to T-114
vertically split casing design, C-143 to C-144
water only cleaning of, online, T-69 to T-70
water- vs. solvent-based cleaners for, T-68 to T-69
computational fluid dynamics (CFD), C-1 to C-7
air flow testing using, E-72
applications of, C-1, C-3 to C-6
case studies in, C-7
CATAPOL project in, C-5, C-7
combustion and incineration modeling using, C-7
complex shape modeling using, C-5
cooling systems modeling using, C-7
die design using, C-4
electrostatic precipitator flow using, C-5
emissions modeling using, C-7
filter flow using, C-4, C-7
Fluent project in, C-6 to C-7
fluid handling and flow distribution modeling using, C-3
gasoline hydro treatment modeling (OLMES project) using, C-7
IcePak for, C-5, C-7
liquid natural gas studies using, L-21, L-23
materials processing modeling using, C-7
mixing of materials in tank using, C-3, C-6
OLMES project in, C-6 to C-7
polymerization temperature prediction using, C-5
reactor modeling using, C-3
separation of materials modeling using, C-7
slide valve and, flow through, C-2
solids concentration in riser using baffle plate, C-2
trajectory of exhaust plume using, C-3
ventilation modeling, C-6
windage heating (labyrinth seals) predictions using, C-6 to C-7
computer aided design/manufacturing (CAD/CAM), A-1, C-1
computer aided tomography (CAT) scan, M-37
computer numerical control (CNC), A-1 to A-3, C-1, N-1
condensate fuel, F-37
condensate pumps, NPSH and, P-236 to P-237, P-243
condensate receiving tank, in reciprocating (labyrinthine) compressors, C-109
condensers, C-233 to C-252
air cooler, C-235 to C-236
air inleakage in, C-247
backpressure and electrical output effects, C-233
cold end optimization in, C-244
corrosion in, C-245
cost-benefit analysis of, C-240
design and manufacture of, C-250
design layout of, C-234 to C-239
dome of, C-234 to C-235
environmental protection and, C-233
flashbox in, C-238 to C-239
fouling in, C-243 to C-244, C-248
foundation mounting and turbine connection, C-239
hotwell in, C-238
installation benefits in, C-240
layout philosophy in, C-244
makeup water in, C-240
material selection in, C-244 to C-246
oxygen content of condensate in, C-240
sacrificial anodes vs. corrosion, C-247
selection criteria, C-250 to C-252
shell of, C-236
sponge ball cleaning system for, C-248 to C-249
startup venting in, C-248
steam dump device (SDD) in, C-248 to C-250
steamside pressure losses in, C-242 to C-243
subcooling in, C-240
support plates in, C-236 to C-238
thermal performance of, C-239, C-242 to C-244
tube bundle, C-234, C-240 to C-242, C-244 to C-246
tubesheet materials in, C-246, C-251
type series of, C-244
venting for, C-246 to C-250
waterbox venting in, C-248
waterboxes in, C-238
condensing steam turbines and, multistage, T-94 to T-96
condition monitoring (CM) (*See also* measurement; vibrational analysis), C-253 to C-331
applications and benefits of, C-253, C-256 to C-257
basic components of, C-257
borescopes in, B-11
diagnosing problems using, C-299
diagnosis grids in, C-255 to C-256
gas path monitoring using, C-299
instrumentation requirements for, C-299
lifecycle assessment (LCA) and, C-253
nonintrusive wear monitoring in, C-330
packaged monitoring systems for, C-286 to C-287
packaged, selection criteria for, C-259 to C-260
parameters for, setting recommendations in, C-258 to C-259
performance analysis (PA) in, C-261, C-299
predictive strategies in, C-254
pressure measurement in, C-328 to C-330
preventive strategies in, C-254 to C-261
programmable logic controllers (PLCs) in, C-259
reactive strategies vs., C-254
retrofitting and, C-255
return on investment (ROI) for, C-299
risk management and, C-254
rules for, C-299 to C-301
scope of systems for, C-253 to C-261
selection criteria for, C-253 to C-261
spectrum analyzer for, C-298 to C-299
surge control in, C-328 to C-330
temperature monitoring in, C-260 to C-261
time between overhaul (TBO) and, C-256
troubleshooting philosophy using, C-298 to C-301
vibration analysis (VA) in (*See* vibrational analysis)
vibration monitoring (VM) in, C-257 to C-258
conductance method, in level sensing, C-388
conduction error, in temperature measurement, M-13
conductive polymers, P-4 to P-7
connectors, in soundproofing and noise control, A-24 to A-25
consolidated diaphragm comparator, M-22
constant fill couplings, C-347
construction industries pollutants, P-27 to P-28
Contex, P-4
continuity equation, pump, P-221 to P-224
continuous emissions monitoring (CEM), C-34
continuous reactors, R-1
control algorithms, for magnetic bearings, B-5, B-10
control panels, seals for, S-8
control regulators (*See* actuators)
control systems and controls (*See also* measurement; sensors; switches; valves), C-331 to C-353, Sp-1 to Sp-3, Sp-5
aeroderivative fuel regulator for gas turbine, retrofit of controls for, C-354 to C-358
airfoil movement and, C-336
antisurge control in, C-359 to C-368
current to pressure (I/P) converters for, C-392 to C-401
DCS in, C-355
dynamic conversion of electrical control signals, A-40
fault tolerance in, C-355
flow control in, C-333
fuel flow, C-403 to C-408, F-29 to F-37
in axial compressors, C-161
in electric heater, H-16 to H-20
in electric motors, E-10 to E-15
in generators and turbogenerators, G-18 to G-20
in hydrodynamic brakes, B-16 to B-19, B-23 to B-24
in magnetic bearings, B-5 to B-6, B-8 to B-11
integrated control system (Series 9500) for gas turbine generators, C-359 to C-361, C-374 to C-377
knife gate valves in, C-399, C-402 to C-403

liquid level/liquid flow control in, C-388 to E-18
load limit control in, C-334
lubrication systems, C-336
malsynchronization control, C-344
man machine interface (MMI) in, C-356
manifold flow (fuel) control in, C-403 to C-408
modular component units for, A-40
monitoring logic in, C-336
open loop, in magnetic bearings, B-10
overload/overspeed protection in, C-336, C-343 to C-350, C-368 to C-374
power limitation in, C-333, C-350 to C-354
pressure control in, C-333, C-368 to C-374, C-383 to C-388
process control in, C-333 to C-334
proportional conversion of electrical control signals, A-40
retrofit controls in, C-354 to C-408
safety systems and, C-332 to C-333
SCADA in, C-355
sensors for, C-377 to E-18
short circuit control, C-344
steam turbines and, T-78 to T-79
stepper motor–driven valves in, C-403 to C-405
switches for, C-377 to E-18
temperature limitation in, C-333, C-377 to C-382
torque control, C-344 to C-345
turbocompressors, C-331 to C-336
valves for, CE-18 to CE-392
vaporizers, V-25 to V-31
vibration limitation in, C-333
conversion factors, vaporizers, V-7
conversion of units, Sp-1 to Sp-3
conversion process, in petroleum industry, R-2 to R-4
conversion tables (*See* specifications list)
converters
current to pressure (I/P), C-392 to C-401
hydrodynamic power transmission and, P-138
ultrasonic cleaners and, U-2
conveyors (*See also* drives; power transmission), A-48, C-408, D-3, E-21 to E-22, Sp-5
coolant, engine, C-408 to C-412
cooler bearings, in electric motors, E-16
coolers, A-48
for agricultural and food products, A-48
condensers in, C-235 to C-236
cooling (*See also* air conditioning; refrigerants), C-413 to C-423
air conditioner sizing and, C-422 to C-423
capacities charts for air conditioners, C-416 to C-417
chlorofluorocarbons (CFCs) in, C-413
computational fluid dynamics modeling using, C-7
cooling towers in, C-423 to C-426
dairy coolers, C-412 to C-413, C-420
design specifications/standards for, C-413 to C-418
ejectors in, E-2 to E-3
electric heater controls, H-18
electric motors and, E-28 to E-29
flow through turbine, L-17
in generators and turbogenerators, G-1 to G-3, G-11 to G-12, G-16
hazardous gas environments, design specifications for, C-415, C-418
mean time between failure (MTBF) of products for, C-418
military standards/specifications (MIL-Std) in, C-414
NEC design specifications for, C-415, C-418
NEMA design specifications for, C-413 to C-414
Peltier Effect in, C-418
in reciprocating (labyrinthine) compressors, C-103
refrigerants in, C-413, R-10 to R-19
reliability of products for, C-418
solid state technology in, C-413
thermoelectric cooling process in, C-418 to C-423
UL/CSA design standards for, C-418
cooling towers, C-423 to C-426, R-8
evaporative, C-423 to C-426
fans, F-4
plume abatement design, C-424 to C-426
cooling valve, in reciprocating (labyrinthine) compressors, C-96
Cooper, C-81
coordinate measuring machine (CMM), A-2 to A-3
copper, P-11 to P-31, P-40 to P-57
conductivity of, vs. polymers, P-5
copper-nickel alloys, in condensers, C-245
copper resistance thermometer, M-4
corrosion, M-40
in air filtration systems and, A-55 to A-59, A-64 to A-71, A-76 to A-77
anticorrosion coatings, C-442
aqueous, M-40
in compressors, T-74 to T-75
in condensers, C-243 to C-245
electric motors and
hot, M-40
in isotherm turbocompressors vs., C-191 to C-193
ozone and, O-8 to O-9
sacrificial anodes vs., C-247
corrosion inhibitors, compressors and, T-68
corrosive gases, C-86
corrugated packaging (*See* packaging; paper products and packaging)
corrugated soundproofing panels, unlined, A-29 to A-33
couplings (*See also* power transmission)
in axial compressors, solid type, C-164 to C-165
brake properties at high speed and acceleration, C-347 to C-350
in centrifugal compressors, solid type, C-176 to C-178
clutch type, C-347
constant fill, C-347
hydrodynamic power transmission and, P-138 to P-147, P-155 to P-165
hydrodynamic principle in turbocouplings and, C-346 to C-347
in isotherm turbocompressors, solid, C-195 to C-201
resonant, C-317
Safeset overspeed/overload protective coupling, C-344 to C-350, P-184 to P-191
synchronous clutches and, P-107 to P-115, P-118
torque converters and, torque limiting, P-184 to P-191
turbo- (type T) in, P-191 to P-196
Type RK variable speed, P-147 to P-149
Type SVL variable speed, P-145 to P-147
type SVNL variable speed, P-142 to P-145
variable speed, C-347
covers, floating, F-12
cracking, of expansion joints, E-60 to E-61
cracking processes, in petroleum industry, P-2 to P-4
cranes and hoists, Sp-5 to Sp-6
crankcase, in reciprocating (labyrinthine) compressors, C-86, C-92, C-107
crankshaft, in reciprocating (labyrinthine) compressors, C-99, C-108
creep deformation, M-39 to M-41
cresol, P-11 to P-31, P-40 to P-57
critical damping, C-312 to C-313, C-315
crosshead fastening, in reciprocating (labyrinthine) compressors, C-86, C-93
crude oil (*See also* refineries, petroleum), F-37 to F-38, F-43 to F-45, R-1 to R-10
crushers, C-442
cryogenic separation, C-17
cryogenic technologies
using reciprocating (labyrinthine) compressors, in natural gas service, C-121 to C-126
turboexpanders and, T-114 to T-115
vaporizers in, V-5 to V-7, V-17 to V-19
crystalline nature of materials, M-39
crystallization
agitators in, A-38
toluene diisocyanate (TDI), C-43
crystallizers, C-62 to C-77
batch process for, C-64
benefits of, C-63 to C-66
capacities for, C-66
chlorobenezene separation in, C-68
drive system in, C-77
easily separable crystals and, scraped surface design for, C-76 to C-77
fatty acid separation in, C-68
fouling tendencies in
high boiling point rise vs., C-67
ideal vs. nonideal cases for, C-72
latent heat of, C-62
process of, C-62
purity of product in, C-63
scraped surface continuous crystallization process for, C-64 to C-66
solubility curves of chemicals in, C-66, C-71 to C-75
solvents and, C-70
temperatures for, C-66
vacuum crystallization process in, C-71
Van T'Hoff equation in, C-72 to C-75
vapor pressures and, C-67
viscous fluids and, C-67
waxes and, C-70
CSA, generators and turbogenerators design, G-1
Cultor Corporation and environmental accountability, E-42 to E-48
cumenes, P-11 to P-31, P-40 to P-57
current, electric motors requirements, E-10, E-12 to E-13, E-15, E-29
current-to-pressure (I/P) converters, C-392 to C-401
current transformers, in generators and turbogenerators, G-19
CVA8 type pumps (API 610) overhung vertical inline integral bearing frame flexibly coupled, P-292 to P-653
CVAR type rigid coupled pumps, P-296
cyanides, P-11 to P-31, P-40 to P-57
cyanoacetamide, C-68
cyclic usage factor, life cycle assessment, L-3 to L-6
cyclohexane, P-11 to P-31, P-40 to P-57
cyclone tube separators, S-12, S-17 to S-18
cylinder velocity recovery capability, fans, F-4
cylinders, in reciprocating (labyrinthine) compressors, C-103, C-126 to C-132
cylinders for holding toxic chemicals, C-52 to C-54

dairy coolers, C-412 to C-413, C-420
dampeners (*See also* pulsating dampeners)
in fuel gas conditioning system, F-27
pulsation type, P-214 to P-218
damping, A-28, A-33, C-264, C-307 to C-313
amplitude in, C-315 to C-317
critical damping in, C-312 to C-313, C-315

displacement and, C-314 to C-315
forced vibration in, C-313 to C-316
friction (coulomb) damping in, C-307
inertia in, C-314 to C-315
magnification factor (D/F/k) in, C-316
natural frequency in, C-316
overdamping and decay in, C-312
phase angle in, C-315 to C-316
solid or structural damping in, C-307
steady-state oscillations and, C-313 to C-314
underdamping and decay in, C-312 to C-313
vibrational analysis (VA), C-305 to C-306
viscous damping in, C-308 to C-311
DCS control systems, C-355
DDT, P-7
dead band, in governors, T-102
deadweight tester and gauges, M-18 to M-20
decabromodiphenyl oxide, P-11 to P-31, P-40 to P-57
deceleration, electric motors, E-29
deforestation effects, F-12
deformation, M-39, P-102, P-104
degree of freedom, in vibrational analysis (VA), C-301 to C-302, C-310
Demag Delaval, C-219 to C-228, C-233 to C-252, C-377 to E-18, L-25 to M-31, P-74 to P-98, P-218 to P-281, T-112 to T-115
demand charge, energy costs and, E-9 to E-10
DeNox systems, in air pollution control, A-90, A-93, A-100
dense phase technology, air pollution control and, A-98
density at reference temperature (DENS.REF), T-25 to T-27
DEPAC system, air pollution control and, A-98 to A-99
Department of Defense, cement specifications, C-22
derating of electric motors, E-29
desalination, D-1 to D-2
metallurgical content of seawater and, D-2
multistage flash (MSF) process in, D-1
reverse osmosis (RO) process in, D-1
desiccants, D-4
detergent cleaners, C-78, T-68, T-70
deterioration of gas turbines, L-10 to L-11
deterioration of steam turbines, L-11
deterministic vibration, in vibrational analysis (VA), C-263
diagnosis grids, in condition monitoring, C-255 to C-256
dialysis, D-2
diaphragm gauges, M-21
diaphragm valves, CE-18 to CE-392
diaphragms, in steam turbines and, T-77
dibutyl cresol, C-68
dibutyl phthalate, P-11 to P-31, P-40 to P-57
dicalcium silicate (C2S), C-25 to C-26
dichloro-2-butylene, V-15
dichlorobenzene, P-11 to P-31, P-40 to P-57
dichloroethane, P-11 to P-31, P-35, P-40 to P-57
dichloromethane, P-11 to P-31, P-35, P-40 to P-57
dieldrin, V-15
dies, computational fluid dynamics to analyze shapes in, C-4
diesel engines, E-38
diesel fuel, F-37
diethanolamine, P-11 to P-31, P-40 to P-57
diethyl ether, V-16
diethyl phthalate, P-11 to P-31, P-40 to P-57
differential pressure, C-389, M-14, M-18 to M-24
differential pressure-actuated switches, C-383
diffuser, in isotherm turbocompressors, cross section, C-213
diffusion rate, M-39
diglycerides, C-68
dilution ventilation, in preventing explosion, E-87
dimensioning, dimensions, Sp-6
ASME certification program for, Sp-30
dimerization, C-58, C-72
dimethyl ether, V-16
dimethyl hydantoin
dimethyl sulfate, P-11 to P-31, P-35, P-40 to P-57
dimethyl terephthalate, C-68, V-15
dimethylaminomethylene, freeze dry production of, D-17
dinitro-o-cresol, P-11 to P-31, P-40 to P-57
dinitrotoluene, P-11 to P-31, P-40 to P-57
di-n-octyl phthalate, P-11 to P-31, P-40 to P-57
dioxane, P-11 to P-31, P-35, P-40 to P-57
dioxin, A-96 to A-97, P-7
discharge head, in pumps, P-223 to P-224
discs, turbine, material selection for, M-40
dislocations, M-39
displacement, vibrational analysis (VA), C-287, C-314 to C-315
displacement probes, in vibrational analysis (VA), C-266 to C-270
displacement pumps, P-260, P-267 to P-268
disposal of toxic chemicals, C-62
distillate No. 2 (*See* diesel fuel)
distillation, C-62, C-67, D-2 to D-3
atmospheric, in petroleum processing, R-2
computation fluid dynamics in, C-1 to C-7
vacuum, in petroleum processing, R-2
distortion (physical), expansion joints vs., E-61
diversion systems, high voltage and lightning strikes, T-30 to T-31
diverters, D-3
doctor, in paper industry, D-3
dome, condenser, C-234 to C-235
Dorr-Oliver Inc., centrifuges, C-35 to C-38
double volute pumps, P-247 to P-248
Dowtherm heater, H-22
drain valve and drains, in air filtration systems, A-56, A-62 to A-63
drawings and terminology, Sp-6 to Sp-7
drilling, M-35
drive belts, vibrational analysis (VA) of, C-296
drives and drive systems (*See also* power transmission), D-3 to D-4
in centrifugal compressors, C-188
in crystallizer, C-77
hydrokinetic (*See* hydrodynamic power transmission)
in isotherm turbocompressors, C-194 to C-200
drug industries pollutants, P-29
drum (*See* separators)
drums for holding toxic chemicals, C-54
dry cleaning products, C-13
dry cooling towers, C-423 to C-426
dry scrubbers, S-10 to S-29
capacity of, S-11 to S-12
cyclone tube in, S-12, S-17 to S-18
design of, S-11 to S-12
filter for, S-13 to S-16
fuel gas conditioning system, F-28 to F-29
optional features of, S-12 to S-13
pressure loss in, S-12
removable tube section in, S-13
drying (*See also* freeze drying), D-4 to D-18
agitators for, D-4
computation fluid dynamics in, C-1 to C-7
dessicants for, D-4
ejectors in, E-2 to E-3
fans for, D-4
fluid bed dryers in, D-4
heat exchangers for, D-4
ovens for, D-4
vacuum drying, D-4, D-12 to D-13
DS F88/146, A-18
ductility, of ceramics, C-38
ducts and ducting (*See also* expansion joints), D-18
dust, vs. air filtration systems, A-51 to A-52, A-56, A-66, A-70, A-74 to A-76
duty cycle, electric motor, E-5
dynamic absorbers, vibration vs., C-276
dynamic conversion of electrical control signals, A-40
dynamic water eliminator (Hydra) filters, A-81

earth loop heat pump, H-1 to H-3
ecolabeling, E-54 to E-55
ecological industrial parks, A-48 to A-49, E-1
ecosystem management, F-12
ecosystems, E-1 to E-3, F-12
eddy current probes, C-267 to C-268
eddy current testing, M-36
efficiency
of electric motors, E-5 to E-6
of gas turbines, T-43 to T-44
of pumps, temperature vs., P-254 to P-255
of steam turbines, T-82, T-84, T-89 to T-90
of worm gears, P-85 to P-88
ejectors, E-2 to E-3, N-1
elastic deformation, M-39
elastic gauges, M-20 to M-22
elbow flowmeters, C-330
electric control signals (*See* control systems)
electric heaters (*See* heaters, electric)
electric hot pipe tank heaters, H-12 to H-15
electric motors and controls, A-48, E-3 to E-36
AC induction motors used for variable frequency control, E-18 to E-35
acceleration in, E-3 to E-5, E-12, E-24, E-29
accessory devices for, E-35
adjustable frequency motors as, E-10 to E-15
applications for, cost effective solutions, E-6
breakdown rpm region in, E-24 to E-25
breakdown torque point in, E-12 to E-13
breather drains in, E-18
carbon-graphite mix products for brushes in, C-13
cast iron construction, in high corrosion environment, E-15 to E-16
centrifugal compressors, C-187 to C-190
controllers for, motor/controller combinations in, E-10
conveyor powering application, E-21 to E-22
cooler bearings in, E-16
cooling in, E-28 to E-29
corrosion prevention in, E-18
cost, energy costs of, E-7 to E-10
cost, operating cost of, E-6 to E-7
current requirements of, E-10, E-12 to E-13, E-15, E-29
deceleration in, E-29
demand charge and, energy costs of, E-9 to E-10
design/parameter considerations in, E-23 to E-24
duty cycle requirements in, E-5
efficiency of, components affecting, E-5 to E-6
enclosures for, environment of operation and, E-15
energy use in, E-3 to E-5
fans and, E-17, E-28 to E-39
flexibility of mechanical design in, E-34 to E-35
flux level in, motor flux, E-32
frame design vs. performance in, E-34 to E-35

frequency requirements of, E-23 to E-24, E-29, E-35
friction in, E-5 to E-6
gaskets in, E-17
harmonics in, E-14, E-33 to E-34
heating, heat transfer (*See* insulation and temperature parameters, below)
high performance drives and, E-23
horsepower requirements of, E-23 to E-24
induction motors as, E-10 to E-15
insulation and temperature parameters for, E-14 to E-15, E-25 to E-28, E-31 to E-32
kilovolt-ampere (KVA) rating in, E-8 to E-9
load requirements in, E-5 to E-7
load torque requirements for, E-11 to E-15
lubrication in, E-15 to E-16
maintenance of, E-7
NEMA design C and D motors in, E-14
noise of, A-24, E-32 to E-34, E-28
oil mist lubrication in, E-16
overload torque in, E-24 to E-25
oversizing (derating) of, disadvantages of, E-29, E-34
parasitic forces and noise in, E-33 to E-34
peak current rating in, E-25 to E-26
positive lubrication system (PLS) in, E-15 to E-16
power factor in, E-7 to E-9
power transistor technology and, E-29 to E-32
pulse wave modulation (PWM) and, E-32
pumping applications for, E-22
reactive kilovolt-ampere (KVAR) rating in, E-8 to E-9
real power kw consumed by, E-7 to E-8
RMS current rating in, E-25 to E-26, E-28
rotor in, E-20
sizing considerations for, E-34
speed range of, E-15
speed torque curves for, E-3 to E-4, E-10 to E-15
speed vs. frequency in, induction type, E-13 to E-14
squirrel cage type, E-19
starting torque in, E-14, E-24
stator in, E-19
synchronous speed point in, E-12 to E-13
temperatures parameters for, E-14
testing of, E-18 to E-22
torque requirements in, E-23 to E-25
transition voltage (dV/dt) time, E-30
vibrational analysis in, E-18 to E-22, E-33
voltage requirements of, E-15, E-23 to E-24, E-29, E-32
voltage unbalance and operating cost in, E-6 to E-7
V-ring shaft slinger (Buna-N shaft seal) in, E-17
electric plastics, P-3 to P-7
Electric Power Research Institute (EPRI), C-351
electric transducers, M-22 to M-24
electric vehicles, conductive polymers in, P-6
electrical and electronics products industries pollutants, P-22 to P-23
electrical contacts, carbon-graphite mix products and, C-13
electrical discharge machining (EDM), M-35
electrical radiant furnace vaporizers, V-5 to V-6
electrical system, in reciprocating (labyrinthine) compressors, C-110
electrodialysis, D-2
Electrofin electric heaters, H-8 to H-12
electrohydraulic actuators, A-37
applications for, A-39
components of, A-41
control regulator function and main features of, A-42
conversion of electrical control signals in, components for, A-40
drive/control value options in, A-45
fuel system, F-31
power regulated electromagnet in, A-41
regulating valves using, A-43
regulator using, electrically controlled, A-44
sensors and, A-46
speed protection device using, A-47 to A-48
technical data for electronic component assemblies in, A-45
electrohydraulic governors, T-104 to T-106
electromagnetic bearings (*See* magnetic bearings)
electromagnets, electrohydraulic actuators using, A-41
electromechanical (displacement) method, in level sensing, C-389
electronic data loggers, for vibrational analysis (VA), C-270
electrostatic precipitators
in air pollution control, A-83 to A-85, A-102
computational fluid dynamics to analyze flow through, C-5
elevators and escalators, Sp-7 to Sp-8, Sp-31 to Sp-32
elutriating stream concept, centrifugation, C-35
emergency power generation (*See* engines, gas)
emissions (*See also* air pollution; carbon dioxide), E-36 to E-38, E-50 to E-52, F-20, P-57 to P-60
acid rain, Canada vs. U.S., A-10 to A-12
boiler, B-11
carbon dioxide (CO_2) (*See* carbon dioxide)
carbon monoxide (CO) as, E-38, P-62 to P-64
CCME (Canada) National Emission Guidelines for kilns, C-28 to C-34
cement kilns and, C-22, C-28 to C-34
computational fluid dynamics to model, C-1 to C-7
continuous emissions monitoring (CEM) in, C-34
crude/heavy fuel oil, F-44 to F-45
environmental accountability, E-40 to E-49
environmental economics of, E-50 to E-52, E-54
fossil fuel, E-36
fuel system control, F-30
gasoline powered engines, E-39
guidelines for, stationary combustion turbines, E-36 to E-38
liquefied natural gas (LNG), F-41
naphtha, F-43
nitrogen oxide (NO_x), F-43, F-45, E-36 to E-38, E-50
ozone, O-4 to O-26
particulate, E-36
power production and, P-72
refrigerants and, R-13
sulfur oxides (SO_x) (*See* sulfur oxides)
emissivity, M-10
emulsification, agitators in, A-38
enclosures, gas turbine (GT) explosion hazard assessment for, E-67, E-70 to E-71
end product handling, air pollution control and, A-83, A-97 to A-98
endrin, V-15
energy efficiency, in isotherm turbocompressors, C-190 to C-191
energy recovery, synchronous clutches and, P-107 to P-108, P-114 to P-115
energy use, pulp and paper industry, P-204 to P-205
Enertran (heat pumps), H-2 to H-6
engine condition monitoring (ECM) (*See* condition monitoring)
engine condition–monitoring systems (ECMS) (*See* condition monitoring)
engines, gasoline powered, E-38 to E-40
coolant in, C-408 to C-412
diesel, E-38
emissions from, E-39
four stroke, E-38, E-40
reciprocating, E-38 to E-39
scavenging in, E-39
torque converters and in, P-172 to P-174
turbochargers for, E-38 to E-39
two stroke, E-38, E-40
enthalpy, steam turbines and, T-82, T-84
Enthone Inc., P-4
entrained air/gases, vs. pump performance., P-271 to P-272, P-278 to P-281
ENVAR biodegradable plastics, P-2
Environment Canada, A-13, O-4 to O-26, P-8, R-1 to R-10
environmental accountability, A-40 to A-49
accidents/incidents and, E-46
environmental economics and, E-49 to E-56
feeding management (livestock) and, E-44
ISO VILJA technology in, E-46, E-48
life cycle inventories (LCIs) in, E-43
performance table for, E-45
reports of, E-47 to E-48
risk management and, E-44
environmental air monitoring (*See* air pollution control; emissions)
environmental controls, computational fluid dynamics to model, C-7
environmental degradation of plastic, P-1
environmental economics, E-47 to E-56
biological diversity and, E-50
cost-benefit analysis for, E-51 to E-56
ecolabeling in, E-54 to E-55
emission reduction and, E-50 to E-52, E-54
environmental accountability and (*See* environmental accountability)
environmental management systems (EMS) in, E-52
forest preservation and, E-52
key ratios in, E-51
life cycle assessment (LCA) in, E-55 to E-56
packaging, resource efficient, E-52 to E-54
profitability, long term, E-52 to E-55
research and development in, E-52
taxes and charges for environmental protection and, E-51
waste reduction, E-54
"yardsticks" of, E-50 to E-54
Environmental Management System (EMS) standard in, F-13 to F-16
environmental management systems (EMS), E-52
environmental protection, Sp-1 to Sp-2
accidents/incidents and, E-46
agricultural and food products, A-49
biological diversity and, E-50
biotopes, F-13
condensers and, C-233
deforestation effects and, F-12
ecolabeling in, E-54
ecolabeling in, E-55
ecological parks, E-1
ecosystems, E-1 to E-3
emission reduction and, E-50 to E-52
emission reduction and, E-54
environmental accountability, E-40 to E-49
environmental economics in, E-49 to E-56
Environmental Management System (EMS) standard in, F-13 to F-16
environmental management systems in, E-52

forest preservation and, E-52
forest product industry, F-12 to F-24
key ratios in, E-51
life cycle assessment (LCA) in, E-55 to E-56
packaging, resource efficient, E-52 to E-54
plastics and, P-1 to P-2
"red tide" algae (*Ptychodiscus brevis*) and, C-78
reindeer, F-16
taxes and charges for, E-51
ultrasonic cleaners and, T-5 to T-6
waste management and, W-1 to W-12
waste reduction, E-54
"yardsticks" of, E-50 to E-54
Environmental Protection Agency (EPA), E-40 to E-49, P-8
enzymes, E-43
epichlorodyndrin, P-11 to P-31, P-36, P-40 to P-57
epoxy, as interior tank coating, T-4
Epson, P-5
equivalent series resistance (ESR) polymers, P-6
erosion, in air filtration systems, A-75 to A-78
erythrobates, E-44
ethane, V-16
ethanol, C-418, F-37, V-15
ethanolamine, V-15
ethoxyethanols, P-11 to P-31, P-40 to P-57
ethyl acrylate, P-11 to P-31, P-36, P-40 to P-57
ethyl chloride, V-15
ethyl ether, C-415
ethylbenzene, P-11 to P-31, P-40 to P-57
ethylene, C-418, P-11 to P-31, P-40 to P-57, V-16 to V-17
ethylene dichloride, V-7, V-15
ethylene glycol (EG), C-409 to C-412, P-11 to P-31, P-40 to P-57
ethylene oxide, C-415, P-11 to P-31, P-36, P-40 to P-57, V-7, V-15
eutrophication, P-64 to P-65
evaporative coolers (*See* chillers; dairy coolers)
evaporative cooling towers, C-423 to C-426
exhaust gas recovery, C-78
exhaust gas temperature monitoring, C-260 to C-261
exhaust plume, computational fluid dynamics modeling of, C-3
exhaust stacks (*See* stacks)
exhausters, centrifugal gas, E-56 to E-57
existing refinery, R-8
expanded refinery, R-8
expanders, turboexpanders, C-151 to C-152, T-114 to T-115
synchronous clutches and, P-107
expansion joints, D-18, E-57 to E-67
ambient temperatures and, E-64 to E-65
axial/vs. axial movement, E-63
bias cutting of, E-65
cold-to-cold, E-58 to E-59
composition of, E-59 to E-60
cracking damage vs., E-60 to E-61
differential thermal expansion in, E-58
distortion damage vs., E-61
fabric vs. metallic, E-60
flexible elements of, E-60
floating sleeves in, E-65 to E-66
heat/vs. heat damage, E-61 to E-62
hot-to-cold, E-58 to E-59
hot-to-hot, E-58 to E-59
insulation and, E-66
insulation pillows and, E-65 to E-66
mounting flanges and, E-63 to E-64
noise vs., E-66 to E-67
outer cover of, E-60
pantograph control mechanism and, E-63
proximity of building to, E-64 to E-65
PTFE in, E-60
radial growth of steel parts vs., E-64 to E-65
support/vs. support frame damage, E-60
thermal barrier of, E-60
water washing and, E-64
explosion hazard assessment, E-67 to E-87
abrasive materials, A-8
air movement studies in, E-67, E-71
American National Standards Institute (ANSI) codes for, E-87
American Petroleum Institute (API) code for, E-86
as low as reasonably practicable (ALARP) risks and, E-80
British Gas Code for, E-86 to E-87
case study in, gas turbine power plants (UK), E-81 to E-85
combined cycle gas turbine (CCGT) plants and, E-67, E-70 to E-71, E-74, E-81 to E-85
combined heat and power (CHP) plants and, E-67, E-70 to E-71, E-81 to E-85
dilution ventilation vs., E-87
electric heater, H-17 to H-18
fault tree logic diagrams for, E-79 to E-80
flammable materials and, E-67, E-76 to E-78, E-84, E-86
fuel leaks and E-69 to E-70, E-76, E-82 to E-85
full air flow balance tests in, E-71
gas detection vs., E-70
gas turbine (GT) enclosures and, E-67, E-70 to E-71
hazard analysis (HAZAN) in, E-68, E-379 to E-80
hazardous operations (HAZOP) review in, E-75 to E-76
Health and Safety at Work (HSWA) Act (UK) and, E-87
identification of hazards in, E-71 to E-76
ignition sources and, E-67, E-78 to E-379
incidence of explosion and, E-84 to E-85
Institute of Petroleum (IP) code for, E-87
liquefied natural gas (LNG), F-39
lower explosion limit (LEL) in, E-70, E-76
methane and, E-76 to E-77
naphtha, F-42 to F-43, E-76
National Fire Protection Association (NFPA) codes for, E-86
natural gas and, E-76
operating conditions vs., E-74
process hazard review (PHR) in, E-67, E-74 to E-76
propane and, E-76
risk based approach to, E-71, E-75 to E-78, E-80 to E-81
smoke tests in, E-73
standards for, E-86 to E-87
static pressure checks in, E-72
tanks and, T-28 to T-29
Teeside Power Station (UK) example of, E-67 to E-87
3–D velocity grid test in, E-72 to E-73
ventilation vs., E-70, E-76, E-87
external gear pumps, P-260 to P-264
extraction governors, T-106
extraction processes, E-44
agitators in, A-38
liquid-solid, E-87
extraction steam turbines, T-98 to T-100
extrusion die, computational fluid dynamics modeling of, C-4
extrusions, computational fluid dynamics to model, C-7
fabric filters, in air pollution control, A-83, A-85 to A-86
fabricated metal industries pollutants and, P-20 to P-21
Fahrenheit temperature conversion, M-12
fans, C-136, F-1 to F-5
acceleration of, F-3
air density vs., F-1, F-3
air horsepower (ahp) of, F-5
applications for, F-2
blades in, F-1 to F-3
capacity (cfm) of, F-1 to F-3
centrifugal fan types, F-1
computational fluid dynamics to model shapes in, C-5
cooling towers and, F-4
cylinder velocity recovery capability of, F-4
drying, D-4
in electric motors, for cooling, E-17, E-28 to E-29
forward vs. backward curved blades in, F-1
in generators and turbogenerators, G-6, G-8, G-11
horsepower of, F-1, F-5
laws of operation in, F-1 to F-2
mass flow rate of, F-4
net flow area of, F-3
performance range, by blade type, F-2 to F-3
speed (rpm) of, F-1
static pressure (hs) of, F-1 to F-5
total pressure differential of, F-4
variable pitch, F-3
velocity of, F-3 to F-4
velocity pressure of, F-4
water density vs., F-3
far fields, in sound, A-20
fast fourier transform (FFT), sound intensity meters using, A-16
fast response valves, C-405 to C-408
fasteners, Sp-8 to Sp-10
fatal accident rate (FAR), E-80
fatigue, M-40
fatty acids, crystallization of, C-68 to C-72
fault tolerance, in control systems, C-355
fault tree logic diagrams, in explosion hazard assessment, E-79 to E-80
federal government service industries, pollutants and, P-31
feeding management (livestock), environmental accountability and, E-44
feedwater heating, in steam turbines, regenerative, T-85 to T-87
fermentation, E-44
ferric oxide (Fe_2O_3), C-25
ferrous alloys, abrasives and, A-2
fertilizers, V-15
fiber forming, computational fluid dynamics to model, C-7
filled system thermometers, M-8
fillers, A-1
Filpac TCR system, A-100 to A-101
Filsorption system, A-96 to A-97, A-100 to A-101
filter designs and materials (*See also* air filtration; air pollution control), C-109, F-5 to F-12
air (*See* air filtration; air pollution control)
air purification using, A-102
carbon-graphite mix products and, C-13
cartridges for, F-6 to F-8
closures for, F-6
computation fluid dynamics in, C-1 to C-7
construction of, F-10
fuel gas conditioning systems, F-25, F-28
gas filters, F-6 to F-11
in line gas, F-10 to F-11

multitube, F-9 to F-10, F-28
optional features in, F-10
separators and, S-13 to S-16
sizing and performance of, F-9 to F-10
filter in/filter out amplitude vs. rpm, in vibrational analysis, C-276 to C-278
filtered signal, vibrational analysis (VA), C-263
fin tube type electric heaters, H-9 to H-12
fire hazards
tanks and, T-28 to T-29
toxic chemicals, C-59
fire ratings, soundproofing materials, A-36
first aid procedures for toxic chemicals, C-61
fittings, Sp-22 to Sp-23
flame arrestors, V-31
flammable materials, in explosion hazard assessment, E-67, E-76 to E-78, E-84 to E-86
flanges, Sp-22 to Sp-23
synchronous clutches and, P-118
flapper valves, D-3
flare carbon, vs. air filtration systems, A-74 to A-75
flare stacks (*See also* stacks), F-12
flashbox, condensers, C-238 to C-239
flexible AC transmission system (FACTS), C-353 to C-354
flexible connectors, in soundproofing and noise control, A-24 to A-25
flexible couplings, synchronous clutches and, P-118
float and tape tank gauges, T-18
float valves, vaporizers, V-25 to V-28
floating covers, F-12
floating sleeve expansion joints, E-65 to E-66
flow control, C-333 to C-334
in hydrodynamic power transmission, P-128, P-131, P-133
in fuel systems, F-29 to F-37
in stacks, design parameters affecting, S-30 to S-33
in turbocompressors, C-333
pulsation dampeners in, P-214 to P-218
flow errors, M-15
flow measurement (*See also* liquid level/liquid flow control), C-389 to C-390, M-24 to M-31, Sp-10
adiabatic expansion factor in, M-25
Bourdon tube in, P-224
capacity of flow in, M-24 to M-25
coefficient of discharge in, M-24
combined flow coefficient in, M-24
compressible fluid, M-28 to M-29
Delaval applications and, M-29 to M-30
differential pressure in, M-24
flow rate calculations in, M-27 to M-30
incompressible fluid, M-28
manometer differential pressure in, M-24
net expansion factor in, M-25
nomenclature and terms in, M-24 to M-25
nozzle and, M-23, M-25 to M-26, M-29
numerical factor in, M-24
orifice and, M-23, M-25, M-29 to M-30
pipe diameter in, M-24
primary element construction and installation for, M-25 to M-27
rate of flow in, M-25
Reynolds number in, M-25
specific heats ratio in, M-24
specific weights in, M-25
thermal expansion factor in, M-24
throat area, M-24
throat diameter in, M-24
velocity of approach factor in, M-24
venturi tube and, M-23, M-26, M-29
flow modeling, computational fluid dynamics, C-3
flow nozzles (ASME), C-330, M-23 to M-29
flow rate calculations, M-27 to M-30
flow resistivity in absorptive materials, A-34
flow stream pressure, M-15
flow switches, C-389
flow-through bioassay, R-9
flow transducers, C-328 to C-330
flowmeters, C-330
Flowserve, USA, S-1 to S-9
flue gas desulfurization (FGD), A-83, A-86, A-89 to A-90
Fluent project, C-6 to C-7
fluid bed dryers, D-4
fluid catalytic cracker (FCC), pulsation dampener in, P-217
fluid handling, computation fluid dynamics in, C-1 to C-7
fluidization, computation fluid dynamics in, C-1 to C-7
fluidized bed, F-12
fluids, hydrodynamic power transmission and, P-123
fluoride ion cleaning, M-34
flux level, motor flux, E-32
fly-ash handling, A-97 to A-98, C-28
foaming cleaners, T-67 to T-68
foams, chlorofluorocarbons in, O-14, O-16 to O-26
food industries (*See also* agriculture and agricultural products)
dairy coolers, C-412 to C-413, C-420
irradiation technology for, I-3 to I-5
pollutants and, P-14 to P-15, P-29
Food Technology Service Inc., food irradiation facility, I-3 to I-5
forced feed type lubrication, L-25
forced vibration, C-264, C-301, C-313 to C-316, C-322 to C-323
forcing frequency in, C-264
forest preservation, E-52
forest product industry (*See also* pulp and paper mills), A-48, F-12 to F-24
AssiDomän forestry management case study in, F-13 to F-18
barrier coating production and, F-15, F-21 to F-23
biotopes in, F-13
carbon dioxide emissions, F-18
contemporary forest and timber industry practices in, F-12 to F-21
corporate environmental objectives of, F-14
deforestation effects and, F-12
ecological balance sheet in, F-16 to F-18
ecological "footprint" of, F-22
emissions control in, F-20
Environmental Management System (EMS) standard in, F-13 to F-16
environmental work list, sample year 1997, F-20
Forest Stewardship Council (FSC) (Sweden) in, F-13
forestry work in, F-13 to F-16
key environmental data for AssiDoman, F-25
packaging and paper products in, F-21 to F-26
reindeer herding as adjunct to, F-16
sawmill and wood processing operations, F-16, F-19
seedlings for, F-21
thinning and regeneration in, F-14 to F-18
timber production in, F-18 to F-21
waste management in, F-20
water conservation and, F-17
Forest Stewardship Council (FSC) (Sweden), F-13
forging, M-43
form scan geometry gauges, A-2
formaldehyde, P-4, P-11 to P-31, P-36, P-40 to P-57, V-7, V-15
forming, computation fluid dynamics in, C-1 to C-7
fosfomycin sodium (FOS), freeze drying and, D-13, D-17
fossil fuel, F-37
ASME certification program for, Sp-30
emissions from, E-36
fouling
in air filtration systems and, A-76, A-78
in condensers, C-243 to C-244, C-248
four-stroke engines, E-38 to E-40
fractional distillation, D-2 to D-3
fractionating column, D-3
fractionator, R-8
fracture, material M-39 to M-40
free vibration, C-264, C-301, C-305 to C-306
freeze drying (*See also* drying), D-4 to D-18
applications for, D-8
bioabsorbable polymer production using, D-17
clothing for TBA handling operators in, D-5 to D-7
ejectors in, E-2 to E-3
fosfomycin sodium (FOS) production using, D-13, D-17
frozen TBA water mixtures in, D-8 to D-9
glass powder production using, D-18
lipids and liposomes, with TBA, D-13 to D-17
liposoluble platinum (II) production using, D-17
macromonomer solution and TBA in, D-18
mass transfer–accelerator effect of TBA in, D-8
nanoparticle drug dispersant production using, D-17
N-methyl pyrrolidone (NMP) as solvent in, D-13
pharmaceutical industry use of, D-4 to D-8
physical properties of, D-5
porous resistance of dry product layer vs. TBA in, D-8, D-10 to D-11
scanning electron microscopic (SEM) studies of TBA solutions in, D-8, D-15 to D-16
sublimation in, D-8
sublimation rates of TBA/water solution in, D-5, D-7
sugar/sucrose and TBA solutions in, D-8 to D-18
TBA–water phase diagram in, D-5 to D-6
tertiary butyl alcohol (TBA) in, D-5 to D-18
vacuum dryer for, D-12 to D-13
water as solvent in, drawbacks of, D-4 to D-5
water-unstable drugs and, D-17
freeze protection, in vaporizers, V-12 to V-13, V-17, V-19
frequency, C-270 to C-272
electric motors requirements, E-13 to E-14, E-23 to E-24, E-29, E-35
sound, A-28
subsynchronrous frequency vibration, C-291 to C-294
in vibrational analysis (VA), C-262, C-272, C-287, C-301 to C-302
frequency control, variable AC induction motors used for, E-18 to E-35
friability of abrasives, A-3 to A-4, A-6
friction, coefficient of, carbon-graphite mix products, C-9
friction, friction loss
in electric motors, E-5 to E-6
in pumps, P-222
in worm gears, P-86 to P-88
friction (coulomb) damping, C-307

Frövi Light paperboard, E-52
FTSI, food irradiation facility, I-2 to I-3
fuel, F-37 to F-45
  oil sands and, O-1
  synthetic crude, O-1 to O-2
fuel and fuel systems
  life cycle assessment (LCA) for, L-8 to L-10
fuel gas conditioning systems
  dampeners, F-27
  filter separator in, F-25
  filter separators in, F-28
  heater, F-27
  line separators in, F-29
  metering, F-27
  multitube filters in, F-28
  pressure regulation station/valves (PRS/PRV) in, F-25 to F-26
  separators for, range of, F-28 to F-29
  vertical absolute separators in, F-29
  vertical dry scrubber in, F-25, F-28 to F-29
  vertical gas separators in, F-28
fuel gas conditioning systems, F-24 to F-29
fuel leaks
  explosion hazard assessment and, E-69 to E-70
  explosion hazard assessment and, E-76
  explosion hazard assessment and, E-82 to E-85
fuel regulation, C-403 to C-408
fuel regulators
  current to pressure (I/P) converters for, C-392 to C-401
  eroderivative fuel regulator for gas turbine, C-354 to C-358
fuel skid, F-34 to F-36
fuel systems and control
  actuators for, F-30, F-31, F-33 to F-34
  emissions control in, F-30
  features of, F-30 to F-33
  schematic of, F-32
  servomotor actuated plug metering valve in, F-36
  skid for, fuel skid, F-33 to F-34
  testing of, F-34 to F-36
  valves for, F-30, F-32 to F-33
fuel systems and control, F-29 to F-37
fuels, V-16
  biomass, P-205 to P-214
  black liquor, P-205 to P-214
  crude oil, F-38, F-43 to F-45
  fossil fuels, F-37
  gaseous fuels, F-37
  heavy fuel oil, F-38, F-43 to F-45
  impurities in, L-9
  liquefied natural gas (LNG), F-38 to F-45
  liquefied petroleum gas (LPG), F-38, F-41 to F-42
  liquid fuels, F-37
  liquid natural gas (LNG), L-21 to L-24
  naphtha, F-38, F-42 to F-43
  water in, L-9
  white liquor, P-205 to P-214
fumigation process, ejectors in, E-2 to E-3
functional food, E-44
furniture and fixture industries, pollutants and, P-18

gamma radiation, food irradiation using, I-1 to I-5
gas actuated sensors, C-378
gas exhausters, E-56 to E-57
gas filters, F-6 to F-11
gas path component management systems, M-41
gas path monitoring, C-299
gas pipeline (*See* pipeline and pipeline pumping stations)
gas seals (*See also* seals), S-1 to S-9
  advanced pattern groove (APG) in, S-3 to S-4
  GASPAC compressor seals, S-1 to S-9
  J ring, S-5 to S-9
  O rings, S-1, S-5
  polytetrafluoroethylene (PTFE) in, S-5 to S-9
  retrofitting of, S-8 to S-9
  symmetrical T groove (SMT) in, S-4 to S-5
gas separator, horizontal, S-27 to S-29
gas separators, vertical, S-22 to S-24
gas treating, R-5
gas turbines (*See* turbines, gas)
gaseous fuels, F-37
gaskets, E-17, Sp-22 to Sp-23
gasoline, C-418
gasoline hydro treatment modeling (OLMES project) using CFD, C-7
GASPAC compressor seals, S-1 to S-9
gate valve, A-43
GateCycle software to monitor biomass fuel use at paper mill, P-211 to P-212
gauge blanks, Sp-11
gauge pressure, M-15
gauge type instruments, pressure switches, C-383
gauges, Sp-11
gearboxes (*See also* power transmission), G-1
gears (*See also* helical gears; power transmission; worm gears), G-1, P-74 to P-98
  adjustment of, P-92
  in agricultural production, A-48
  American Gear Manufacturers Association (AGMA) and
  automatic turning, synchronous clutches and, P-107 to P-113
  cross sectional views of, P-78 to P-79
  design requirements/specifications for, P-75 to P-76
  distress in, P-74 to P-75
  durability of, P-75 to P-76
  in gas turbines, C-343, C-345
  in generators and turbogenerators, G-16
  hardness (Sc) values of, P-78
  helical, P-74 to P-82
  high speed, P-98 to P-107
  hydrodynamic power transmission and, P-131
  installation of, P-82, P-97 to P-98
  in isotherm turbocompressors, C-200
  lubrication of, P-81 to P-82, P-96 to P-97
  maintenance of, P-82
  number of teeth in, P-92 to P-93
  overload in, P-74 to P-75
  pitting in, P-74 to P-75
  reduction type, P-77, P-79 to P-81
  scoring in, P-74 to P-75
  scuffing in, P-75
  self-locking, P-88
  sizing of, P-75 to P-76
  in steam turbines, T-79
  synchronous clutches and, P-107, P-113, P-118
  tooth breakage in, P-74 to P-75
  tooth contact in, P-90 to P-92
  tooth form in, P-88 to P-90
  vibrational analysis (VA) and, C-294 to C-296, P-82
  worm, P-82 to P-98
General Electric, M-31
General Electric LM-2500 gas generator, M-33
generators and turbogenerators, G-1 to G-20
  accessories for, G-3 to G-4
  arrangement forms for, G-3
  axial fan in, G-11
  balancing of, G-11
  base frame, G-20
  bearing end shields in, G-6 to G-7
  bearings in, G-7 to G-9
  brush gear in, G-16
  brushless excitation in, G-12 to G-16
  carbon-graphite mix products for brushes in, C-13
  configuration of, G-1
  constant winding temperature operations in, G-20
  control and protection in, G-18 to G-20
  cooling in, G-1 to G-3, G-11 to G-12, G-16
  current transformers in, G-19
  excitation system for, G-3
  exciter housing in, G-15
  fan and fan covers for, G-6, G-8
  heating elements for, G-19
  inspection and testing of, G-17 to G-18
  insulation in, G-6, G-10 to G-11
  low ambient temperature operation in, G-20
  main exciter in, G-12 to G-13
  noise reduction in, G-20
  operating characteristics of, G-20
  overspeed running of, G-11
  pilot exciter in, G-15
  protective equipment for, G-19 to G-20
  rotating rectifier in, G-13
  rotor cooling in, G-11 to G-12
  rotor in, G-3, G-9 to G-10, G-16 to G-17
  rotor retaining and support rings, G-11
  rotor terminals in, G-9 to G-10
  rotor winding in, G-10 to G-11
  slip ring housing in, G-16 to G-17
  slip ring shaft in, G-16
  standards, standard design for, G-1
  static excitation in, G-16 to G-17
  static thyristor rectifier as excitation system in, G-3
  stator core in, G-4 to G-5
  stator terminals in, G-6
  stator winding in, G-5
  stators and stator frame for, G-4 to G-5
  support bearing in, G-15
  surface treatment for, G-16
  synchronous clutches and, P-115 to P-121
  synchronous compensator operation in, G-20
  technical data for, G-4
  temperature monitoring and control, G-18 to G-19
  vibration measurement, in bearing, G-19
genetic modification, E-44
genetically modified micro-organism (GMM), E-44
genetically modified organism (GMO), E-44
GeoCenters Inc., D-17
geothermal heat pumps, H-1 to H-6
geothermal plants, centrifugal gas exhausters in, E-56 to E-67
glass bead peening, A-1
glass powder, freeze dry production of, D-18
global warming and GWP, C-13, C-28 to C-34, R-11, R-13 to R-14
globe valves, CE-18 to CE-392
glycerine, V-15
glycol, as coolant, C-413
governors
  dead band in, T-102
  electrohydraulic, T-104 to T-106
  extraction type, T-106
  mechanical, T-101 to T-102
  mechanical-hydraulic, T-102 to T-104
  steam turbines and, T-100 to T-108
grade of abrasives, A-5 to A-7
grain, in materials, M-39
grain boundaries, M-39
grain growth, M-39
grain size of abrasives, A-1, A-6

graphite, carbon-graphite mix products, C-7 to C-13
Gravi Merge Blending Silos, T-8
gravity blending, in tanks, T-4 to T-8
gravity mixers, agitators, A-38
grease lubrication, L-25 to L-29
Great Lakes toxic chemical pollution, P-65 to P-72
Greater Vancouver Regional District (GVRD), R-8
greenhouse gases, C-13 to C-14
  chlorofluorocarbons (CFCs) in, C-413
  IEA Greenhouse Gas Implementing Agreement, C-14
grinding (*See also* abrasives), A-1, A-3 to A-5, M-35
grinding wheels, A-1 to A-7
grit, for shot peening, A-7 to A-9
grit size of abrasives, A-5 to A-6
gross observed volume (GOV), T-25 to T-27
gross standard volume (GSV), T-25 to T-27
ground injection of CO_2, in Sweden, C-14 to C-21
grounding, tanks and, T-31 to T-32
GT 7 gas turbine (Alstom), C-79
guards, machine, Sp-11
gust loading, stacks and, S-35 to S-38

halocarbons, R-13
Halon, ozone depletion and, O-14
hardness of abrasives, A-5 to A-7
hardness (Sc) values, gears, P-78
hardware production pollutants, P-30
harmonic distortion, in power supplies, C-351 to C-352
harmonics
  in electric motors, E-14, E-33 to E-34
  in vibrational analysis (VA), C-261 to C-262, C-266 to C-267, C-282, C-302, C-305, C-310 to C-311, C-314
Hastelloy, M-41
hazard analysis (HAZAN), in explosion hazard assessment, E-68, E-79 to E-80
hazardous operations (HAZOP), explosion hazard assessment, E-75 to E-76
hazardous or toxic materials (*See also* chemicals; explosion hazard assessment; pollution), C-42 to C-62
  abrasives, abrasive materials, A-8
  ASME certification program for, Sp-30
  cement using, C-33
  Chemical Manufacturers Association (CMA) guidelines for, C-61
  CHEMTREC information service, telephone number, C-61
  container for, C-45
  cooling and, C-415, C-418
  cylinders for shipment of, unloading, C-52 to C-54
  decontamination of empty containers and, C-62
  disposal of, C-62
  drums for shipment of, unloading, C-54
  explosion hazard assessment, E-67 to E-88
  fire hazards of, C-59
  first aid procedures for, C-61
  health hazards of, C-59
  incineration plant for, A-97
  Material Safety Data Sheets (MSDS), C-43, C-58
  metallurgy and, M-32
  protective clothing for handling of, C-59 to C-61
  reactivity of, C-43 to C-45
  respirators for safety in handling, C-59 to C-61
  shipping and handling of, C-45 to C-54, C-58 to C-61
  spills and leaks of, cleanup, C-61 to C-62
  storage containers for, C-56 to C-58
  tank car unloading guidelines for, C-46 to C-52
  tank truck unloading guidelines for, C-51 to C-52
  Threshold Limit Value of, C-61
  toluene diisocyanate (TDI), C-42 to C-62
  transport of, T-40 to T-41
  unloading of, C-45 to C-54
  waste management and, W-1 to W-12
hazards (*See* color coding; explosion; specifications lists)
head, P-222, P-224 to P-228
Health and Safety at Work (HSWA) Act (UK), explosion hazard assessment, E-87
health hazards of toxic chemicals, C-59
heat, air purification using, A-102
heat and power (H&P) applications, C-81
heat exchanger control, hydrodynamic brakes, B-17
heat exchangers (*See also* cogeneration; regenerator; vaporizers), D-4, H-1
heat pumps, H-1 to H-6
  dehumidification (mechanical) and, H-4 to H-5
  earth loop in, H-1 to H-3
  heat reclaim options/opportunities shown for, H-5 to H-6
  high humidity conditions and, H-4
  horizontal earth loop in, H-2
  hybrid systems using, H-5
  liquid cooled air conditioning, H-4
  liquid to air systems, H-3
  liquid to liquid systems, H-3
  on demand hot water (ODHW) heating system using, H-4
  open loop (well system), H-1 to H-2
  operating costs comparisons, H-4
  partial hot water (PHW) heating systems using, H-3 to H-4
  pond and lake loop in, H-1
  vertical earth loop in, H-2
heat recovery steam generator (HRSG) (*See also* cogeneration), C-78, P-208
heat recovery systems, nitrogen oxide (NO_x) emission vs., E-37 to E-38
heat sinks, C-419 to C-421
heat transfer
  computation fluid dynamics in, C-1 to C-7
  condensers, C-239, C-242 to C-243
  electric motors and, E-25 to E-28
  expansion joints and, E-61 to E-62
  impedance type electric heaters, H-8
heat treatment (*See* metallurgy)
heaters, electric, H-6 to H-23
  bayonet type, H-13
  coil type stab in type, H-14
  controls for, H-16 to H-20
  cooling for control systems in, H-18
  Dowtherm type, H-22
  Electrofin type, H-8 to H-12
  explosion proof control panels for, H-17 to H-18
  fin tube type, H-9 to H-12
  heat transfer/pressure drop impedance type, H-8
  horizontal in tank type, H-14
  hot pipe tank heaters, H-12 to H-15
  impedance type, H-6 to H-12, V-1 to V-5
  Inconel type, H-10
  line type, H-13
  ohmic type, H-19 to H-23
  process type, H-15 to H-16
  radiant type, H-22 to H-23
  resistance type elements in, H-11, V-1 to V-5
  sheathed element process type, H-15 to H-16
  suction type, H-13
  thyristor controls in, H-16 to H-19
  vapor type, H-11, V-1 to V-5
  vertical cluster in tank type, H-14
heating elements, in generators and turbogenerators, G-19
heating pollutants, P-30
heating systems/heat pumps, H-1 to H-6
heavy fuel oil, F-37 to F-38, F-43 to F-45
heavy metals, A-96 to A-97
helical gears, P-74 to P-82
  arrangements of, P-76 to P-81
  cross sectional views of, P-78 to P-79
  design requirements/specifications for, P-75 to P-76
  distress in, P-74 to P-75
  durability of, P-75 to P-76
  hardness (Sc) values of, P-78
  installation of, P-82
  lubrication of, P-81 to P-82
  maintenance of, P-82
  overload in, P-74 to P-75
  pitting in, P-74 to P-75
  reduction type, P-77, P-79 to P-81
  scoring in, P-74 to P-75
  scuffing in, P-75
  service factor values for, P-77
  sizing of, P-75 to P-76
  tooth breakage in, P-74 to P-75
  vibrational analysis of, P-82
  worm type, reduction, P-84 to P-87
helical tube sensors, C-386
helium, C-95, C-99
Hepralidae moth in air filter system, A-51
Hercules filters, A-81
hertzian stress, P-76
hexane, C-418
Hickman butyl phthalate manometer, M-22
high efficiency (Hercules) filters, A-81 to A-82
high pressure systems, Sp-11
high speed drive systems (*See* power transmission)
high speed gears, P-98 to P-107
  axial tilting pad bearings in, P-104 to P-107
  back-to-back test bed for, P-99 to P-101
  deformation analysis in, P-102, P-104
  design considerations in, P-107
  radial tilting pad bearings in, P-101 to P-104
high velocity oxygen fuel (HVOF) coatings, M-35
high voltage direct current (HVDC), C-353 to C-354
high voltage suppression systems, T-30
high vs. low velocity air filtration systems, A-74
Hoechst Acetyls Singapore, C-41
Hoechst AG, P-5
homogenization, A-38, A-48
Homprera moth in air filter system, A-51 to A-52
horizontal gas separator, S-27 to S-29
horizontal in tank electric heater, H-14
horsepower
  in electric motors, E-23 to E-24
  in fans, F-1, F-5
  in gears, loss of
  pump requirements for, P-225 to P-226
  in rotary pumps, P-269 to P-270
  in steam turbines and, T-81
hot corrosion, M-40
hot isostatic pressing (HIP), M-41
hot-to-cold expansion joints, E-58 to E-59
hot-to-hot expansion joints, E-58 to E-59
hot water, pumps and NPSH, for, P-236
hotwell, condensers, C-238
housings for air filtration systems and, A-53 to A-58, A-70
huff-and-puff design, A-49 to A-50

humidification process, ejectors in, E-2 to E-3
humidity
  vs. air filtration systems., A-51 to A-53, A-57, A-74
  vs. axial compressors., C-156
  gas turbines and, T-58, T-65 to T-67
  heat pump and, H-4
  in isotherm turbocompressors vs., C-191, C-194
hybrid heat pump systems, H-5
hybrid inventory measurement system (HIMS) tank gauges, T-22 to T-24, T-26 to T-27, T-36, T-39
Hydra filters, A-81
hydraulic amplification, A-41
hydraulic filters (*See* filters)
Hydraulic Institute Standards, pumps and, P-231
hydraulic pressure pumps, P-242 to P-243
hydraulics, pump, P-221 to P-241
hydrazine, P-11 to P-31, P-36, P-40 to P-57
hydrocarbons, C-85, O-17 to O-18
  as refrigerants, R-15 to R-18
  toxic byproducts of, C-42 to C-62
hydrochloric acid, A-9, P-11 to P-31, P-40 to P-57
hydrochlorofluorcarbons (HCFCS), R-10 to R-15
hydrocracking, in petroleum industry, R-3
hydrodynamic brakes (*See* brakes, hydrodynamic)
hydrodynamic power transmission, P-121 to P-166
  annulus in, P-123 to P-127
  arrangement of, P-128
  blades in, P-123, P-138
  boiler feed pumps use of, P-152 to P-164
  characteristics of, P-134 to P-136
  converter circuit in, P-138
  cost of operation of, P-137 to P-138
  coupling selection for, P-164 to P-165
  cutaway view of, P-130
  features of, P-128
  fluid flow through, P-128, P-131, P-133
  fluids in, P-123
  gears in, P-131
  impeller in, P-123 to P-127
  load in, P-128
  mechanical elements to influence converter circuit in, P-138
  offshore pumping station use of, P-151 to P-152
  operation of, P-128 to P-134
  petrochemical plant use of, P-138 to P-147
  pipeline pumping station use of, P-147 to P-152
  power absorption in, P-138
  scope for varying characteristics in, P-138
  speed regulation using, P-155 to P-164
  torque converter in, P-123 to P-127, P-134 to P-136, P-166 to P-184
  torque in, P-128, P-133 to P-134
  transmission ratio in, P-128
  Trilok converters for, P-138
  Type RK variable speed coupling in, P-147 to P-149
  Type SVL variable speed coupling in, P-145 to P-147
  Type SVNL variable speed coupling in, P-142 to P-145
  variable speed couplings in, P-138 to P-147, P-155 to P-164
  vibration in, P-128, P-132
hydrodynamic principle, in turbocouplings, C-346 to C-347
hydrofluorocarbons (HFCS), R-10
hydrogen, C-15, C-85, C-95, C-415, F-37
hydrogen bonding, C-72
hydrogen bromide, V-16
hydrogen chloride, A-9, C-86, V-15
hydrogen cyanide, P-11 to P-31, P-40 to P-57, V-15
hydrogen fluoride, P-11 to P-31, P-40 to P-57, V-16
hydrogen sulfide, C-15, C-86, V-16
hydrokinetic drives (*See* hydrodynamic power transmission)
hydroquinone, P-11 to P-31, P-40 to P-57
hydrostatic power transmission, P-121 to P-124
hydrostatic tank gauges (HTG), T-21 to T-22, T-25 to T-26, T-35 to T-36, T-39
hydrotreating, in petroleum industry, R-4 to R-5
hysteresis, A-41

ice cream, C-76
IcePak, C-5, C-7
icing conditions vs. air filtration, A-49 to A-50
ideal vs. real systems in, C-264
idler rotors, in rotary pumps, P-264
IEA Greenhouse Gas Implementing Agreement, C-14
ignition sources for explosion hazard, E-67, E-78 to E-79, E-83
imbalance (*See* balancing)
impact tubes, in pressure measurement, M-15
impedance type electric heaters, H-6 to H-12, V-1 to V-5
impellers
  in centrifugal compressors, C-172, C-174 to C-177, C-186
  in centrifugal pumps and, P-219, P-226 to P-228
  in hydrodynamic power transmission, P-123 to P-127
  in isotherm turbocompressors, C-191, C-193, C-207, C-223
  in pumps, P-219
  vibrational analysis (VA) of, C-325
in-house power production (IPP), P-72 to P-73
incineration, computational fluid dynamics modeling of, C-1 to C-7
incompressible fluid, flow measurement, M-28
Inconel electric heater, H-10
Inconel, M-40 to M-41
induction electric motors, E-10 to E-15
  AC induction motors used for variable frequency control, E-18 to E-35
induction steam turbines T-98 to T-100
industrial ecological park (*See* ecological parks)
industrial ecology (*See* ecological parks)
industrial effluent, P-71 to P-72
industrial platinum resistance thermometer, M-4
industrial trucks, Sp-11
inertia, vibrational analysis (VA), C-314 to C-315
influence coefficient balancing, C-325 to C-327
Information Handling Services (IHS), ASME, Sp-32
inks, environmentally friendly, F-22
inlet ducts and silencers (*See* acoustic enclosures; air filtration; ducting)
inlet guide vane assembly
  in centrifugal compressors, C-181
  in isotherm turbocompressors, C-207 to C-208, C-214 to C-216
inorganic chemicals, C-41 to C-42, C-64
insect control, insecticides, A-49, A-51, A-66, I-2
inspections
  authorized, Sp-4
  computer aided tomography (CAT) scan in, M-37
  eddy current testing in, M-36
  laser techniques in, M-37
  liquid penetrant (LPI) in, M-36 to M-37
  magnetic particle, M-36
  metallurgy and, M-35
  nondestructive test/ (NDT/NDI), M-35 to M-36
  radiographic, M-35
  ultrasonic, M-36
instrumentation (*See also* condition monitoring; control systems; measurement), Sp-1 to Sp-3
  in reciprocating (labyrinthine) compressors, C-103, C-108, C-111
  in sound measurement, A-14, A-16 to A-17
  in synchronous clutches, P-118 to P-121
insulated gate bipolar transistors (IGBT), E-29
insulation, I-1
  brick lining as, B-23
  chlorofluorocarbons (CFC) in, O-14, O-16 to O-26
  electric motors and, E-14 to E-16, E-25 to E-28, E-31 to E-32
  expansion joints and, E-60, E-66
  generators and turbogenerators, G-6, G-10 to G-11
  MICAFOLD, G-6
  MICAREX, G-5
insulation pillows, expansion joints and, E-65 to E-66
integrally geared compressors, C-219 to C-228
  applications for, C-220 to C-222, C-225 to C-228
  compact (CVK) design, C-227 to C-228
  HVK series, C-220
  internal view of, C-229, C-233, C-235, C-237
  multistage design in, C-219
  operating envelope for, C-230, C-234, C-236 to C-237
  performance data for, C-220 to C-228
  process radial gas turbines (PRT series), C-222 to C-225
  SEE series, C-220
  SEZ series, C-220
  single stage design (direct driven centrifugal), C-220 to C-222
  testing of, C-226, C-234
  VK series, C-220
integrated control system (Series 9500) for gas turbine generators, C-359 to C-361, C-374 to C-377
integrated gasification combined cycle (IGCC), CO_2 and, C-14 to C-16
intensity, of sound, A-11
intercoolers, C-340
  in isotherm turbocompressors, C-193 to C-196, C-207 to C-208, C-215 to C-216, C-219, C-222, C-226
internal gear pumps, P-260 to P-264
International Atomic Energy Agency (IAEA), D-2
International Organization for Standardization (ISO), E-44
inventory control
  hybrid inventory measurement system (HIMS) tank gauges in, T-22 to T-24
  tank gauging in, T-15
  tanks and, central inventory management system for, T-36 to T-39
ionization gauges, M-22
irradiation, food product, I-1 to I-5
ISO 3740–3747, A-18, A-22
ISO 9000 registration program, Sp-29
ISO VILJA technology, E-46, E-48
ISO/DP 9614, A-18
isobutylene, V-16
isodrin, V-15
isoprene rubber, V-15
isopropyl alcohol, P-11 to P-31, P-40 to P-57

isopropylidenediphenol, P-11 to P-31, P-40 to P-57
isotherm turbocompressors (*See also* compressors; turbocompressors), C-136, C-145 to C-146, C-190 to C-219
  applications for, C-190, C-192
  ARF design and performance, C-209 to C-219
  ARI design and performance, C-221
  axial radial concept in, C-209 to C-211
  axial thrust bearings in, C-200 to C-202
  axial thrust transfer in, C-195, C-199 to C-200
  bearings in, C-211, C-214
  blade carrier in, C-211 to C-215
  casing for, C-205 to C-206, C-210 to C-211
  corrosion resistance in, C-191 to C-193
  diffuser in, cross section of, C-213
  discharge temperature in, C-204
  erection and dismantling of, C-200
  features of, C-190 to C-208
  gears in, C-200
  horizontally split casing in, C-210 to C-211
  humidity vs., C-191, C-194
  impellers in, C-191, C-193, C-207, C-223
  inlet guide vanes in, C-207 to C-208, C-214 to C-216
  intercooler in, C-193 to C-196, C-207 to C-208, C-215 to C-216, C-219, C-222, C-226
  journal bearings in, C-200 to C-202
  maintenance of, C-200
  materials used in, C-210
  noise level of, C-194
  operating conditions vs. performance in, C-203
  operating range of, C-190, C-192
  performance data for, C-202 to C-208
  power consumption in, C-190 to C-191
  power oil supply in, C-217 to C-218, C-225
  reliability of, C-201
  RIK design and performance, C-208, C-211 to C-212, C-217
  RIO design and performance, C-208 to C-209, C-217 to C-219
  rotor in, C-193 to C-194, C-197, C-207, C-214, C-218 to C-219, C-225
  seals in, C-206 to C-207, C-217, C-224
  selection charts for, C-205 to C-206
  shaft string drive in, C-194 to C-200
  skid mount for, C-205
  solid couplings in, C-195 to C-201
  space requirements of, C-200 to C-201
  stator blade adjustment in, C-215 to C-217, C-223 to C-224
  stator blades in, C-211 to C-215
  suction side bearing seal in, C-217
  technical data and dimensions chart, C-213

J ring seals, S-5 to S-9
J.M. Voith GmbH, A-39 to A-48, C-392 to C-401, F-29 to F-37, P-121 to P-184
jet A fuel, F-37
jet vacuum pumps, P-321 to P-325
Johns Hopkins Applied Physics Lab, P-4
journal bearings, B-2 to B-6
  in axial compressors and, C-163
  in centrifugal compressors, C-178 to C-181
  in isotherm turbocompressors, C-200 to C-202
  in steam turbines, T-78
  in synchronous clutches, P-116 to P-117

Kawasaki, C-81
Kaybob, C-81
Kemet Electronics Corp., P-6
kerosene, F-37
ketones, P-11 to P-31, P-40 to P-57
keys, Sp-11
kilovolt-ampere (KVA) rating, electric motor, E-8 to E-9
kinetic barriers, M-39
kinetic head, P-222
knife gate valves, C-399, C-402 to C-403
knock out drum (*See also* separators), S-10
Kodak Corporation and environmental accountability case, E-40 to E-42
kraft paper, eco white, E-52
Kronecker delta, C-327

labeling, ecolabeling, E-54 to E-55
labyrinth design pistons, C-112 to C-115, C-121
labyrinth seals, windage heating prediction using CFD, C-6 to C-7
labyrinthine (laby) compressors (*See* reciprocating or labyrinthine compressors)
lactic acid, C-412
lactose, C-68
landfill, R-8
laser cleaning, M-34
laser cutting (*See* metallurgy)
laser drilling, M-35
laser inspection, M-37
laser isokinetic sampling probe (LISP), liquid natural gas (LNG) and, L-23 to L-24
laser machining, M-35
laser repair, M-31
laser welding, M-37
lathes, C-1, M-35
laurolactam, C-68
LCA (*See* life cycle assessment)
leachate, R-8
leaching processes, agitators in, A-38
lead, P-7, P-11 to P-31, P-37, P-40 to P-57
lead angle, worm gears and, P-84
leakage and explosion hazard, fuel leaks and, E-69 to E-70, E-76, E-82 to E-85
leaks, storage tanks, T-16 to T-17
leather and allied products industries, pollutants, P-17
level sensing (*See* liquid level/liquid flow control)
levulinic acid, C-68
life cycle assessment (LCA), C-253, E-43 to E-44, E-55 to E-56, L-1 to L-21, M-31
  algorithms for, L-3
  codes and specifications in, L-19
  cyclic usage factor in, L-3
  design assessment for maximum TBOs and, L-8 to L-10
  fuel quality and machinery selection example of, L-8 to L-10
  gas turbine deterioration and diagnosis example of, L-10 to L-11
  importance of, L-1 to L-2
  life cycle defined in, L-2
  life usage and, L-2 to L-7
  measurement in, L-12 to L-15
  modifications to operating parameters based on, L-7 to L-8
  operational optimization audits in, L-19 to L-21
  performance analysis (PA) with gas path parameters in, L-11 to L-17
  risk and weighting factors in, L-10
  service bulletins (SBs) and, L-3 to L-6
  specific applications of case history in, L-6 to L-7
  steam turbine deterioration and diagnosis example of, L-11
  time between overhaul (TBO) adjustment based on, L-7 to L-10
  triple redundancy and, T-42 to T-43
  turbine example of, L-6 to L-7
  vibrational analysis (VA) and, L-18 to L-19
life cycle inventories (LCIs), E-43 to E-44
life usage, in life cycle assessment, L-2 to L-7
lift check valves, C-392
lifting devices, automotive, Sp-4
lightning strikes, tanks and, T-29 to T-30
lime/limestone FGD, air pollution control and, A-90
limestone ($CaCO_3$), C-14, C-28 to C-30
lindane, P-7
line separators, F-29, S-24 to S-27
line-type electric heater, H-13
linoleic acid, C-66
lipids, freeze drying, with TBA, D-13 to D-17
liposoluble platinum (II), freeze drying, D-17
liposomes, freeze drying, with TBA, D-13 to D-17
liquefied natural gas (LNG), F-37 to F-45, L-21 to L-24
  cold utilization of, F-40
  combustibility of, F-39
  computation fluid dynamic (CFD) studies in, L-21, L-23
  emissions of, F-41
  energy and project integration in, F-40 to F-41
  in line testing of, without plant shutdown, L-23 to L-24
  laser isokinetic sampling probe (LISP) for, L-23 to L-24
  process system for feed, liquefaction, and refrigeration of, L-22
  production of, F-38 to F-39
  safety and health issues in production/transport of, F-39 to F-41
  vaporizers, V-17
  vessel sizing, proprietary scheme for, L-23
liquefied petroleum gas (LPG), F-37 to F-38, R-8, V-16
liquid-cooled air conditioning, H-4
liquid eliminator (*See* separators)
liquid-filled sensors, C-378 to C-382
liquid fuels, F-37
liquid-in-glass thermometers, M-1 to M-2
liquid-jet vacuum pumps, P-321 to P-325
liquid-level gauges, M-17 to M-18
liquid-level measurement, C-388
  capacitance method in, C-388
  conductance method in, C-388
  differential pressure method in, C-389
  electromechanical (displacement) method in, C-389
  flow measurement sensing in, C-389 to C-390
  flow switches, C-389
  magnetic float principle in, C-388
  positive displacement flow measurement in, C-389
  pressure head flow measurement in, C-389
  reed switch, C-390
  single pole double throw (SPDT) reed switch, C-390
  single pole single throw (SPST) reed switch, C-390
  tank gauges for, T-24 to T-27
  turbine flow measurement, C-390
  ultrasonic flow measurement in, C-390
  ultrasonic method in, C-388
  variable area flow measurement in, C-390
  vortex flow measurement, C-390
liquid-liquid extraction, R-8
liquid penetrant inspection (LPI), M-36 to M-37
liquid phase methanol synthesis (LPMeOH) in, C-17 to C-18
liquid ring vacuum pumps, P-318 to P-321
liquid-solid extraction, E-87
liquid-to-air heat pump systems, H-3
liquid-to-liquid heat pump systems, H-3
Lissajous patterns, in vibrational analysis (VA), C-270, C-282 to C-286

LM-2500 gas generator, General Electric, M-33
LNG (*See* liquid natural gas)
load
in electric motors, E-5, E-7, E-11 to E-15
in hydrodynamic power transmission, P-128
on stacks, from wind, S-33 to S-38
torque converters and, fluctuation in, P-172 to P-174
in turbocompressors, control of, C-334
load bearing capacity, carbon-graphite mix products, C-9
load-commutated inverters, in centrifugal compressors, C-185
lobe pumps, P-260 to P-264
lobes, A-48
local-mount liquid filled sensors, C-379 to C-380
logging industry (*See also* forest products industry; pulp and paper mills), P-13
logic trees, in explosion hazard assessment, E-79 to E-80
Los Alamos National Laboratory, P-7
low density polyethylene (LDPE) plastics, P-2
low NO_x burners (LNBs), emission reduction in cement production, C-32 to C-33
low pressure loss filtration, in air filtration systems and, A-81 to A-83
low pressure steam turbines and (high pressure insert), T-100
lower explosion limit (LEL), E-70, E-76
lubrication, L-24 to L-29
actuators and, A-42
AD CARB, carbon–graphite mix products, C-8 to C-13
in axial compressor, C-339, C-341, C-343
carbon–graphite mix products for, C-7 to C-13
cold start requirements of, L-25 to L-26
control of, C-336
in electric motors, E-15 to E-16
forced feed type, L-25
in gears, P-81 to P-82, P-96 to P-97
grease, L-25 to L-29
impurities in, L-25 to L-26
in isotherm turbocompressors, C-217 to C-218, C-225
maintenance of oils and grease in, L-28
methods for, L-25
oil analysis in, O-1
oil rings, ring oiling in, L-25
oil selection chart for, L-24 to L-25, L-27
oils in, L-25 to L-26
piping for, L-29
in reciprocating (labyrinthine) compressors, C-94 to C-95, C-98 to C-99
seals, C-336
selection criteria for, L-24 to L-25
specifications for, L-24 to L-25
splash type, L-25
in steam turbines and, T-79, T-109
viscosity of oils in, L-25 to L-26
lyophilization (*See* freeze drying)

MAAG Gear Co., P-98 to P-107
machine guards, Sp-11
machinery industries pollution, P-21
machining, C-1, M-35
macromonomer solution, freeze dry production of, D-18
magnesium, as fuel impurity, L-9
magnesium oxide (MgO), C-25
magnetic bearings, B-5 to B-11
actuators in, B-5 to B-9
advantages and benefits of, B-10 to B-11
analog control systems for, B-9
axis of control for, B-6
centrifugal compressors, C-185 to C-186, C-189 to C-190
control algorithms for, B-5, B-10
control system for, B-5 to B-6, B-8 to B-11
noncontacting technology in, B-5
open loop control system in, B-10
plant controller for, B-8
position sensors in, B-6
power amplifier in, B-6, B-8
power supply for, B-8
radial type, B-6 to B-7
rotor dynamic analysis in, B-10
sensors in, B-5 to B-9
stator and rotor in, B-6 to B-7
system components and operation in, B-6 to B-11
thrust type, B-6, B-8
transfer function in, B-10
user interface in, B-9
magnetic drives, actuators, A-42, A-45
magnetic float principle, in level sensing, C-388
magnetic particle inspection, M-36
magnification factor (D/F/k), vibrational analysis (VA) and damping, C-316
magnitude, in vibrational analysis (VA), C-263
maintenance
gears, P-82
lubricating oils and grease, L-28 to L-29
service life for turbine components vs. material selection, M-41 to M-42
makeup water, in condensers, C-240
maleic anyhydride, P-11 to P-31, P-40 to P-57, V-15
malsynchronization, C-344
man-machine interface (MMI), in control systems, C-356
manganese, P-11 to P-31, P-40 to P-57
manifold flow (fuel), control of, C-403 to C-408
manlifts, Sp-12
manometer differential pressure, in flow measurement, M-24
manometers, C-329, M-17 to M-18, M-22
manufacturers, Sp-2
manufacturing industries, pollutants and, P-27
Mar M247, M-41
margarine, C-76
maritime use of air filtration systems, A-61
mass flow rate, fans, F-4
mass law performance, sound, A-33
mass transfer
agitators for, A-38
computation fluid dynamics in, C-1 to C-7
mass transfer–accelerator, TBA and freeze drying, D-8
material fundamentals, metallurgy, M-38 to M-40
Material Safety Data Sheets (MSDS), C-43, C-58
material characteristics (*See also* materials selection)
alloys in, M-39
aqueous corrosion in, M-40
compounds in, M-39
corrosion in, M-40
creep deformation in, M-39
creep deformation in, M-40 to M-41
crystalline nature of, M-39
deformation in, M-39
diffusion rate of, M-39
dislocations in, M-39
elastic deformation in, M-39
fatigue in, M-40
fractures in, M-39 to M-40
grain boundaries in, M-39
grain growth in, M-39
grains in, M-39
hot corrosion in, M-40
kinetic barriers in, M-39
metastable conditions in, M-39
microstructure of, M-40
orientation of crystals in, M-39
oxidation in, M-40
phases in, M-39
plastic deformation in, M-39
recrystallization in, M-39
selection of (*See* materials selection)
solid solutions in, M-39
materials processing, computation fluid dynamics modeling of, C-1 to C-7
material selection (gas turbines), M-40 to M-42
blades, M-41
combustion cans, M-40 to M-41
compressor rotor, M-40
pumps and, P-241
service life for turbine components vs., M-41 to M-42
steam turbine, M-42
turbine discs, M-40
turbine vanes, M-41
maximum daily amount, in petroleum industry, R-8
McLeod gauge, M-22
MDS Nordion, I-2
mean time between failure (MTBF), C-418
measurement (*See also* condition monitoring; control systems; flow measurement; pressure measurement; temperature measurement), M-1 to M-31, Sp-12
computation fluid dynamics in, C-1 to C-7
flow measurement (*See* flow measurement)
life cycle assessment (LCA) and, L-12 to L-15
pressure measurement (*See* pressure measurement)
tank gauges in, T-13 to T-40
temperature (*See* temperature measurement)
mechanical governors, T-101 to T-102
mechanical power transmission, P-121 to P-124
mechanical rating, worm gears, P-94
mechanical strength, in carbon-graphite mix products, C-9
mechanical thermal switches (MTS), P-202 to P-204
mechanical-hydraulic governors, T-102 to T-104
medical waste incinerators, ASME certification program for, Sp-30
menthol, C-68
mercaptans, R-8 to R-9
Merco centrifuge, C-36 to C-37
mercury, P-11 to P-31, P-37, P-40 to P-57
mercury micromanometer, M-22
metal diaphragm sensors, C-383
metal industries, pollutants and, P-19 to P-20
metallurgical refurbishment (*See also* metallurgy), M-31 to M-43
metallurgical repair (*See also* metallurgy), M-31 to M-43
metallurgy, L-9, M-31 to M-43, Sp-2
activated diffusion healing (ADH) in, M-32
air plasma coatings in, M-35
anticorrosion coatings, C-442
autoclaving in, M-34
brazing, M-32
casting in, M-43
cleaning and stripping in, M-32, M-34
coatings in, M-34 to M-35
computer aided tomography (CAT) scan in, M-37
dabber TIG welding in, M-38
drilling in, M-35
eddy current testing in, M-36
electrical discharge machining (EDM) in, M-35

fluoride ion cleaning in, M-34
forging in, M-43
grinding in, M-35
high velocity oxygen fuel (HVOF) coatings in, M-35
hot isostatic pressing (HIP) in, M-41
laser cleaning in, M-34
laser drilling in, M-35
laser inspection in, M-37
laser machining in, M-35
laser welding in, M-37
lathes in, M-35
liquid penetrant inspection (LPI) in, M-36 to M-37
machining in, M-35
magnetic particle inspection in, M-36
manufacture in, M-42 to M-43
material fundamentals in, M-38 to M-40
material selection (gas turbines) and, M-40 to M-42
milling in, M-35
nondestructive test/inspection (NDT/NDI), M-35 to M-36
partitioned allow component healing (PACH) in, M-32
physical vapor deposition (PVD) in, M-34
plasma transfer arc welding in, M-38
plastic cleaning in, M-34
powder, M-37
radiographic inspection in, M-35
refurbishment in, M-32 to M-35
repair in, M-32 to M-35
robotic welding in, M-38
service life for turbine components vs. material selection and, M-41 to M-42
superalloy welding in, M-38
thermally densified coatings (TDC) in, M-35
ultrasonic inspection, M-36
vapor coatings in, M-35
water jet cleaning in, M-34
water jet machining in, M-35
welding in, M-37 to M-38
metals as pollutants, P-30
metastable conditions, M-39
metering, fluids (*See* flow control; fuel systems)
methane, C-418
explosion hazard assessment and, E-76
flammability of, E-76 to E-77
methanol, C-16 to C-18, C-72, C-418, F-37, P-11 to P-31, P-40 to P-57, V-15
cost vs. energy efficiency for, C-18 to C-20
liquid phase methanol synthesis (LPMeOH) in, C-17 to C-18
methionine, C-68
methoxyethanl, P-11 to P-31, P-40 to P-57
methyl acrylate, P-11 to P-31, P-40 to P-57
methyl bromide, I-2
methyl chloride, V-15 to V-16
methyl ethyl ketone, P-11 to P-31, P-40 to P-57
methyl isobutyl ketone, P-11 to P-31, P-40 to P-57
methyl methacrylate, P-11 to P-31, P-40 to P-57
methyl tert-butyl ether, P-11 to P-31, P-40 to P-57
methylamine, V-16
methylenbis (phenylisocyanate), P-11 to P-31, P-40 to P-57
methylene chloride, V-16
methylenebis (2-choloraniline), P-11 to P-31, P-37, P-40 to P-57
methylmethacrylate (MMA) monomers, C-41
metric system, Sp-2, Sp-12
MICAFOLD insulation, G-6
MICAREX insulation, G-5
micrometers, laser, A-2
microstructure of materials, M-40
military standards/specifications (MIL-Std), cooling, C-414
Milliken & Co., P-4
milling, C-1, M-35
minimum flow through pumps, P-237 to P-240
mining industry pollutants, P-13
misalignment, vibrational analysis (VA) and, C-290 to C-291
mist eliminators (*See* separators)
mist extractor, separators and, S-18 to S-19, S-22
mixers (*See also* agitators; centrifuges), A-38
mixing process
in centrifuges, C-34 to C-38
computation fluid dynamics in, C-1 to C-7
modal balancing, C-327 to C-328
modeling, computational fluid dynamics for, C-5
modulation, pulse wave modulation (PWM), E-32
molds, computational fluid dynamics to model, C-7
molecular vacuum gauges, M-22
Mollier diagrams, steam turbines and, T-82, T-84
molybdenum alloys, M-42
molybdenum trioxide, P-11 to P-31, P-40 to P-57
monitoring (*See also* condition monitoring)
power transmission assemblies, P-202 to P-204
monitoring logic, in turbocompressors, C-336
monoethanol amine (MEA), C-15
monoglycerides, crystallization of, C-68 to C-71
monomers, P-4 to P-5
monthly amount, in petroleum industry, R-9
Montreal Protocol, O-15 to O-16
Moog valves, C-405
Mopico compressor, gas pipeline application, C-182 to C-186
motor flux, E-32
motor vehicle industries, pollutants and, P-29 to P-30
motors (*See* electric motors)
mounting flanges, expansion joints and, E-63 to E-64
MSHA, C-61
Multipulse electrostatic precipitator, A-84 to A-85
multiresistance thermometers for, T-34 to T-35
multistage condensing steam turbines, T-94 to T-96
multistage flash (MSF) desalination process, D-1
multistage pumps (*See* pumps)
multitemperature thermometers, T-34 to T-35
multitube filters, F-28
municipal solid waste (MWC), ASME certification program for, Sp-30

N-butyl alcohol, V-15
nanoparticle drug dispersant, freeze dry production of, D-17
naphtha, C-418, F-37 to F-38, F-42 to F-43
explosion hazard assessment and, E-69 to E-70, E-76
napthalene, C-72, P-11 to P-31, P-40 to P-57
National Fire Protection Association (NFPA), explosion hazard assessment, E-86
National Gas Turbine Establishment (NGTE), A-69
National Oceanic and Atmospheric Administration (NOAA), C-78
National Pollution Release Inventory (NPRI), P-8 to P-72
natural frequency, in vibrational analysis (VA), C-272 to C-273, C-307, C-316
natural gas, C-95, C-418, F-37
biomass gasification and, CO_2 removal, C-18
explosion hazard assessment and, E-76
in reciprocating (labyrinthine) compressors for, low gas temperature, C-121 to C-136
natural gas combined cycle (NGCC), CO_2 and, C-14 to C-16
NBS, M-12
near vs. far fields, in sound measurement, A-20
NEC design specifications, cooling, C-415, C-418
needle bearings, B-1 to B-2
needle globe valves, CE-18 to CE-392
negative spring rate sensor, C-386 to C-387
NEMA
cooling specifications, C-413 to C-414
generators and turbogenerators design, G-1
neoprene, V-15
net expansion factor in, M-25
net flow area, fans, F-3
net positive suction head (NPSH), P-232 to P-237, P-257
neutron bombardment, nonintrusive wear monitoring in, C-330
new refinery, R-9
nickel and nickel alloys, M-40 to M-42, P-11 to P-31, P-37, P-40 to P-57
abrasives and, A-2
nickel resistance thermometer, M-4
nickel sulfate, C-72
Nimonic, M-41
NIOSH, C-61
Nippon Shokubai, C-41
nitric acid, A-9, P-11 to P-31, P-40 to P-57, V-15
nitrilotriacetic acid, P-11 to P-31, P-38, P-40 to P-57
nitrochlorobenzene, C-68
nitrogen, C-95, V-16
nitrogen oxides (NOx), A-9 to A-11, A-83 to A-90, E-36 to E-38, E-50, F-43, F-45, L-9
in acid rain, A-9 to A-11
air pollution control and, A-83 to A-90
cement production and, C-29 to C-31
emission guidelines for, stationary combustion turbines, E-36 to E-38
oxygen analysis and, O-3 to O-4
ozone and, O-5 to O-6, O-11 to O-15
nitroglycerin, P-11 to P-31, P-40 to P-57
nitropropane, P-11 to P-31, P-38, P-40 to P-57
N-methyl pyrrolidone (NMP), as freeze drying solvent, D-13
noise (*See also* acoustic enclosures)
in electric motors, E-28, E-32 to E-34
expansion joints vs., E-66 to E-67
in generators and turbogenerators, G-20
in isotherm turbocompressors, C-194
nonclogging pumps, P-243
noncontact thermal switches (BTS), P-202 to P-204
noncontacting technology, magnetic type bearings, B-5
nondestructive test/inspection (NDT/NDI), M-35 to M-36
nonintrusive wear monitoring, C-330
nonlubricated sealing system, C-110 to C-112
nonmetallic mineral products industries, pollutants and, P-23
non-Newtonian fluids, pumps and, P-272
nonreturn or check valves, C-392
non-self-supporting hydrodynamic brakes, B-14 to B-16

nozzles, M-25 to M-26, M-29, N-1
in centrifuge, C-35 to C-38
in steam turbines, T-88 to T-89
nozzle rings, in steam turbines, T-76 to T-77
nuclear power plants and technology, Sp-13
ASME accreditation packages for, Sp-25 to Sp-28
ASME codes, Sp-34
desalination processes and, D-1 to D-2
numerical factor, in flow measurement, M-24
NUTEK study of CO_2 ground injection, C-14 to C-21
Nyquist plots, in vibrational analysis (VA), C-270, C-280 to C-282

O rings, S-1, S-5
octane, R-9
offshore or coastal environments, Sp-14
air filtration systems and, A-57, A-66 to A-84
stacks and, S-29 to S-38
offshore pumping, hydrodynamic power transmission and, P-151 to P-152
ohmic electric heaters, H-19 to H-23
oil analysis, O-1
oil mist lubrication, E-16
oil rings, ring oiling, L-25
oil sands, E-87, O-1
oil supply system
in steam turbines and, T-79
temperature monitoring of, C-261
oils for lubrication, L-25 to L-26
oleic acid, C-66
OLMES project, C-6 to C-7
on-demand hot water (ODHW) heating pump system, H-4
once-through cooling water, R-9
one day amount, in petroleum industry, R-9
onspeed balancing, rotors, B-1
open loop (well system), heat pump, H-1 to H-2
open loop control system, magnetic bearings, B-10
operating parameters, life cycle assessment (LCA) and modifications to, L-7 to L-8
operational optimization audits in, L-19 to L-21
operator qualifications and certification, Sp-14
optical comparators, A-2
optical pyrometers, M-11
optimization audits, L-19 to L-21
Optipulse air cleaning system, A-85 to A-86, A-89
orbits, in vibrational analysis (VA), C-270, C-282 to C-286
organic acids, C-72
organic chemicals, C-41 to C-42
organic production processes, E-44
Organon International B.V., D-12
orifice, in flow measurement, M-23, M-25, M-29 to M-30
orifice plates, C-330
oscillation, C-261 to C-262
steady-state, C-313 to C-314
OSHA, C-61
outages, power supply, C-350 to C-354
ovens, drying, D-4
overdamping, C-312
overhaul and repair processes, chemical cleaning, C-38
overload/overspeed control, A-47 to A-48, C-336, C-343 to C-350
brake properties at high speed and acceleration, C-347 to C-350
clutch type couplings in, C-347
constant fill couplings, C-347
fault conditions and, C-344
gas turbines, C-336, C-343 to C-350
gearboxes in, C-343, C-345
hydrodynamic principle in turbocouplings and, C-346 to C-347
limits for, C-345
malsynchronisation and, C-344
Safeset coupling in, C-344 to C-350
short circuits and, C-344
slip curves for, C-347 to C-348
in steam turbines and, C-368 to C-374, T-78, T-106 to T-108
torque limiting requirements for, C-344 to C-345
variable speed couplings in, C-347
overspeed (*See* overload/overspeed control)
overtorque (*See* overload/overspeed control)
oxidation, C-9, M-40
oxidative degradation of plastics, P-2
oxygen, V-16
oxygen analysis, O-1 to O-4
oxygen condensers, condensate content, C-240
oxygen demand, R-8
ozonation, R-9
ozone, C-413, O-4 to O-26
ambient air quality objective for, O-9 to O-10
chemical precursors to, O-5 to O-6
chlorofluorcarbons and, C-13 to C-14
coatings and CFCs vs., O-14, O-16 to O-26
corrosion effects of, O-8 to O-9
depletion of, in stratospheric level, O-12 to O-13, O-15 to O-16, R-10
emission control options for, O-10 to O-15
foams and CFCs vs., O-14, O-16 to O-26
ground level, effects of, O-6 to O-9
Halon and, O-14
insulation and CFCs vs., O-14, O-16 to O-26
materials damage caused by, O-9
Montreal Protocol and, O-15 to O-16
nitrogen oxides (NO_x) and, O-5 to O-6, O-11 to O-15
packaging and CFCs vs., O-14, O-16 to O-26
refrigerants and CFCs vs., O-14, O-16 to O-26
regional remedial measures for, examples of, O-12 to O-13
solvents and CFCs vs., O-14, O-16 to O-26
sterilants and CFCs vs., O-14, O-16 to O-26
United National Environment Programme (UNEP) and, O-13
vegetation effected by, O-8 to O-9
Vienna Convention for the Protection of the Ozone Layer and, O-12 to O-13
volatile organic compounds (VOCs), O-5 to O-6, O-10 to O-15

package, for reciprocating (labyrinthine) compressors, C-110
packaging and paper products, F-21 to F-26, P-1
barrier coatings for, F-15, F-21 to F-23
carton materials, F-24
chlorofluorocarbons (CFC) in, O-14, O-16 to O-26
forest product industry and, F-12 to F-24
inks and, environmentally friendly, F-22
recycling in, F-22
resource efficient, E-52 to E-54
sack manufacture and, F-23 to F-24
waste reduction in, E-54
wastewater management in, F-24
packed reactors, T-40
paint, blistering, A-70
pallets, Sp-14
palm oil, C-68
pantograph control mechanism, expansion joints and, E-63
paper (*See* packaging and paper products; pulp and paper)
paracresol, C-68
paracymene, V-16
paradicholorbenzene, C-68
paraffins, C-72
parasitic forces and noise, electric motors and, E-33 to E-34
parazylene, C-68
partial hot water (PHW) heat pump heating systems, H-3 to H-4
particle fusion, air filtration systems and, A-78
particulate emissions, E-36
partitioned allow component healing (PACH), M-32
p-dichlorobenzene, P-35
Peabody TecTank, T-1 to T-8
peak current rating, electric motors and, E-25 to E-26
peening operations, A-1, A-7 to A-9
Peerless USA, F-24 to F-29, L-21 to L-24, P-214 to P-218, S-10 to S-29, T-108 to T-112
pelletizers, A-48, B-28
Peltier Effect, C-418
pentaerythritol, C-68
peracetic acid, P-11 to P-31, P-40 to P-57
perchloroethylene, V-15
performance analysis (PA) (*See also* condition monitoring), C-253, C-299
performance test codes, ASME, Sp-34 to Sp-35
periodic frequency, vibrational analysis (VA), C-263
periodic motion, vibrational analysis (VA), C-11, C-302, C-305, C-310
personal and household service industries, pollutants and, P-31
pesticides, A-49, P-7
Petrochemical Company of Singapore (PCS), C-38 to C-41
petrochemical complex/plant, C-38 to C-41
hydrodynamic power transmission and, P-138 to P-147
Petrochemical Corporation of Singapore (PCS), C-403 to C-408
petroleum and natural gas industries
acid treatment in, R-5
additives and, R-5 to R-6
alkylation in, R-4
atmospheric distillation, R-2
blending processes in, R-2, R-5 to R-6
catalytic cracking in, P-2 to P-3
chemical treating in, R-5
coking processes in, R-4
combining processes in, R-4
conversion process in, R-2 to R-4
cracking processes in, P-2 to P-4
crude oil composition and, R-1 to R-2
deposits and compliance assessment for, R-5 to R-6
gas treating in, R-5
glossary of terms for, P-6 to P-10
hydrocracking in, R-3
hydrotreating in, R-4 to R-5
physical treatments in, R-5
pollutants and, P-13 to P-14
polymerization in, R-4
rearranging processes in, R-4
separation process in, R-2
solvent extraction in, R-5
sweetening processes in, R-5
tanks and, T-16
treatment process in, R-2, R-4 to R-5
vacuum distillation in, R-2
visbreaking in, R-3
Petrotech Inc. (retrofit controls), C-354 to C-408

pharmaceuticals, Sp-2
freeze drying process in, D-4 to D-18
phase, in vibrational analysis (VA), C-270, C-272 to C-282
phase angle, in vibrational analysis (VA), C-265, C-305 to C-306, C-315 to C-318
phases, of materials, M-39
phathalate, P-10 to P-31, P-33, P-40 to P-57
phenol, P-11 to P-31, P-40 to P-57
phenylphenol, P-12 to P-31, P-40 to P-57
Philips Electronics, P-5
Philips Pening gauges, M-22
phosgene, V-15
phosphates, C-78
phosphoric acid, P-12 to P-31, P-40 to P-57
phosphorus, P-12 to P-31, P-40 to P-57, P-64 to P-65
photodegradation of plastics, P-2
photosynthetic action, R-9
phtalic anhydride, P-12 to P-31, P-40 to P-57
physical vapor deposition (PVD), M-34
pinch valves, CE-18 to CE-392
pipe diameter, in flow measurement, M-24
pipelines and pipeline pumping stations
centrifugal compressors used in, C-182 to C-186
hydrodynamic power transmission used in, P-147 to P-152
pollutants and, P-28
piping, Sp-16
centrifugal pump, P-257
lubrication line, L-29
pressure measurement in, M-15 to M-16
in reciprocating (labyrinthine) compressors, C-103
rotary pump, P-273 to P-274
Pirani gauges, M-22
piston rods, in reciprocating (labyrinthine) compressors, C-91 to C-94
piston type pressure switches, C-385 to C-386
pistons
in actuators, A-42
labyrinth design, C-112 to C-115, C-121
in reciprocating (labyrinthine) compressors, C-86 to C-88, C-93 to C-97, C-112 to C-115, C-121, C-126 to C-132
pitch, L-25, R-9
pitot static tubes, C-329, M-15
pitting, gear, P-74 to P-75
plankton, C-78
plant controller, magnetic bearings, B-8
plasma transfer arc welding, M-38
plastic cleaning, M-34
plastic deformation, M-39
plastics, P-1 to P-7, Sp-2
biodegradation of, P-2 to P-3
biodistegrable, P-2
conductive polymers in, P-4 to P-7
electric, P-3 to P-7
ENVAR biodegradable, P-2
environmental degradation of, P-1
equivalent series resistance (ESR) polymers, P-6
low density polyethylene (LDPE), P-2
monomers, P-4 to P-5
oxidative degradation of, P-2
photodegradation of, P-2
pollutants and, P-16 to P-17
polyacetylene, P-5 to P-7
polyaniline, P-5 to P-7
polyethylene, P-2
polypyrrole, P-4
polythiophene, P-3 to P-7
smart membranes using conductive polymers, P-7
thermoset, Sp-18
platinum resistance thermometer, M-4
plug valves, CE-18 to CE-392
plumbing, P-30, Sp-17
plume abatement cooling towers, C-424 to C-426
poisoning of catalyst, in air pollution control, A-96
polar solutes/solvents, C-72
pollution (*See also* air pollution control; environmental accountability; water pollution), P-7 to P-22
accidents/incidents and, E-46
acid rain and, A-9 to A-13, P-60 to P-62
agricultural chemicals and, A-49, P-12
air emissions, P-57 to P-60
beverage industries and, P-15, P-29
biochemical oxygen demand (BOD) in, P-69
business service industries and, P-31
Canadian studies in, P-8 to P-72
carbon dioxide (CO_2), C-13 to C-21
carbon monoxide and, P-62 to P-64
cement kilns and, C-22, C-28 to C-34
chemical and chemical products industries and, P-25 to P-26
chlorofluorocarbons (CFCs) in, C-413
communication industries and, P-29
condensers and, C-233
construction industries and, P-27 to P-28
continuous emissions monitoring (CEM) in, C-34
drug industries and, P-29
ecological parks, E-1
ecosystems, E-1 to E-3
electrical and electronics products industries and, P-22 to P-23
environmental accountability, E-40 to E-49
eutrophication in, P-64 to P-65
fabricated metal industries and, P-20 to P-21
federal government service industries and, P-31
food industries and, P-14 to P-15, P-29
furniture and fixture industries and, P-18
IEA Greenhouse Gas Implementing Agreement, C-14
industrial effluent in, P-71 to P-72
leather and allied products industries, P-17
logging industry and, P-13
machinery industries and, P-21
manufacturing industries (other), P-27
metal industries and, P-19 to P-20
metals, hardware, plumbing, heating, building materials industries, P-30
mining industry and, P-13
motor vehicle industries and, P-29 to P-30
National Pollution Release Inventory (NPRI) for (Canada), P-8 to P-72
nonmetallic mineral products industries and, P-23
ozone, O-4 to O-26
personal and household service industries and, P-31
petroleum and natural gas industries and, P-13 to P-14
phosphates and, C-78
phosphorus in, P-64 to P-65
pipeline transport industries and, P-28
plastics and, P-16 to P-17
printing, publishing and allied industries, P-19
pulp and paper industries and, P-18 to P-19
recovery, reuse, recycling in, P-10, P-54 to P-58
"red tide" algae (*Ptychodiscus brevis*) and, C-78
releases of, P-8 to P-9
rubber products industries and, P-15 to P-16
service industries and, P-28, P-31
service industries of mineral extraction and, P-14
sewage (*See also* wastewater), P-69 to P-72
storage and warehousing industries and, P-29
sulfur dioxide in, P-60 to P-62
surface waters and, P-40 to P-48
textile industries and, P-17 to P-18
tobacco industries and, P-29
toxic chemicals and, in Great Lakes, P-65 to P-72
trade contracting industries and, P-28
transfer of, P-9, P-49 to P-54
transportation equipment industries and, P-22
transportation industries and, P-28
utility industries and, P-29
waste management and, W-1 to W-12
wastewater flows in, P-69 to P-72
water pollution and, P-64 to P-65
wholesale products and industries and, P-30 to P-31
wood industries and, P-18
polyacetylene, P-5 to P-7
polyamide epoxy primer, as tank coatings, T-4 to T-8
polyaniline, P-5 to P-7
polychlorinated biphenyls (PCBs), P-7
polyene, freeze dry production of, D-17
polyethylene plastics, P-2
polymerization, C-43, C-58
computation fluid dynamics in, C-1 to C-7
in petroleum industry, R-4
polypyrrole, P-4
polytetrafluoroethylene (PTFE) seals, S-5 to S-9
polythiophene, P-3 to P-7
pond and lake loop heat pump, H-1
Portland cement (*See* cement)
position sensors, A-46, B-6
positive displacement flow measurement, C-389
positive lubrication system (PLS), electric motors and, E-15 to E-16
potassium, as fuel impurity, L-9
potassium chloride, C-68
potassium nitrate, C-68, C-72
potential head, P-222
powder metallurgy, M-37
power
in gas turbines, atmospheric conditions vs. degradation in, T-65 to T-67
in hydrodynamic brakes, B-16, B-20 to B-21
in hydrodynamic power transmission, P-138
in pumps, requirement for, P-225 to P-226, P-269 to P-270
in steam turbines, T-81
of sound (PWL), A-14 to A-19
power amplifiers, magnetic bearings, B-6, B-8
power control, in turbocompressors, C-333
power factor, electric motor, E-7 to E-9
power generation
ASME certification program for, Sp-30
explosion hazard assessment in, E-67 to E-87
gas turbines and, T-47
oxygen analysis in, O-2 to O-4
power production (IPP/SPP), P-72 to P-73
power rotor, in rotary pumps, P-264
power stations, synchronous clutches and, P-107 to P-113
power supplies
control of, C-350 to C-354
demand charge and, energy costs of, E-9 to E-10
electric motors and, E-3 to E-5
flexible AC transmission system (FACTS) for, C-353 to C-354
harmonic distortion in, C-351 to C-352
high voltage direct current (HVDC) in, C-353 to C-354
kilovolt-ampere (KVA) rating in, E-8 to E-9

magnetic bearings, B-8
outages and disturbances in, C-350 to C-354
peak current rating in, E-25 to E-26
power factor in, E-7 to E-9
PQ2000 system for, C-351 to C-354
reactive kilovolt-ampere (KVAR) rating in, E-8 to E-9
real power, in calculating energy consumption costs, E-7 to E-8
RMS current rating in, E-25 to E-26, E-28
ultrasonic cleaning, U-1 to U-2
voltage sags in, C-350 to C-354
voltage unbalance and, electric motor operating costs, E-6 to E-7
power transistors, in electric motors, E-29 to E-32
power transmission (*See also* gears; hydrodynamic power transmission; synchronous clutch), P-73 to P-204
gears in, P-74 to P-98
hydrodynamic, P-121 to P-166
hydrostatic, P-121 to P-124
mechanical, P-121 to P-124
monitoring devices in, P-202 to P-204
Safeset couplings in, P-184 to P-191
synchronous clutch couplings and, P-107 to P-115
torque converters and, P-166 to P-184
torque limiting safety coupling in, P-184 to P-191
turbocouplings (type T) in, P-191 to P-196
types of, P-121 to P-127
powered platforms, Sp-17
PQ2000 power supply system, C-351 to C-354
Pratt and Whitney, M-31
precision platinum resistance thermometer, M-4
predictive strategies, in condition monitoring, C-254
pressure angle, worm gears, P-84
pressure control, C-333 to C-334
in steam turbines, C-368 to C-374
in turbocompressors, C-333
pressure differential transmitter (PDT), C-333 to C-334
pressure gauge, C-107
pressure head, P-221 to P-224
pressure head flow measurement, C-389
pressure measurement (*See also* pressure switches), C-328 to C-339, M-14 to M-31
absolute pressure in, M-14 to M-15
alphatron gauges in, M-22
ambient air pressure (P_0), T-55 to T-58
ambient air temperature (T_0) in, T-58
barometers in, M-18
bellows gauges in, M-21
Bourdon tube in, M-21
calibration of, M-16
connections in, M-15 to M-17
consolidated diaphragm comparator in, M-22
deadweight tester and gauges in, M-18 to M-20
diaphragm gauges in, M-21
differential pressure in, M-14, M-18 to M-22
elastic gauges in, M-20 to M-22
electric transducers for, M-22 to M-24
errors in, M-15 to M-16
flow errors in, M-15
flow stream pressure in, M-15
gauge pressure in, M-15
Hickman butyl phthalate manometer, M-22
impact tubes and, M-15
ionization gauges in, M-22
liquid level gauges in, M-17 to M-18
manometers in, M-17 to M-18, M-22
McLeod gauge for, M-22
mercury micromanometer in, M-22
molecular vacuum gauges in, M-22
Philips Pening gauges in, M-22
piping and, M-15 to M-16
Pirani gauges in, M-22
pitot tubes in, M-15
pressure defined for, M-14
pressure relationships defined for, M-14
static pressure in, M-15
static taps and, M-15
static tubes and, M-15
thermal conductivity gauges in, M-22
thermocouple gauges in, M-22
total pressure in, M-15
turbulence errors in, M-15
vacuum pressure in, M-15
velocity head in, M-15
velocity pressure in, M-15
pressure regulation valves (PRV), F-25 to F-26
pressure relationships, M-14
pressure switches (*See also* pressure measurement), C-383 to C-388
absolute pressure, C-383
accuracy and lifespan of, C-387
applications and cost of, C-387 to C-388
Belleville washer negative spring rate sensor in, C-386 to C-387
bellows type sensors in, C-386
Bourdon tube sensors in, C-383 to C-385
differential pressure-actuated, C-383
gauge type instruments in, C-383
helical tube sensors in, C-386
metal diaphragm sensors in, C-383
negative spring rate sensor in, C-386 to C-387
piston type, C-385 to C-386
proof pressure in, C-383
unsealed piston sensors in, C-387
pressure transducers, C-329
pressure transmitter, C-329, C-333 to C-334
pressure vessels, Sp-17
ASME accreditation packages for, Sp-25 to Sp-28
ASME CD-ROM for, Sp-32
ASME codes, Sp-35
books of interest on, Sp-37 to Sp-38
data report forms for, Sp-36 to Sp-37
international code for, Sp-24
ISO 9000 registration program, Sp-29
pressure-intensity (P-I) index of sound, A-16, A-18 to A-19
pressurized storage tanks, vaporizers and, V-22 to V-25
preventive strategies, in condition monitoring, C-254 to C-261
priming pumps, P-254
printing, publishing and allied industries, pollutants and, P-19
priority pollutants, R-9
probes
sound intensity, A-16 to A-17
ultrasonic cleaners and, U-2 to U-3
vibrational analysis (VA), C-266 to C-270
process control, in turbocompressors, C-333 to C-334
process hazard review (PHR), in explosion hazard assessment, E-67, E-74 to E-76
process industry, pumps and for, P-285 to P-309
process radial gas turbines (PRT series), C-222 to C-225
process type electric heaters, H-15 to E-16
programmable logic controllers (PLCs), N-1
condition monitoring (CM) and, C-259
propagation of sound, A-27
propane, C-418, E-76, F-41, R-11, V-15 to V-17
propanol, V-15
proportional conversion of electrical control signals, A-40
propylene, P-12 to P-31, P-40 to P-57, V-16
propylene glycol (PG), C-408 to C-412
propylene oxide, C-415, P-12 to P-31, P-38, P-40 to P-57, V-15 to V-16
prostaglandin E1 (PGE-1), freeze dry production of, D-17
protective clothing
freeze drying and TBA handling, D-5 to D-7
toxic chemicals handling, C-59 to C-61
proximity probes, vibrational analysis (VA), C-266 to C-270
PTFE, expansion joints using, E-60
pulp and paper industries (*See also* forest products), P-204 to P-214, Sp-2
back-pressure turbine in, P-210
biomass fuel from, P-205 to P-214
biomass gasifier (BIG) in, P-208 to P-210
black liquor gasifier (BLG) in, P-209
black liquor production in, P-205 to P-214
combined heat and power (CHP) in, P-208, P-210
duct burner in, biomass fuel, P-210
energy consumption by, P-204 to P-205
gas turbine in, using biomass fuels, P-210 to P-211
GateCycle software to monitor biomass fuel use at, P-211 to P-212
heat recovery steam generator (HRSG) in, P-208, P-210
pollutants and, P-18 to P-19
Tomlinson boiler in, P-210
white liquor production in, P-205 to P-214
pulsating vibration, C-264
pulsation dampeners, P-214 to P-218
pulse jet–type air filters, A-49
pulse wave modulation (PWM), electric motors and, E-32
pumping stations, hydrodynamic power transmission and, P-151 to P-152
pumps, P-214 to P-325, Sp-17
abrasive fluids and, P-274
agricultural and food products, A-48
API 610 double suction type, P-296 to P-299
API 610 rigid or flexible coupled, P-296
applications for, P-241 to P-255, P-281 to P-285
axial balance in, P-243 to P-247, P-275 to P-276
axial piston, P-260 to P-264
Bernoulli's theorem and, P-222
boiler feed, P-242
Bourdon tube to measure flow in, P-224
CAP 8 type (API 610 process pumps), P-285 to P-292
casings for, P-276
cavitation in, P-232
centrifugal (*See* centrifugal pumps)
characteristic curves of performance for, P-228
condensate, NPSH and, P-236 to P-237
condensate, P-243
continuity equation in, P-221 to P-224
CVA8 type (API 610) overhung vertical inline integral bearing frame flexibly coupled, P-292 to P-296
CVAR type rigid coupled pumps, P-296
displacement of, P-260, P-267 to P-268
double suction, P-296 to P-299
double volute, P-247 to P-248
electric motors and in, E-22
entrained air/gases and, P-271 to P-272, P-278 to P-281
external gear, P-260 to P-264
friction loss in, P-222
head in, P-222, P-224 to P-228
heavy duty double case multistage, P-299 to P-309
hot water, NPSH and, P-236
Hydraulic Institute Standards for, P-231

hydraulic pressure, P-242 to P-243
hydraulics of, P-221 to P-241
hydrodynamic brakes, controller in, B-17 to B-19
hydrodynamic power transmission and, P-152 to P-164
impellers in, P-219, P-226 to P-228
inlet pressure in, P-276
installation of, P-257 to P-258, P-277 to P-278
internal gear, P-260 to P-264
kinetic head in, P-222
lobe, P-260 to P-264
materials selection, by liquids to be pumped, P-241
minimum flow through, P-237 to P-240
non-Newtonian fluids and, P-272
nonclogging, P-243
operation of, P-257 to P-258, P-277 to P-278
parallel operations for, P-228 to P-230
performance analysis of, P-226 to P-228, P-265 to P-281
piping for, P-257, P-273 to P-274
potential head in, P-222
power/horsepower requirement calculation for, P-225 to P-226, P-269 to P-270
pressure head in, P-221 to P-224
priming of, P-254
process industry uses of, P-285 to P-309
recirculation connection for, P-240 to P-241
rotary (*See* rotary pumps), P-259 to P-281
rotors in, P-276 to P-277
screw, P-260 to P-264
seals in, P-250 to P-254, P-276
series operations for, P-228 to P-230
single stage, double suction type, P-241 to P-242
sliding vane, P-260 to P-264
specific speed of, P-219 to P-221
static head in, P-221 to P-224
stuffing boxes for, P-248 to P-254
suction conditions, suction lift in, P-272 to P-273
suction head in, net positive (NPSH), P-232 to P-237, P-257
suction head in, P-222
suction lift in, P-222
temperature rise in, P-237 to P-240
temperature vs. efficiency in, P-254 to P-255
theoretical capacity (Q_t) of
theory of operation for, P-218 to P-281
timed screw, P-260 to P-264
total discharge head in, P-223 to P-224
total head in, P-222
troubleshooting, P-258 to P-259
types of, by application, P-281 to P-285
untimed screw, P-260 to P-264
vacuum type (*See* vacuum pumps), P-309 to P-325
valves in, P-257
velocity head in, P-221 to P-224
vibration limits for, P-255 to P-258
viscous fluids and, P-230 to P-232, P-265 to P-267, P-270 to P-273
warmup procedures for, P-254
purification
of air, A-101 to A-102
centrifugal, C-35 to C-38
pyridine, V-16
pyrometers, M-11
pyrometry, M-10
pyruvic acid, C-412

quality control, in reciprocating (labyrinthine) compressors, C-116 to C-121
quill shafts, synchronous clutches and, P-118

RA search online service, ASME, Sp-33
radar tank gauges, T-19 to T-21, T-33 to T-34
radial magnetic bearing, B-6 to B-7
radial tilting pad bearings, in high speed gears, P-101 to P-104
radiant electric heaters, H-22 to H-23
radiation error, in temperature measurement, M-13
radiation thermometers, M-10 to M-11
radiographic inspection, M-35
rainfall, vs. air filtration systems, A-50 to A-63
random vibration, in vibrational analysis (VA), C-263
Rankine cycle, T-82 to T-84
rate of flow in, M-25
reaction, computation fluid dynamics in, C-1 to C-7
reactive kilovolt-ampere (KVAR) rating, E-8 to E-9
reactive sound fields, A-20
reactive strategies vs. condition monitoring, C-254
reactivity index of sound, A-12, A-16, A-18 to A-19
reactors, R-1
computational fluid dynamics modeling for, C-3 to C-4
packed type, T-40
tray type, T-40
reaffirmation (R) design, Sp-3
rearranging processes, in petroleum industry, R-4
reciprocating (labyrinthine) compressors, C-81, C-84 to C-136
acoustic calculations for, C-116
applications for, C-85, C-95 to C-110
arrangement and drive in, C-103 to C-108
balanced opposed type, C-88
bearings in, C-86, C-92
benefits of, C-88 to C-95
bone dry natural gas and, C-126
coding of, C-104
condensate receiving tank for, C-109
cooling and piping in, C-103
cooling valve in, C-96
crankcase deformation at cryogenic temperatures, C-132
crankcase of, C-86, C-92, C-107
crankshaft in, C-99, C-108
crankshaft seal in, C-114 to C-115, C-123 to C-124
crosshead fastening in, C-86, C-93
cryogenic temperatures and, C-121 to C-126
cutaway view of, showing features, C-91
cylinders in, C-103, C-126 to C-132
D type, C-117, C-119
design and maintenance features of, C-86 to C-88
dimensions of, C-89, C-104, C-119 to C-120
double acting piston in, C-130
dynamic crank throw behavior in, C-116, C-126
E type, C-117, C-119
electrical system of, C-110
features of, design/special, C-99 to C-108
filter system for, C-109
gas stream through, C-108
gases compressed by, C-85 to C-86, C-95
instrumentation in, C-103, C-108, C-111
K type, C-118, C-120, C-129
labyrinth piston design in, C-112 to C-115, C-121
leaks in, at cryogenic temperatures, C-132 to C-135
liquefied natural gas service (low gas temp application), C-121 to C-136
lubrication in, C-99
maintenance of, C-126, C-128, C-135
materials used in, C-104, C-116, C-126, C-129 to C-131
nonlubricated sealing system in, C-110 to C-112
oil wiper packing in, C-94 to C-95, C-98
operating data for, C-105 to C-106
optional features for, C-110
package for, C-110
performance parameters of, C-119 to C-120
performance range of, typical, C-89
piston rod gland in, C-114, C-123
piston rod guide bearing in, C-114, C-123
piston rod packing in, C-91 to C-94, C-97
piston rod runout in, C-86 to C-88, C-93
pistons of, C-88, C-94, C-126 to C-132
pressure gauge in, C-107
process conditions for, C-85 to C-86
quality control for, C-116 to C-121
remote controls for, C-109
research and development in, labyrinth design, C-115 to C-121
safety valve in, C-107
sealing labyrinth design in, C-116, C-125
seals in, C-110 to C-112, C-134
selection charts for, C-90, C-104
skid mount for, C-108, C-128
startup procedures for, C-135 to C-136
supply scope of, standard, C-108 to C-110
temperature control in cryogenic applications, C-132
testing of, C-110
tools used/supplied with, C-91
valves in, C-88 to C-91, C-95, C-107, C-115, C-122, C-124, C-135
vertical, inline type, C-87
water system for, C-109
reciprocating engines, E-38 to E-39
recirculation connection, in pumps, P-240 to P-241
recorders/recording systems, in vibrational analysis (VA), C-270 to C-286
recovery, reuse, recycling, P-10, P-54 to P-58
recrystallization, M-39
rectifiers
generators and turbogenerators, G-13
static thyristor, G-3
recycling, P-10, P-54 to P-58
packaging and paper products, F-22
plastic, P-1
resource efficient packaging and, E-52 to E-54
waste reduction, E-54
"red tide" algae (*Ptychodiscus brevis*), C-78
reducers, worm gears, P-84 to P-87
reduction gears, helical, P-77, P-79 to P-81
reduction gears, worm, P-84 to P-87
redundancy, triple, T-41 to P-43
reed switch, C-390 to E-18
reference crude rate (RCR), R-9
refineries, petroleum (*See also* petroleum industries), R-1 to R-10
refinery gas, F-37
refrigerants (*See also* cooling), R-10 to R-19, V-16
air conditioning and, R-11 to R-13
alternative types, R-10 to R-14
American Society of Heating, Refrigeration, Air Conditioning Engineers (ASHRAE) classification, R-11
ammonia as, R-13 to R-18
azeotrope mixtures for, R-11
balance between ozone depleting fluids and other emissions, R-13
carbon dioxide as, R-13 to R-18
chloroluorcarbons (CFCs) in, O-14, O-16 to O-26, R-10 to R-15
coefficient of performance (COP) in, R-18
comfort conditioning and, R-11 to R-13
design constraints and, R-18 to R-19

development of refrigeration systems and, R-14 to R-15
global warming potential (GWP) of, R-11, R-13 to R-14
halocarbons in, R-13
hydrocarbons as, R-15 to R-18
hydrochlorofluorcarbons (HCFCs) in, R-10
hydrofluorocarbons (HFCs) in, R-10
mixtures for, R-10 to R-11
natural types, R-14 to R-18
ozone depletion by, R-10
propane and, R-11
R22 and, R-17 to R-18
R22 in comfort conditioning, R-11 to R-13
thermoelectric cooling, C-418 to C-423
threshold limit value (TLV) of, R-19
time weighted average (TWA) exposure to, R-19
total equivalent warming impact (TEWI) of, R-12 to R-14
water as, R-15 to R-18
zeotrope mixtures for, R-11
regenerative cycle, in steam turbines, T-85
regenerators, R-19, T-40
regulators, electrohydraulic actuator in, A-44
regulatory affairs, in environmental accountability, E-44
reheat cycle, in steam turbines, T-84 to T-85
reindeer, environmental protection, F-16
reinforced thermoset plastics, Sp-18
relative humidity, gas turbines and, T-58, T-65 to T-67
release of pollutants, P-8 to P-9
Reliance Electric (electric motors), E-3 to E-36
relief valves, ASME accreditation packages for, Sp-25 to Sp-28
remote controls, C-109
Rene 80, M-41
residual pitch, R-9
resin, in lubricating oil, L-25
resistance thermometers in, M-2 to M-5
resistance type electric heating elements, H-11, V-1 to V-5
resistive thermal detectors (RTDs), C-261
resonance, A-27 to A-28, C-272 to C-273
resonant couplings, C-317
respirators for safety in handling toxic chemicals, C-59 to C-61
response time, in temperature switches, C-380
retrofit control systems (*See also* control systems), C-354 to C-408
aeroderivative fuel regulator for gas turbine, C-354 to C-358
antisurge control in, C-359 to C-368
fault tolerance in, C-355
integrated control system (Series 9500) for gas turbine generators, C-359 to C-361, C-374 to C-377
overload/overspeed protection for steam turbines, C-368 to C-374
pressure control for steam turbines, C-368 to C-374
retrofitting, condition monitoring (CM) and, C-255
reverse osmosis (RO) desalination process, D-1
Reynolds number in, M-25
risers, solids concentration with baffle plate, using computational fluid dynamics, C-2
risk management/assessment
as-low-as-reasonably-practicable (ALARP) risks and, E-80
condition monitoring (CM) and, C-254
environmental accountability and, E-44
explosion hazard assessment and, E-71
life cycle assessment (LCA) and, L-10
RMS current rating, electric motors, E-25 to E-26, E-28
robotics, welding using, M-38
roller bearings, B-1 to B-2
rolling contact type bearings, B-1 to B-2
Rolls Royce, M-31 to M-34
rotary piston blowers, C-232
rotary pumps, P-259 to P-281
abrasive fluids and, P-274
applications for, P-270
axial balance in, P-275 to P-276
axial piston, P-260 to P-264
capacity of, P-267 to P-268
casings for, P-276
classification of, P-260 to P-265
design details of, P-274 to P-277
displacement of, P-267 to P-268
displacement pumps and, P-260
entrained air/gases and, P-271 to P-272, P-278 to P-281
external gear, P-260 to P-264
idler rotors in, P-264
inlet conditions vs. performance in, P-265 to P-267
inlet pressure in, P-276
installation of, P-277 to P-278
internal gear, P-260 to P-264
journal bearing theory in, P-264 to P-265
lobe, P-260 to P-264
non Newtonian fluids and, P-272
operation of, P-277 to P-278
performance analysis of, P-265 to P-281
pipe size for, P-273 to P-274
power rotor in, P-264
power/horsepower requirements of, P-269 to P-270
pressure in, P-268 to P-269
rotors in, P-264, P-276 to P-277
screw, P-260 to P-264
sealing rotor in, P-264
seals in, P-276
selection criteria for, P-270
sliding vane, P-260 to P-264
speed of, P-265, P-273
suction conditions, suction lift in, P-272 to P-273
theoretical capacity (Q_t) of, P-265
timed screw, P-260 to P-264
untimed screw, P-260 to P-264
viscous fluids and, P-265 to P-267, P-270 to P-273
rotating machinery, Sp-3
rotating positive displacement compressors, C-228 to C-232
applications for, C-230 to C-232
rotors in, C-229
rotating stall, C-328
rotational velocity, vibrational analysis (VA), C-265
rotors
in axial compressors, C-160
balancing, onspeed, B-1
balancing of (*See also* vibrational analysis), C-288 to C-291, C-318
damping in (*See also* vibrational analysis), C-318
in centrifugal compressors, C-189 to C-190
in electric motors, E-20
in generators and turbogenerators, G-3, G-9 to G-10, G-16 to G-17
in isotherm turbocompressors, C-193 to C-194, C-197, C-207, C-214, C-218 to C-219, C-225
influence coefficient balancing and, C-325 to C-327
magnetic bearings and, B-5 to B-7
material selection for, M-40
misalignment and, C-290 to C-291
modal balancing in, C-327 to C-328
in rotating positive displacement compressors, C-229
in rotary pumps, P-264, P-276 to P-277
in steam turbines, T-76
subsynchronrous frequency vibration in, C-291 to C-294
vibrational analysis (VA) of, C-288 to C-291, C-301 to C-325
RPM sensors, A-46
rubber products industries, pollutants and, P-15 to P-16
rubbing, vibrational analysis (VA) and, C-287

sack (paper) manufacture, F-23 to F-24
sacrificial anodes vs., C-247
Safeset couplings in, P-184 to P-191, C-344 to C-350
safety, Sp-3
accident management, A-9
ASME codes, Sp-35
tanks and, T-28 to T-32
safety systems, in turbocompressors, C-332 to C-333
safety valve, C-107, Sp-25 to Sp-28
salt corrosion, in air filtration systems, A-57 to A-64, A-69, A-72 to A-74
sawmills and wood processing operations, F-16, F-19
Saybolt, P-272
SCADA, control systems and, C-355
scanning electron microscopic (SEM), freeze drying of TBA solutions, D-8, D-15 to D-16
scavenging, in gasoline powered engines, E-39
Schott Glaswerke, D-18
scoring, gear, P-74 to P-75
screw compressors (*See* rotating positive displacement compressors)
screw pumps, P-260 to P-264
screw threads, Sp-18
scrubbers, E-40 to E-42, T-40
dry (*See* dry scrubbers)
fuel gas conditioning systems, F-25, F-28 to F-29
scuffing, gear, P-75
sealing rotor, rotary pumps, P-264
seals (*See also* gas seals), S-1 to S-9
advanced pattern groove (APG) in, S-3 to S-4
axial compressors and, C-162 to C-163, C-342
barrier type, S-8
carbon-graphite mix products and, C-12
in centrifugal compressors, C-180
centrifugal pumps and, P-250 to P-254
control panels and, S-8
electric motors and, E-17
GASPAC compressor seals, S-1 to S-9
in isotherm turbocompressors, C-206 to C-207, C-217, C-224
J ring, S-5 to S-9
lubrication of, C-336
O rings, S-1, S-5
polytetrafluoroethylene (PTFE) in, S-5 to S-9
in reciprocating (labyrinthine) compressors, C-110 to C-112, C-134
retrofitting of, S-8 to S-9
rotary pumps, P-276
in steam turbines, T-77 to T-80
symmetrical T groove (SMT) in, S-4 to S-5
seawater FGD, A-90, A-92
sebacic acid, C-68
sedimentation
centrifugal, C-35
computation fluid dynamics modeling of, C-1 to C-7
Seiko Co., P-4 to P-5

selective catalytic reduction (SCR), A-83, A-90, A-93 to A-96
selective noncatalytic reduction (SNCR), emission reduction in cement production, C-33
selenium, P-12 to P-31, P-40 to P-57
Selexol process, CO_2, C-15 to C-17
self-assessment, in environmental accountability, E-44
self-excited vibration, C-322 to C-323
self-locking worm gears, P-88
semibatch reactors, R-1
semiconductors, C-419
  conductive polymers in, P-5 to P-7
  thermoelectric cooling devices and, C-419
  thermoelectric cooling process in manufacture of, C-418 to C-423
Semipulse electrostatic precipitator, A-84 to A-85
SEN, generators and turbogenerators design, G-1
sensors (*See also* measurement; switches), A-40, A-46, C-377 to E-18
  Belleville washer negative spring rate sensor, C-386 to C-387
  bellows type, C-386
  bimetallic, C-377
  Bourdon tube, C-383 to C-385
  bulb and capillary, C-378 to C-379
  conductive polymers in, P-6
  electric transducer, M-23
  electrohydraulic actuators and, A-46
  gas actuated sensors in, C-378
  helical tube in, C-386
  liquid filled, C-378 to C-382
  liquid level/liquid flow control in, C-388 to E-18
  local mount liquid filled, C-379 to C-380
  magnetic bearings using, B-5 to B-9
  metal diaphragm, C-383
  negative spring rate, C-386 to C-387
  piston type pressure switches in, C-385 to C-386
  position, A-46
  pressure switches and, C-383 to C-388
  proof pressure in, C-383
  proof temperatures for, C-380 to C-381
  response time in, C-380
  RPM, A-46
  temperature switches, C-377 to C-382
  thermowells in, C-381 to C-382
  unsealed piston, C-387
  vapor pressure sensors in, C-377 to C-378
separation
  computation fluid dynamics modeling, C-1 to C-7
  in petroleum industry, R-2
separators, F-28 to F-29, S-10 to S-29
  capacity of, S-11 to S-12
  computational fluid dynamics to model, C-7
  cyclone tube in, S-12, S-17 to S-18
  design of, S-11 to S-12
  dry scrubbers, S-10 to S-29
  filter for, S-13 to S-16
  filter separators in, F-28
  fuel gas conditioning, F-28 to F-29
  high pressure type, S-27
  horizontal gas, S-27 to S-29
  knockout drums as, S-10
  line separators, F-29, S-24 to S-27
  mist extractor in, S-18 to S-19, S-22
  optional features of, S-12 to S-13
  pressure loss in, S-12
  removable tube section in, S-13
  steam type, for steam drum applications, T-108 to T-112
  vane type, S-19 to S-22
  vari line type, S-26 to S-27
  vertical absolute, F-29, S-16 to S-19
  vertical gas, F-27 to F-28, S-22 to S-24
Seraya Chemicals Singapore, C-41
service bulletins (SBs) and life cycle assessment, L-3 to L-6
service industries, pollutants and, P-28, P-31
service life for turbine components vs. material selection, M-41 to M-42
service symbols, Sp-3
servo tank gauges, T-18 to T-19, T-32 to T-33
servomotors
  in axial compressors and, C-161 to C-162
  in fuel system control, F-36
severity levels of accidents, A-9
sewage (*See also* wastewater), P-69 to P-72
sex hormone–related diseases, E-44
shaft gland seal ring, in steam turbines, T-78
shaft string drive, in isotherm turbocompressors, C-194 to C-200
shafts, synchronous clutches and, P-118
shale, O-1
shear, pumping applications and non Newtonian fluids, P-272
shear tubes, P-191 to P-192
sheathed element electric heaters, H-15 to H-16
short circuit, C-344
shortcircuiting, in chemical reactors, R-1
shot, A-1
  military specification (MIL-13165-C), A-7
shot peening, A-7 to A-9
Siemens, M-31
signal-to-noise (S/N) ratio, C-271
silencer outlet, air filtration systems and, A-64
silicon carbide, A-4, A-6
silicon controlled rectifiers (SCRs), H-18 to H-19
silicon dioxide (SiO_2), C-25
silos (*See* tanks)
silver nitrate, C-68
silver, P-12 to P-31, P-40 to P-57
Simmers, O-2 to O-4
Singapore Acrylic Pte Ltd (SAA), C-41
Singapore Monomer Pte Ltd (SMM), C-41
single pole double throw (SPDT) reed switch, C-390 to E-18
single pole single throw (SPST) reed switch, C-390 to E-18
sintering of catalyst, in air pollution control, A-96
sinusoidal waveforms, in vibrational analysis (VA), C-261 to C-262
site classification categories, waste management, W-1 to W-12
skid mount
  in isotherm turbocompressors, C-205
  in reciprocating (labyrinthine) compressors, C-108, C-128
skid, fuel skid, F-34 to F-36
slide valve, flow through, using computational fluid dynamics, C-2
sliding contact bearings, B-2 to B-5
sliding vane pumps, P-260 to P-264
slip curves, for gas turbines, C-347 to C-348
smart membranes, conductive polymers in, P-7
smoke test, in explosion hazard assessment, E-74 to E-75
snubbers (*See* pulsation dampeners)
SOAP, C-261
soap, in lubricating oil, L-25
Society of Automotive Engineers (SAE), A-7
sodium, as fuel impurity, L-9
sodium carbonate, C-68, C-72
sodium lauryl sulfate, C-68
sodium sulfate, C-68, C-72
solid or structural damping, C-307
solid solutions, M-39
solid-state technology, cooling products using, C-413
solubility curves of chemicals in crystallization of, C-71 to C-75
solvent extraction, R-5
solvents, C-72
  chlorofluorocarbons in, O-14, O-16 to O-26
  crystallization of, C-70
sorbic acid, C-68
sound (*See* soundproofing and noise control)
sound intensity levels (SIL), A-18 to A-19, A-22 to A-26
sound intensity meters, A-16
sound intensity probes, A-16 to A-17, A-21
sound pressure levels (SPL), A-11 to A-12, A-14 to A-16, A-18 to A-19
sound reduction index (SRI), A-22, A-27 to A-28, A-36
soundproofing and noise control, A-10 to A-37
  absorption of sound, A-11
  absorptive linings in, A-33 to A-37
  acoustic behavior of products in, A-27 to A-28
  acoustic design in, lightweight gas turbine enclosures, A-26 to A-37
  acoustic performance, A-37
  active vs. reactive sound fields in, A-20
  attenuation of sound, A-33 to A-37
  background noise measurement in, A-20 to A-21
  bending stiffness of panels vs., A-29 to A-31
  "coincidence frequency" in, A-27, A-30
  corrugated panels in, lined, A-33 to A-37
  corrugated panels in, unlined, A-29 to A-33
  damping in, A-28, A-33
  distance between source and measurement probe in, A-19 to A-20
  environment, environment's effects on, A-21
  fire ratings for, A-36
  flat panels in, lined, A-33 to A-37
  flat panels in, unlined, A-27 to A-29
  flexible connectors and, A-24 to A-25
  flow resistivity in absorptive materials and, A-34
  frequency in, A-28
  instrumentation and meters to measure sound in, A-14, A-16 to A-17
  intensity probe, A-21
  limitations to measurement in, A-20 to A-22
  mass law performance in, A-33
  measurement guidelines and standards for, A-17 to A-20
  motors, relative noise of, A-24
  near vs. far fields in, A-20
  nomenclature of, A-26
  pressure-intensity (P-I) index of sound in, A-16, A-18 to A-19
  propagation of sound in, A-27
  rank ordering of components in terms of A-weighted SPLs, A-23
  reactivity index of sound, A-12, A-16, A-18 to A-19
  resonance in, A-27 to A-28
  sound intensity (SIL) in, A-14 to A-19, A-22 to A-26
  sound intensity measurement in, A-11 to A-14
  sound power (PWL) in, A-14 to A-16, A-18 to A-19
  sound pressure levels (SPL) in, A-11 to A-12, A-14 to A-19
  sound reduction index (SRI) in, A-22, A-27 to A-28, A-36
  sound reference levels of, A-15 to A-16
  soundproofing panels for, testing of, A-21 to A-22, A-26 to A-33
  source location and, A-21, A-25 to A-26
  standards for, A-17 to A-20

subareas in measurement of, A-19
surface area vs., A-12
sweep vs. point measurement of sound in, A-19
tonal noise source and, measurement of, A-22
transmission loss in, A-27 to A-28, A-31 to A-33
uncertainty of determination of sound pressure levels, A-18
soundproofing panels, A-21 to A-22, A-26 to A-33
sour water, R-9
specific heats ratio, in flow measurement, M-24
specific weights in, M-25
specifications
American Society of Mechanical Engineers (ASME), A-1
commonly used, Sp-1 to Sp-3
gears, P-75 to P-76
life cycle assessment (LCA) and, L-19
lubrication and, L-24 to L-25
tanks, for potable water, T-9 to T-13
spectrum analyzer
automatic peak hold in, C-272
transient data capture in, C-271
in vibrational analysis (VA), C-266, C-270 to C-272, C-298 to C-299
speed (rpm), fans, F-1
speed protection device
electrohydraulic actuator in, A-47 to A-48
trigger criteria in, A-48
speed regulation
in hydrodynamic power transmission, P-155 to P-164
in torque converters, P-174
spin tubes, air filtration systems and, A-57
splash type lubrication, L-25
sponge ball cleaning system, condensers, C-248 to C-250
squirrel cage induction motors, E-19
stacks, S-29 to S-38
cleaning of, C-78
cost analysis for, height vs. cost, S-30 to S-32
design parameters for, S-30 to S-33
gust loading on, S-35 to S-38
height of, S-30 to S-33
nomenclature used with, S-30 to S-31
steady-state wind loading on, S-33 to S-35
steel, Sp-18
supports for, S-30 to S-33
weight of, S-30 to S-33
staged air combustion, emission reduction in cement production, C-33
stainless steel, M-40
in air filtration systems and housing, A-58 to A-63, A-71 to A-72
in condensers, C-245 to C-246
stall, C-328, T-48 to T-49
standards, Sp-1 to Sp-3
American Society of Mechanical Engineers (ASME), A-1, Sp-36
starters
synchronous clutches and, P-107 to P-108
torque converters and, P-171 to P-172
static bioassay, R-9 to R-10
static excitation, in generators and turbogenerators, G-16 to G-17
static head, P-219, P-221 to P-224
static pressure (hs), F-1 to F-5, M-15
static taps, pressure measurement and, M-15
static thyristor rectifier, in generators and turbogenerators, G-3
static tubes, in pressure measurement, M-15
Statoil, C-14
stators
in electric motors, E-19
in generators and turbogenerators, G-4 to G-5
in isotherm turbocompressors, C-211 to C-215, C-223 to C-224
in magnetic bearings, B-5 to B-7
steady-state oscillations, vibrational analysis (VA) and, C-313 to C-314
steady-state wind loading, stacks and, S-33 to S-35
steam drums, steam separators for, T-108 to T-112
steam dump device (SDD), condensers, C-248 to C-250
steam generators (*See also* boilers), S-38
steam rate calculations, for steam turbines, T-92 to T-94
steam regulators, current to pressure (I/P) converters for, C-392 to C-401
steam seal system, in steam turbines, T-79 to T-80
steam supply, S-38
steam turbines (*See* turbines, steam)
steel belt conveyors, C-408
steels and iron, M-40
Stefan Boltzmann constant, M-10
stepper motor–driven valves, C-403 to C-405
SteriGenics food irradiation facility, I-1 to I-5
sterilants, chlorofluorocarbons in, O-14, O-16 to O-26
sterilization, of air, A-101 to A-102
Sterling Drug, D-17
sterols, C-68
stiffness coefficient, vibrational analysis (VA), C-305 to C-306
Stokes Vacuum Inc. dryer, D-12 to D-13
storage and warehousing industries, pollutants and, P-29
storage tanks (*See* tanks)
stress tables, ASME, Sp-33
strip chart recorders, vibrational analysis (VA), C-270
strippers, T-40
stripping, metallurgy, M-32, M-34, R-10
strobe lights, vibrational analysis (VA) and balancing, C-278 to C-280
stroboscopes, vibrational analysis (VA), C-282 to C-286
stuffing boxes, centrifugal pumps and, P-248 to P-254
styrene, P-12 to P-31, P-38, P-40 to P-57
styrene monomer/propylene oxide (SMPO), C-41
styrene oxide, P-12 to P-31, P-38, P-40 to P-57
subcooling, condensers, C-240
sublimation, freeze drying, D-8
subsynchronrous frequency vibration, C-291 to C-294
suction head, P-222
net positive (NPSH), P-232 to P-237, P-257
suction lift, P-222, P-272 to P-273
suction type electric heater, H-13
sugar/sucrose and TBA in freeze drying, D-8 to D-18
sulfate levels in lakes, Ontario and Quebec, A-13
sulfur, C-15, L-9
sulfur dioxide (SO_2), A-83, C-34, E-38, F-43, F-45, L-9, P-60 to P-62, V-16
sulfur hexafluoride, V-16
sulfur trioxide (SO_3), C-25, V-16
sulfuric acid, A-9, P-12 to P-31, P-40 to P-57
sulfur oxides (SO_x), A-9 to A-10, E-36, E-50
Sulzer–Burckhardt, C-84 to C-232, E-42
Sumitomo Chemical, C-41
Sumitomo Pharmaceuticals Ltd., D-17
Suomen Rehu, E-46
superabrasive wheels, vitrified, A-2
superabrasives, A-1
superalloys, M-42 to M-43
abrasives and, A-2
cobalt based, A-2
nickel based, A-2
welding, M-38
superheaters, vaporizers, V-1 to V-5, V-13 to V-17
superposed steam turbines, T-96 to T-98
support systems
flexible, vibrational analysis of, C-318 to C-321
rigid, vibrational analysis of, C-318 to C-321
surface finish, A-1
surface quality, Sp-19
surge, C-264, T-48 to T-49
surge control (*See also* antisurge control), C-328 to C-330
sweetening processes, R-5
swing check valves, C-392
switches (*See also* measurement; sensors), switches, C-377 to C-391
absolute pressure switches in, C-383
actuation values in, C-377
Belleville washer negative spring rate sensor in, C-386 to C-387
bellows type sensors in, C-386
bimetallic type sensors, C-377
Bourdon tube sensors in, C-383 to C-385
bulb and capillary sensors in, C-378 to C-379
differential pressure-actuated, C-383
flow measurement sensors, C-389
gas actuated sensors in, C-378
gauge type instruments in, C-383
helical tube sensors in, C-386
liquid filled sensors in, C-378 to C-382
liquid flow instrumentation, C-388
liquid level instrumentation, C-388
local mount liquid filled sensors in, C-379 to C-380
mechanical thermal (MTS), P-202 to P-204
metal diaphragm sensors, C-383
negative spring rate sensor in, C-386 to C-387
noncontact thermal (BTS), P-202 to P-204
piston type pressure switches in, C-385 to C-386
pressure switches, C-383 to C-388
proof pressure in, C-383
proof temperatures for, C-380 to C-381
reed switch, C-390
response time in, C-380
sensors and, C-377
single pole double throw (SPDT) reed switch, C-390
single pole single throw (SPST) reed switch, C-390
temperature switches, C-377 to C-382
thermowells in, C-381 to C-382
unsealed piston sensors in, C-387
vapor pressure sensors in, C-377 to C-378
symmetrical T groove (SMT) seals, S-4 to S-5
synchronous clutch couplings, P-107 to P-115
alternators and, P-107, P-112
automatic turning gears and, P-107 to P-113
clutch assembly in, P-118
cogeneration and, P-107 to P-108, P-114 to P-115
design lettering designations for, P-111
elements of, P-107 to P-108
energy recovery and, P-107 to P-108, P-114 to P-115
flanges in, rigid, P-118
flexible couplings in, P-118
freestanding (type MS), P-113 to P-114
geared systems for, P-118
generators and, P-115 to P-121

instrumentation for, P-118 to P-121
journal bearings in, P-116 to P-117
power station, power generator use of, P-107 to P-113
quill shafts in, P-118
sectional view of, P-109
teeth in, P-116
thrust bearings in, P-117
thrust cones in, P-117 to P-118
type designations of (MS, DS, HS), P-110
syngas, C-17 to C-18
synthetic crude, O-1 to O-2
System 3 tank exterior coating, T-5

tank capacity tables (TCTs), T-24
tank cars, toxic chemical unloading procedures for, C-46 to C-52
tank gauges, T-13 to T-40
central inventory management system for, T-36 to T-39
diversion systems for, T-30 to T-31
float and tape, T-18
future developments in, T-39 to T-40
grounding for, T-31 to T-32
hybrid inventory measurement system (HIMS), T-22 to T-24, T-26 to T-27, T-36, T-39
hydrostatic (HTG), T-21 to T-22, T-25 to T-26, T-35 to T-36, T-39
manual, T-17 to T-18
quantity assessment using, T-24 to T-27
radar, T-19 to T-21, T-33 to T-34
servo, T-18 to T-19, T-32 to T-33
suppression systems for, T-30
temperature type, T-34 to T-35
uncertainties and errors in, T-27 to T-28
tank heaters, H-12 to H-15
tanker trucks, toxic chemical unloading guidelines for, C-51 to C-52
tanks, storage, T-1 to T-40, Sp-18
central inventory management system for, T-36 to T-39
density at reference temperature (DENS.REF) in, T-25 to T-27
errors and uncertainties in tank gauging and, T-27 to T-28
exterior coatings for, T-5
fire and explosion hazards, T-28 to T-29
flame arrestors for, V-31
float and tape gauges in, T-18
gauges for, T-13 to T-40
general storage type, T-1 to T-8
Gravi Merge Blending Silos, T-8
gravity blending in, T-4 to T-8
gross observed volume (GOV) in, T-25 to T-27
gross standard volume (GSV) in, T-25 to T-27
grounding for, T-31 to T-32
high voltage diversion systems for, T-30 to T-31
high voltage suppression systems for, T-30
hybrid inventory measurement system (HIMS) tank gauges in, T-22 to T-24, T-26 to T-27, T-36, T-39
hydrostatic tank gauges (HTG) in, T-21 to T-22, T-25 to T-26, T-35 to T-36, T-39
interior coatings for, T-4 to T-8
inventory control in, tank gauging for, T-15
leak detection and repair in, T-16 to T-17
lightning strikes and, T-29 to T-30
liquid storage, T-9 to T-13
manual gauging in, T-17 to T-18
oil movement, T-16
pneumatic conveying fill system for, T-7
quantity assessment, using tank gauges, T-24 to T-27
radar tank gauges in, T-19 to T-21, T-33 to T-34
recirculation blending while filling in, T-8
safety and, T-28 to T-32
servo gauges in, T-18 to T-19, T-32 to T-33
specifications sheets for, sample of, T-9 to T-13
tank capacity tables (TCTs) for, T-24
temperature gauges for, T-34 to T-35
toxic chemicals, C-56 to C-58
transfer of product, tank gauging for, T-15 to T-16
vaporizers, pressurized, V-22 to V-25
vents in, V-31
volume correction factor (VCF) in, T-25 to T-27
water storage (potable), T-9 to T-13
welded exterior coatings for, T-5
welded interior coatings for, T-4 to T-8
tar sands, O-1
TCR, air pollution control and, A-99 to A-100
TECA (cooling), C-413 to C-423
teeth, gear, P-88 to P-93, P-116
temperature control
in generators and turbogenerators, G-18 to G-19
in turbocompressors, C-333
temperature measurement (*See also* temperature switches), C-260 to C-261, M-1 to M-14, M-30 to M-31
absorptivity in, M-10
bimetallic thermometers for, M-8 to M-9
calibration of instruments for, M-11 to M-12
Celsius scale in, M-12
conduction error in, M-13
emissivity in, M-10
Fahrenheit scale in, M-12
filled system thermometers in, M-8
liquid in glass thermometers in, M-1 to M-2
multiresistance thermometers for, T-34 to T-35
multitemperature thermometers, T-34 to T-35
optical pyrometer in, M-11
pyrometers in, M-11
pyrometry in, M-10
radiation error in, M-13
radiation thermometers in, M-10 to M-11
in rapidly moving gas, M-13 to M-14
resistance thermometers in, M-2 to M-5
steam turbines and, T-80
Stefan Boltzmann constant in, M-10
tank gauges for, T-34 to T-35
thermistors in, M-4 to M-5
thermocouple thermometers for, M-5 to M-8
thermometers for, M-1 to M-8
tolerance in thermometers for, M-2 to M-3
temperature switches (*See also* temperature measurement), C-377 to C-382
actuation values in, C-377
bimetallic sensors in, C-377
bulb and capillary sensors in, C-378 to C-379
liquid filled sensors in, C-378 to C-382
local mount liquid filled sensors in, C-379 to C-380
proof temperatures for, C-380 to C-381
response time in, C-380
thermowells in, C-381 to C-382
vapor pressure sensors in, C-377 to C-378
temperature transmitter, C-333 to C-334
tertiary butyl alcohol (TBA) (*See also* freeze drying), D-5 to D-18
test codes, ASME, Sp-34 to Sp-35
testing
of centrifugal compressors, C-188 to C-189
eddy current, M-36
of fuel systems and controls, F-34 to F-36
of generators and turbogenerators, G-17 to G-18
of integrally geared compressors, C-226
liquid natural gas (LNG) and, L-23 to L-24
of reciprocating (labyrinthine) compressors, C-110
tetracalcium aluminoferrite (C4AF), C-25 to C-26
tetrachloroethylene, P-12 to P-31, P-39 to P-57
tetracholorbenzene, C-68
tetrahedral mesh modeling, C-5
tetramethy benzene, C-68
textile industries, pollutants and, P-17 to P-18
texts, Sp-1 to Sp-3
theoretical capacity (Q_t), pumps and, P-265
thermal conductivity gauges, M-22
thermal efficiency, steam turbine, T-82, T-84
thermal expansion factor, in flow measurement, M-24
thermal expansion, coefficient of, carbon-graphite mix products, C-9
thermal rating, worm gear, P-94
thermally densified coatings (TDC), M-35
thermistors, M-4 to M-5
thermocouples, M-5 to M-8, M-22
pressure measurement, M-22
synchronous clutches and, P-118
temperature monitoring, C-260 to C-261
thermometers for, M-5 to M-8
thermodynamics
in condensers, C-242 to C-244
in gas turbines, T-55
thermoelectric cooling process, C-418 to C-423
thermoforming, computational fluid dynamics to model, C-7
thermometers, M-1 to M-8
multiresistance, T-34 to T-35
multitemperature, T-34 to T-35
thermoset plastics, Sp-18
thermowells, C-381 to C-382
thin film processors (*See* chillers)
thiourea, P-12 to P-31, P-39 to P-57
threads, Sp-18
three-lobe journal bearings, B-3
threshold limit value (TLV), C-61, R-19
throat area, in flow measurement, M-24
throat diameter, in flow measurement, M-24
through-flow control, in hydrodynamic brakes, B-18
thrust bearings (*See also* axial thrust bearings), B-4, B-6, B-8
in axial compressors, C-163 to C-164
in centrifugal compressors, C-178 to C-181
in steam turbines, T-78
in synchronous clutches, P-117
thrust cones, in synchronous clutches, P-117 to P-118
thyristors
electric heater, H-16 to H-19
rectifiers using, G-3
tilting pad journal bearings, B-4, L-25
timber production (*See also* forest products), F-18 to F-21
time between overhaul (TBO), L-7 to L-10
adjustment to, based on LCA, L-7 to L-8
condition monitoring (CM) and, C-256
time waveform analysis, in vibrational analysis (VA), C-270, C-280 to C-282
time weighted average (TWA) exposure, refrigerants, R-19
timed screw pumps, P-260 to P-264
titanium and titanium alloys, C-246, C-251, M-40, M-42
titanium dioxide, V-15
titanium tetrachloride, P-12 to P-31, P-40 to P-57
Toagoseia, C-41
tobacco industries pollutants, P-29
tolerance in degrees, thermometers, M-2

tolerances
ASME certification program for, Sp-30
carbon-graphite mix products and, C-10
toluene diisocyanate (TDI), C-42 to C-62, P-12 to P-31, P-39 to P-57, V-15
Chemical Manufacturers Association (CMA) guidelines for, C-61
CHEMTREC information service, telephone number, C-61
color/discoloration of, at unloading, C-49
container for, C-45
cylinders for shipment of, unloading, C-52 to C-54
decontamination of empty toxic chemical containers, C-62
disposal of, C-62
drum unloading of, C-54
fire hazards of, C-59
first aid procedures for, C-61
health hazards of, C-59
heat and, reactivity of, C-43, C-45
Material Safety Data Sheets (MSDS) for, C-43, C-58
physical properties and toxicity of, C-43
protective clothing for handling of, C-59 to C-61
reactivity of, C-43 to C-45, C-58 to C-59
respirators for safety in handling, C-59 to C-61
shipping and handling of, C-45 to C-54, C-58 to C-61
spills and leaks of, C-61 to C-62
storage containers for, C-56 to C-58
tank car unloading, C-46 to C-52
tank truck unloading of, C-51 to C-52
thawing of, C-54 to C-56
Threshold Limit Value of, C-61
Types I and II, C-43
unloading of, C-45 to C-54
water and, reactivity of, C-43
white precipitates of, at unloading, C-48 to C-49
toluene, P-12 to P-31, P-39 to P-57
toluene-2,4-diisocyanate, P-12 to P-31, P-40 to P-57
Tomlinson boiler, P-210
tonal noise source, measurement of, A-22
tools, Sp-19 to Sp-22
tooth breakage, gear, P-74 to P-75
topping turbines, T-97
torque, C-344
in electric motors, E-3 to E-4, E-10 to E-15, E-23 to E-25
hydrodynamic braking and, B-16, B-20 to B-21
in hydrodynamic power transmission, P-128, P-133 to P-134
in torque converters, P-170 to P-171, P-174
torque converter (*See also* hydrodynamic power transmission), P-166 to P-184
adjustable, P-169
characteristics of, P-134 to P-136
compact design (Vorecon type RWE) in, P-174 to P-177
components of, P-170 to P-171
expanded speed range applications (Vorecon type RWS) in, P-177
filling and draining facilities in, P-172 to P-173
gas turbine starter for, P-171 to P-172
hydrodynamic power transmission and, P-123 to P-127
models available, P-174
multistage variable speed drives and, P-181 to P-184
operation of, P-170 to P-171
power vs. efficiency in, P-177
relieve startup application (Vorecon type RW) in, P-177 to P-181
schematic of, P-172
speed regulation in, P-174
symbols for, P-169
torque in, P-170 to P-171, P-174
variable speed engine and fluctuating load in, P-172 to P-174
torque limiting safety coupling, torque converters and, P-184 to P-191
total equivalent warming impact (TEWI), refrigerants and, R-12 to R-14
total head, P-222
total pressure, M-15
total quality management (TQM), environmental accountability and, E-40 to E-49
total signal, in vibrational analysis (VA), C-263
towers and columns, T-40
toxaphene, P-7
toxic chemicals (*See* chemicals; hazardous materials)
toxic gases, C-86
trade contracting industries, pollutants and, P-28
trajectories, computational fluid dynamics to calculate, C-3
transducers
pressure measurement, M-22 to M-24
vibrational analysis (VA) and, C-266 to C-270
transfer of pollutants, P-9, P-49 to P-54
transformers, in generators and turbogenerators, G-19
transient data capture, spectrum analyzers, C-271
transient vibration in, C-264
transistors, power transistors and electric motors, E-29 to E-32
transition voltage (dV/dt) time, electric motors and, E-30
translational velocity, vibrational analysis (VA), C-265
transmission loss, sound, A-27 to A-33
transmissions (*See* power transmission)
transmitters, electric transducer, M-23
transportation equipment industries, pollutants and, P-22
transportation industries, pollutants and, P-28
transportation of bulk chemicals, T-40 to T-41
tray-type reactors, T-40
treatment process, in petroleum industry, R-2, R-4 to R-5
tricalcium aluminate (C3A), C-25 to C-26
tricalcium silicate (C3S), C-25 to C-26
trichloroethane, P-12 to P-31, P-39 to P-57, V-15
Trilok converters, hydrodynamic power transmission and, P-138
trimethylbenzene, P-12 to P-31, P-40 to P-57
triple redundancy, T-41 to T-43
tropical environments vs. air filtration, A-50 to A-61
trucks, industrial, Sp-11
tube bundles, tubes
condensers, C-234, C-240 to C-242, C-244 to C-246
vaporizers, V-7 to V-10
tubesheet condensers, C-246, C-251
tubular reactors, R-1
tungesten inert gas (TIG) welding, M-38
tungsten alloys, M-42
TURBAIR vacuum blowers, C-149 to C-150
turbine damage, in air filtration systems, A-58
turbine discs, material selection for, M-40
turbine flow measurement, C-390
turbine inlet temperatures (TIT), monitoring of, C-261
turbine vanes (*See* vanes, turbine)
turbines, gas, T-43 to T-76, Sp-22
acoustic design in, lightweight gas turbine enclosures, A-26 to A-37
acoustic enclosure for soundproofing and noise control in, A-10 to A-37
aeroderivative fuel regulator for, C-354 to C-358
air filtration for (*See* air filtration)
air/gas conditions in, T-53 to T-55
airflow heating in, T-45 to T-46
airflow through, T-44 to T-46, T-49, T-53 to T-55
ambient air pressure (P_0) in, T-55 to T-58
ambient air temperature (T_0) in, T-58
ambient air relative humidity in, T-58, T-65 to T-67
atmospheric conditions vs. power degradation in, T-65 to T-67
axial flow compressor design in, T-47 to T-48
axial flow through, T-51 to T-53
biomass fuel fed, from pulp and paper mill, P-210 to P-211
brake properties at high speed and acceleration, C-347 to C-350
cleaning or washing of, T-59 to T-75
closed cycle, T-44 to T-45
clutch type couplings in, C-347
combustion chamber in, T-49 to T-51
compressor for, T-47
condensers connection to, C-239
configurations for, T-53
constant fill couplings, C-347
description of, T-43 to T-60
deterioration of, L-10
efficiency of, T-43 to T-44
fouling of compressors in, T-63 to T-65, T-67
gearboxes in, C-343
gears in, C-345
hydrodynamic principle in turbocouplings and, C-346 to C-347
integrated control system (Series 9500) for, C-359 to C-361, C-374 to C-377
life cycle assessment (LCA) and, L-15 to L-17
offshore environments for, A-26
onshore environments for, A-26
open cycle, T-44 to T-45
operating conditions for, T-58 to T-60
operating cycle in main parts of, T-44
overload/overspeed control, C-336, C-343 to C-350
performance analysis of, T-55
power generation in, T-47
Safeset overspeed/overload protective coupling, C-344 to C-350
self-sustaining speed of, T-46 to T-47
slip curves for, C-347 to C-348
stall in, of compressor, T-48 to T-49
surging in, T-48 to T-49
thermodynamic factors in, T-55
torque converters and for starter in, P-171 to P-172
turbine in, T-51 to T-53
variable speed couplings in, C-347
witness testing of soundproofing for, A-22 to A-26
turbines, steam, T-76 to T-112, Sp-22
auxiliary systems for, T-78 to T-80
back pressure, T-96 to T-98
bearing housings in, T-78
blades for, T-76, T-88 to T-90
casing for, T-76
classification of, T-87
control systems for, T-78 to T-79
deterioration of, L-11
diaphragms in, T-77
efficiency of, T-82, T-84, T-89 to T-90

enthalpy in, T-82, T-84
extraction type, T-98 to T-100
feedwater heating in, regenerative, T-85 to T-87
governors for, T-100 to T-108
helical flow stage in, T-91
impulse stage in, T-89
induction type, T-98 to T-100
interstage steam sealing in, T-77
journal bearings in, T-78
low pressure type (high pressure insert), T-100
lubrication system for, T-79, T-109 to T-110
material selection for, M-42
Mollier diagrams for, T-82, T-84
multistage condensing, T-94 to T-96
nozzle rings for, T-76 to T-77
nozzles in, T-88 to T-89
oil supply system in, T-79
operational theory of, T-80 to T-108
overload/overspeed protection in, C-368 to C-374, T-78, T-106 to T-108
p5 type, T-111
power output from, T-81
pressure control in, C-368 to C-374
Rankine cycle in, T-82 to T-84
reaction stage in, T-88 to T-89
regenerative cycle in, T-85
reheat cycle in, T-84 to T-85
rotors in, T-76
seals in, T-77
shaft gland seal ring in, T-78
single stage, T-91 to T-94
steam cycles in, T-82 to T-87
steam path design in, T-87 to T-91
steam rate calculations for, T-92 to T-94
steam seal system in, T-79 to T-80
steam separators for steam drum applications, T-108 to T-112
superposed, T-96 to T-98
temperature sensors in, T-80
thermal efficiency in, T-82, T-84
thrust bearings in, T-78
topping, T-97
turning gear system in, T-79
valve gear assembly for, T-78
vibration monitoring in, T-80
turbochargers, E-38 to E-39, T-112 to T-114
turbocompressors, C-136 to C-232
antisurge control in, C-332 to C-335, C-359 to C-368
control systems for, C-331 to C-336
discharge pressure control in, C-333
flow control in, C-333
load limit control in, C-334
monitoring logic in, C-336
power limitation in, C-333
pressure control in, C-333
pressure limitation in, C-333
process control in, C-333 to C-334
safety systems and, C-332 to C-333
suction pressure control in, C-333
temperature limitation in, C-333
vibration limitation in, C-333
turbocouplings, hydrodynamic principle in, C-346 to C-347, P-191 to P-196
turboexpanders, C-151 to C-152, T-114 to T-115
turbogenerators (*See* generators), G-1 to G-20
turbomachinery, vibrational analysis (VA) of, C-268, C-297 to C-298, C-308
turbotransmission (*See* hydrodynamic power transmission)
turbulence errors, M-15
Turcon CTo electrohydraulic actuator, A-47
turning gear system, in steam turbines and, T-79
two-stroke engines, E-38 to E-40
Udimen, M-41
UL/CSA design standards, cooling, C-418
ultrasonic cleaning, U-1 to U-9
booster for, U-3
converter for, U-2
EPA environmental testing packages using, T-5 to T-6
1500 watt processors, T-7 to T-9
400 and 600 watt processors, T-6 to T-7
power supply for, U-1 to U-2
probes for, U-2 to U-3
ultrasonic flow measurement, C-390
ultrasonic method, in level sensing, C-388
ultraviolet irradiation
air purification using, A-102
ozone and, O-5 to O-6
underdamping, C-312 to C-313
Uniax, P-5
United National Environment Programme (UNEP), ozone and
United States Surgical Corporation, D-17
unsealed piston sensors, C-387
untimed screw pumps, P-260 to P-264
Upjohn Company, D-17
urea, C-33
urethane, C-58
user interface, in magnetic bearings, B-9
utility industries pollutants, P-29

vacuum blowers, TURBAIR, C-149 to C-150
vacuum crystallization process, C-71
vacuum devices, ejectors, E-2 to E-3
vacuum distillation, petroleum industry, R-2
vacuum drying, D-4, D-12 to D-13, E-2 to E-3
vacuum pressure, M-15
vacuum pumps, P-309 to P-325
dry types, P-312
liquid jet, P-321 to P-325
liquid types, P-312
single stage, liquid ring, P-318 to P-321
valves, A-40, C-107, Sp-22 to Sp-23
antisurge, C-332 to C-335
ASME accreditation packages for, Sp-25 to Sp-28
ball, CE-18 to CE-392
butterfly, C-392
centrifugal pumps and, P-257
control, CE-18 to CE-392
current to pressure (I/P) converters and, C-392 to C-401
diaphragm, CE-18 to CE-392
diverters, D-3
electrohydraulic actuators in, A-43
fast response, C-405 to C-408
flapper, D-3
float type, V-25 to V-28
fuel regulation using, C-403 to C-408, F-30, F-32 to F-33
gate, A-43
globe, CE-18 to CE-392
knife gate, C-399, C-402 to C-403
lift check, C-392
manifold flow (fuel) control using, C-403 to C-408
Moog, C-405
needle globe, CE-18 to CE-392
nonreturn or check, C-392
pinch, CE-18 to CE-392
plug, CE-18 to CE-392
pressure regulation (PRV) in, F-25 to F-26
in reciprocating (labyrinthine) compressors, C-88 to C-91, C-95, C-115, C-122 to C-124, C-135
in steam turbines, T-78
stepper motor–driven in, C-403 to C-405
swing check, C-392
Van T'Hoff equation, crystallization, C-72 to C-75
vanadium, A-6, L-9, P-12 to P-31, P-40 to P-57
vane type separators, A-63, A-74, S-19 to S-22
vanes, turbine (*See also* metallurgy)
material selection for, M-41
vapor coatings, M-35
vapor pressure sensors, C-377 to C-378
vapor type electric heater, H-11
vaporization, C-62
vaporizers, V-1 to V-31
ammonia in, V-16
applications for, V-15 to V-16
chlorine in, V-16
combination electric indirect, V-20 to V-22
constant vapor outlet temperature in, V-29 to V-31
control systems for, V-25 to V-31
control systems in, V-1 to V-5
conversion factors for
cryogenic, V-5 to V-7, V-17 to V-19
design criteria, by fluid type, V-16 to V-17
design features of, V-9 to V-12
direct steam heated types, V-19
electric resistance, V-1 to V-5
electrical radiant furnace, V-5 to V-6
ethylene in, V-17
float valves in, V-25 to V-28
fluids vaporized in, V-15 to V-16
freeze up protection in, V-12 to V-13, V-17 to V-19
impedance electric heater, V-1 to V-5
indirect fluid heater, V-1 to V-5
lethal fluids in, V-17
liquid to vaporizer–vapor direct to load system in, V-28 to V-29
liquefied natural gas (LNG) in, V-17
operation of, V-10 to V-12
pressurizing storage tanks for, V-22 to V-25
propane and butane in, V-17
small electric indirectly heated, V-19 to V-20
specifications and process parameters for, V-6 to V-8
steam feed for, V-10
superheater, V-1 to V-5, V-13 to V-17
tube bundles in, V-7 to V-10
tubular low temperature, V-1 to V-5
types of, V-1 to V-5
vertical, V-1 to V-5
vertical bayonet type, V-7 to V-12
working pressure in, V-9
vari-line separators, S-26 to S-27
variable area flow measurement, C-390
variable frequency control, AC induction motors used for, E-18 to E-35
variable frequency drives (VFD), in centrifugal compressors, C-185
variable pitch fan, F-3
variable speed couplings, C-347
in hydrodynamic power transmission, P-138 to P-147, P-155 to P-164
Type RK variable speed coupling in, P-147 to P-149
Type SVL variable speed coupling in, P-145 to P-147
Type SVNL, P-142 to P-145
variable speed drives, torque converters and, P-181 to P-184
vegetation
acid rain and, P-60 to P-62
ozone and damage to, O-8 to O-9
velocity
in fans, F-3 to F-4
in vibrational analysis (VA), C-287, C-305, C-311
velocity head, M-15, P-221 to P-224
velocity of approach factor, flow measurement, M-24
velocity pressure, F-4, M-15

velocity probes, in vibrational analysis (VA), C-268
ventilation
  computation fluid dynamics in, C-1 to C-7
  vs. explosion hazard, E-70, E-76, E-87
venting, in condensers, C-246 to C-250
vents and flame arrestors, V-31
Venturi tubes, C-330, C-333, M-23, M-26, M-29
verification, in environmental accountability, E-44
vertical absolute separators, F-29, S-16 to S-19
vertical bayonet vaporizers, V-7 to V-12
vertical cluster in tank electric heater, H-14
vertical deflection, in vibrational analysis (VA), C-262
vertical dry scrubbers, F-28 to F-29
vertical gas separators in, F-28, S-22 to S-24
VHBI hydrodynamic brakes, B-14 to B-16, B-25 to B-28
VHBK hydrodynamic brakes, B-27
VHBM hydrodynamic brakes, B-14 to B-16
vibrational analysis (VA) (*See also* condition monitoring), C-253, C-257 to C-258, C-261 to C-328, O-1
  acceleration, conversion factors for, C-265
  acceleration in, C-287, C-305, C-311
  accelerometers in, C-269, C-324
  amplitude in, C-263, C-268, C-302, C-315 to C-316
  amplitude vs. frequency in, C-270 to C-272
  amplitude vs. frequency vs. time in, C-270, C-272
  amplitude vs. phase in, C-280 to C-282
  amplitude vs. phase vs. machine rpm in, C-270, C-272 to C-280, C-300
  amplitude vs. time in, C-270
  anti node in plots of, C-276
  balancing and, C-278 to C-280, C-288 to C-291, C-325 to C-328
  blade tip rub and, C-294
  Bode plots in, C-270, C-272 to C-280
  Campbell diagrams for, C-323 to C-326
  cavitation in, C-264
  centrifugal pumps and, P-255 to P-258
  complex vibration in, C-263
  compressors and, C-264
  critical damping in, C-312 to C-313, C-315
  critical speed map for, C-322
  damped systems in, C-307 to C-313
  damping in, C-264, C-305 to C-306
  degree of freedom in, C-301 to C-302, C-310
  deterministic vibration in, C-263
  displacement and, C-287, C-314 to C-315
  displacement or proximity probes for, C-266 to C-270
  drive belts and, C-296
  dynamic absorbers and, C-276
  eddy current probes in, C-267 to C-268
  electric motors and, E-18 to E-22, E-33
  electronic data loggers in, C-270
  filter in/filter out amplitude vs. rpm in, C-276 to C-278
  filtered signal in, C-263
  flexible supports and, C-318 to C-322
  forced vibration in, C-264, C-301, C-313 to C-316, C-322 to C-323
  forcing frequency in, C-264
  free vibration in, C-264, C-301 to C-307
  frequency components of, C-87
  frequency in, C-262, C-300 to C-302
  friction (coulomb) damping in, C-307
  gear rpm and, C-294 to C-296
  gears, P-82
  generators and turbogenerators, G-19
  guideline limits for, C-300
  harmonic waveforms in, C-261 to C-262
  harmonics in, C-266 to C-267, C-282, C-302, C-305, C-310, C-314
  hydrodynamic power transmission and, P-128, P-132
  ideal vs. real systems in, C-264
  impeller and, C-325
  inertia in, C-314 to C-315
  influence coefficient balancing and, C-325 to C-327
  life cycle assessment (LCA) and, L-18 to L-19
  limitations in, C-269
  Lissajous patterns in, C-270, C-282 to C-286
  loose assemblies and, C-296
  magnification factor (D/F/k) in, C-316
  magnitude in, C-263
  mature units and, contingency corrective measures for, C-296 to C-297
  misalignment and, C-290 to C-291
  modal balancing in, C-327 to C-328
  natural frequency in, C-264 to C-265, C-307, C-316
  nonintrusive wear monitoring in, C-330
  Nyquist plots in, C-270, C-280 to C-282
  orbits in, C-270, C-282 to C-286
  oscillations of vibration in, C-261 to C-262
  overdamping and decay in, C-312
  packaged monitoring systems for, C-286 to C-287
  periodic frequency in, C-263
  periodic motion in, C-302, C-305, C-310
  phase analysis in, C-278 to C-280
  phase angle in, C-265, C-305 to C-306, C-315 to C-316
  principal modes of vibration in, C-302
  pulsating vibration in, C-264
  random vibration in, C-263
  recorders for, C-270 to C-286
  remote applications for, probe selection, C-270
  resonance in, C-264 to C-265
  rigid supports and, C-318 to C-321
  rotational velocity, conversion factors for, C-265
  rotor dynamics in, C-301 to C-325
  rotor systems and, C-318
  rubbing and, C-287
  self-excited vibration in, C-322 to C-323
  severity charts for, C-287
  signal-to-noise (S/N) ratio in, C-271
  "signatures" of, C-296 to C-297
  simple harmonic motion, C-266 to C-267
  sinusoidal waveforms in, C-261 to C-262
  solid or structural damping in, C-307
  spectrum analyzer for, C-266, C-270 to C-272, C-298 to C-299
  spring mass system and, C-305, C-311
  steady-state oscillations and, C-313 to C-314
  steam turbines and, T-80
  stiffness coefficient in, C-305 to C-306
  strip chart recorders in, C-270
  strobe lights for balancing and, C-278 to C-280
  stroboscopes for, C-282 to C-286
  subsynchronrous frequency orders and, C-291 to C-294
  surge in, C-264
  time waveform analysis in, C-270, C-280 to C-282
  total signal in, C-263
  transducers or probes used in, C-266 to C-270
  transient vibration in, C-264
  translational velocity, conversion factors for, C-265
  troubleshooting using, C-287 to C-298
  in turbocompressors, C-333
  turbomachinery and, C-268, C-297 to C-298, C-308
  underdamping and decay in, C-312 to C-313
  velocity in, C-287, C-305, C-311
  velocity probes in, C-268
  vertical deflection in, C-262
  viscous damping in, C-308 to C-311
  waterfall graphs or cascade diagrams in, C-272 to C-273
  waveforms in, C-261 to C-262
Vienna Convention for the Protection of the Ozone Layer, O-12 to O-13
vinyl acetate monomer (VAM), C-41
vinyl acetate, P-12 to P-31, P-40 to P-57, V-15
vinyl chloride, P-12 to P-31, P-40 to P-57, V-15 to V-16
vinylidene chloride, P-12 to P-31, P-40 to P-57, V-15 to V-16
visbreaking, in petroleum industry, R-3
viscosity, lubrication and, L-25 to L-26
viscous damping, C-308 to C-311
viscous fluids
  crystallization of, C-67
  pumps and pumping of, P-230 to P-232
  in rotary pumps, P-265 to P-267, P-270 to P-273
vitamins, C-68
Voith (*See* J.M. Voith GmbH)
Voith hydrodynamic brakes, B-14 to B-16
volatile organic compounds (VOCs), O-5 to O-6, O-10 to O-15
voltage requirements, electric motors, E-15, E-23 to E-24, E-29, E-32
voltage sags, in power supplies, C-350 to C-354
voltage unbalance, in electric motors, operating cost in, E-6 to E-7
volume correction factor (VCF), T-25 to T-27
Vorecon type RW torque converter, P-177 to P-181
Vorecon type RWE torque converter, P-174 to P-177
Vorecon type RWS torque converter, P-177
vortex flow measurement, C-390
Vosper Thornycroft, C-405
V-ring shaft slinger (Buna–N shaft seal), electric motors and, E-17

W.R. Grace, P-4
washing
  centrifugal, C-35 to C-38
  chemical cleaning and, C-38
waste heat recovery (WHR) (*See also* cogeneration), C-78, C-84, V-31
waste management (*See also* pollutants; recycling), E-54, F-20, W-1 to W-12, Sp-30
wastewater flow, P-69 to P-72
water
  in lubricating oil, L-25
  as refrigerant, coolant, R-15 to R-18
  tanks for, T-9 to T-13
water conservation, C-423 to C-426, F-17
water density, for fans, F-3
water eliminator, in air filtration systems, A-82 to A-83
water jet cleaning, M-34
water jet machining, M-35
water pollution, C-78, E-52, P-40 to P-48, P-64 to P-65
  accidents/incidents and, E-46
  biochemical oxygen demand (BOD) in, P-71
  condensers and, C-233
  desalination, D-1 to D-2
  environmental accountability, E-40 to E-49
  eutrophication in, P-64 to P-65
  forest conservation and, F-17
  Great Lakes, toxic chemicals and, P-65 to P-72
  industrial effluent in, P-71 to P-72

packaging and paper production process vs., F-24
phosphorus in, P-64 to P-65
"red tide" algae (*Ptychodiscus brevis*) and, C-78
sewage (*See also* wastewater), P-69 to P-72
waste management and, W-1 to W-12
wastewater flows in, P-69 to P-72
water system, C-109
waterboxes, condensers, C-238, C-248
waterfall graphs, in vibrational analysis (VA), C-272 to C-273
waveforms, in vibrational analysis (VA), C-261 to C-262
waxes, C-68, C-70
wear monitoring, nonintrusive, C-330
weather louvers/weather hoods, in air filtration systems, A-55 to A-61, A-74
weighting factors, in life cycle assessment (LCA), L-10
Weir Westgarth (WW), D-1
welding, C-1, M-31, M-37 to M-38
dabber TIG welding, M-38
laser, M-37
plasma transfer arc, M-38
robotics in, M-38
superalloy, M-38
tank exteriors, T-5
tank interiors, T-4 to T-8
Weldolet couplings, M-15
wet/dry flue gas desulfurization, A-89 to A-91, A-100
Wetpac TCR system, A-100 to A-101
white liquor, P-205 to P-214
Whittaker Controls (fuel systems), F-34 to F-36
wholesale products and industries pollutants, P-30 to P-31
wind loading, stacks and, S-33 to S-38
windings, computational fluid dynamics to analyze heating curves in, C-6 to C-7
wood industries pollutants, P-18
Worldwide Standard Service, ASME, Sp-32
worm gears, P-82 to P-98
adjustment of, P-92
bearing loading in, P-94
bolt stress in, P-94
circular pitch in, P-84
classification of, P-84 to P-85
coefficient of friction curves for, P-86 to P-88
design considerations for, P-92 to P-94
double reduction, P-84 to P-87
efficiency of, P-85 to P-88
gear blank under rim diameter in, P-93
gear face width in, P-93
gear pitch diameter in, P-93
gear ratio in, P-93
helical reduction, P-84 to P-87
horizontal shaft type, P-84
inner diameter of worm in, P-83
installation of, P-97 to P-98
lead angle in, P-84
lead of worm in, P-84
lubrication of, P-96 to P-97
mechanical elements of, P-83 to P-84
mechanical rating of, P-94
number of teeth in, P-92 to P-93
operation of, P-97 to P-98
outer diameter of gear in, P-83
outer diameter of worm in, P-83
performance of, P-89 to P-90, P-94 to P-96
pitch diameter of gear in, P-84
pitch of, P-93
pressure angle in, P-84, P-93
ratio of transmission in, P-84
reducers for
self-locking, P-88
shaft mount type, P-85
shaft stress in, P-94
single reduction, P-84 to P-87
speed ratios in, P-83
starting load for
thermal rating of, P-94 to P-96
throat diameter of gear in, P-83
tooth contact in, P-90 to P-92
tooth form in, P-88 to P-90
vertical output shaft type, P-84
worm face in, P-94
worm pitch diameter in, P-93

X rays (*See also* irradiation, food product), I-5
xylene, C-66, C-72, P-12 to P-31, P-40 to P-57

zeolite catalyst, R-10
zeotrope refrigerant mixtures, R-11
zinc, P-12 to P-31, P-40 to P-57
zinc primer tank exterior coating, T-5
zirconium oxide probes, O-1
zirconium oxide, A-4