

A Simple Yet Effective and Efficient Collaborative Filtering Based Recommendation System

Masum Billal Mahmudul Hasan Munna

April 15, 2021

Abstract

In this paper, we describe a simple yet effective way to recommend items to a user and predict the rating of an item given by a user with high accuracy.

1 Introduction

A common problem (insert relevant papers) with typical filtering based recommendation systems they usually consider all users similar to a user. To mitigate performance problems, (insert relevant papers) show that we can simply consider only a handful of neighbors for a particular user.

2 Algorithm

Let us first describe the assumption problem that we want to solve. Let \mathcal{M} be a set of movies and \mathcal{U} be a set of users. We are given a set of triplets $(u, m, r) \in \mathcal{S}$ such that $u \in \mathcal{U}, m \in \mathcal{M}$ and $1 \leq r \leq 5$ which denotes the rating r of movie m given by user u . We are also given a set of pairs $(u, m) \in \mathcal{T}$ such that $u \in \mathcal{U}, m \in \mathcal{M}$ and we want to predict the rating r given by user u to the movie m . Let r_{um} be the rating of movie m given by user u and C_{uv} be the set of items that both u and v rated. We use the *Pearson Correlation Coefficient* (see Freedman, Pisani, and Purves [1]) as the measure of correlation between user u and v . However, we will use a normalized version of it for practical consideration as follows:

$$S_{uv} = \frac{\sum_{m \in C_{uv}} (r_{um} - \bar{r}_u)(r_{vm} - \bar{r}_v)}{\sqrt{\sum_{m \in C_{uv}} (r_{um} - \bar{r}_u)^2} \sqrt{\sum_{m \in C_{uv}} (r_{vm} - \bar{r}_v)^2}}$$
$$S_{uv} \leftarrow \frac{S_{uv} + 1}{2}$$

This normalization is done using the fact that Pearson correlation coefficient p_{uv} is always in the range $[-1, 1]$. We call two users u and v similar if $S_{uv} \geq s$ for some positive real number s such that $0 \leq s \leq 1$. Typically, we want s in the range $[.5, 1]$. For this paper, we will consider $s \in \{.7, .8, .9\}$. For a movie m , let \mathcal{U}_m be the set of users who rated m and M_u be the set of movies rated by user u . For a set or tuple A , let \bar{A} denote the average of the numbers in A . For a tuple of weights $\mathbf{w} = (w_1, \dots, w_n)$ such that $0 \leq w_i \leq 1$ and $\sum_{i=1}^n w_i = 1$ and a tuple of positive real numbers $\mathbf{a} = (a_1, \dots, a_n)$, the *weighted harmonic mean* of \mathbf{a} is defined as

$$\mathfrak{H}(\mathbf{a}, \mathbf{w}) = \frac{\sum_{i=1}^n w_i}{\sum_{i=1}^n \frac{w_i}{a_i}}$$

Usually, *weighted arithmetic mean* is used to predict the ratings in a recommendation system. But in this paper, we have investigated the results using harmonic mean. Next, we describe the rating prediction algorithm for a pair (u, m) .




Algorithm 1: Algorithm to predict rating




Input: Test data in the format (u, m) , Threshold t , similarity s , T to take first T neighbors for a user u




Output: A single integer in the range $[1, 5]$ denoting the predicted rating




Data: Train data in the format (u, m, r)




```
1  $W = []$ 
2  $X = []$ 
3  $tot \leftarrow 0$ 
4  $R \leftarrow U_m$ 
5  $res = 0$ 
6 for  $v \in R$  do
7   if  $|C_{uv}| < t$  then
8     continue
9   end
10  if  $S_{uv} < s$  then
11    continue
12  end
13  if  $S_{uv} \geq s$  then
14     $W \leftarrow [W, s]$ 
15     $X \leftarrow [X, r_{vm}]$ 
16     $tot \leftarrow tot + 1$ 
17    if  $tot > T$  then
18      break
19    end
20  end
21 end
22 if  $tot > 0$  then
23    $res = \mathfrak{H}(X, W)$ 
24 end
25 else
26   if  $|M_u| > 0$  then
27      $res = \bar{M}_u$ 
28   end
29   else
30      $res = \bar{R}_m$ 
31   end
32 end
33  $res = res + .5$ 
34  $res = \text{floor}(res)$ 
35 return  $res$ 
```











References

- [1] David Freedman, Robert Pisani, and Roger Purves. “Statistics (international student edition)”. In: *Pisani, R. Purves, 4th edn. WW Norton & Company, New York* (2007).