Problem List

Submit

Premium

Description | Editorial | Solutions | Submissions

219. Contains Duplicate II

Solved

Easy | Topics | Companies

Given an integer array `nums` and an integer `k`, return `true` *if there are two* ***distinct indices*** `i` *and* `j` *in the array such that* `nums[i] == nums[j]` *and* `abs(i - j) <= k`.

Example 1:

```
Input: nums = [1,2,3,1], k = 3
Output: true
```

Example 2:

```
Input: nums = [1,0,1,1], k = 1
Output: true
```

Example 3:

```
Input: nums = [1,2,3,1,2,3], k = 2
Output: false
```

Constraints:

- `1 <= nums.length <= 10^5`
- `-10^9 <= nums[i] <= 10^9`
- `0 <= k <= 10^5`



Seen this question in a real interview before? 1/6

7.8K | 472 | 53 Online

Code

C++ | Auto

```cpp
class Solution {
public:
    bool containsNearbyDuplicate(vector<int>& nums, int k) {
        unordered_map<int, int> lastSeen;

        for (int i = 0; i < nums.size(); i++) {
            // Check if number was seen before
            if (lastSeen.find(nums[i]) != lastSeen.end()) {
                if (i - lastSeen[nums[i]] <= k) {
                    return true;
                }
            }

            // Store/update the latest index
            lastSeen[nums[i]] = i;
        }

        return false;
    }
};
```

probal2006

Access all features with our Premium subscription!

My Lists | Notebook | Progress | Points

Try New Features

Orders

My Playgrounds

Settings

Appearance

Sign Out

Saved

Ln 1, Col 1

Testcase | Test Result

Problem List

Submit

Premium

Description | Editorial | Solutions | Submissions

238. Product of Array Except Self

Solved

Medium | Topics | Companies | Hint

Given an integer array `nums`, return *an array* `answer` *such that* `answer[i]` *is equal to the product of all the elements of* `nums` *except* `nums[i]`.

The product of any prefix or suffix of `nums` is **guaranteed** to fit in a **32-bit** integer.

You must write an algorithm that runs in `O(n)` time and without using the division operation.

Example 1:

```
Input: nums = [1,2,3,4]
Output: [24,12,8,6]
```

Example 2:

```
Input: nums = [-1,1,0,-3,3]
Output: [0,0,9,0,0]
```

Constraints:

- `2 <= nums.length <= 10^5`
- `-30 <= nums[i] <= 30`
- The input is generated such that `answer[i]` is **guaranteed** to fit in a **32-bit** integer.

Follow up: Can you solve the problem in `O(1)` extra space complexity? (The output array **does not** count as extra space for space complexity analysis.)

Track every major AI platform in one dashboard
Try for free

26.5K | 652 | 288 Online

Code

C++ | Auto

```cpp
class Solution {
public:
    vector<int> productExceptSelf(vector<int>& nums) {
        int n = nums.size();
        vector<int> answer(n, 1);

        // Prefix product
        int prefix = 1;
        for (int i = 0; i < n; i++) {
            answer[i] = prefix;
            prefix *= nums[i];
        }

        // Suffix product
        int suffix = 1;
        for (int i = n - 1; i >= 0; i--) {
            answer[i] *= suffix;
            suffix *= nums[i];
        }

        return answer;
    }
};
```

probal2006

Access all features with our Premium subscription!

My Lists | Notebook | Progress | Points

Try New Features

Orders

My Playgrounds

Settings

Appearance

Sign Out

Saved

Ln 1, Col 1

Testcase | Test Result