1 Verification

Each v0.1 report in the table can be checked with one command, from an empty directory,

```
uvx agent-evidence-vectors==0.31.1 -read-w3c-report <file>
```

which prints `conforms`, or one line per shape error or rejection row, and exits 0 when the report conforms, 1 when it does not, and 2 when the reader reached no verdict. Rows that are not reports (readers' verdicts, comparisons, census counts) are checked by their rerun command instead. The evidence classes are their authors' words: "reproduction in O8's sense" (Oct/0163), "a reader written from the 0087 text alone" and "proposed" (Oct/0162), "the closest this paper comes to an independent record" (Oct/0150). The class of every cell this appendix runs is "automated rerun from the pins, operated by the appendix's author". Following Oct/0163, units differ by row and no column is summed.

Table 1: The verification column. Commands run in the appendix directory unless they start with `uvx`.

Row	Command	Verdict	Unit	Denominator	Evidence class
R1	`-read-w3c-report report.json`	conforms	checks	272	reproduction in O8's sense (Oct/0170, Oct/0171)
R2	`-read-w3c-report` on each of the three reports	conforms	checks	72, 168, 750	reproduction in O8's sense (Oct/0064)
R3-v01	`-read-w3c-report run-report-v01.json`	conforms	checks	48	producer's converter (Nov/0000)
R4	`-read-w3c-report` on each of the three reports	conforms from v0.18.1; rejected under W3C-R-020 before v0.18	checks	76, 67, 16	the closest to an independent record, through the producer's glue (Oct/0150)
R4-driver	`python rerun.py R4-driver`	equal to the recorded run	cases	as recorded	without the glue (Nov/0003)
R5	`-read-w3c-report finality-threshold-report.level1.json`	conforms	draws against thresholds	150,006	reproduction in O8's sense (Oct/0083, Oct/0084)
R6	`python rerun.py R6`	reproduced; no report file	tests	4 baseline, 6 claim-boundary	reproduction in O8's sense (Oct/0018)
R7	`python rerun.py R7`	reproduced; a native packet, not a v0.1 report	outcomes	21	reproduction in O8's sense (Oct/0085, Oct/0184)
R8	`python rerun.py R8`	reproduced	members	169 judged	a reader written from the 0087 text alone
R8-compare	`python rerun.py R8-compare`	92 of 96; 23, 2, 44 of 69	members	96 and 69	a comparison (Oct/0188, Nov/0002)
R9	`python rerun.py R9`	83/82 at v0.17.4; 41/124 at v0.18.0 and v0.18.1	members	165	a comparison across releases
R10	`python rerun.py R10` (added)	bytes as posted	values	1	posted measurement (Oct/0038, Oct/0046)
R11	`python rerun.py R11`	output digest as posted	members	165	a reader written from the text
R12	`python rerun.py R12`	per-member verdicts as posted	members x paths	33 x 3	proposed
R13	`python rerun.py R13`	every listed file OK	synthetic cases	5	reproduction in O8's sense (Oct/0178); proposed
R14	`python matrix/matrix.py run`	see the matrix below	verdicts	reports x readers	a comparison
R15	none posted	tally only: 3 of 592	artifacts	592	the producer's own count (Oct/0162)

Every report under every reader. The reader matrix reruns R1, R2, R3, R3-v01, R4 and R5 from their pins, keeps the nine files that declare the v0.1 format, and reads each with eleven readers: the Python reference reader at 0.12.0, 0.13.0, 0.17.4, 0.18.1 and 0.31.0; the Go and Rust readers at v0.18.1 and at the current commit; and the two readers written from the text, Rouiada Abbas's of Oct/0039 and Lars Kersten Kroehl's at 6d8ee54b. Those two read corpus members, so each report is wrapped as a member with an adapter that writes `{"id": <input>,`

`"subject": <report>}` and nothing else. Every report conforms under every reader except R4's three, which the Python readers of 0.12.0 to 0.17.4 reject under W3C-R-020. No cell contradicts a verdict posted on the list (R14).

Negative controls for the readers. A reader that accepted everything would pass R14, so each reader also reads single-field copies of the reports, each aimed at one rejection row: 153 copies per reader, plus 7 positive controls whose check identity is non-ASCII and whose root is recomputed over the RFC 8785 form. The Python reader from 0.18.1 on and the Go and Rust readers reject 153 of 153 and accept the 7 positive controls. The Python readers of 0.12.0 to 0.17.4 reject 146; they accept the 7 copies whose root is computed over the ASCII-escaped form and reject the 7 positive controls, the cause Kenne Ives gave for R4 (Oct/0150). A declared moved that disagrees with the recomputed value is aimed at W3C-R-021; a recomputed moved outside compared is W3C-R-016.

The readers written from the text answer cannot-tell where the text leaves the reading open, as the reader of 0039 was built to (Oct/0039), so their results are split by what the copy is aimed at. These are findings for their authors, not faults, and go to them first.

Table 2: The two readers written from the text, on the 153 copies and 7 positive controls, by target: rejected / conforms / cannot tell.

Copies aimed at	Rouiada Abbas's reader (Oct/0039)	Lars Kersten Kroehl's reader (6d8ee54b)
Rows 1 to 14 (56 copies)	55 / 1 / 0	55 / 0 / 1
Unnumbered requirements (81 copies)	3 / 70 / 8	17 / 26 / 38
Not v0.1-shaped (16 copies)	0 / 8 / 8	3 / 8 / 5
Positive controls (7)	0 / 7 / 0	0 / 7 / 0

On rows 1 to 14 the one copy neither reader rejects is the same: R1 with a qualifier on a non-verdict check, aimed at row 6.