1 What the runs turned up

Table 1: Findings from running and rerunning the v0.1 reports and readers. Each is credited to whoever posted it, in the order of the message chain. The narrative of the first two is Guigui Wang's (Oct/0148).

Finding	Where	Who, message chain	What changed	Release
At v0.17.4 the Python reference reader wrote the integer `-0` as 0 and the Go reader as `-0`	R10	Rouiada Abbas raised it, read in source (Oct/0026); Lars Kersten Kroehl measured it (Oct/0038); Kenne Ives proposed the rule (Oct/0040); Guigui Wang's third reading gave RFC 8785's answer, 0 (Oct/0046)	Both readers write 0	v0.18.0 (Oct/0079)
43 members rejected under W3C-R-016 at v0.17.4 on which the reader of Oct/0039 answered cannot-tell	R8, R9	Rouiada Abbas (Oct/0039); Nicolás Rocchia read section 2 as moved recomputed (Oct/0048); Lars Kersten Kroehl showed the reference reader checks the declared moved (Oct/0054); the 43rd member, vd4eb88d206b3abdd, Rouiada Abbas (Oct/0103) and Nicolás Rocchia (Oct/0123)	42 members moved to accept and one family re-cut; the section 10 selection went from 83 reject and 82 accept to 41 and 124	v0.18.0 (Oct/0079)
Readers before v0.18 reject R4's three reports under W3C-R-020: they compute the check-set root over `json.dumps` with non-ASCII escaped	R4, R14	Kenne Ives (Oct/0121, Oct/0150)	v0.18.1 accepts all three	v0.18
R3's run report was not v0.1-shaped: no format string, checks under `records`, no run-level domain	R3	Michael Blake found it with the v0.18.1 reader; Anton Sokolov re-encoded the same run (Nov/0000)	`run-report-v01.json` (sha256 0e608637…), which the v0.18.1 reader reads as conforms (Nov/0001)	none
R6's report stopped at the same shape check: the format named in words, `records`, the domain under run	R6	Michael Blake raised it first; Roel Schuurkes re-encoded the report, no test re-run (Nov/0006)	`run-report-v01.json` (sha256 `699a52b3...`), which the v0.18.1 reader reads as conforms; a result about form, not about the tests (Nov/0006)	none
The 92-of-96 comparison depends on which four judged members are left out: w3c-f-29 (inferred) or w3c-f-22	R8	Michael Blake repeated the comparison, inferred the rule and asked (Oct/0188); Roel Schuurkes spotted the selection error in a recount (Nov/0004); Rouiada Abbas named the written rule of Oct/0022 and the four w3c-f-22 members (Nov/0002); Michael Blake confirmed the run (Nov/0004)	None to the figures: either exclusion gives 92 of 96, and 23, 2 and 44 of 69	none
The harness tally (272 of 272) and the report's roll-up (239 fail, 31 pass, 2 inconclusive) count different things	R1	Prasanna Bableshwar raised it (Oct/0170); Nicolás Rocchia settled it (Oct/0171)	R1 reads the roll-up	none
`run.json` labelled all three R4 runs independent	R4	Nicolás Rocchia found it (Oct/0101); Kenne Ives fixed it (Nov/0003)	A rerun of the native verifier by someone else is labelled a reproduction	AgentAvow a88394f
R9's checker line names the Rust reader before v0.18.0, where it does not yet exist	R9	the appendix's rerun of R9 at v0.17.4, offered to Roel Schuurkes as a correction to the row	Python and Go readers at v0.17.4; all three from v0.18.0	none
The `python -c` command of Nov/0000, which parses with `json.load`, raises `TypeError` on 8 corpus members carrying numbers the digest rule refuses or must compare	corpus	the appendix's author, measured over `vectors-w3c-report` at 4cb988e8	`-read-w3c-report` parses with the reader's own loader and gives each of the 8 its expected verdict: 6 rejected under W3C-R-020, 2 accepted	0.32.1