

Implementing Inference Methods in Anglican

Jan-Willem van de Meent




Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta))
```

Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta))
```




Likelihood Weighting
(implemented by hand)

```
(defn importance-one-flip
  [outcome]
  (let [theta (sample* (beta 1 1))
        lp (observe* (flip theta) outcome)]
    {:log-weight lp
     :result theta
     :predicts []}))
```

Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```




Likelihood Weighting
(implemented by hand)

```
(defn importance-one-flip
  [outcome]
  (let [theta (sample* (beta 1 1))
        lp (observe* (flip theta) outcome)]
    {:log-weight lp
     :result theta
     :predicts []}))
```

Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta))
```




Likelihood Weighting
(implemented by hand)

```
(defn importance-one-flip
  [outcome]
  (let [theta (sample* (beta 1 1))
        lp (observe* (flip theta) outcome)]
    {:log-weight lp
     :result theta
     :predicts []}))
```

Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```



Likelihood Weighting
(implemented by hand)

```
(defn importance-one-flip
  [outcome]
  (let [theta (sample* (beta 1 1))
        lp (observe* (flip theta) outcome)]
    {:log-weight lp
     :result theta
     :predicts []}))
```

Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta))
```

- *Language Runtime*
All deterministic operations
- *Inference Back End*
Implements **sample** and **observe**

Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta))
```

Anglican Backend Implementation

- Repeat until finished:
 - Call **exec** to run program until next **sample** or **observe**
 - Perform algorithm-specific actions and continue

Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta))
```

```
(use '[anglican emit runtime inference state])
(exec :importance one-flip [true] initial-state)
```

Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta))
```

```
(use '[anglican emit runtime inference state])
(exec :importance one-flip [true] initial-state)
```

Algorithm

Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta))
```

```
(use '[anglican emit runtime inference state])
(exec :importance one-flip [true] initial-state)
```

Query

Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta))
```

```
(use '[anglican emit runtime inference state])
(exec :importance one-flip [true] initial-state)
```

Argument values

Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta))
```


```
(use '[anglican emit runtime inference state])
(exec :importance one-flip [true] initial-state)
```

Execution state

Interface for Inference

```
(defquery one-flip [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta))
```

```
(use '[anglican emit runtime inference state])  
(exec :importance one-flip [true] initial-state)
```



Program Execution


```
#anglican.trap.sample{:id S23882,  
  :dist (anglican.runtime/beta 1 1),  
  :cont #function[...],  
  :state {:log-weight 0.0,  
    :predicts [],  
    :result nil,  
    :anglican.state/mem {},  
    :anglican.state/store nil}}
```

Interface for Inference

```
(query [outcome]  
  (let [theta (sample (beta 1 1))]  
    (observe (flip theta) outcome)  
    theta)))
```

Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```




Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe 'O24724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
      $state)))
```


Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```




Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe 'O24724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
      $state)))
```


Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```



Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe 'O24724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
      $state)))
```




Returns

```
{:id 'S24726
 :dist (beta 1 1)
 :cont (fn [theta $state]
         ...)
 :state $state}
```


Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```



Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe '024724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
      $state)))
```




Returns

```
{:id 'S24726
 :dist (beta 1 1)
 :cont (fn [theta $state]
         ...)
 :state $state}
```


Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```



Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe 'O24724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
    $state)))
```




Returns

```
{:id 'S24726
 :dist (beta 1 1)
 :cont (fn [theta $state]
         ...)
 :state $state}
```


Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```



Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe 'O24724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
    $state)))
```




Returns

```
{:id 'S24726
 :dist (beta 1 1)
 :cont (fn [theta $state]
         ...)
 :state $state}
```


Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```



Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe 'O24724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
    $state)))
```




Returns

```
{:id 'S24726
 :dist (beta 1 1)
 :cont (fn [theta $state]
         ...)
 :state $state}
```


Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```




Continuation Passing Style

```
(let [x (sample* dist)]
  (cont x $state))
```



Inference Backend

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe 'O24724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
    $state)))
```




Returns

```
{:id 'S24726
 :dist (beta 1 1)
 :cont (fn [theta $state]
  ...)
 :state $state}
```


Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```




Continuation Passing Style

```
(let [x (sample* dist)]
  (cont x $state))
```



Inference Backend

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe 'O24724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
    $state)))
```




Returns

```
{:id 'S24726
 :dist (beta 1 1)
 :cont (fn [theta $state]
  ...)
 :state $state}
```



Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```



Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe '024724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
        $state))
    $state)))
```




Returns

```
{:id '024724
 :dist (flip theta)
 :value outcome
 :cont (fn [_ $state]
          (->result
            theta $state))
 :state $state}
```


Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```



Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe '024724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
    $state)))
```




Returns

```
{:id '024724
 :dist (flip theta)
 :value outcome
 :cont (fn [_ $state]
          (->result
            theta $state))
 :state $state}
```


Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```



Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe '024724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
    $state)))
```




Returns

```
{:id '024724
 :dist (flip theta)
 :value outcome
 :cont (fn [_ $state]
         (->result
           theta $state))
 :state $state}
```


Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```



Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe '024724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
    $state)))
```




Returns

```
{:id '024724
 :dist (flip theta)
 :value outcome
 :cont (fn [_ $state]
         (->result
           theta $state))
 :state $state}
```

Interface for Inference


```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```




Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe '024724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
        $state))
    $state)))
```

```
(let [lp (observe* dist value)]
  (cont nil (add-log-weight
    $state lp)))
```



Inference Backend




Returns

```
{:id '024724
 :dist (flip theta)
 :value outcome
 :cont (fn [_ $state]
   (->result
     theta $state))
 :state $state}
```

Interface for Inference


```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```




Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe '024724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
    $state)))
```

```
(let [lp (observe* dist value)]
  (cont nil (add-log-weight
    $state lp)))
```



Inference Backend




Returns

```
{:id '024724
 :dist (flip theta)
 :value outcome
 :cont (fn [_ $state]
          (->result
            theta $state))
 :state $state}
```

Interface for Inference


```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```




Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe '024724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
    $state)))
```

```
(let [lp (observe* dist value)]
  (cont nil (add-log-weight
    $state lp)))
```



Inference Backend




Returns

```
{:id '024724
 :dist (flip theta)
 :value outcome
 :cont (fn [_ $state]
          (->result
            theta $state))
 :state $state}
```


Interface for Inference

```
(query [outcome]
  (let [theta (sample (beta 1 1))]
    (observe (flip theta) outcome)
    theta)))
```



Continuation Passing Style

```
(fn [outcome $state]
  (->sample 'S24726
    (beta 1 1)
    (fn [theta $state]
      (->observe 'O24724
        (flip theta)
        outcome
        (fn [_ $state]
          (->result theta $state))
          $state))
    $state)))
```



Returns

```
{:result theta
 :log-weight
   (:log-weight $state)
 :predicts
   (:predicts $state)}
```


Likelihood Weighting

Implementation for **sample**

```
(let [x (sample* dist)]  
  (cont x $state))
```

Implementation for **observe**

```
(let [lp (observe* dist value)]  
  (cont nil (add-log-weight  
              $state lp)))
```

Likelihood Weighting

```
(defmulti checkpoint
  (fn [alg cpt] [alg (type cpt)]))

(defmethod checkpoint
  [:importance anglican.trap.sample] [alg smp]
  (let [cont (:cont smp)
        x (sample* (:dist smp))
        state (:state smp)]
    (fn [] (cont x state))))

(defmethod checkpoint
  [:importance anglican.trap.observe] [alg obs]
  (let [cont (:cont obs)
        lp (observe* (:dist obs) (:value obs))
        state (:state obs)]
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint
  (fn [alg cpt] [alg (type cpt)]))

(defmethod checkpoint
  [:importance anglican.trap.sample] [alg smp]
  (let [cont (:cont smp)
        x (sample* (:dist smp))
        state (:state smp)]
    (fn [] (cont x state))))

(defmethod checkpoint
  [:importance anglican.trap.observe] [alg obs]
  (let [cont (:cont obs)
        lp (observe* (:dist obs) (:value obs))
        state (:state obs)]
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint
  (fn [alg cpt] [alg (type cpt)]))

(defmethod checkpoint
  [:importance anglican.trap.sample] [alg smp]
  (let [cont (:cont smp)
        x (sample* (:dist smp))
        state (:state smp)]
    (fn [] (cont x state))))

(defmethod checkpoint
  [:importance anglican.trap.observe] [alg obs]
  (let [cont (:cont obs)
        lp (observe* (:dist obs) (:value obs))
        state (:state obs)]
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint
  (fn [alg cpt] [alg (type cpt)]))

(defmethod checkpoint
  [:importance anglican.trap.sample] [alg smp]
  (let [cont (:cont smp)
        x (sample* (:dist smp))
        state (:state smp)]
    (fn [] (cont x state))))

(defmethod checkpoint
  [:importance anglican.trap.observe] [alg obs]
  (let [cont (:cont obs)
        lp (observe* (:dist obs) (:value obs))
        state (:state obs)]
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint
  (fn [alg cpt] [alg (type cpt)]))

(defmethod checkpoint
  [:importance anglican.trap.sample] [alg smp]
  (let [cont (:cont smp)
        x (sample* (:dist smp))
        state (:state smp)]
    (fn [] (cont x state))))

(defmethod checkpoint
  [:importance anglican.trap.observe] [alg obs]
  (let [cont (:cont obs)
        lp (observe* (:dist obs) (:value obs))
        state (:state obs)]
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint  
  (fn [alg cpt] [alg (type cpt)]))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.sample] [alg smp]  
  (let [cont (:cont smp)  
        x (sample* (:dist smp))  
        state (:state smp)]  
    (fn [] (cont x state))))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.observe] [alg obs]  
  (let [cont (:cont obs)  
        lp (observe* (:dist obs) (:value obs))  
        state (:state obs)]  
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint  
  (fn [alg cpt] [alg (type cpt)]))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.sample] [alg smp]  
  (let [cont (:cont smp)  
        x (sample* (:dist smp))  
        state (:state smp)]  
    (fn [] (cont x state))))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.observe] [alg obs]  
  (let [cont (:cont obs)  
        lp (observe* (:dist obs) (:value obs))  
        state (:state obs)]  
    (fn [] (cont nil (add-log-weight state lp)))))
```


Likelihood Weighting

```
(defmulti checkpoint  
  (fn [alg cpt] [alg (type cpt)]))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.sample] [alg smp]  
  (let [cont (:cont smp)  
        x (sample* (:dist smp))  
        state (:state smp)]  
    (fn [] (cont x state))))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.observe] [alg obs]  
  (let [cont (:cont obs)  
        lp (observe* (:dist obs) (:value obs))  
        state (:state obs)]  
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint  
  (fn [alg cpt] [alg (type cpt)]))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.sample] [alg smp]  
  (let [cont (:cont smp)  
        x (sample* (:dist smp))  
        state (:state smp)]  
    (fn [] (cont x state))))
```


```
(defmethod checkpoint  
  [:importance anglican.trap.observe] [alg obs]  
  (let [cont (:cont obs)  
        lp (observe* (:dist obs) (:value obs))  
        state (:state obs)]  
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint
  (fn [alg cpt] [alg (type cpt)]))

(defmethod checkpoint
  [:importance anglican.trap.sample] [alg smp]
  (let [cont (:cont smp)
        x (sample* (:dist smp))
        state (:state smp)]
    (fn [] (cont x state))))

(defmethod checkpoint
  [:importance anglican.trap.observe] [alg obs]
  (let [cont (:cont obs)
        lp (observe* (:dist obs) (:value obs))
        state (:state obs)]
    (fn [] (cont nil (add-log-weight state lp)))))
```

 (->sample ...)

Likelihood Weighting

```
(defmulti checkpoint  
  (fn [alg cpt] [alg (type cpt)]))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.sample] [alg smp]  
  (let [cont (:cont smp)  
        x (sample* (:dist smp))  
        state (:state smp)]  
    (fn [] (cont x state))))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.observe] [alg obs]  
  (let [cont (:cont obs)  
        lp (observe* (:dist obs) (:value obs))  
        state (:state obs)]  
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint  
  (fn [alg cpt] [alg (type cpt)]))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.sample] [alg smp]  
  (let [cont (:cont smp)  
        x (sample* (:dist smp))  
        state (:state smp)]  
    (fn [] (cont x state))))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.observe] [alg obs]  
  (let [cont (:cont obs)  
        lp (observe* (:dist obs) (:value obs))  
        state (:state obs)]  
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint  
  (fn [alg cpt] [alg (type cpt)]))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.sample] [alg smp]  
  (let [cont (:cont smp)  
        x (sample* (:dist smp))  
        state (:state smp)]  
    (fn [] (cont x state))))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.observe] [alg obs]  
  (let [cont (:cont obs)  
        lp (observe* (:dist obs) (:value obs))  
        state (:state obs)]  
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint  
  (fn [alg cpt] [alg (type cpt)]))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.sample] [alg smp]  
  (let [cont (:cont smp)  
        x (sample* (:dist smp))  
        state (:state smp)]  
    (fn [] (cont x state))))
```

(->observe ...)

```
(defmethod checkpoint  
  [:importance anglican.trap.observe] [alg obs]  
  (let [cont (:cont obs)  
        lp (observe* (:dist obs) (:value obs))  
        state (:state obs)]  
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint  
  (fn [alg cpt] [alg (type cpt)]))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.sample] [alg smp]  
  (let [cont (:cont smp)  
        x (sample* (:dist smp))  
        state (:state smp)]  
    (fn [] (cont x state))))
```

```
(defmethod checkpoint  
  [:importance anglican.trap.observe] [alg obs]  
  (let [cont (:cont obs)  
        lp (observe* (:dist obs) (:value obs))  
        state (:state obs)]  
    (fn [] (cont nil (add-log-weight state lp)))))
```


Likelihood Weighting

```
(defmulti checkpoint
  (fn [alg cpt] [alg (type cpt)]))

(defmethod checkpoint
  [:importance anglican.trap.sample] [alg smp]
  (let [cont (:cont smp)
        x (sample* (:dist smp))
        state (:state smp)]
    (fn [] (cont x state))))

(defmethod checkpoint
  [:importance anglican.trap.observe] [alg obs]
  (let [cont (:cont obs)
        lp (observe* (:dist obs) (:value obs))
        state (:state obs)]
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint
  (fn [alg cpt] [alg (type cpt)]))

(defmethod checkpoint
  [:importance anglican.trap.sample] [alg smp]
  (let [cont (:cont smp)
        x (sample* (:dist smp))
        state (:state smp)]
    (fn [] (cont x state))))

(defmethod checkpoint
  [:importance anglican.trap.observe] [alg obs]
  (let [cont (:cont obs)
        lp (observe* (:dist obs) (:value obs))
        state (:state obs)]
    (fn [] (cont nil (add-log-weight state lp)))))
```

Likelihood Weighting

```
(defmulti checkpoint
  (fn [alg cpt] [alg (type cpt)]))

(defmethod checkpoint
  [:importance anglican.trap.sample] [alg smp]
  (let [cont (:cont smp)
        x (sample* (:dist smp))
        state (:state smp)]
    (fn [] (cont x state))))

(defmethod checkpoint
  [:importance anglican.trap.observe] [alg obs]
  (let [cont (:cont obs)
        lp (observe* (:dist obs) (:value obs))
        state (:state obs)]
    (fn [] (cont nil (add-log-weight state lp)))))
```

Implementation of `exec`

`exec`: *calls `checkpoint` to handle interrupts*

```
(defn exec
  "executes the program, calling checkpoint handlers
  at the checkpoints and stopping when the handler
  returns a non-callable value"
  [algorithm prog value state]
  (loop [step (trampoline prog value state)]
    (let [next (checkpoint algorithm step)]
      (if (fn? next)
          (recur (trampoline next)
                 next))))))
```


Likelihood Weighting

infer: *calls **exec** to construct sample sequence*

```
(defmulti infer
  (fn [alg prog value & _] alg))

(defmethod infer :importance
  [alg prog value & opts]
  (letfn [(sample-seq []
            (let [result (exec ::algorithm
                                prog
                                value
                                initial-state)]
              (cons (:state result)
                    (sample-seq))))])
  (sample-seq)))
```


Likelihood Weighting

infer: *calls **exec** to construct sample sequence*

```
(defmulti infer
  (fn [alg prog value & _] alg))

(defmethod infer :importance
  [alg prog value & {}]
  (letfn [(sample-seq []
            (let [result (exec ::algorithm
                               prog
                               value
                               initial-state)]
              (lazy-seq
               (cons (:state result)
                     (sample-seq))))))]
    (sample-seq)))
```

doquery: *wrapper around **infer***

Algorithm Implementations

15+ algorithms, ~180 lines of code per algorithm on average

| Algorithm | Type | Lines | Citation | Description |
|------------|-------------|------------|--------------------------------------|---|
| smc | IS | 127 | Wood et al. AISTATS, 2014 | Sequential Monte Carlo |
| importance | IS | 21 | | Likelihood weighting |
| pcascade | IS | 176 | Paige et al., NIPS, 2014 | Particle cascade |
| bbvb | IS | 480 | van de Meent et al., AISTATS, 2016 | Black Box Variational Inference |
| ipmcmc | PMCMC | 198 | Rainforth et al., ICML, 2016 | Interacting Particle Markov Chain Monte Carlo |
| pgibbs | PMCMC | 121 | Wood et al. AISTATS, 2014 | Particle Gibbs (iterated conditional SMC) |
| pimh | PMCMC | 68 | Wood et al. AISTATS, 2014 | Particle independent Metropolis-Hastings |
| pgas | PMCMC | 179 | van de Meent et al., AISTATS, 2015 | Particle Gibbs with ancestor sampling |
| lmh | MCMC | 177 | Wingate et al., AISTATS, 2011 | Lightweight Metropolis-Hastings |
| almh | MCMC | 320 | Tolpin et al., ECML PKDD, 2015 | Adaptive scheduling lightweight Metropolis-Hastings |
| rmh | MCMC | 377 | - | Random-walk Metropolis-Hastings |
| palmh | MCMC | 66 | - | Parallelised adaptive scheduling lightweight MH |
| plmh | MCMC | 62 | - | Parallelised lightweight Metropolis-Hastings |
| bamc | MAP | 318 | Tolpin et al., SoCS, 2015 | Bayesian Ascent Monte Carlo |
| siman | MAP | 193 | Tolpin et al., SoCS, 2015 | MAP estimation via simulated annealing |