

Title: Crear Lanzador GnomeShell Date: 2015-12-6 17:30 Category: Linux Tags: linux, gnome shell Slug: crearlanzadorgnomeshell Summary: Para crear accesos directos en el menu de gnome shell tienes que tener un fichero en. Status: published

Below is a sample of desktop file:

```
[Desktop Entry]
Type=Application
Encoding=UTF-8
Name=Application Name
Comment=Application description
Icon=/path/to/icon.xpm
Exec=/path/to/application/executable
Terminal=false
Categories=Tags;Describing;Application
```

Explanation

- **[Desktop Entry]** the **Desktop Entry** group header identifies the file as a desktop entry
- **Type** the type of the entry, valid values are **Application**, **Link** and **Directory**
- **Encoding** the character encoding of the desktop file
- **Name** the application name visible in menus or launchers
- **Comment** a description of the application used in tooltips
- **Icon** the icon shown for the application in menus or launchers
- **Exec** the command that is used to start the application from a shell.
- **Terminal** whether the application should be run in a terminal, valid values are true or false
- **Categories** semi-colon (;) separated list of menu categories in which the entry should be shown

Command line arguments in the Exec key can be signified with the following variables:

- **%f** a single filename.
- **%F** multiple filenames.
- **%u** a single URL.
- **%U** multiple URLs.
- **%d** a single directory. Used in conjunction with **%f** to locate a file.
- **%D** multiple directories. Used in conjunction with **%F** to locate files.
- **%n** a single filename without a path.
- **%N** multiple filenames without paths.
- **%k** a URI or local filename of the location of the desktop file.
- **%v** the name of the Device entry.

Este serie un ejemplo de un fichero

```
vim /usr/share/applications/thunderbird.desktop
```

```
[Desktop Entry]
Encoding=UTF-8
Name=Thunderbird
Comment=Access the Internet
Exec=/opt/thunderbird/thunderbird
Terminal=false
Icon=/opt/thunderbird/icons/logo.png
Type=Application
Categories=Networkr;
```

##Importante Para hacer que se pueda hacer: “abrir con” de cualquier tipo de fichero/extension hay que añadir **%F**

```
Exec=geany %F
```

Fuentes: 1