Liquids to Value

BACK

Order Code for VESTA® Sampling Valves

Type H_A/I 2/2 Way Seat Valve

Made by GEA Tuchenhagen

VESTA® Sampling Valve, Type H_A/I 2/2 Way Seat Valve

The VESTA® sampling valve is used for aseptic product sampling from pipes or tanks. The VESTA® sampling valve prevents product contamination, thus keeping the process system free from germs.



VESTA® and VARIVENT® - a strong team

In combination with our VARIVENT® and VARINLINE® series the requirement of full CIP/SIP compatibility is easily met.
As installation fitting for the VESTA® sampling valve the VARIVENT® and VARINLINE® access units are available with all their benefits:

- Pocket-free design, without domes and sumps
- Valve body drains completely, even in straight pipes
- Hermetic sealing of the valve interior against the external atmosphere using a patented bellows sealing system
- Reliable CIP/SIP cleaning thanks to optimised flow characteristics
- VARIVENT® / VARINLINE® interface

Design features

- Aseptic bellows sealing system
- Pressure and vacuum resistant
- One-piece PTFE bellows for universal applications
- Defined pretension of the seal
- Self-locking groove nut connection
- Pocket-free design

Benefits

- Valve body drains completely in straight pipes
- Reliable CIP/SIP cleaning thanks to optimised flow characteristics
- Long service life for the PTFE bellows
- Height of the valve body corresponds to that of the connecting piping
- Minimum space requirement, low process volume
- Easy and safe maintenance
- Wide range of body variants
- Sizes up to DN 65 available, larger sizes on request

Operating media

• Operating temperature	-10 °C to max. 135 °C
• Sterilisation temperature	max. 150 °C for 1h
• Operating pressure	0 to 6 bar

Control air

• Control air temperature - NO function	min. 0 °C, max. 70 °C
• Control air pressure - NC function	min. 5 bar, max. 6 bar
• Control air pressure	min. 5 bar, max. 8 bar
• Valve port cross-section	100 %

Materials, product contact parts

• Housing	1.4435 (AISI 316L)
• Housing socket	1.4435 (AISI 316L)
• Delta ferrite content	optional
• Bellows material	TFM1705 (PTFE), FDA-conformity

Materials, non-product contact parts

- Stainless steel actuator 1.4301 (AISI 304)
- Synthetic actuator polyphenylene sulphide (PPS)

VESTA® Sampling Valve, Type H_A/I 2/2 Way Seat Valve

Example for an order code

Code																		
Code	H	L	A	I/N	P	NW	NW	M	Z	000	0	0	–	0	2	52	K	-
Item	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18

H — **1. Valve type VESTA® Sampling Valve**

2. Valve body combination

L T

A — **3. Aseptic bellows seal**

4. Housing specification

I/F = DN 25/32, ISO 33.7
I/N = DN 40/50, ISO 42.4/48,3/60.3, OD 1.5"/2"
I/S = DN 65/80, OD 2.5"/3"



VESTA® Sampling Valve
manual actuator

P — **5. PTFE bellows seal**

Bellows material TFM1705 (PTFE), conforms to: FDA, 21CFR 177.150, USP class VI
For documentation see Item 16

6. Nominal width, process connection VESTA®

DIN Outside diameter acc. to DIN 11850, series II, DIN 11866, series A

	Ø	C	D	D1	E	H1	H2	H3	H4	H5	X1	X
DN 10	13x1.5	60	50	59	40	130	163	29.5	113	146	187	198
DN 15	19x1.5	60	50	59	40	133	163	32.5	116	146	197	208

ISO Outside diameter acc. to DIN EN ISO 1127, series II, DIN 11866, series B

	Ø	C	D	D1	E	H1	H2	H3	H4	H5	X1	X
ISO 13.5	13.5x1.6	60	50	59	40	130	163	29.5	113	146	187	198
ISO 17.2	17.2x1.6	60	50	59	40	133	163	32.5	116	146	197	208

Inch OD Outside diameter acc. to ASME-BPE 1997, DIN 11866, series C

	Ø	C	D	D1	E	H1	H2	H3	H4	H5	X1	X
0.5" OD	12.7x1.65	60	50	59	40	130	163	29.5	113	146	187	198
0.75" OD	19.05x1.65	60	50	59	40	133	163	32.5	116	146	197	208

X (included the clearance required for maintenance)



VESTA® Sampling Valve
pneumatic actuator

Recommended flow direction

VESTA® Sampling Valve, Type H_A/I 2/2 Way Seat Valve

Example for an order code

Code																		
Code	H	L	A	I/N	P	NW	NW	M	Z	000	0	0	–	0	2	52	K	-
Item	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18

7. Nominal width, flange

See brochure VARINLINE® housings and connetion flanges, Accessories Register 9

8. Type of actuator

P = synthetic material (PPS)
M = stainless steel (1.4301/316)
H = manual actuator (PPS)

9. Non-actuated position

Z = air-to-open/spring-to-close // and manual actuator
A = air-to-close/spring-to-open
J = air-to-open/air-to-close

Control air volume [dm3N]

Function	DN 10, 0.5" OD ISO 13.5	DN 15 0.75" OD	ISO 17.2
Z (NC)	0.011	0.013	0.014
A (NO)	0.026	0.026	0.028

10. Type/location of feedback element

TV1 = position indicator / control module type T.VIS® V-1 (for nominal size up to DN 32, 1" OD, ISO 33.7)
TP1 = position controller T.VIS® P-1 (for nominal size up to DN 32, 1" OD, ISO 33.7)
Ex = SEE / ATEX (only stainless steel actuator)
INA = proximity switch holder
ooo = visual indication (standard), (manual/pneumatic actuator)

11. Control module type / solenoid valve

N = without solenoid valve (TV1)
P = one solenoid valve (TV1, SEE)
I = two solenoid valves (TV1, TP1)
o = without solenoid valve (INA, ooo)

VESTA® Sampling Valve, Type H_A/I 2/2 Way Seat Valve

Example for an order code

Code	Code	H	L	A	I/N	P	NW	NW	M	Z	000	0	0	–	0	2	52	K	-
	Item	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18

12. Number of feedback signals

0 = without (000)
1 = one feedback signal (INA)
2 = two feedback signals (TV1, TP1, INA)

13. Type of sensor connection

A = AS Interface (TV1)
B = 24 V DC, 3 Draht, PNP (TV1, INA)
N = 24 V DC, 3 Draht, NPN (TV1, INA)
D = DeviceNet (TV1)
E = EEX / ATEX (SEE, INA)
P = 24 V DC, programmable (TP1)
X = proximity switch acc. to customer's specification

14. Electrical connection (cable gland) / air connection

0 = without
D = 5-pin connector M 12 / Ø 6/4 mm (TV1, TP1, TM1, TV20, TP20)
K = 5-pin connector M 12 / Ø 6.35/4.35 mm, 0.25“ OD - (TV1, TP1, TM1, TV20, TP20)
M = connection for air hose Ø 6/4 mm, proximity switch with terminal box and cable terminals (INA, 000, manual actuator)
Z = connection for air hose 0.25" OD (6.35/4.35 mm), proximity switch with terminal box and cable terminals (INA, 000)

15. Surface finish

1 = inside surfaces $R_a \leq 0.8$ µm, socket welds unpolished, body electrochemically cleaned
2 = inside surfaces $R_a \leq 0.4$ µm, socket welds polished, body electropolished

16. Valve tag

52 = adhesive plate

VESTA® Sampling Valve, Type H_A/I 2/2 Way Seat Valve

Example for an order code

Code																		
Code	Code	H	L	A	I/N	P	NW	NW	M	Z	000	0	0	–	0	2	52	K	-
	Item	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18

17. Certificates

0 = without
Z = certificate acc. to EN10204-3.1
W = factory test certificate EN10204-2.2
F = ferrite content certificate
O = surface test certificate
K = certificate of FDA conformity
U = certificate of USP class VI conformity
X = acceptance acc. to customer's specification

18. Accessories

20 = stroke limiter open
21 = seal adjuster close
22 = 5 pin connector/junction box
29 = quick release handle

The VARIVENT® / VARINLINE® housing



VESTA® Sampling Valve, Type H_A/I 2/2 Way Seat Valve

Key figures

	Ø	Stroke [mm]	Kv-Value [m³/h] I-II	I-III	III-I	Weight acc. to actuator [kg] Typ H_A/I Synthetic	Stainless Steel	Manual
DIN Outside socket diameter, acc. to DIN11866, series A / DIN11850, series II								
DN 10	13x1.5	2.1	2	2.3	2.1	0.86	1.32	0.86
DN 15	19x1.5	4	6.4	6.5	5.9	0.84	1.3	0.84
Inch OD Outside socket diameter, acc. to ASME-BPE, DIN11866, series C								
0.5" OD	12.7x1.65	2.1	2.1	2.2	2.2	0.86	1.32	0.86
0.75" OD	19.05x1.65	4	6.6	6.9	6	0.84	1.3	0.84
ISO Outside socket diameter, acc. to DIN EN ISO1127, DIN11866, series B								
ISO 13.5	13.5x1.6	2.1	2.4	2.8	2.5	0.86	1.32	0.86
ISO 17.2	17.2x1.6	2.9	4.1	5.2	4.5	0.84	1.3	0.84



Kv- flow direction



GEA Mechanical Equipment

GEA Tuchenhagen GmbH

Am Industriepark 2-10, 21514 Büchen, Germany
Phone +49-4155 49-0, Fax +49-4155 49-2423
sales.geatuchenhagen@geagroup.com, www.tuchenhagen.com

657e7-02/2010 Order Code Sampling Valves