

Deltapilot S FMB70

71008645

Hydrostatic, Transmitter S-Class

Item	QTY	Description	Unit Price in EUR	Total Price in EUR
-	1	PCE		
		Deltapilot S FMB70 Order code : FMB70-SBY1F42TRCAA	On Request	On Request
		Digital pressure transmitter, hydrostatic. Sensor: CONTITE, flush mounted. High-Performance. Typ. Linear. +/-0.1%, (max TD 100:1). Modular transmitter. High long term stability. :: Safe humidity protect.,climate proof. :: High reliability through process monitoring.		
		S Approval: FM IS Cl.I,II,III Div.1 Gr.A-G, NI Cl.I Div.2 Gr.A-D, AEx ia, zone 0,1,2,20,21,22 Measurement rucksack - Maximum working pressure(MWP) : 0 - Overpressure single side : 0 - Max. pressure : 0 - Factor : 1		
		B Output; Operating: 4-20mA HART; inside + LCD		
		Y Housing; Cover Sealing; Cable Entry: M12 Turck Plug :		
		1F Sensor Range; Sensor Overload Limit: 400mbar/40kPa/6psi/4mH2O/160inH2O 8bar/800kPa/120psi/80mH2O/3200inH2O		
		4 Calibration; Unit: Sensor range; inH2O/ftH2O Measurement rucksack - Low range value : 0inH2O - Factor : 1		
		2 Membrane Material; Seal: AlloyC276; welded		
		TR Process Connection: Varivent N tube DN40-162 PN40, 316L, 3A, EHEDG		
		C Fill Fluid: Synthetic oil (FDA)		
		A Additional Option 1: Not selected		
		A Additional Option 2: Not selected		
		Production days : On Request		