

BALDOR · RELIANCE II

Product Information Packet

CESSWDM23934T

20HP,1760RPM,3PH,60HZ,256TC,3960M,TEFC,F

Part Detail										
Revision:	W	Status:	PRD/A	Change #:		Propriet	ary:	N	10	
Туре:	AC	Prod. Type:	3960M	Elec. Spec:	39WGX521	CD Diag	ıram:			
Enclosure:	TEFC	Mfg Plant:		Mech. Spec:	39E119	Layout:				
Frame:	256TC	Mounting:	F1	Poles:	04	Created	Created Date:		09-26-2005	
Base:	RG	Rotation:	R	Insulation:	F	Eff. Date:		1	1-12-2013	
Leads:	9#12	Literature:		Elec. Diagram:		Replaced By:				
Nameplate NF	1953D02									
CAT.NO.		CESSWDM23934T	CESSWDM23934T							
SPEC.		39E119X521G1	39E119X521G1							
HP		20	20							
VOLTS		230/460	230/460							
AMP		46.8/23.4	46.8/23.4							
RPM		1760	1760							
FRAME		256TC	256TC P		I Z		PH	3		
SER.F.		1.00	1.00		CODE		DES	В	CLASS	
NEMA-NOM-EFF		93		PF	PF		86			
RATING		40C AMB-CONT	40C AMB-CONT							
СС		010A	010A		USABLE AT 208V					
DE		6309	6309		ODE		6208			
ENCL		TEFC		SN	SN					

Parts List				
Part Number	Description	Quantity		
SA133713	SA 39E119X521G1	1.000 EA		
RA123574	RA 39E119X521G1	1.000 EA		
09FN3001D01SP	EXTERNAL FAN, PLASTIC	1.000 EA		
S/P107-000-005	SUPER-E PROC'S(254/6 FR.) ZK PLANT - POL	1.000 EA		
WD1000B17	T&B CX35TN TERMINAL	1.000 EA		
11XW1032S06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA		
39EP1901A01	S.S. FR ENDPLATE, MACH	1.000 EA		
HW5100A08	W3118-035 WVY WSHR (WB)	1.000 EA		
HW4606A16	PROTECH/SEAL (WDE-1575-2125-BG38)	1.000 EA		
39EP1903A01	S.S. C-FACE PU ENDPLATE, MACH	1.000 EA		
10XN2520S28	1/4-20X 1 3/4 HEX HD SS X	4.000 EA		
HW4606A15	PROTECH/SEAL (WDE-1688-2250-BG37)	1.000 EA		
XY3816S12	3/8-16 HEX FINISHED NUT SS	8.000 EA		
09FH4014A01	304 S.S. FAN COVER & GRILL W/#4 FINISH	1.000 EA		
10XN2520S08	SCREW, 1/4-20 X 1/2 HHCS SS	3.000 EA		
HW1001S25	WASHER, 1/4 SPLT LK, STAINLESS STEEL	3.000 EA		
09CB1505A01	S.S. LIPPED KOBX LID	1.000 EA		
12GS1002	GASKET, CONDUIT BOX LID, NEOP	1.000 EA		
10XN3118S12	5/16-18 X 3/4 HEX HEAD CAP, STAINLESS ST	2.000 EA		
HW1001S31	WASHER, 5/16 SPLT LK, STAINLESS STEEL	2.000 EA		
HW2502G25	#303 SS,SQ KEY 3/8 X 2.880	1.000 EA		
MJ5002A02	NON-CORROSIVE SILICONE, DOW 748, 10.3 OZ	0.031 EA		
LB5040	INSTRUCTION TAG, AC & DC	1.000 EA		
HW4032A01	BLACK DRAIN PLUG FOR WASH DOWN MOTORS	3.000 EA		

BALDOR • RELIANCE Product Information Packet: CESSWDM23934T - 20HP,1760RPM,3PH,60HZ,256TC,3960M,TEFC,F

Parts List (continued)					
Part Number	Description	Quantity			
MJ1000A75	GREASE, POLYREX EM EXXON	0.030 LB			
HW4032A01	BLACK DRAIN PLUG FOR WASH DOWN MOTORS	3.000 EA			
HA3154S06	THRUBOLT STUD 3/8-16 X 16.875 SS	4.000 EA			
HW2500S25	USA#1008-WOODRUFF KEY#B STAINLESS:	1.000 EA			
51XB1214A20	12-14X1.25 HXWSSLD SERTYB	1.000 EA			
LB1125C02	SUPER-E (STOCK CTN LABEL SUPER-E WITH FL	4.000 EA			
39PA1000	PACKAGING GROUP 39 PRINT	1.000 EA			

93.8

18.3

1773.4

93.9

1782.4

13.6

Efficiency:

Line Amperes:

Speed:

91.6

9.87

1790.7

Performance Data at 460V, 60Hz, 20.0HP (Typical performance - Not guaranteed values)								
General Characteristics								
Full Load Torque:		59.8 LB-FT		Start Configuration:		DOL		
No-Load Current:		8.32 Amps		Break-Down Torque:		224.0 LB-FT		
Line-line Res. @ 25°C.:		0.43317 Ohms A Ph / 0.0 Ohms B Ph		Pull-Up Torque:		75.2 LB-FT		
Temp. Rise @ Rated Load:		84 C		Locked-Rotor Torque:		120.0 LB-FT		
Temp. Rise @ S.F. Load:				Starting Current:		165.0 Amps		
Load Characteristics								
% of Rated Load	25	50	75	100	125	150	S.F.	
Power Factor:	52.0	74.0	81.0	87.0	88.0	88.0	0.0	

93.2

23.2

1763.2

92.1

29.0

1751.9

90.5

36.4

1737.2

0.0

0.0

0.0

