

BALDOR · RELIANCE II

Product Information Packet

CESSWDM3613T

5HP,3480RPM,3PH,60HZ,184TC,3636M,TEFC,F1

BALDOR • RELIANCE Product Information Packet: CESSWDM3613T - 5HP,3480RPM,3PH,60HZ,184TC,3636M,TEFC,F1

Part Detail							
Revision:	L	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:	3636M	Elec. Spec:	36WGT873	CD Diagram:	
Enclosure:	TEFC	Mfg Plant:		Mech. Spec:	36L738	Layout:	
Frame:	184TC	Mounting:	F1	Poles:	02	Created Date:	07-12-2006
Base:	RG	Rotation:	R	Insulation:	F	Eff. Date:	03-21-2012
Leads:	9#16	Literature:		Elec. Diagram:		Replaced By:	


Parts List			
Part Number	Description	Quantity	
SA147552	SA 36L738T873G1	1.000 EA	
RA136593	RA 36L738T873G1	1.000 EA	
34FN3002B02	EXTERNAL FAN, PLASTIC, .905/.907 HUB W/	1.000 EA	
36CB1003A01	CONDUIT BOX	1.000 EA	
36GS1024	36 MOLDED GASKET W/LIP, 1.12 LEAD HOLE,	1.000 EA	
10XN2520A08	1/4-20X1/2 HEX HEAD CAP	2.000 EA	
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA	
HW3001B01	003SS CUP WASHER, FOR #8 SCREW	1.000 EA	
36FE1907A01	FR EP ASSY W/EP FROM SOUTHERN TOOL STAIN	1.000 EA	
HW4606A02	JM CLIPPER/SEAL (LWE-0938-1624-AL23)	1.000 EA	
HW5100A05	WVY WSHR F/205 & 304 BRGS	1.000 EA	
36EP1908A03	PUEP, FOR LOCKED 6206 BRG	1.000 EA	
HW4500A33	1/8 NPT STAINLESS,HOLO-KROME #13002,PRES	3.000 EA	
10XN2520S28	1/4-20X 1 3/4 HEX HD SS X	4.000 EA	
HA1049A02	DUBO LOK WASHER SIZE 1/4 (NYLON LOCK SEA	4.000 EA	
HA1049A02	DUBO LOK WASHER SIZE 1/4 (NYLON LOCK SEA	4.000 EA	
36FH4011	WASHDOWN FAN COVER #304 STAINLESS W/NOTC	1.000 EA	
10XN1032S06	HEX HD CAP SCREW, SS	3.000 EA	
36CB4517	36 LIPPED CB LID #304 STAINLESS STEEL	1.000 EA	
37GS3010SP	1/16"WHITE LID GASKET	1.000 EA	
59XN0832S07	8/32 X 7/16 HX WS HD SER X	4.000 EA	
HW4606A03	JM CLIPPER/SEAL (LWE-1156-1875-AL44)	1.000 EA	
HW2502E16	#303 SS,SQ KEY 1/4 X 1.750	1.000 EA	
HA7000A02	KEY RETAINER RING. 1 1/8 DIA. 1 3/8 DIA	1.000 EA	


BALDOR • RELIANCE Product Information Packet: CESSWDM3613T - 5HP,3480RPM,3PH,60HZ,184TC,3636M,TEFC,F1

Parts List (continued)				
Part Number	Description	Quantity		
MJ5001A02	732 CL SEALANT 3 OZ DIXIE BEARING 289100	0.001 EA		
HW3200S01	EYEBOLT 3/8-16 X3/4 S.S. TDR #35988	1.000 EA		
MJ1000A75	GREASE, POLYREX EM EXXON	0.050 LB		
51XB1214A16	12-14X1.00 HXWSSLD SERTYB	1.000 EA		
HA3101S29	THRUBOLT- 1/4-20X13.00 SS	4.000 EA		
LB1125C02	SUPER-E (STOCK CTN LABEL SUPER-E WITH FL	1.000 EA		
36PA1001	PACKAGING GROUP	1.000 EA		
LB1357	ENERGY GUIDE LABEL (BOX LABEL)	1.000 SH		

Performance Da	ta at 460V, 60Hz,	5.0HP (Typical perf	ormance - Not guar	anteed values)				
General Characterist	ics							
Full Load Torque:		7.55 LB-FT	7.55 LB-FT		Start Configuration:		DOL	
No-Load Current:		2.11 Amps	2.11 Amps		Break-Down Torque:		50.4 LB-FT	
Line-line Res. @ 25°C.:		1.87 Ohms A Ph	1.87 Ohms A Ph / 0.0 Ohms B Ph		Pull-Up Torque:		27.1 LB-FT	
Temp. Rise @ Rated Load:		82 C	82 C		Locked-Rotor Torque:		38.1 LB-FT	
Temp. Rise @ S.F. Load:		99 C	99 C		Starting Current:		69.6 Amps	
Load Characteristics								
% of Rated Load	25	50	75	100	125	150	S.F.	
Power Factor:	54.0	76.0	87.0	91.0	93.0	94.0	92.0	
Efficiency:	83.4	88.9	90.4	90.4	89.7	88.0	90.0	
Speed:	3568.0	3541.0	3514.0	3484.0	3451.0	3417.0	3464.0	
Line Amperes:	2.61	3.44	4.49	5.71	7.05	8.48	6.51	

Performance Graph at 460V, 60Hz, 5.0HP Typical performance - Not guaranteed values





MTL: -