Pressure regulator LR-1-D-MAXI


Part number: 159627





General operating conditions

Data sheet



Data sheet

Feature	values
Delivery date:	→ View
Size	Maxi
Series	D
Actuator lock	Rotary knob with lock
Assembly position	Any
Design structure	Piloted piston regulator
Controller function	Output pressure constant
	with secondary exhaust
Pressure gauge	with pressure gauge
Operating pressure	0 16 bar
Pressure regulation range	0,5 12 bar
Max. pressure hysteresis	0,4 bar
Standard nominal flow rate	11.500 l/min
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
	Inert gases
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further
	operation)
Air purity class at output	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
	Inert gases
Medium temperature	-10 60 °C
Ambient temperature	-10 60 °C
Authorisation	Germanischer Lloyd
Product weight	1.200 g
Mounting type	Front panel installation
	Line installation
	with accessories
Pneumatic connection, port 1	G1
Pneumatic connection, port 2	G1
Materials note	Conforms to RoHS
Materials information for sub-base	Zinc die-casting
Materials information for seals	NBR
Materials information, housing	Zinc die-casting