

BALDOR® • RELIANCE

Product Information Packet

IDVSWDM3538

.5HP,1765RPM,3PH,60HZ,56C,3516M,TENV,F1

Part Detail									
Revision:	G	Status:	PRD/A	Change #:		Proprietary:	No		
Type:	AC	Prod. Type:	3516M	Elec. Spec:	35WGM303	CD Diagram:			
Enclosure:	TENV	Mfg Plant:		Mech. Spec:	35S639	Layout:			
Frame:	56C	Mounting:	F1	Poles:	04	Created Date:	11-24-2010		
Base:	N	Rotation:	R	Insulation:	H	Eff. Date:	10-17-2012		
Leads:	9#18	Literature:		Elec. Diagram:		Replaced By:			
Nameplate NP1608L									
CAT NO	IDVSWDM3538								
SPEC.	35S639M303G1								
FRAME	56C	HP	.5	TE					
VOLTS	230/460								
MAG CUR	1.4/7	FLA	1.8/9						
RPM	1765	RPM MAX	6000						
HZ	60	PH	3	CLASS	H				
SER.F.	1.00	DES	B	SL HZ	1.2				
NEMA-NOM-EFF	84	WK2	0.1						
BLWR V		PH		HZ		A			
RATING	40C AMB-CONT								
DE BRG	6205	ODE BRG	6203						
CC		SN							

Parts List		
Part Number	Description	Quantity
SA212871	SA 35S639M303G1	1.000 EA
RA200100	RA 35S639M303G1	1.000 EA
NS2512A01	INSULATOR, CONDUIT BOX X	1.000 EA
35CB5001A03	CONDUIT BOX KIT, FOR SUPER II WASHDOWN	1.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
35EP3100M72MU	SPL FR EP-ENCL-203 BRG-DIE CAST ALUM(BAL	1.000 EA
HW4500A33	1/8 NPT STAINLESS,HOLO-KROME #13002,PRES	3.000 EA
HW5100A03SP	WAVY WASHER (W1543-017)	1.000 EA
35EP3300A75MU	PU E.P., CAST-FACE MTD-56C-205 BRG(BALL	1.000 EA
HW4500A33	1/8 NPT STAINLESS,HOLO-KROME #13002,PRES	3.000 EA
HW4606A02	JM CLIPPER/SEAL (LWE-0938-1624-AL23)	1.000 EA
12XN1032S20	10-32 X 1-1/4 HEX M.S. , STAINLESS STEEL	2.000 EA
HA1049A01	DUBO LOK WASHER SIZE 10 (NYLON LOCK SEAL	2.000 EA
HA1049A01	DUBO LOK WASHER SIZE 10 (NYLON LOCK SEAL	4.000 EA
HW2502D13	SS KEY, 3/16 SQ X 1.375	1.000 EA
HA7000A04	KEY RETAINER 0.625 DIA SHAFTS	1.000 EA
MJ5001A02	732 CL SEALANT 3 OZ DIXIE BEARING 289100	0.001 EA
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 EA
LB1164	LABEL,WARNING AND DRAIN	1.000 EA
HA5027A04	HA4054 T-DRAIN X2 BAGGED	1.000 EA
MJ1000A75	GREASE, POLYREX EM EXXON	0.050 LB
HA3100S12	THRUBOLT 7.625 LENGTH 1.250 TH LENGTH SS	4.000 EA
LB1125C01	STD (STOCK) CARTON LABEL BALDOR WITH FLA	1.000 EA
LC0145B01	CONNECTION LABEL	1.000 EA

Parts List (continued)		
Part Number	Description	Quantity
NP1608L	SS WD INV UL CSA CC REV MTG	1.000 EA
35PA1066	PACKING GROUP COMBINED PRINT	1.000 EA
PK3082	STYROFOAM CRADLE	1.000 EA

Performance Data at 460V, 60Hz, 0.5HP (Typical performance - Not guaranteed values)

General Characteristics							
Full Load Torque:		1.49 LB-FT		Start Configuration:		DOL	
No-Load Current:		0.655 Amps		Break-Down Torque:		8.65 LB-FT	
Line-line Res. @ 25°C.:		25.6 Ohms A Ph / 0.0 Ohms B Ph		Pull-Up Torque:		4.54 LB-FT	
Temp. Rise @ Rated Load:		54 C		Locked-Rotor Torque:		5.09 LB-FT	
Temp. Rise @ S.F. Load:				Starting Current:		7.54 Amps	
Load Characteristics							
% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor:	26.0	41.0	54.0	64.0	70.0	75.0	0.0
Efficiency:	65.5	77.9	81.9	83.6	83.9	83.5	0.0
Speed:	1793.0	1783.0	1774.0	1765.0	1755.0	1745.0	0.0
Line Amperes:	0.674	0.725	0.793	0.885	0.986	1.11	0.0

Performance Graph at 460V, 60Hz, 0.5HP Typical performance - Not guaranteed values

BALDOR ELECTRIC COMPANY

Typical performance - not guaranteed values.


WINDING # 09WGZ580

15 HP 3 PH 60 HZ 3525 RPM 200 V 0930M



TORQUES(LB-FT): PO=90.9 PU=29.3 LR=36.4 LRA=262

TORQUE _____
RPM _____
KW _____


Guest S/30/2013 ACPERf, record # 30931



CD0005

LOW VOLTAGE
(2Y)

LINE

HIGH VOLTAGE
(1Y)

LINE

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS

REV. LTR: E

BY: JLP

REVISED: 01/19/99 10:15

TDR: 0171435

900000

FILE: AAA00005140

MDL: -

MTL: -

BALDOR ELECTRIC Co.

3PH, DV, 9 LEADS

CD0005