
304C Instrumentation Ball Valve




| Dimensions (Inches) | | | | | | | | | | | | | |
|---------------------|------|------|------|----------------|----------------|----------------|------|----------------|----------------|------|------|------|------|
| Size | L | С | D | D ₁ | D ₂ | D ₃ | D 4 | d ₁ | d ₂ | M | Н | h | S |
| 1/4 | 3.33 | 2.60 | 0.43 | 0.47 | 1.65 | 1.42 | 0.99 | 0.24 | 0.24 | 5.32 | 1.46 | 0.35 | 0.36 |
| 3/8 | 3.49 | 2.60 | 0.49 | 0.47 | 1.65 | 1.42 | 0.99 | 0.24 | 0.24 | 5.32 | 1.46 | 0.35 | 0.36 |
| 1/2 | 3.76 | 2.60 | 0.59 | 0.47 | 1.65 | 1.42 | 0.99 | 0.24 | 0.24 | 5.32 | 1.46 | 0.35 | 0.36 |
| 3/4 | 4.13 | 2.80 | 0.79 | 0.47 | 1.65 | 1.42 | 0.99 | 0.24 | 0.24 | 5.32 | 1.65 | 0.37 | 0.36 |
| 1 | 4.69 | 3.03 | 0.99 | 0.55 | 1.97 | 1.65 | 1.18 | 0.28 | 0.24 | 6.30 | 1.91 | 0.43 | 0.43 |



- Temperature Range (RTFE):-20°F - 450°F
- Maximum Pressure (RTFE): 1000 PSI (1/4" - 1")





1 14 Gland Washer 304SS 2 301SS 15 Belleville Washe 16 Stem Nut 304SS 1 17 Nut Stop 304SS 1 18 Stop Pin Bolt 1 304SS 1 304SS 19 Space Washer 1 20 Handle Nut 304SS 1 21 Handle 304SS 22 Handle Cover 1 Vinvl 2 23 Locking Nut 316SS 24 Front Ferrule 316SS 2 25 Back Ferrule 316SS * Go to 304F series brochure for ordering information

Qty.

2

2

2

1

1

4

4

1

1

1

1

1

A351 Gr. CF8M

RTFE (15% C.F.)

A351 Gr. CF8M

PTFF

31655

304SS

304SS

304SS

PEEK

Viton 90

316SS

304SS

PTFE

Part Name

1 End Cap

2 Body Seal

3 Seat

4 Ball

5 Body

6 Spring Washer

9 Thrust Washer

10 Stem O-Ring

12 Stop Pin Nut

13 Stem Packing Set

11 Stem

7 Body Nut

8 Body Bolt

9056 Garvey Avenue Rosemead, CA 91770 Tel: (626) 813-6188 Fax: (626) 813-6186 www.ballvalve.com info@ballvalve.com