



VISCO JET®
- the original

VISCO JET® VJ490

Mobile Column Stirrer





► Special advantages

- Cone principle for gentle stirring
- Low rotational speeds
- No air inclusion
- No foam formation
- No product warming
- Mobile unit

► A quantum leap in mixing technology

The VISCO JET® system is the original one by VISCO JET®, a conical, slow-running, momentum-based range of stirrers. This principle enables the efficient mixing of a range of products even at low circumferential speeds.

► A quantum leap in convenience

The VISCO JET® VJ490 mobile, stand-mounted stirrer would be hard to beat for flexibility. As easy to handle as a normal pallet trolley, the stirrer can be quickly transported to where it is needed. Utterly simple. With its wide fork spacing, this stirrer is also suitable for container applications.

► Technical Data

- Drive: P=1.5 kW
230/400 V, 50 Hz
Variable-speed gear-motor unit with mechanical speed regulation using a handwheel with a speed scale
- Stirrer shaft: d=30 mm, L=1000 mm
With a sleeve coupling connecting it to the drive shaft, shaft end has G 1/2", male thread, in stainless steel, 1.4571 (V4A), installed in a cage with shaft-protection unit
- Stirrer head: VISCO JET® 3-fold, d₂=320 mm, hub thread G 1/2", stainless steel, 1.4571 (V4A)
- Stand: Massive lift column. Linear guiding by ball-bushing set running on ground, hard-chrome-plated shafts. Manual height adjustment with 2 roller chains and a counterweight in the lift column. Easy height adjustment with locking device. With a limit switch for the working position. The functional parts of the lifting mechanism have stainless steel covers to protect them.
- Overhang: 700 mm
Lift stroke: 900 mm
- All other parts are made from mild steel and painted (colour RAL 9010, pure white)

► Options

- Quick-change coupling, complete and mounted on the drive
- VISCO JET® 2-fold stirrer, "Tornado" d₂=650 mm, foldable for use in containers with DN 150 opening
- ☠ Stirrer in EX version
- Complete control system for ☠ and normal versions
- Stirrer stand available in stainless steel
- Electrical height adjustment with hoist motor

VISCO JET Rührsysteme GmbH

Daimlerstraße 1
D-79761 Waldshut-Tiengen

Phone: +49 7741 96567 0
Fax: +49 7741 96567 15

www.viscojet.com
info@viscojet.com