



**Ordering data:** 1LE1023-1BB29-0JB4  
M2F  
1AV3112B

**Motor type:**

Client order no.:

Order no.:

Offer no.:

Remarks:

Item no.:

Consignment no.:

Project:

U	Δ / Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			I <sub>A</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub>	M <sub>K</sub> /M <sub>N</sub>	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I <sub>I</sub> /I <sub>N</sub>	T <sub>I</sub> /T <sub>N</sub>	T <sub>B</sub> /T <sub>N</sub>	
460	Δ	60	3.70	5.0	6.50	1770	20.0	89.5	89.5	88.5	0.80	0.75	0.65	8.2	2.9	4.3	NPE
IM B35 / IM 2001			FS 112 M		34 kg	IP55		IEC/EN 60034		IEC, EN, NEMA MG1-12-12, UL, CSA							

Mechanical data		
Sound pressure level 50 Hz/60Hz (load)	58 db(A)	62 db(A)
Moment of inertia	0.017 kg m²	
Bearing DE   NDE	6206 2ZC3	6206 2ZC3
Bearing lifetime	40000 h	
Lubricants	Esso Unirex N3	
Regreasing device	No	
Grease nipple	- / -	
Type of bearing	Preloaded bearing NDE	
Condensate drainage holes	No	
External earthing terminal	No	
Vibration class	A	
Insulation	155(F) to 130(B)	
Duty type	S1	
Direction of rotation	bidirectional	
Frame material	aluminum	
Data of anti condensation heating	-/-	
Coating	Special paint finish	
Color	RAL7030	
Motor protection	(B) 3 PTC thermistors - for tripping	
Method of cooling	IC411 - self ventilated, surface cooled	

Terminal box	
Terminal box position	top
Material of terminal box	Aluminium
Type of terminal box	TB1 F00
Contact screw thread	M4
Max. cross-sectional area	4.0 mm²
Cable diameter from ... to ...	11.0 mm - 21.0 mm
Cable entry	2xM32x1,5-1xM16x1,5
Cable gland	3 plugs

Special design	
M2F	460 VD for 60 Hz, 50-Hz power

### Environmental conditions

Ambient temperature -20 °C - +40 °C

Altitude above sea level 1000 m

### Explosion protection

Type of protection - / -