


Helical In-line Ordering Guide



SK

Gear Unit

Shaft/Mounting

Reducer Options

Input/Motor

Motor Options

1	2	3	-	4	
----------	----------	----------	---	----------	--

see page 816

see page 816

Gear Unit					
11E	02	03	12/02	63/22	63/23
21E	12	13	22/02	73/22	73/23
31E	22	23	32/12	73/32	83/33N
41E	32	33N	42/12	83/32	93/43
51E	42	43	52/12	83/42	103/53
	52	53		93/42	
	62	63		93/52	
	72	73		103/52	
	82	83			
	92	93			
	102	103			

Shaft/Mounting	
Blank - Footed	XZ - Foot/B14 Flange
F - B5 Flange	XF - Foot/B5 Flange

Reducer Options	
<input type="checkbox"/> VL - Heavy Duty Output Bearings	<input type="checkbox"/> OSG - Oil Sight Glass
<input type="checkbox"/> PR - Flange Pilot Removal	<input type="checkbox"/> OA - Oil Expansion Chamber
<input type="checkbox"/> FKM - Fluoro Rubber Seals	<input type="checkbox"/> OC - Oil Cooler
<input type="checkbox"/> SWV - Special Solid Shaft	<input type="checkbox"/> LL - Long Term Storage
<input type="checkbox"/> SM5 - Stainless Steel Output Shaft	<input type="checkbox"/> MDP - Magnetic Drain Plug
<input type="checkbox"/> Cross Drilled Shaft	<input type="checkbox"/> ADP - Additional Drain Plug

Input Shaft	NEMA Adapter	IEC	Integral Motors		Integral Energy Efficient Motors		Scoop	Motor Platform	Servo Adapter (Keyed)
W	N56C	IEC 63	63S/4 - 0.16hp	160L/4 - 20hp	80LH/4 - 1hp	200LH/4 - 40hp	S56	MKN056	SEP 100
	N140TC	IEC 71	63L/4 - 0.25hp	180MX/4 - 25hp	90SH/4 - 1.5hp	225SH/4 - 50hp	S140T	MKN140	SEP 130
	N180TC	IEC 80	71S/4 - 0.33hp	180LX/4 - 30hp	90LH/4 - 2hp	225MH/4 - 60hp	S180T	MKN180	SEP 165
	N210TC	IEC 90	71L/4 - 0.50hp	200L/4 - 40hp	100LH/4 - 3hp	250MH/4 - 75hp	S210T	MKN210	SEP 215
	N250TC	IEC 100	80S/4 - 0.75hp	225S/4 - 50hp	112MH/4 - 5hp	280SH/4 - 100hp	S250T	MKN250	SEP 300
	N280TC	IEC 112	80L/4 - 1hp	225M/4 - 60hp	132SH/4 - 7.5hp	280MH/4 - 125hp	S280T	MKN280	Servo Adapter (Clamp)
	N320TC	IEC 132	90S/4 - 1.5hp	250M/4 - 75hp	132MH/4 - 10hp	315SH/4 - 150hp	S320T	MKN320	
	N360TC	IEC 160	90L/4 - 2hp	280S/4 - 100hp	160MH/4 - 15hp	315MH/4 - 175hp	S360T	MKN360	SEK 100
	N400TC	IEC 180	100L/4 - 3hp	280M/4 - 125hp	160LH/4 - 20hp	315MAH/4 - 200hp	S400T	MKN400	SEK 130
		IEC 200	100LA/4 - 5hp	315S/4 - 150hp	180MH/4 - 25hp	315LH/4 - 250hp			SEK 165
		IEC 225	112M/4 - 5.4hp	315M/4 - 175hp	180LH/4 - 30hp				SEK 215
		IEC 250	132S/4 - 7.5hp	315MA/4 - 200hp					SEK 300
		IEC 280	132M/4 - 10hp	315L/4 - 250hp					
		IEC 315	160M/4 - 15hp	Other Speeds Available		Other Speeds Available			

Product Specifications

Ratio :1
see pages 112 - 154

— OR —

Output Speed rpm
see pages 112 - 154

Mounting Position

☐ M1

☐ M2


☐ M3

☐ M4

☐ M5

☐ M6

☐ Special



Paint

☐ Standard Stainless Steel Paint

☐ NSD+ (gray)

☐ NSD+W (white)

☐ NSD-X3 (gray)

☐ NSD-X3W (white)

☐ Casting Primed

☐ Special

Lubricant

☐ Standard

☐ Synthetic

☐ Food Grade

☐ Other

B5 Flange Diameter (If required)


Gearmotor Only Details

Voltage & Frequency

- ☐ 230/460V-60Hz (460V only ≥ 40 hp)
- ☐ 575V-60Hz
- ☐ 208V-60Hz
- ☐ 400V-50Hz
- ☐ 115/230V-60Hz, 1 ph.
- ☐ Other

Terminal Box Pos.


- ☐ TB1
- ☐ TB2
- ☐ TB3
- ☐ TB4



Mtg. Pos. M1 Shown

Conduit Entry Loc.

- ☐ CE I *
- ☐ CE II
- ☐ CE III *
- ☐ CE IV



* Brakemotor

Mtg. Pos. M1 Shown