



Sanitary Gauges & Diaphragm Seal Assembly

Open Front 63mm & 100mm

USG Location: Largo, FL

MODEL CSTG All-Welded Sanitary System

Part Number Configuration ¹

Base Model (1 through 4)

CSTG Tr-Clover clamp sanitary gauge & seal assembly

Process Connection Size (5 and 6)

15 1-1/2" (63mm gauges only, see next two pages for 100mm with 1-1/2" Tri-Clover)

20 2"

30 3"

Pressure Gauge Connection & Type (7)

C USG Model 656 63mm (2-1/2") CBM

L USG Model 656 63mm (2-1/2") LM

B USG Model 656 100mm (4") LM (2" and 3" Tri-Clover only)

A USG Model 656 100mm (4") LBM (2" and 3" Tri-Clover only)

Pressure Gauge Range (8 through 10)

315 30" Hg VAC - 0 - 15 PSI

015 0 - 15 PSI

030 0 - 30 PSI

060 0 - 60 PSI

100 0 - 100 PSI

160 0 - 160 PSI

300 0 - 300 PSI

600 0 - 600 PSI

Case Fill Fluid (11 and 12)

-- No option used

GL Glycerin

MI Mineral oil

VO Vegetable oil

System Fill Fluid (13 and 14)

GL Glycerin

MI Mineral oil

NE Neobee 20

VO Vegetable oil

Special Options (15 and more as necessary)

- No option used

C C of C

T Gauge locking device

A Mill certs

/C NIST cert (instrument)

F Service Tag

C	S	T	G	5	6	7	8	9	10	11	12	13	14	15
----------	----------	----------	----------	----------	----------	----------	----------	----------	-----------	-----------	-----------	-----------	-----------	-----------

¹ Typical configurations only. Contact USG Sales for additional materials and options.