

BALDOR · RELIANCE II

Product Information Packet

CEWDM3610T

3HP,3450RPM,3PH,60HZ,182TC,3532M,TEFC,F1

Part Detail										
Revision:	Н	Status:	PRD/A	Change #:		Proprieta	ry:	No		
Type:	AC	Prod. Type:	3532M	Elec. Spec:	35WGQ060	CD Diagi	am:			
Enclosure:	TEFC	Mfg Plant:		Mech. Spec:	35MM213	Layout:				
Frame:	182TC	Mounting:	F1	Poles:	02	Created	Date:	06-14-2010		
Base:	RG	Rotation:	R	Insulation:	F	Eff. Date	•	07-12-2011		
Leads:	9#18	Literature:		Elec. Diagram:		Replaced	By:			
Nameplate NP	1669L									
		CEWDM3610T								
SPEC. 3		35MM213Q060G1	35MM213Q060G1							
HP		3								
VOLTS		208-230/460								
AMP		7.9-7.2/3.6								
RPM		3450								
FRAME 1		182TC	82TC		HZ		PH	3		
SER.F.	SER.F. 1		.15		CODE		DES	B CLASS	F	
NEMA-NOM-EFF		86.5		PF	PF		92			
RATING		40C AMB-CONT								
CC 01		010A	010A		USABLE AT 208V		7.9			
DE 6		6206	6206		ODE		6203			
ENCL		TEFC		SN						
BLANK										

Parts List					
Part Number	Description	Quantity			
SA198572	SA 35MM213Q060G1	1.000 EA			
RA185939	RA 35MM213Q060G1	1.000 EA			
34FN3002B01	EXTERNAL FAN, PLASTIC, .637/.639 HUB W/	1.000 EA			
NS2512A01	INSULATOR, CONDUIT BOX X	1.000 EA			
35CB3010A01MU	CONDUIT BOX, BALL BURNISHED, MACHINED -	1.000 EA			
35GS1039	05 MOLDED GASKET W/LIP, 1.12 LEAD HOLE,	1.000 EA			
51XB1016A07	10-16 X 7/16 HXWSSLD SERTYB	2.000 EA			
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA			
35EP3100M04MW	FREP TEFC,"O" DRILLS,NO GRSR, MACH.WHITE	1.000 EA			
HW4032A01	BLUE DRAIN PLUG FOR WASH DOWN MOTORS	3.000 EA			
HW4600B39SP	SEAL 0.550 X .790 X .180 FACE SEALING	1.000 EA			
HW5100A03SP	WAVY WASHER (W1543-017)	1.000 EA			
35EP3304A02MW	STD PULLEY 182-4TC ENCL 206 BRG (WHITE)	1.000 EA			
HW4032A01	BLUE DRAIN PLUG FOR WASH DOWN MOTORS	3.000 EA			
HW4600B50SP	SEAL 1.156 X 1.874 X 0.250 SINGLE LIP DB	1.000 EA			
10XN2520S24	1/4-20X 1 1/2 HEX HD SS	4.000 EA			
35FH4005A32SP	IEC FH NO GRSR W/3 HOLES - W/AUTOPHERETI	1.000 EA			
11XW1032S06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	3.000 EA			
35CB4522	35 LIPPED CB LID AUTOPHORETIC	1.000 EA			
35GS1030A02	35 GS FOR CB LID - WHITE NEOPRENE	1.000 EA			
59XW0832S07	TAPTITE II,HEX WSHR UNSLTD SER,410 S.S.,	4.000 EA			
HW1003S08	WASHER, #8 EX TH LK, SS	4.000 EA			
HW4600B36SP	V-RING SLINGER 1.188 X 1.690 X 0.240	1.000 EA			
HW2502E16	#303 SS,SQ KEY 1/4 X 1.750	1.000 EA			

Parts List (continued)					
Part Number	Description	Quantity			
HA7000A02	KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA	1.000 EA			
MJ5001A01	46-665 RED SEALER	0.001 QT			
10XF0440S02	04-40 X 1/8 TYPE F HEX HD STAINLESS STIC	2.000 EA			
LB1164	LABEL, WARNING AND DRAIN	1.000 EA			
S/P107-000-001	SUPER E PROC'S-FS & WS PLTS-POLYREX EM G	1.000 EA			
MJ1000A75	GREASE, POLYREX EM EXXON	0.050 LB			
MG1025W01	PAINT- 781-01 WILKOFAST WHITE EPOXY	0.017 GA			
HA3100S09	THRUBOLT 9.25 LENGTH SS	4.000 EA			
LC0005	CONN.DIA.,TY M,9-LD,DUAL VOLT,REVERSING	1.000 EA			
LB1172A01	CUSTOM MTR CARTON LABEL LASER PRINTER	1.000 EA			
LB5040	INSTRUCTION TAG, AC & DC	1.000 EA			
LB1357	ENERGY GUIDE LABEL (BOX LABEL)	1.000 SH			
NP1669L	WD, SUPER-E, UL CSA CC, LASER	1.000 EA			
36PA1000	PACK GROUP W/LB5001	1.000 EA			

General Character	ristics							
Full Load Torque:		4.5 LB-FT	4.5 LB-FT		Start Configuration:		DOL	
No-Load Current:		1.2 Amps	1.2 Amps		Break-Down Torque:		18.0 LB-FT	
Line-line Res. @ 25°C.:		4.72 Ohms A	4.72 Ohms A Ph / 0.0 Ohms B Ph		Pull-Up Torque:		11.0 LB-FT	
Temp. Rise @ Rated Load:		61 C	61 C		Locked-Rotor Torque:		16.0 LB-FT	
Temp. Rise @ S.F. Load:		76 C	76 C		Starting Current:		33.0 Amps	
Load Characteristi	cs							
% of Rated Load	25	50	75	100	125	150	S.F.	
Power Factor:	62.0	81.0	88.0	92.0	93.0	94.0	0.0	
Efficiency:	83.7	87.9	88.2	87.2	85.6	83.5	0.0	
Speed:	3562.0	3531.0	3498.0	3462.0	3421.0	3375.0	0.0	
Line Amperes:	1.5	2.1	2.8	3.6	4.5	5.4	4.1	

Performance Graph at 460V, 60Hz, 3.0HP Typical performance - Not guaranteed values





