



# Service unit combination LFR-1/4-D-MINI-KC

Part number: 185733

**FESTO**

consisting of manual on/off valve and filter regulator, with mounting brackets. With manual condensate drain.



General operating conditions

Data sheet

## Data sheet

Feature	values
Delivery date:	→ View
Size	Mini
Series	D
Actuator lock	Rotary knob with lock
Assembly position	Vertical +/- 5°
Grade of filtration	40 µm
Condensate drain	manual rotary
Design structure	On/off valve Filter regulator with pressure gauge
Max. condensate volume	22 cm <sup>3</sup>
Bowl guard	Metal bowl guard
Pressure gauge	with pressure gauge
Operating pressure	1 ... 16 bar
Pressure regulation range	0,5 ... 12 bar
Max. pressure hysteresis	0,2 bar
Standard nominal flow rate	1.150 l/min
Operating medium	Compressed air in accordance with ISO8573-1:2010 [:-:-]
Corrosion resistance classification CRC	2
Air purity class at output	Compressed air in accordance with ISO8573-1:2010 [7:8:4] Inert gases
Medium temperature	-10 ... 60 °C
Ambient temperature	-10 ... 60 °C
Authorisation	Germanischer Lloyd
Product weight	700 g
Mounting type	Optional Line installation with accessories
Pneumatic connection, port 1	G1/4
Pneumatic connection, port 2	G1/4
Materials information, housing	Zinc die-casting
Materials information for bowl	PC