AtomB Series - Heat Pump

220-240V/1Ph/50(60)Hz

Model			MDV-V12WDHN1(AtB)	MDV-V18WDHN1(AtB)	MDV-V21WDHN1(AtB)
Power supply		V-Ph-Hz	220-240/1/ 50(60)		
Cooling[1]	Capacity	kBtu/h	12	18	21
		kW	3.5	5.3	6.2
	Input	kW	0.94	1.47	1.85
	EER	kW/ KW	3.71	3.6	3.35
Heating[2]	Capacity	kBtu/h	13	20	20.5
		kW	3.8	5.8	6
	Input	kW	0.88	1.35	1.41
	COP	kW/ kW	4.43	4.3	4.25
Connectable indoor unit	Total capacity		45-130% of outdoor unit capacity		
	Quantity		1-3	1-3	1-3
Compressor	Type		DC inverter	DC inverter	DC inverter
	Quantity		1	1	1
Fan	Motor type		DC motor	DC motor	DC motor
	Quantity		1	1	1
	Output	W	65	65	65
Outdoor air flow		m3/h	2500	2700	2700
Sound pressure level[3]		dB(A)	53	54	55
Net dimensions (W x H x D)		mm	845 × 555 × 365	845 × 555 × 365	845 × 555 × 365
Packed dimensions (W x H x D)		mm	915 x 610 x 420	915 x 610 x 420	915 x 610 x 420
Net weight		kg	35	35	35
Gross weight		kg	38.5	38.5	38.5
Refrigerant	Type		R410A	R410A	R410A
	Factory charge	g	1450	1450	1450
	Throttle type		Electronic expansion valve		
Pipe connections	Liquid pipe	mm	6.35	6.35	9.53
	Gas pipe	mm	12.7	12.7	15.9
Ambient Temp. operation range	Cooling	°C	-15-55		
	Heating	°C	-15-27		

Model			MDV-V48WDHN1(AtB)	MDV-V56WDHN1(AtB)	MDV-V60WDHN1(AtB)
Power supply		V-Ph-Hz	220-240/1/ 50(60)		
Cooling[1]	Capacity	kBtu/h	47	52	59
		kW	14	15.5	17.5
	Input	kW	3.97	4.87	6.12
	EER	kW/ KW	3.53	3.18	2.86
Heating[2]	Capacity	kBtu/h	54	61	66
		kW	16	18	19.5
	Input	kW	3.98	4.82	5.57
	COP	kW/ kW	4.02	3.73	3.5
Connectable indoor unit	Total capacity		45-130% of outdoor unit capacity		
	Quantity		1-8	1-9	1-9
Compressor	Type		DC inverter	DC inverter	DC inverter
	Quantity		1	1	1
Fan	Motor type		DC motor	DC motor	DC motor
	Quantity		1	1	1
	Output	W	170	170	170
Outdoor air flow		m3/h	5200	5000	5300
Sound pressure level[3]		dB(A)	56	56	57
Net dimensions (W x H x D)		mm	950 840 440	950 840 440	1040 865 523
Packed dimensions (W x H x D)		mm	1025 950 510	1025 950 510	1120 980 560
Net weight		kg	75	77.5	90.5
Gross weight		kg	82	84.5	91
Refrigerant	Type		R410A	R410A	R410A
	Factory charge	g	3100	3600	4600
	Throttle type		Electronic expansion valve		
Pipe connections	Liquid pipe	mm	9.53	9.53	9.53
	Gas pipe	mm	15.9	19.1	19.1
Ambient Temp. operation range	Cooling	°C	-15-55		
	Heating	°C	-15-27		

Model			MDV-V28WDHN1(AtB)	MDV-V36WDHN1A(AtB)	MDV-V42WDHN1A(AtB)
Power supply		V-Ph-Hz	220-240/1/ 50(60)		
Cooling[1]	Capacity	kBtu/h	27	34	42
		kW	8	10	12.3
	Input	kW	2.1	2.66	3.39
	EER	kW/ KW	3.81	3.76	3.63
Heating[2]	Capacity	kBtu/h	30	41	47
		kW	9	12	14
	Input	kW	2.04	3.15	3.64
	COP	kW/ kW	4.41	3.81	3.85
Connectable indoor unit	Total capacity		45-130% of outdoor unit capacity		
	Quantity		1-4	1-6	1-7
Compressor	Type		DC inverter	DC inverter	DC inverter
	Quantity		1	1	1
Fan	Motor type		DC motor	DC motor	DC motor
	Quantity		1	1	1
	Output	W	80	80	170
Outdoor air flow		m^3/h	3750	5200	5000
Sound pressure level[3]		dB(A)	54	54	56
Net dimensions (W x H x D)		mm	910 712 426	910 712 426	950 840 440
Packed dimensions (W x H x D)		mm	1048 810 485	1048 810 485	1025 950 510
Net weight		kg	49	52.5	62.5
Gross weight		kg	53	56.5	69.5
Refrigerant	Type		R410A	R410A	R410A
	Factory charge	g	1700	2600	3200
	Throttle type		Electronic expansion valve		
Pipe connections	Liquid pipe	mm	9.53	9.53	9.53
	Gas pipe	mm	15.9	15.9	15.9
Ambient Temp. operation range	Cooling	°C	-15-55		
	Heating	°C	-15-27		

Notes:
1.Indoor temperature 27°C DB, 19°C WB; outdoor temperature 35°C DB; equivalent refrigerant piping length 7.5m with zero level difference;connect to Cassette type indoor unit.
2.Indoor temperature 20°C DB; outdoor temperature 7°C DB, 6°C WB; equivalent refrigerant piping length 7.5m with zero level difference;connect to Cassette type indoor unit.
3. Sound pressure level is measured at a position 1m in front of the unit and 1m above the floor in a semi-anechoic chamber.

