AtomC Series – Cooling Only

Sale Model			MDVC-V12WDHN1(AtC)	MDVC-V18WDHN1(AtC)	MDVC-V24WDHN1(AtC)
Power supply			220-240V~ 50/60Hz		
Cooling[1]	Capacity	kW	3.5	5.3	7.1
		kBtu/h	12	18	24
	Input	kW	0.94	1.47	1.78
	EER		3.72	3.61	4.00
Connected indoor unit	Total capacity		50%-130% of ODU capacity		
	Maximum quantity		3	3	4
Compressor	Type		DC inverter		
	Quantity		1		
Fan	Type		DC		
	Quantity		1		
Refrigerant	Type		R410A		
	Factory charge	kg	1.45	1.45	1.33
Pipe connections[3]	Gas pipe	mm	φ12.7	φ12.7	φ15.9
	Liquid pipe	mm	φ6.35	φ6.35	φ6.35
Sound pressure level		dB(A)	51	51	51
Outdoor Unit	Dimension(W x H x D)	mm	845×555×360	845×555×360	910x712x345
	Packing (W x H x D)	mm	915x610x420	915x610x420	1045x800x485
	Net/Gross weight	kg	35/38	35/38	45.5/51.5
Ambient temp. operation range	Cooling (DB)	°C	-15-55		



AtomC Series – Cooling Only

Sale Model			MDVC-V28WDHN1(AtC)	MDVC-V36WDHN1(AtC)	MDVC-V42WDHN1(AtC)
Power supply			220-240V~ 50/60Hz		
Cooling[1]	Capacity	kW	8	10	12
		kBtu/h	27	34	41
	Input	kW	2.00	2.55	3.10
	EER		4.00	3.92	3.87
Connected indoor unit	Total capacity		50%-130% of ODU capacity		
	Maximum quantity		4	6	7
Compressor	Type		DC inverter		
	Quantity		1		
Fan	Type		DC		
	Quantity		1		
Refrigerant	Type		R410A		
	Factory charge	kg	1.33	1.56	1.85
Pipe connections[3]	Gas pipe	mm	15.9	15.9	15.9
	Liquid pipe	mm	9.53	9.53	9.53
Sound pressure level		dB(A)	51	52	54
Outdoor Unit	Dimension(W x H x D)	mm	910 x 712 x 345	910 x 712 x 345	910 x 712 x 345
	Packing (W x H x D)	mm	1045 x 800 x 485	1045 x 800 x 485	1045 x 800 x 485
	Net/Gross weight	kg	45.5/51.5	48.5/52.5	51.0/55.0
Ambient temp. operation range	Cooling (DB)	°C	-15-55		

Sale Model			MDVC-V48WDHN1(AtC)	MDVC-V56WDHN1(AtC)	MDVC-V60WDHN1(AtC)
Power supply			220-240V~ 50/60Hz		
Cooling[1]	Capacity	kW	14	16	17.5
		kBtu/h	47	54	59
	Input	kW	3.88	4.80	5.20
	EER		3.61	3.33	3.37
Connected indoor unit	Total capacity		50%-130% of ODU capacity		
	Maximum quantity		8	9	9
Compressor	Type		DC inverter		
	Quantity		1		
Fan	Type		DC		
	Quantity		1		
Refrigerant	Type		R410A		
	Factory charge	kg	2.35	2.45	2.85
Pipe connections[3]	Gas pipe	mm	15.9	15.9	15.9
	Liquid pipe	mm	9.53	9.53	9.53
Sound pressure level		dB(A)	56	56	57
Outdoor Unit	Dimension(W x H x D)	mm	950 x 840 x 360	950 x 840 x 360	950 x 840 x 360
	Packing (W x H x D)	mm	1025 x 860 x 510	1025 x 860 x 510	1025 x 860 x 510
	Net/Gross weight	kg	63.0/74.5	69.0/80.5	70.0/81.5
Ambient temp. operation range	Cooling (DB)	°C	-15-55		