14-18HP

Table 2-1.1: 14-18HP specifications

HP			14	16	18
Model			MVi-400WV2GN1(A)	MVi-450WV2GN1(A)	MVi-500WV2GN1(A)
Power supply			380-415V, 3N~, 50/60Hz		
Cooling(T1)[1]	Capacity	kW	40	45	50
		kBtu/h	136.5	153.5	170.6
	Power input	kW	11.2	12.0	12.8
	EER		3.57	3.75	3.91
Cooling(T3)[1]	Capacity	kW	34.3	36.7	38.4
		kBtu/h	117.0	125.0	131.0
	Power input	kW	12.2	11.3	10.3
	EER		2.80	3.24	3.73
Heating[2]	Capacity	kW	45	50	56.5
		kBtu/h	153.5	170.6	192.8
	Power input	kW	10.7	11.1	13.8
	COP		4.21	4.50	4.11
Connected indoor unit	Total capacity		50-130% of outdoor unit capacity		
	Maximum quantity		22	26	29
Compressor	Type		DC inverter		
	Quantity		1		
	Oil type		FVC68D		
	Start-up method		Soft start		
Fan	Type		Propeller		
	Motor type		DC		
	Quantity		2		
	Motor output	kW	0.2×2		0.56×2
	Static pressure	Pa	0-35 (default); 35-80 (customized)		
	Airflow rate	m^3/h	12500	12500	20000
	Drive type		Direct		
Refrigerant	Type		R410A		
	Factory charge	kg	7.4	8	8
Pipe connections[3]	Liquid pipe	mm	Φ12.7	Φ15.9	
	Gas pipe	mm	Φ25.4	Φ28.6	
Sound pressure level[4]		dB(A)	59	60	61
Net dimensions (W×H×D)		mm	1130×1760×580		1250×1760×580
Packed dimensions (W×H×D)		mm	1210×1916×597		1330×1916×597
Net weight		kg	185	192	213
Gross weight		kg	199	206	228
Ambient temp. operation range	Cooling	°C	-15 to 55	-15 to 55	-15 to 55
	Heating	°C	-30 to 30	-30 to 30	-30 to 30

Notes:
1. Indoor air temperature 27°C DB, 19°C WB; outdoor air temperature 35/43°C(T1/T3) DB; equivalent refrigerant piping length 5m with zero level difference.
2. Indoor air temperature 20°C DB; outdoor air temperature 7°C DB, 6°C WB; equivalent refrigerant piping length 5m with zero level difference.
3. Diameters given are those of the unit's stop valve.
4. Sound pressure level is measured at a position 1m in front of the unit and 1.3m above the floor in a semi-anechoic chamber.