SPECIFICATIONS

One-Way Cassette

Model			MI2-06Q1DHN18(At)	MI2-07Q1DHN18(At)	MI2-09Q1DHN18(At)
Power supply			1-phase, 220-240V, 50/60Hz		
Cooling[1]	Capacity	kW	1.8	2.2	2.8
		kBtu/h	6.0	7.0	9.0
	input	W	15	19	27
Heating[2]	Capacity	kW	2.0	2.5	3.2
		kBtu/h	6.8	8.0	10.0
	input	W	15	19	27
Air flow rate[3]		m^3/h	300/283/266/250/233/216/200	400/375/350/325/300/275/250	550/516/483/450/416/383/350
Sound power level		dB(A)	28/27/26/26/25/24/24	32/31/30/29/28/27/26	33/32/31/30/29/28/27
Main body	Net dimensions[5] (W×H×D)	mm	700×178×425	700×178×425	900×178×425
	Net dimensions(no water tray)(W×H×D)	mm	700×130×425	700×130×425	900×130×425
	Packed dimensions (W×H×D)	mm	880×225×510	880×225×510	1080×225×510
	Net/Gross weight	kg	9.6/11.9	9.6/11.9	11.2/13.8
Panel	Net dimensions (W×H×D)	mm	980×64×475	980×64×475	1180×64×475
	Packed dimensions (W×H×D)	mm	1070×100×560	1070×100×560	1270×100×560
	Net/Gross weight	kg	2.4/4.4	2.4/4.4	3/5.2
Refrigerant type			R410A/R32		
Pipe connections	Liquid/Gas pipe	mm	Ø6.35/Ø12.7		
	Drain pipe	mm	OD Ø25		

Model			MI2-12Q1DHN18(At)	MI2-15Q1DHN18(At)	MI2-18Q1DHN18(At)	MI2-24Q1DHN18(At)
Power supply			1-phase, 220-240V, 50/60Hz			
Cooling[1]	Capacity	kW	3.6	4.5	5.6	7.1
		kBtu/h	12.0	15.0	19.0	24.0
	input	W	29	30	40	52
Heating[2]	Capacity	kW	4.0	5.0	6.3	8.0
		kBtu/h	13.0	17.0	21.0	27.0
	input	W	29	30	40	52
Air flow rate[3]		m^3/h	550/516/483/450 416/383/350	850/791/733/675 616/558/500	1000/941/883/825 766/708/650	1050/1000/950/900 850/800/750
Sound power level		dB(A)	36/34/33/32/30/29/28	39/37/36/35/33/32/31	44/42/41/40/38/37/36	47/45/44/43/42/41/40
Main body	Net dimensions[5] (W×H×D)	mm	900×178×425	1200×178×425	1200×178×425	1200×178×425
	Net dimensions(no water tray)(W×H×D)	mm	900×130×425	1200×130×425	1200×130×425	1200×130×425
	Packed dimensions (W×H×D)	mm	1080×225×510	1280×225×510	1280×225×510	1280×225×510
	Net/Gross weight	kg	12.2/14.7	14.3/17.7	15.5/18.8	15.5/18.8
Panel	Net dimensions (W×H×D)	mm	1180×64×475	1480×64×475	1480×64×475	1480×64×475
	Packed dimensions (W×H×D)	mm	1270×100×560	1570×100×560	1570×100×560	1570×100×560
	Net/Gross weight	kg	3/5.2	3.8/6.5	3.8/6.5	3.8/6.5
Refrigerant type			R410A/R32			
Pipe connections	Liquid/Gas pipe	mm	Ø6.35/Ø12.7			Ø9.52/Ø15.9
	Drain pipe	mm	OD Ø25			

Notes:
1. Indoor temperature 27°C DB, 19°C WB; outdoor temperature 35°C DB; equivalent refrigerant piping length 7.5m with zero level difference.
2. Indoor temperature 20°C DB; outdoor temperature 7°C DB, 6°C WB; equivalent refrigerant piping length 7.5m with zero level difference.
3. Each model's 7 airflow rate options are listed in order, from highest to lowest.
4. Each model's 7 sound pressure levels are listed in order from highest to lowest and correspond to the model's 7 airflow rate options (see Note 3).Sound pressure level is measured 1.4m below the unit in a anechoic chamber.
5. Unit body dimensions given are the largest external dimensions of the unit, including hanger attachments.
6. These products are under development and the specifications are always subject to change



Four-Way Cassette

