SPECIFICATIONS

Four-way Cassette

Model			MI2-28Q4DHN18(At)	MI2-32Q4DHN18(At)	MI2-36Q4DHN18(At)
Power supply			1-phase, 220-240V, 50/60Hz		
Cooling[1]	Capacity	kW	8.0	9.0	10.0
		kBtu/h	28.0	32.0	36.0
	Power input	W	41.0	43.0	74.0
Heating[2]	Capacity	kW	9.0	10.0	11.2
		kBtu/h	32.0	36.0	40.0
	Power input	W	41.0	43.0	74.0
Air flow rate[3]		m^3/h	1100/1019/939/858/777/697/616	1330/1239/1148/1057/965/874/783	1470/1360/1250/1141/1031/921/811
Sound pressure level[4]		dB(A)	42.5/40/38/36/34/32/30	38/37/35/34/32/31/29	43/41/40/38/36/35/33
Sound power level		dB(A)	57/55/53/51/49/47/45	55/54/52/51/50/48/47	58/57/55/53/51/49/47
Main body	Net dimensions[5] (W×H×D)	mm	840×204×840	840×246×840	840×246×840
	Packed dimensions (W×H×D)	mm	940×250×940	940×295×940	940×295×940
	Net/Gross weight	kg	19.5/22.4	21.5/25.4	21.5/25.4
Panel	Net dimensions6 (W×H×D)	mm	950 53 950	950×53×950	950×53×950
	Packed dimensions (W×H×D)	mm	1030 95 1030	1030×95×1030	1030×95×1030
	Net/Gross weight	kg	5.6/8.0	5.6/8.0	5.6/8.0
Refrigerant type			R410A/R32		
Pipe connections	Liquid/Gas pipe	mm	Ø9.52/Ø15.9	Ø9.52/Ø15.9	Ø9.52/Ø15.9
	Drain pipe	mm	OD Ø25		

Model			MI2-40Q4DHN18(At)	MI2-48Q4DHN18(At)	MI2-56Q4DHN18(At)	MI2-60Q4DHN18(At)
Power supply			1-phase, 220-240V, 50/60Hz			
Cooling[1]	Capacity	kW	11.2	14.0	16.0	18.0
		kBtu/h	40.0	48.0	56.0	60.0
	Power input	W	61.0	118.0	110.0	145.0
Heating[2]	Capacity	kW	12.5	16.0	18.0	20.0
		kBtu/h	43.0	56.0	60.0	68.2
	Power input	W	61.0	118.0	110.0	145.0
Air flow rate[3]		m^3/h	1600/1497/1393/1290/ 1186/1083/979	1900/1787/1673/1560/ 1446/1333/1219	2100/1900/1760/1630/ 1500/1380/1270	2300/2140/1960/1770/ 1600/1430/1270
Sound pressure level[4]		dB(A)	41/40/38/37/36/34/33	47.5/46/44/42/40/38/36.5	48/46/44/43/41/39/37	52/49/47/45/42/39/38
Sound power level		dB(A)	57/56/55/54/53/52/51	64/63/61/60/58/56/54	57/56/54/52/50/47/46	60/58/56/54/52/49/46
Main body	Net dimensions[5] (W×H×D)	mm	840×288×840	840×288×840	950×300×950	950×300×950
	Packed dimensions (W×H×D)	mm	940×335×940	940×335×940	1050×350×1050	1050×350×1050
	Net/Gross weight	kg	24/27.7	24/27.7	32.6/37.2	32.7/37.3
Panel	Net dimensions6 (W×H×D)	mm	950×53×950	950×53×950	1050×55×1050	1050×55×1050
	Packed dimensions (W×H×D)	mm	1030×95×1030	1030×95×1030	1115×100×1115	1115 100 1115
	Net/Gross weight	kg	5.6/8.0	5.6/8.0	7.4/9.7	7.4/9.7
Refrigerant type			R410A/R32			
Pipe connections	Liquid/Gas pipe	mm	Ø9.52/Ø15.9	Ø9.52/Ø15.9	Ø9.52/Ø15.9	Ø9.52/Ø19.1
	Drain pipe	mm	OD Ø25			

Notes:
1. Indoor temperature 27°C DB, 19°C WB; outdoor temperature 35°C DB; equivalent refrigerant piping length 7.5m with zero level difference.
2. Indoor temperature 20°C DB; outdoor temperature 7°C DB, 6°C WB; equivalent refrigerant piping length 7.5m with zero level difference.
3. Air flow rate are from the highest speed to the lowest speed, total 7 rates for each model.
4. Sound pressure level is from highest level to lowest level, total 7 levels for each model. Sound pressure level is measured 1.5m below the unit in an anechoic chamber.
5. The dimension is only the body size, excluding the size of the installation lug, connecting copper pipe, etc. For detailed dimensions, please refer to the installation manual.
6. Exposed height of the panel after being installed on the ceiling.



Compact Four-Way Cassette

