1 Specifications

8-12HP

Table 2-1.1: 8-12HP specifications

HP			8	10	12
Model			MVi-252WV2GN1(B)	MVi-280WV2GN1(B)	MVi-335WV2GN1(B)
Power supply			380-415V, 3N~, 50/60Hz		
Cooling(T1)[1]	Capacity	kW	25.2	28	33.5
		kBtu/h	86.0	95.5	114.3
	Power input	kW	5.8	7.5	8.0
	EER		4.38	3.73	4.21
Cooling(T3)[1]	Capacity	kW	24.3	26.0	31.2
		kBtu/h	82.9	88.7	106.5
	Power input	kW	8.1	10.8	12.7
	EER		2.99	2.41	2.46
Heating[2]	Capacity	kW	27	31.5	37.5
		kBtu/h	92.1	107.5	128.0
	Power input	kW	5.7	6.8	7.9
	COP		4.78	4.67	4.78
Connected indoor unit	Total capacity		50-130% of outdoor unit capacity		
	Maximum quantity		13	16	19
Compressor	Type		DC inverter		
	Quantity		1		
	Oil type		FVC68D		
	Start-up method		Soft start		
Fan	Type		Propeller		
	Motor type		DC		
	Quantity		2		
	Motor output	kW	0.2×2		
	Static pressure	Pa	0-35 (default); 35-80 (customized)		
	Airflow rate	m^3/h	11800	12500	12500
	Drive type		Direct		
Refrigerant	Type		R410A		
	Factory charge	kg	6.1	6.1	6.4
Pipe connections[3]	Liquid pipe	mm	Φ12.7		
	Gas pipe	mm	Φ25.4		
Sound pressure level[4]		dB(A)	56	57	58
Net dimensions (W×H×D)		mm	1130×1760×580		
Packed dimensions (W×H×D)		mm	1210×1916×597		
Net weight		kg	182	182	185
Gross weight		kg	196	196	199
Ambient temp. operation range	Cooling	ºC	-15 to 55	-15 to 55	-15 to 55
	Heating	ºC	-30 to 30	-30 to 30	-30 to 30

Notes:
1. Indoor air temperature 27°C DB, 19°C WB; outdoor air temperature 35/43°C(T1/T3) DB; equivalent refrigerant piping length 5m with zero level difference.
2. Indoor air temperature 20°C DB; outdoor air temperature 7°C DB, 6°C WB; equivalent refrigerant piping length 5m with zero level difference.
3. Diameters given are those of the unit's stop valve.
4. Sound pressure level is measured at a position 1m in front of the unit and 1.3m above the floor in a semi-anechoic chamber.