20-24HP

Table 2-1.2: 20-24HP specifications

HP			20	22	24
Model			MVi-560WV2GN1(A)	MVi-615WV2GN1(A)	MVi-5670WV2GN1(A)
Power supply			380-415V, 3N~, 50/60Hz		
Cooling(T1)[1]	Capacity	kW	56	61.5	67
		kBtu/h	191.1	209.8	228.6
	Power input	kW	16.3	18.1	19.7
	EER		3.44	3.40	3.41
Cooling(T3)[1]	Capacity	kW	46.4	46.8	47.5
		kBtu/h	158.4	159.6	162.1
	Power input	kW	14.9	13.6	13.0
	EER		3.12	3.45	3.65
Heating[2]	Capacity	kW	63	69	75
		kBtu/h	215.0	235.4	255.9
	Power input	kW	15.3	16.9	17.5
	COP		4.12	4.08	4.29
Connected indoor unit	Total capacity		50-130% of outdoor unit capacity		
	Maximum quantity		33	36	39
Compressor	Type		DC inverter		
	Quantity		1		
	Oil type		FVC68D		
	Start-up method		Soft start		
Fan	Type		Propeller		
	Motor type		DC		
	Quantity		2		
	Motor output	kW	0.56×2		
	Static pressure	Pa	0-35 (default); 35-80 (customized)		
	Airflow rate	m^3/h	18500	19000	19000
	Drive type		Direct		
Refrigerant	Type		R410A		
	Factory charge	kg	8.5	8.5	9.7
Pipe connections[3]	Liquid pipe	mm	Φ15.9		
	Gas pipe	mm	Φ28.6		
Sound pressure level[4]		dB(A)	61	62	64
Net dimensions (W×H×D)		mm	1250×1760×580		
Packed dimensions (W×H×D)		mm	1330×1916×597		
Net weight		kg	223	233	238
Gross weight		kg	238	248	253
Ambient temp. operation range	Cooling	°C	-15 to 55	-15 to 55	-15 to 55
	Heating	°C	-30 to 30	-30 to 30	-30 to 30

Notes:
1. Indoor air temperature 27°C DB, 19°C WB; outdoor air temperature 35/43°C(T1/T3) DB; equivalent refrigerant piping length 5m with zero level difference.
2. Indoor air temperature 20°C DB; outdoor air temperature 7°C DB, 6°C WB; equivalent refrigerant piping length 5m with zero level difference.
3. Diameters given are those of the unit's stop valve.
4. Sound pressure level is measured at a position 1m in front of the unit and 1.3m above the floor in a semi-anechoic chamber.