

9 promenade Jeanne Hachette
94200 Ivry sur Seine - FRANCE
Tel : 33 1 46720369 - Fax : 33 1 4959 8731



N°122

FICHE TECHNIQUE DU PAPIER ECO 68 PRODI ECO 68 PRODI PAPER TECHNICAL SHEET

PAPIER ECO 68
ECO 68 PAPER

CATEGORIE CATEGORY	Impression sur rotative offset Heatset web offset papers,	GRADE	Machine finished speciality (MFS)
UTILISATION FINALE END USE	Publicité, Parois légères, Magasines, Envois direct, Encarts journaux, Journaux Advertising material, Board lining, Magazine, Direct mailing, Newspaper inserts, Newspaper	FINISH	Matt Matt
FIBRE FURNISH	Pâte à papier mécanique, Fibre recycler Mechanical pulp, Recycled fibre	METHODE D'IMPRESSION PRINTING METHOD	Impression sur rotative offset Heatset web offset

FORMAT SIZE	Bobines Reels	DIAMETRE (cm) DIAMETER	90.0 – 150.0
LAIZE (cm) WIDTH	22.5 – 380.0	MANDRIN (mm) CORE	76.0 – 150.0
EMBALLAGE WRAPPING	Strong kraft paper, Strong moisture proof polythylene laminated kraft paper	CERTIFICATS ET LABELS CERTIFICATE S AND LABELS	Blue Angel RAL- UZ 72, EMAS, EN 16001, EU Ecolabel, FSC Chain-of-Custody, FSC Recycled, ISO 14001, ISO 50001, ISO 9001, OHSAS 18001, PEFC Chain-of- Custody

VALEURS TECHNIQUES
TECHNICAL TARGETS VALUES

GRAMMAGE DISPO (ISO 536) BASIS WEIGHT (g/m2)	45.0	48.8	52.0	55.0
MICRON (ISO 534) BULK (cm3/g)	1.15	1.10	1.10	1.10
BRILLANCE D65 (ISO 2470 - 2) BRIGHTNESS D65 (%)	68.0	68.0	68.0	68.0
OPACITE (ISO 2471) OPACITY (%)	91.0	93.0	94.0	95.0

DOUCEUR PPS 10 (ISO 8791-4) SMOOTHNESS PPS 10 (μm)	2.5	2.5	2.5	2.5
L-VALUE D65 (D65/10°) (ISO 5631 - 2)	86.0	86.0	86.0	86.0
a-VALUE D65 (D65/10°) (ISO 5631 - 2)	(-)0.5	(-)0.5	(-)0.5	(-)0.5
b-VALUE D65 (D65/10°) (ISO 5631 - 2)	(-)0.8	(-)0.8	(-)0.8	(-)0.8