

9 promenade Jeanne Hachette
94200 Ivry sur Seine - FRANCE
Tel : 33 1 46720369 - Fax : 33 1 4959 8731



FICHE TECHNIQUE DU PAPIER N°122

JOURNAL BLANC

WHITE NEWSPRINT PAPER

TECHNICAL SHEET

PAPIER JOURNAL BLANC
WHITE NEWSPRINT PAPER

CATEGORIE CATEGORY	Offset en continu sans sécheur <i>Coldset web offset</i> papers	GRADE	Journal <i>Newsprint</i>
UTILISATION FINALE END USE	Publicité, Encarts de presses, Journaux <i>Advertising material,</i> <i>Nespaper inserts,</i> <i>Newspapers</i>	FINISH	Matt
FIBRE FURNISH	Pâte mecanique, Recyclage <i>Mechanical pulp,</i> <i>Recycled fibre</i>	METHODE D'IMPRES SION PRINTING METHOD	Offset en continu sans sécheur, Flexo, Typographie <i>Coldset web offset, Flexo,</i> <i>Letterpress</i>
FORMAT SIZE	Bobines <i>Reels</i>	DIAMETRE (cm) DIAMETER	80.0 – 150.0
LAIZE (cm) WIDTH	25.0 – 432.0	MANDRIN (mm) CORE	76.0 / 150.0
EMBALLAGE WRAPPING	Strong kraft paper, Strong moisture proof polythylene laminated kraft paper	CERTIFICA TS ET LABELS CERTIFICA TES AND LABELS	Blue Angel RAL-UZ 72, EMAS, EN 16001, EU Ecolabel, FSC Chain-of- Custody, FSC Recycled, ISO 14001, ISO 50001, ISO 9001, OHSAS 18001, PEFC Chain-of-Custody

VALEURS TECHNIQUES
TECHNICAL TARGETS
VALUES

GRAMMAGE DISPO (ISO 536) BASIS WEIGHT (g/m²)	40.0	42.0	42.5	45.0	52.0	48.8
MICRON (ISO 534) BULK (cm³/g)	1.40 - 1.55	1.30	1.40 - 1.55	1.40 - 1.55	1.40 - 1.50	1.30 - 1.60
BLANCHEUR D65 (ISO 2470- 2) BRIGHTNESS D65 (%)	58.0	58.0	58.0	58.0	58.0	58.0
L-VALUE D65 (D65/10°) (ISO 5631-2)	83.4	82.0	83.4	83.4	83.4	83.4
a-VALUE D65 (D65/10°) (ISO 5631-2)	(-)0.3	(-)0.1	(-)0.3	(-)0.3	(-)0.3	(-)0.3
b-VALUE D65 (D65/10°) (ISO 5631-2)	4.2 - 4.5	2.4	4.2 - 4.5	4.2 - 4.5	4.2 - 4.5	4.2 - 4.5
OPACITE (ISO 2471) OPACITY (%)	91.0 - 93.5	94.0	92.0 - 94.0	93.0 - 95.0	94.5 – 96.0	94.5 - 96.0
RUGOSITE BENDTSEN (ISO 8791-2) ROUGHNESS BENDTSEN (ml/min)	100.0 - 205.0	205.0	100.0 - 160.0	100.0 - 205.0	100.0 – 205.0	100.0 - 205.0