

DATABASE SCHEMA REFERENCE

HIUSA Data Dictionary

Current Laravel / MySQL Schema

45 tables | 510 fields

Schema snapshot: September 16, 2026

Derived from a clean execution of all repository migrations.

About this dictionary

This document replaces the earlier 25-table reference with the complete current schema. It includes organization isolation, SAO governance, approval routing, financial reporting, AI auditability, academic structure, biometric attendance, and Laravel framework tables.

Constraint notation

Notation	Meaning
PK	Primary key
FK	Foreign key and referenced table/field
NOT NULL / NULL	Whether a value is required
UNIQUE	Uniqueness constraint or composite unique key
INDEX	Lookup or composite performance index
DEFAULT	Database default value

Table inventory

1. organizations	24. financial_report_deadlines
2. academic_programs	25. collections
3. academic_sections	26. remittances
4. users	27. cash_advances
5. sbo_positions	28. cash_advance_repayments
6. fingerprints	29. invoices
7. fingerprint_verifications	30. invoice_payments
8. password_reset_tokens	31. merchandise
9. sessions	32. orders
10. personal_access_tokens	33. approval_requests
11. announcements	34. audit_logs
12. announcement_recipients	35. elections
13. announcement_views	36. election_positions
14. notifications	37. partylists
15. events	38. candidates
16. tasks	39. votes
17. task_progress_updates	40. attendance
18. ai_outputs	41. cache

19. task_recommendations	42. cache_locks
20. budgets	43. jobs
21. transactions	44. job_batches
22. financial_forecasts	45. failed_jobs
23. financial_reports	

Table 1

DATA DICTIONARY OF ORGANIZATIONS TABLE

Field Name	Constraints	Data Type	Description
id	PK, NOT NULL, AUTO_INCREMENT	bigint unsigned	Unique organization identifier.
name	NOT NULL, UNIQUE	varchar(255)	Full student organization name.
slug	NOT NULL, UNIQUE	varchar(255)	URL-safe organization identifier.
college	NULL	varchar(255)	College or department connected to the organization.
acronym	NULL	varchar(50)	Short organization acronym.
is_active	NOT NULL, DEFAULT 1	tinyint(1)	Determines whether the organization can be selected before login.
created_at	NULL	timestamp	Time the record was created.
updated_at	NULL	timestamp	Time the record was last updated.
gcash_qr_url	NULL	varchar(500)	Stored URL for the related gcash qr resource.
organization_type	NOT NULL, DEFAULT STUDENT_ORGANIZATION	varchar(50)	Classifies the workspace as a student organization or system-administration office.
description	NULL	text	Detailed description of the record.
logo_url	NULL	varchar(255)	Stored URL for the related logo resource.

Stores organization workspaces, including the Student Affairs Office and student organizations. It is the principal ownership boundary used to isolate records and users.

The final migrated definition contains 12 fields, 0 foreign-key relationships, and 2 explicit unique constraints. Constraints shown above reflect the current forward migration state.

Table 2

DATA DICTIONARY OF ACADEMIC_PROGRAMS TABLE

Field Name	Constraints	Data Type	Description
id	PK, NOT NULL, AUTO_INCREMENT	bigint unsigned	Unique identifier for the academic program record.
organization_id	FK -> organizations(id), NOT NULL, UNIQUE (organization_id, name)	bigint unsigned	References organizations(id) and links this record to the related organization.
name	NOT NULL	varchar(120)	Display name of the academic program.
created_at	NULL	timestamp	Date and time when the record was created.
updated_at	NULL	timestamp	Date and time when the record was last updated.

Defines the academic programs available within an organization for student profile classification.

The final migrated definition contains 5 fields, 1 foreign-key relationship, and 1 explicit unique constraint. Constraints shown above reflect the current forward migration state.

Table 3

DATA DICTIONARY OF ACADEMIC_SECTIONS TABLE

Field Name	Constraints	Data Type	Description
id	PK, NOT NULL, AUTO_INCREMENT	bigint unsigned	Unique identifier for the academic section record.
academic_program_id	FK -> academic_programs(id), NOT NULL, UNIQUE (academic_program_id, year_level, name)	bigint unsigned	References academic_programs(id) and links this record to the related academic program.
year_level	NOT NULL	tinyint unsigned	Numeric value representing year level.
name	NOT NULL	varchar(60)	Display name of the academic section.
created_at	NULL	timestamp	Date and time when the record was created.
updated_at	NULL	timestamp	Date and time when the record was last updated.

Defines year-level and section combinations under an academic program.

The final migrated definition contains 6 fields, 1 foreign-key relationship, and 1 explicit unique constraint. Constraints shown above reflect the current forward migration state.

Table 4

DATA DICTIONARY OF USERS TABLE

Field Name	Constraints	Data Type	Description
school_id	PK, NOT NULL	int unsigned	Primary school identifier for the user account; referenced instead of a users.id column.
first_name	NOT NULL	varchar(60)	User first name.
last_name	NOT NULL	varchar(60)	User last name.
is_member	NOT NULL, DEFAULT 0	tinyint(1)	Indicates if the user is a registered organization member.
email	NOT NULL	varchar(100)	User email address.
password_hash	NOT NULL	varchar(255)	Hashed account password.
biometric_template	NULL	longblob	Legacy DigitalPersona-compatible binary biometric template stored on the user record.
created_at	NULL	timestamp	Time the record was created.
updated_at	NULL	timestamp	Time the record was last updated.
organization_id	FK -> organizations(id), NOT NULL, UNIQUE (organization_id, email), INDEX	bigint unsigned	References organizations(id). Added by organization migration.
position_title	NULL	varchar(100)	Stores the position title value for this user record.
role	NOT NULL, DEFAULT STUDENT	dropColumn	Role used for authorization and dashboard routing.
notification_preferences	NULL	json	Stores the notification preferences value for this user record.
account_status	NOT NULL, DEFAULT active, INDEX	index	Stores the account status value for this user record.
department	NULL	varchar(120)	Stores the department value for this user record.
program	NULL	varchar(120)	Stores the program value for this user record.
year_level	NULL	varchar(30)	Numeric value representing year level.
major	NULL	varchar(120)	Stores the major value for this user record.
section	NULL	varchar(60)	Stores the section value for this user record.
contact_number	NULL	varchar(30)	Stored contact number value for the record.

Stores authenticated accounts for the SAO/Super Admin, organization administrators, SBO officers, department heads, and students. The school_id field is the primary key used by all user relationships.

The final migrated definition contains 20 fields, 1 foreign-key relationship, and 1 explicit unique constraint. Constraints shown above reflect the current forward migration state.

Table 5

DATA DICTIONARY OF SBO_POSITIONS TABLE

Field Name	Constraints	Data Type	Description
id	PK, NOT NULL, AUTO_INCREMENT	bigint unsigned	Unique identifier for the sbo position record.
organization_id	FK -> organizations(id), NOT NULL, UNIQUE (organization_id, role, title), INDEX	index	References organizations(id) and links this record to the related organization.
title	NOT NULL	varchar(100)	Short title displayed for the record.
description	NULL	text	Detailed description of the record.
is_active	NOT NULL, DEFAULT 1	tinyint(1)	Boolean flag indicating whether active applies.
created_at	NULL	timestamp	Date and time when the record was created.
updated_at	NULL	timestamp	Date and time when the record was last updated.
role	NOT NULL, DEFAULT SBO_OFFICER	varchar(30)	System role used for authorization or workflow routing.

Defines organization positions and the system role associated with each position title.

The final migrated definition contains 8 fields, 1 foreign-key relationship, and 1 explicit unique constraint. Constraints shown above reflect the current forward migration state.

Table 6

DATA DICTIONARY OF FINGERPRINTS TABLE

Field Name	Constraints	Data Type	Description
id	PK, NOT NULL, AUTO_INCREMENT	bigint unsigned	Unique identifier for the fingerprint record.
organization_id	FK -> organizations(id), NOT NULL, INDEX (organization_id, template_format), UNIQUE (organization_id, user_id, finger_index)	bigint unsigned	References organizations(id) and links this record to the related organization.
user_id	FK -> users(school_id), NOT NULL	foreign	References users(school_id) and links this record to the related user.
template	NOT NULL	longtext	Encoded biometric template used for fingerprint matching.
template_format	NOT NULL	varchar(100)	Format and version identifier used to interpret the biometric template.
finger_index	NOT NULL, DEFAULT 0	tinyint unsigned	Numeric identifier for the enrolled finger.
enrolled_by	FK -> users(school_id), NULL	foreign	References users(school_id) and links this record to the related user.
enrolled_at	NOT NULL	timestamp	Date and time when enrolled occurred.
created_at	NULL	timestamp	Date and time when the record was created.
updated_at	NULL	timestamp	Date and time when the record was last updated.

Stores organization-scoped biometric templates enrolled for attendance verification. Templates are retained as long text with an explicit template format.

The final migrated definition contains 10 fields, 3 foreign-key relationships, and 1 explicit unique constraint. Constraints shown above reflect the current forward migration state.

Table 7

DATA DICTIONARY OF FINGERPRINT_VERIFICATIONS TABLE

Field Name	Constraints	Data Type	Description
id	PK, NOT NULL, AUTO_INCREMENT	bigint unsigned	Unique identifier for the fingerprint verification record.
organization_id	FK -> organizations(id), NOT NULL	bigint unsigned	References organizations(id) and links this record to the related organization.
user_id	FK -> users(school_id), NULL	foreign	References users(school_id) and links this record to the related user.
performed_by	FK -> users(school_id), NULL	foreign	References users(school_id) and links this record to the related user.
event_id	FK -> events(id), NULL	bigint unsigned	References events(id) and links this record to the related event.
result	NOT NULL, INDEX	varchar(32)	Stores the result value for this fingerprint verification record.
score	NULL	decimal(10,4)	Similarity score produced by biometric verification.
threshold	NULL	decimal(10,4)	Minimum verification score required for a successful match.
verified_at	NOT NULL, INDEX	timestamp	Date and time when verified occurred.
created_at	NULL	timestamp	Date and time when the record was created.
updated_at	NULL	timestamp	Date and time when the record was last updated.

Records biometric verification attempts, scores, thresholds, operators, and optional event context for accountability.

The final migrated definition contains 11 fields, 4 foreign-key relationships, and 0 explicit unique constraints. Constraints shown above reflect the current forward migration state.