BINDING DATA SUBMISSION

Public Address and General Alarm System

Project	OSV-45 Multipurpose Offshore Support Vessel (Hull 101)
Document No.	ASS-BD-0457
Revision	0
Date	28.05.2026
Prepared by	Acme Sound Systems
Purchase order	EX-101-PO-0457
Status	Submitted for approval

1. Equipment List and Technical Particulars

S.No	Name of the equipment	Dimensions (W x H x D mm)	Maintenance envelope	Weight	Power rating	Heat dissipation	Mounting
1	Amplifier rack, main (1 kW)	600 x 1800 x 600	800 mm front	185 kg	1.6 kW	450 W	Deck
2	Amplifier rack, standby (1 kW)	600 x 1800 x 600	800 mm front	185 kg	1.6 kW	450 W	Deck
3	Battery and charger unit, 24 V DC	500 x 900 x 400	600 mm front	Not stated	0.6 kW	120 W	Bulkhead
4	Wheelhouse paging console	300 x 120 x 250	-	4 kg	25 W	20 W	Table top
5	Engine control room paging station	200 x 300 x 100	-	3 kg	15 W	10 W	Bulkhead
6	Horn loudspeaker, 25 W (machinery spaces)	280 x 300 x 350	-	3.5 kg	25 W	-	Bulkhead
7	Cabin loudspeaker, 6 W	180 x 180 x 90	-	1.2 kg	6 W	-	Bulkhead
8	Weather-deck loudspeaker, 25 W	280 x 300 x 350	-	4 kg	25 W	-	Bulkhead

2. System Description

The system uses dual 1 kW amplifier racks with manual changeover by a selector switch on the rack. On loss of 230 V AC the system transfers to 24 V DC batteries, which support a 20-minute alarm broadcast.

Weather-deck loudspeakers are IP56. Cable glands supplied for weather-deck loudspeakers are IP54 brass glands from our standard range.

3. Drawings and Calculations

Document	Reference	Status
General arrangement of amplifier racks	ASS-DWG-101	Enclosed
Single line diagram	ASS-DWG-102	Enclosed
Interconnection diagram	-	To follow after zone finalisation
Cable schedule	ASS-DWG-104	Enclosed; gland details not included
Loudspeaker layout	ASS-DWG-105	Enclosed
Sound pressure level calculation	-	To follow

4. Certificates and Test Reports

Document	Reference	Remarks
Marine type-approval certificate	TA-2019-4471	Valid until 30.06.2024; renewal applied for
IEC 60945 environmental test report	TR-8821	Temperature and humidity only
MTBF calculation	ASS-RAM-07	Amplifier rack only

5. Spares and Support

A recommended spares list for one (1) year of operation is enclosed (ASS-SP-09). A draft operation and maintenance manual is enclosed (ASS-OM-11).

Warranty is twelve (12) months from commissioning. The factory acceptance test will follow the vendor's standard test sheet; a procedure can be furnished on request.