DESIGN STANDARD DS-100

Shipboard Electrical Cable Installation

Project	OSV-45 Multipurpose Offshore Support Vessel (Hull 101)
Document No.	EX-DS-100
Revision	2
Date	15.09.2026
Prepared by	Example Shipbuilders Ltd.

1. Purpose

This internal standard of Example Shipbuilders Ltd. sets minimum requirements for the routing and installation of shipboard electrical cables, in addition to class rules and IEC 60092-352.

2. Segregation

2.1 Power cables and instrumentation cables running in parallel for more than 3 m shall be separated by at least 150 mm, unless a screened tray with a continuous earth bond is used.

2.2 Cables of duplicated essential services shall be routed separately, as far apart as practicable.

3. Support

3.1 Cable supports on horizontal runs shall be at a maximum spacing of 300 mm.

3.2 Cable ties in open-deck locations shall be of stainless steel. Non-metallic ties alone are not permitted where a cable could fall during a fire.

4. Penetrations

4.1 Bulkhead and deck penetrations shall use type-approved transit systems which maintain the fire and watertight rating of the division.

4.2 Each transit shall have at least 20% spare capacity at delivery.

5. Open-Deck Cable Glands

5.1 Cable glands on open decks shall be at least IP56, matching the equipment they serve. This clause was added after harbour-trial findings on recent projects.