

Comprehensive Technical Framework and Proposal Strategy for the High-Fidelity Digital Twin of a Gas Turbine Starter Engine

Strategic Imperative and Defense Innovation Ecosystem Overview

The global aerospace and defense sectors are currently navigating a profound paradigm shift driven by the integration of cyber-physical systems. This transition is moving military aviation away from reactive, schedule-based maintenance paradigms toward predictive, condition-based, and highly prescriptive asset management strategies.¹ Within the Indian defense ecosystem, this technological leap is actively catalyzed by the Innovations for Defence Excellence (iDEX) framework and the Defence Innovation Organisation (DIO).³ Specifically, the DPSU-driven Research & Innovation for Strategic and High-impact Technology Integration (DRISHTI) initiative has been launched to foster sovereign technological independence.⁵ The DRISHTI program connects deep-tech startups, Micro, Small, and Medium Enterprises (MSMEs), and independent innovators directly with real-world, highly complex problem statements issued by major Defence Public Sector Undertakings (DPSUs).⁶

Among the exhaustive list of operational challenges curated to foster indigenous defense capabilities, Hindustan Aeronautics Limited (HAL) has issued Challenge 5, which explicitly demands the "Design, Development and Creation of a High-Fidelity Digital Twin Software Model for a Gas Turbine Starter Engine".⁵ This challenge is supported by a substantial tentative development budget of INR 5.12 Crores⁵, distinguishing it from standard Defence India Startup Challenge (DISC) grants which typically cap at INR 1.5 Crores.⁴ This elevated financial commitment reflects the extreme technical complexity and the critical operational importance of the asset in question.

The problem statement addresses a fundamental vulnerability in combat aviation readiness. Gas Turbine Starter Units (GTSU), such as the indigenous GTSU-110 and its derivatives utilized in the Light Combat Aircraft (LCA) Tejas, are mechanically indispensable for initiating the main propulsion systems, including the GE-F404 or the indigenous Kaveri engines.⁹ A failure or degradation in the starter unit grounds the aircraft, directly degrading sortie generation rates, operational availability, and overall mission readiness.¹¹ The development of a high-fidelity digital twin for the GTSU aims to introduce a highly advanced, data-driven modeling approach supported by a modular software architecture featuring integrated analytics, prognostics, and

3D visualization layers.⁵

To successfully secure funding and formal acceptance from HAL under this DRISHTI challenge, a submitting entity must not merely outline a generic software development plan. Evaluators within the Technical Evaluation Committee (TEC) scrutinize submissions based on stringent rubrics covering technical feasibility, defense relevance, innovation, team capability, and scalability.¹⁴ The technical document must present a rigorous, defense-grade engineering blueprint that proves an intimate understanding of aerospace thermodynamics, advanced data science, military airworthiness certification, and commercial deployment architectures. This report provides an exhaustive, expert-level breakdown of the technical, architectural, certification, and procedural requirements strictly necessary to formulate an unimpeachable and winning technical proposal for HAL Challenge 5.

Definition of the Physical Asset: The Gas Turbine Starter Unit

Architecting a high-fidelity digital twin inherently demands an uncompromising understanding of the physical asset it is intended to replicate. A digital twin is not a generalized simulation; it is an exact, serialized virtual replica that mirrors the specific physical characteristics, thermodynamic responses, and dynamic operational environment of its real-world counterpart.¹⁵ For Challenge 5, the physical entity is the HAL-developed Gas Turbine Starter Unit, specifically the GTSU-110 model and its associated iterations.¹⁰

The GTSU-110 is a highly specialized Jet Fuel Starter (JFS) engineered by HAL's Engine Design Bureau.¹¹ Unlike standard Auxiliary Power Units (APUs) that provide continuous pneumatic or electrical power to the aircraft while engines are inactive, the JFS is a small turbo-shaft engine that is mechanically coupled directly to the main engine.¹⁷ Its sole purpose is to drive the massive main jet engine to its self-accelerating revolutions per minute (RPM).¹⁷ The GTSU-110 possesses the critical capability to provide in-flight starting for the LCA main engine up to an altitude of 6 kilometers, a capability that has been rigorously proven in extreme high-altitude operational environments such as the Leh airbase.¹⁰

The Starter Electronic Control Unit (SECU) Architecture

The physical behavior of the GTSU-110 is entirely governed by its Starter Electronic Control Unit (SECU). The SECU is an advanced avionics Line Replaceable Unit (LRU) that manages the precise fuel flow into the starter's combustion chamber via a highly calibrated 3-phase stepper motor.¹⁸ The digital twin must interface seamlessly with the deterministic data structures output by this unit, requiring a deep understanding of its internal processing logic.

The SECU is built upon a highly reliable ARM-processor-based controller augmented by a SPARTAN 6 Field Programmable Gate Array (FPGA), providing robust, dual-redundant digital input/output processing.¹⁹ The control architecture of the SECU is bifurcated into two primary processing streams that the digital twin software must accurately simulate, monitor, and

predict:

- 1. **Main Processor (Closed-Loop Control):** This primary system manages the highly sensitive start and acceleration sequence. It operates in a continuous feedback loop governed by three mission-critical parameters: Gas Generator Speed (Ngg), the Pressure Ratio across the compressor (P2/P1), and the Jet Pipe Temperature (JPT1).¹⁸ The logic dictates specific control thresholds; for instance, the JPT1 operates under a strict limit of 900°C during ground operations and expands to 1020°C during in-flight operations.¹⁸ Furthermore, successful engine light-up detection is triggered either when Ngg exceeds 12,625 RPM or when JPT1 rapidly climbs above 135°C.¹⁸
- 2. **Independent Protection System (IPS) (Open-Loop Control):** Operating as a dedicated fail-safe mechanism, the IPS continuously monitors the health of the main processor.¹⁸ If the main processor is healthy, the IPS monitors for abnormal mechanical or thermal conditions to initiate an emergency engine shut-off. If the main processor fails, the IPS assumes control of the fuel flow in a degraded, open-loop control state.¹⁸

The physical asset operates within a highly constrained electrical and communication environment. It requires either a 115/200V AC (400 Hz, 3-Phase) or a 16 to 31.5V DC power supply, consuming approximately 75 Watts to 200 Watts depending on the specific operational mode.¹⁹ Crucially for the digital twin data ingestion strategy, the SECU interfaces with the aircraft's central mission computers and diagnostic logging systems utilizing the military-standard MIL-STD-1553B data bus, alongside ARINC 429 and discrete analog outputs.¹⁹

Digital Twin Sensor Telemetry and Data Ingestion Strategy

A technically sound proposal must explicitly detail how the digital twin will securely ingest, parse, and process the specific telemetry generated by the GTSU-110 and its surrounding aircraft systems. The software model cannot operate in a vacuum; it requires a continuous, high-frequency stream of structured data to synchronize the virtual replica with the physical asset.¹ The following table comprehensively outlines the critical sensor parameters that form the foundational data ingestion layer, mapping the physical engineering units to their specific modeling purpose within the digital twin.

Parameter Category	Sensor Data Point / Variable	Engineering Unit & Operational Characteristics	Digital Twin Computational Modeling Purpose
Thermodynamic	Jet Pipe Temperature (JPT1)	Celsius (°C). Subject to rigid control thresholds (900°C ground limit, 1020°C flight)	Critical for monitoring internal thermal gradients, detecting dangerous hot

		limit). ¹⁸	starts, and calculating cumulative creep life consumption in hot gas path components. ²¹
Aerodynamic	Pressure Ratio (P2/P1)	Dimensionless Ratio / Kilopascals (kPa) tracking absolute compressor discharge pressure.	Utilized for evaluating instantaneous compressor efficiency, plotting surge margins, and detecting progressive compressor fouling or mass flow reductions. ²²
Kinematic	Gas Generator Speed (N _{gg})	Revolutions Per Minute (RPM) / Percentage of maximum speed (%).	Essential for identifying hung starts, verifying mechanical light-up detection logic (e.g., N _{gg} > 12,625 rpm), and monitoring rotor dynamic stability. ¹⁸
Environmental	Outside Air Temperature (OAT)	Celsius (°C). Ranging from -100°C to +300°C, typically provided via the external Air Data Unit (ADU). ¹⁹	Required for normalizing ambient conditions within the thermodynamic equations to calculate accurate baseline model corrections and expected efficiency. ¹⁹
Actuation &	Stepper Motor Fuel	Discrete Steps	Analyzed in

Control	Position	mapped to Fuel Mass Flow Rate (kg/h). Controls combustion input. ¹⁸	correlation with Ngg to simulate fuel-air mixture optimizations, detect control loop anomalies, and identify parasitic mechanical drag. ¹⁸
Avionics & Status	SECU Health & BIT Status	Discrete Boolean markers and MIL-STD-1553B hexadecimal words. ¹⁸	Required to simulate processor health states, trigger virtual Built-in-Test (BIT) routines, and log historical IPS takeover events for reliability analysis. ¹⁸

Technical Solution Approach: The High-Fidelity Software Architecture

The official HAL DRISHTI challenge statement specifically mandates a "modular software architecture with analytics, prognostics and visualisation layers".⁵ To satisfy the rigorous technical expectations of the defense evaluators, the proposed architecture must advance far beyond rudimentary data dashboarding. It must represent a genuine, bidirectional Cyber-Physical System (CPS) integration.²⁵ The most critical element of the technical proposal is the justification of a Hybrid Modeling Engine, combining the deterministic reliability of first-principles physics models with the adaptive pattern-recognition capabilities of advanced data-driven machine learning algorithms.²⁵

Architectural Layer 1: Edge Middleware and Data Synchronization

The foundational layer of the digital twin connects the physical aerospace asset to the virtual computational environment. Because military avionics telemetry operates at exceedingly high frequencies, the data ingestion pipeline must be highly optimized to strictly minimize communication latency and ensure deterministic processing.²⁷

The technical proposal should specify an architecture compliant with the ISO 23247 standard for manufacturing and operational digital twins.²⁸ This requires deploying robust edge computing middleware capable of parsing raw MIL-STD-1553B and ARINC 429 hexadecimal data streams in real-time.¹⁹ The data architecture must feature a centralized, highly scalable time-series database (Data Lake) capable of handling high-velocity, multi-dimensional data.

This repository serves as the single source of truth, storing historical run-to-failure datasets, synthetic degradation trajectories generated by simulations, and detailed maintenance overhaul logs.³⁰ To address cyber security requirements inherent in defense applications, the proposal must detail the use of unidirectional data diodes or highly encrypted application programming interfaces (APIs) to ensure that the physical engine control (SECU) cannot be maliciously manipulated from the virtual environment.³²

Architectural Layer 2: The Hybrid Computational Modeling Engine

A defining feature that separates acceptable proposals from winning proposals is the mathematical sophistication of the modeling layer. Purely data-driven machine learning models are inherently flawed in aerospace applications; they suffer from poor generalizability outside their specific training distributions and require massive amounts of run-to-failure data, which is rarely available due to strict preventative maintenance schedules.³⁴ Conversely, pure physics-based models (such as full 3D Navier-Stokes Computational Fluid Dynamics) are computationally exhaustive, rendering them entirely unsuitable for real-time state estimation and edge computing deployments.³⁵

Therefore, the technical document must strongly advocate for a sophisticated Hybrid (Physics-Empirical) Model²⁵:

1. **Aero-Thermal Physics Baseline Model:** This structural module utilizes 1D mean-line thermodynamic equations and highly optimized 3D CFD Reduced-Order Models (ROMs) to mathematically replicate the gas path analysis of the compressor, combustor, and turbine stages.²⁵ Utilizing real-time inputs of Outside Air Temperature and altitude, this model continuously computes the exact theoretical expected outputs of the GTSU-110 if it were in a perfect, pristine condition.²³
2. **Physics-Informed Neural Networks (PINNs):** To bridge the critical gap between theoretical physics and actual degraded performance, the architecture must leverage PINNs. These advanced networks integrate physical domain knowledge—such as thermodynamic conservation laws, fatigue accumulation equations, and Navier-Stokes principles—directly as mathematical regularizers within the neural network's loss function.³⁰ This rigid structural constraint forces the artificial intelligence to respect the laws of physics, allowing the model to converge rapidly and accurately even with extremely limited historical failure data.³⁰ Furthermore, PINNs effectively mitigate the numerical diffusion commonly found in rapid CFD approximations, allowing for the accurate, real-time simulation of highly transient engine start-up behaviors.³⁶
3. **Data-Driven Residual Analytics:** By continuously comparing the pristine theoretical output of the physics model against the actual degraded telemetry received from the engine, a mathematical residual is generated. Advanced machine learning algorithms analyze these specific residuals to isolate faults, separate sensor noise from actual mechanical degradation, and quantify the exact loss in efficiency.³⁸

Architectural Layer 3: Analytics, Prognostics, and Health Management (PHM)

The Prognostics and Health Management (PHM) layer is where the digital twin delivers its primary operational value, transforming raw computational models into actionable military intelligence. The proposal must emphasize the strategic shift from diagnostics (identifying what has already failed) to prognostics (predicting exactly when a component will fail in the future).⁴⁰

The PHM layer executes two primary functions:

- **Dynamic Health State Estimation:** Utilizing advanced filtering algorithms such as Kalman tuners or Nonlinear Autoregressive with Exogenous Inputs (NARX) models coupled with Bayesian regularization, the software continuously estimates the hidden, unobservable states of engine degradation.⁴⁰ This allows the twin to calculate metrics like instantaneous compressor efficiency or precise combustion temperature spreads that physical sensors cannot directly measure.²²
- **Remaining Useful Life (RUL) Prediction:** To predict future failure, the architecture employs advanced deep learning structures, specifically Long Short-Term Memory (LSTM) networks or Gated Recurrent Units (GRU).⁴⁴ These models analyze the temporal sequences of evolving health indicators—such as the gradual decay of the Exhaust Gas Temperature (EGT/JPT1) margin or the steady amplification of rotor vibration—to mathematically forecast the exact operational timeframe remaining before a critical component breaches its ultimate safety threshold.⁴⁰

Architectural Layer 4: High-Fidelity 3D Visualization and Human-Machine Interface

The uppermost layer is the human-facing visualization module. To strictly meet HAL's "high-fidelity" requirement, the user interface cannot be restricted to conventional 2D charts, static spreadsheets, or generic dashboards.⁴⁵

The proposal must outline the integration of advanced 3D rendering technologies, leveraging professional gaming engines such as Unity, Unreal Engine, or highly optimized WebGL libraries (e.g., three.js) to render a precise, interactive 3D Computer-Aided Design (CAD) model of the GTSU-110.⁴⁵ Crucially, this is not merely a static model; it requires Contextual Data Mapping. Real-time thermal gradients, localized mechanical stresses, and internal airflow paths must be visually projected onto the specific 3D components.²² For instance, if the underlying analytics layer detects stage-specific compressor fouling, those exact compressor blades should highlight dynamically on the 3D model, instantly allowing maintenance engineers to visually pinpoint the exact location and severity of the degradation without dismantling the engine.²²

Degradation Mechanisms and Diagnostic Strategies

A comprehensive and compelling technical proposal must explicitly detail the specific

mechanical and thermodynamic failure modes the software is purposefully designed to detect, classify, and prognose. Gas turbines operating in demanding military environments experience continuous, gradual degradation that silently drains fuel efficiency and compromises operational safety.¹² Evaluators will look for an intimate, expert-level understanding of the thermodynamic mechanisms behind these specific failures.

Tracking Progressive Thermodynamic Degradation

1. **Compressor Fouling:** This is the insidious accumulation of sub-5 micron particles—such as dust, pollen, and salt spray—adhering to the finely tuned compressor blade profiles, fundamentally altering their aerodynamic geometry.¹² The digital twin must simulate this specific degradation by tracking the gradual divergence in the pressure ratio ($P2/P1$) against the theoretical baseline, noting the subsequent, necessary increase in JPT1 as the ECU forces the engine to burn more fuel to maintain the required RPM.²²
2. **Thermal Fatigue and Creep Life Consumption:** The hot gas path components, particularly the high-pressure turbine blades and combustor liners, undergo extreme and rapid thermal cycling during the violent start-up process. The digital twin must integrate cumulative creep strain mathematical estimates and low-cycle fatigue models based on historical JPT1 temperature peaks and total operational hours to accurately predict long-term structural compromises.²²

Starter-Specific Failure Modes and Transient Analytics

Because the GTSU-110 is specifically a starter unit and not a continuous-thrust propulsion engine, its failure modes differ significantly, occurring primarily during highly transient acceleration phases. The digital twin must possess bespoke logic to detect and classify these specific start anomalies:

- **Hot Starts:** This dangerous condition is characterized by internal temperatures (JPT1) rapidly exceeding safe structural limits due to excessive fuel flow relative to the available compressor airflow.²¹ The twin's anomaly detection algorithms must instantly trigger prescriptive alerts if the temperature gradients steepen beyond the nominal acceleration curves established by the physics model.
- **Hung Starts:** A hung start occurs when the engine successfully ignites but fails to accelerate to the required self-sustaining RPM, stalling at a dangerous, lower speed.⁴⁹ The digital twin will actively correlate the 3-phase Stepper Motor Position against the Ngg output to identify instances of highly inefficient combustion or excessive parasitic mechanical drag preventing acceleration.²¹
- **Virtual Sensor Redundancy and Fault Isolation:** Physical sensors degrade. The digital twin acts as an analytical "Virtual Sensor." If a physical pressure or temperature probe begins to drift or outputs erratic noise beyond the bounds of physical inertia, the digital twin's Software-in-the-Loop (SIL) architecture immediately isolates the faulty hardware sensor, allowing the control logic to switch to the virtual estimates to ensure continuous,

safe operation.³⁸

The following table meticulously maps these critical failure mechanisms to the proposed digital twin analytical approaches, providing a clear matrix of the software's capabilities for the evaluation committee.

Primary Failure Mechanism	Affected Engine Component	Diagnostic Sensor Signature	Digital Twin Prognostic and Analytical Approach
Compressor Fouling	Compressor Rotor & Stator Blades	Gradual drop in P2/P1 ratio; corresponding rise in Stepper Motor fuel flow required to maintain baseline Ngg.	Physics-based shift in simulated compressor maps; LSTM time-series forecasting of efficiency drop to predict precise washing intervals. ²²
Hot Corrosion & Creep	Turbine Blades, Combustor Liners	Elevated JPT1 baselines, subtle vibration anomalies, performance efficiency loss.	Hybrid model integrating the Larson-Miller parameter for accurate creep life consumption tracking and structural fatigue prognosis. ¹²
Sensor Drift or Failure	Pressure Probes, Thermocouples	Step-changes, flatlining, or erratic signal noise completely out of bounds of engine physical inertia.	Analytical sensor redundancy. The twin acts as a "Virtual Sensor," isolating the faulty hardware via rigorous Software-in-the-Loop comparisons. ³⁸
Hung Start	Main Shaft,	Ngg plateaus	Real-time

Phenomenon	Aerodynamic Flow Path	significantly below the 12,625 RPM threshold while JPT1 remains stable or slowly rises.	classification algorithms (e.g., Support Vector Regression or Random Forests) continuously comparing the transient start profile against the golden baseline. ¹⁸
------------	-----------------------	---	---

Verification, Validation, and Military Airworthiness Certification Framework

Developing any software model intended for integration with military aviation assets requires strict, uncompromising adherence to rigorous certification standards. The HAL problem statement explicitly demands a "Validation and verification framework to ensure model accuracy and efficacy".⁵ Submitting a DRISHTI proposal without exhaustively detailing compliance to both global engineering protocols and Indian defense airworthiness standards will result in immediate disqualification. The digital twin is a critical engineering tool subject to severe safety and reliability evaluations.³¹

The ASME V&V Standards Framework

The American Society of Mechanical Engineers (ASME) has established the internationally recognized gold standard for assessing computational model credibility. The technical proposal must structurally anchor its Verification, Validation, and Uncertainty Quantification (VVUQ) strategy around these specific protocols:

- **ASME V&V 10 (Computational Solid Mechanics):** This standard is utilized to rigorously verify the mathematical structural integrity, low-cycle fatigue predictions, and thermal stress models of the GTSU components simulated within the twin.²⁸
- **ASME V&V 20 (Computational Fluid Dynamics and Heat Transfer):** This is applied directly to validate the aerodynamic flow models, transient pressure ratios, and complex combustion thermodynamics generated by the hybrid software.²⁸
- **ASME V&V 50 (Advanced Manufacturing & Digital Twins) & ISO 23247:** These evolving, highly specific standards govern the overall architectural compliance, real-time data synchronization credibility, and interoperability of the complete digital twin system.²⁸

CEMILAC and DGAQA Airworthiness Compliance

Within the Indian defense framework, any software interfacing with, supporting, or modeling airborne systems must successfully navigate the complex, concurrent certification processes

of the Centre for Military Airworthiness and Certification (CEMILAC) and the Directorate General of Aeronautical Quality Assurance (DGAQA).⁵²

Even if the digital twin itself operates exclusively on secure, ground-based servers (off-board monitoring), its outputs directly influence critical maintenance, repair, overhaul (MRO), and flight dispatch decisions, thus requiring rigorous regulatory scrutiny.

1. **DDPMAS Guidelines Alignment:** The Design, Development, and Production of Military Airborne Systems (DDPMAS) documentation strictly outlines the required stages of design review. The digital twin software development lifecycle must flawlessly align with the Preliminary Design, Detail Design, and System Certification Review Board (SCRB) milestones.⁵⁴
2. **Software Aspects of Certification (DO-178C):** The GTSU-110's physical SECU is already certified to the stringent DO-178 Level-B standard.¹⁹ The digital twin's edge middleware and data ingestion protocols must mathematically guarantee that connecting to the aircraft's internal MIL-STD-1553B bus for data extraction does not introduce any cybersecurity vulnerabilities, timing faults, or processing latency into the flight-critical hardware.¹⁹
3. **Independent Verification & Validation (IV&V):** The proposal must explicitly account for the establishment of an IV&V process. During this phase, third-party system experts, alongside CEMILAC and DGAQA representatives, will conduct thorough audits of the source code, hardware test plans, and mathematical model accuracy.⁵² This regulatory requirement heavily favors the use of transparent, physics-informed architectures over opaque, "black-box" pure deep-learning systems, as the reasoning behind every prognostic prediction must be mathematically justifiable to the authorities.³⁰

Structuring the iDEX DRISHTI Technical Proposal

The application process for the iDEX DRISHTI challenges demands a highly structured, meticulously formatted document. The TEC evaluators are explicitly searching for a seamless convergence of technical brilliance, practical defense applicability, and robust commercial execution.⁷

Mandatory Application Sections

Based on the official iDEX guidelines and the specific requirements of Category 46 and Challenge 5, the proposal must integrate the following components into a cohesive, persuasive narrative:

1. **Core Entity and Point of Contact Details:** This establishes the legal and commercial credibility of the applying Startup, MSME, or academic innovator. It includes incorporation details, PAN, and the designation of a core team member as the primary liaison.⁵⁶
2. **Concise Overview & Problem Statement:** A highly refined, maximum 250-word executive summary that clearly defines the GTSU-110 modeling problem and presents a

high-level summary of the proposed hybrid digital twin solution.⁵⁷

3. **Detailed Technical Solution & Architecture:** This is the core of the document. It must dive deep into the thermodynamic equations, the specific machine learning models (PINNs, LSTMs), the ISO 23247 edge-to-cloud architecture, and the 3D visualization stack, clearly establishing the "Key Features & Innovation".⁵⁷
4. **Expected Outcomes and Deliverables:** A precise outline of the exact software modules, source code transfers, user interface dashboards, API endpoints, and technical training manuals to be ultimately handed over to HAL.⁵
5. **Comprehensive Development Plan, Milestones, and Financials:** A rigorously phased execution strategy that clearly aligns with the INR 5.12 Cr budget ceiling and the structured iDEX funding tranches.⁵

Strategic Alignment with TEC Evaluation Criteria

The Technical Evaluation Committee scores proposals utilizing a strict, predefined rubric.¹⁴ A winning technical document must structurally address and maximize scoring in each criterion:

TEC Evaluation Criterion	Weightage	Strategic Proposal Alignment and Justification Strategy
Innovation and Originality	25%	Heavily emphasize the technological leap from traditional, static Gas Path Analysis (GPA) to dynamic, Hybrid Physics-Informed Neural Networks (PINNs). Highlight the extreme novelty of combining edge-based real-time telemetry parsing with advanced, cloud-based predictive creep modeling and 3D contextual visualization. ³⁶
Defence Relevance	25%	Directly tie the digital twin's predictive maintenance capabilities to significantly increased LCA Tejas fleet availability. Emphasize that

		accurately predicting and preventing GTSU-110 failures directly ensures rapid scramble capabilities and higher overall sortie generation rates during critical operational deployments. ¹⁰
Technical Feasibility	20%	Prove absolute feasibility by deeply grounding the software architecture in established global V&V standards (ASME V&V 20/50) and leveraging proven, enterprise-grade software stacks (e.g., Unity/Unreal for UI, Python/PySINDy for backend AI). Detail a clear Software-in-the-Loop (SIL) and Hardware-in-the-Loop (HIL) testing plan. ²⁸
Team Capability	15%	Highlight profound multidisciplinary expertise. The proposing team <i>must</i> explicitly include not just generic software engineers, but deeply specialized domain experts in turbomachinery thermodynamics, aerospace airworthiness certification (CEMILAC/DGAQA), and advanced AI/ML data science. ³³
Scalability	15%	Demonstrate that the modular, API-driven architecture developed

		specifically for the GTSU-110 can be rapidly retrained via transfer learning for other critical HAL engines. This includes the HTSE-1200, HTFE-25, or the Auxiliary Power Units (APUs) of the upcoming Advanced Medium Combat Aircraft (AMCA) and Indian Multi-Role Helicopter (IMRH). ⁹
--	--	---

Phased Project Lifecycle and Milestone Execution

iDEX DRISHTI funding is disbursed strictly on a milestone basis.¹⁴ To successfully justify and draw down the INR 5.12 Cr budget, the proposal must offer a thoroughly de-risked, phased project lifecycle that aligns perfectly with the AWEIL/iDEX standard disbursement structure.⁵ The project timeline should realistically span 12 to 18 months to ensure adequate time for rigorous certification testing.

Phase 1: Proof of Concept and Architecture Definition (20% Funding Tranche)

Target Duration: Months 1 - 4

- **Strategic Objectives:** Comprehensive requirements gathering, initial mathematical modeling of the GTSU-110 baseline thermodynamics, and formal software architecture design.
- **Key Actions:** Finalize the thermodynamic equations for the 1D mean-line gas path models. Establish the edge-to-cloud data flow protocols.
- **Required Deliverables:**
 - System Requirement Document (SRD).
 - Software Architecture Document (SAD) compliant with ISO 23247.
 - Interactive mock-up of the 3D visualization dashboard.
 - Initial Feasibility Report.
- **Acceptance Criteria:** Formal approval of the design documents by the HAL Project Monitoring Group (PMG) and an initial proof-of-concept demonstration.¹⁴

Phase 2: Prototype Development, AI Training, and Integration (50% Funding Tranche)

Target Duration: Months 5 - 12

- **Strategic Objectives:** Core software coding, intense AI model training, and complex systems integration.
- **Key Actions:**
 - Ingest historical LCA Tejas GTSU sensor data (Ngg, P2/P1, JPT1, Stepper Motor Position) provided by HAL to train the LSTM and XGBoost prognostic algorithms.⁴⁴
 - Develop and refine the Physics-Informed Neural Networks to accurately predict thermal stress and transient start behaviors.³⁶
 - Construct and render the high-fidelity 3D digital replica within the chosen visualization engine.⁴⁵
 - Perform rigorous Software-in-the-Loop (SIL) and Hardware-in-the-Loop (HIL) testing utilizing simulated MIL-STD-1553B data streams to mimic the SECU outputs flawlessly.³⁸
- **Required Deliverables:** Functional Alpha version of the Digital Twin software, fully trained ML models, and comprehensive interim testing reports.¹⁴
- **Acceptance Criteria:** Successful, documented performance validation of the software against baseline specifications in a tightly controlled simulated environment, subject to PMG scrutiny.¹⁴

Phase 3: Field Trials, Validation, and Final Handover (30% Funding Tranche)

Target Duration: Months 13 - 18

- **Strategic Objectives:** Real-world physical deployment, final V&V execution, and complete technology transfer to HAL.
- **Key Actions:**
 - Deploy the completed software onto HAL's designated secure servers or cloud infrastructure.
 - Feed real-time, live data from an operational GTSU-110 physical test-bed into the digital twin to actively track live degradation and evaluate prognostic accuracy in a real-world scenario.⁵⁸
 - Execute the formal Verification and Validation protocols strictly against ASME V&V standards and DDPMAS guidelines.²⁸
- **Required Deliverables:** Fully deployed, stable Beta software, comprehensive and well-documented source code, final V&V airworthiness clearance reports, and exhaustive end-user training manuals.⁵
- **Acceptance Criteria:** Final prototype operational demonstration, compliance with all operational requirements, and ultimate sign-off by the System Certification Review Board (SCRB).¹⁴

Resource Allocation and Budget Justification Strategy

When detailing the specific utilization of the INR 5.12 Cr budget ceiling, evaluators are actively

looking for a pragmatic, highly efficient distribution of funds that prioritizes deep R&D, specialized engineering talent, and essential high-performance computing infrastructure, rather than generic corporate overhead.⁵

- **Computational Infrastructure & Cloud Resources (25%):** Procurement of necessary High-Performance Computing (HPC) clusters or secure, scalable cloud instances required to process complex CFD simulations and train deep, multi-layered neural networks.⁶³
- **Software Licensing and Edge Hardware Interfaces (15%):** Essential licenses for commercial 3D gaming engines (if applicable, though open-source alternatives are often preferred for sovereign IP retention), advanced databases, and specialized hardware interfaces required to physically parse military avionics data buses (e.g., dedicated MIL-STD-1553B PCI cards).¹⁹
- **Human Resources & Multidisciplinary Expertise (45%):** Funding the core multidisciplinary team. This must be the highest cost center, requiring top-tier domain experts in turbomachinery, data science, software architecture, and specialized aerospace certification engineers.³³
- **Testing, V&V, and Contingency Buffers (15%):** A dedicated budget allocated specifically for independent auditing, rig testing integration, travel for field trials, and vital risk mitigation financial buffers.⁵²

Risk Identification and Mitigation Strategy

A hallmark of a truly expert-level proposal is the proactive, transparent identification of severe technical risks, accompanied by the provision of robust, highly credible mitigation strategies. This is a specific requirement outlined in the HAL problem statement.⁵

1. **The Data Scarcity Risk:** Gas turbines in military aviation rarely run to catastrophic failure due to strict preventative maintenance. This results in heavily skewed datasets with a severe lack of actual fault data required to train machine learning models effectively.³⁴
 - *Mitigation Strategy:* The proposal mitigates this critical flaw by generating synthetic degradation trajectories using the high-fidelity physics and CFD models. This synthetic fault data is then utilized to heavily supplement the training of the machine learning algorithms, allowing the AI to learn failure patterns without needing physical engines to break.²⁰
2. **The Computational Latency Risk:** High-fidelity 3D CFD models are mathematically massive and far too slow for real-time operational monitoring or edge computing.³⁵
 - *Mitigation Strategy:* The software architecture will rely entirely on Reduced Order Models (ROMs) and surrogate neural networks (specifically PINNs) that mathematically map the complex physics into far lighter, rapidly executable algorithms. This ensures the sub-second analytics latency required to monitor a rapidly accelerating starter engine.³⁵
3. **Cybersecurity and Airworthiness IP Risk:** Integrating operational, flight-critical defense

hardware with external software networks introduces severe cybersecurity attack vectors.³²

- *Mitigation Strategy:* The digital twin will be designed to operate via strict one-way data diodes for telemetry ingestion. This hardware-enforced security ensures that the physical engine control (SECU) can never be manipulated remotely from the virtual environment, perfectly preserving the DO-178 Level-B integrity of the aircraft's internal systems.¹⁹

Commercialization, Scaling, and Business Plan

While the immediate, primary objective of the proposal is securing the 5.12 Cr grant to solve the GTSU-110 problem, the broader, overarching vision must be commercialization. This is a core, mandated tenet of the iDEX philosophy; the defense establishment wants to invest in sustainable businesses, not just science experiments.³ The proposal must articulate a compelling, highly lucrative business plan that extends far beyond the initial grant.⁵⁶

The modular, layer-based nature of the proposed digital twin architecture guarantees exceptional scalability. The base framework—comprising the data ingestion middleware, the hybrid modeling engine, and the 3D visualization platform—is fundamentally platform-agnostic.⁶⁶ By simply altering the underlying thermodynamic maps and importing new 3D CAD assets, the exact same core software architecture can be rapidly commercialized and transitioned to other massive markets:

- **Advanced Defense Engine Programs:** Adapting the digital twin to monitor the HTSE-1200 turboshaft engine, the HTFE-25 turbofan, or the highly complex Auxiliary Power Units (APUs) of the upcoming Advanced Medium Combat Aircraft (AMCA) and the Indian Multi-Role Helicopter (IMRH).⁹
- **Marine and Industrial Turbines:** Scaling the technology to monitor heavy marine gas turbines, such as the LM2500 used in naval vessels, directly addressing similar, highly lucrative DRISHTI challenges from major shipyards like GRSE or MDL.⁶⁷
- **Global Civil Aviation MRO:** Transitioning the predictive maintenance algorithms to the massive commercial airline Maintenance, Repair, and Overhaul (MRO) market, offering airlines millions in savings by preventing unscheduled engine removals.⁵⁹

By successfully proving this highly advanced technology on a smaller, extremely critical subsystem like the GTSU-110, the innovating entity establishes itself as a premier, sovereign provider of digital thread capabilities. This positions the company perfectly for highly lucrative, long-term procurement contracts with HAL, the Indian Armed Forces, and the global aerospace industry.

Works cited

1. Prognostic and Health Management of Critical Aircraft Systems and Components: An Overview - PMC, accessed on May 4, 2026,

- <https://pmc.ncbi.nlm.nih.gov/articles/PMC10574896/>
2. The Digital Twin in Aviation: A Review of Core Technologies, Lifecycle Applications, and Future Challenges - TechRxiv, accessed on May 4, 2026, <https://www.techrxiv.org/doi/pdf/10.36227/techrxiv.176524820.07513276/v1?download=true>
 3. Defence India Start-up Challenge 5.0 - Drishti IAS, accessed on May 4, 2026, <https://www.drishtias.com/daily-news-analysis/defence-india-start-up-challenge-5-0>
 4. Innovations for Defence Excellence - myScheme, accessed on May 4, 2026, <https://www.myscheme.gov.in/schemes/idx>
 5. dhrishtichallengesops.pdf
 6. DRISHTI Challenges India – Defence Funding & Eligibility - Startup Grants Hub, accessed on May 4, 2026, <https://startupgrantshub.com/opportunities/drishti-challenges-dpsu-driven-defence-innovation-program/>
 7. DRISHTI Challenges - iDEX, accessed on May 4, 2026, <https://idx.gov.in/disc-category/46>
 8. iDEX Scheme - Drishti IAS, accessed on May 4, 2026, <https://www.drishtias.com/daily-updates/daily-news-analysis/idx-scheme>
 9. ALH Final Assembly Project Report | PDF | Helicopter Rotor | Aviation - Scribd, accessed on May 4, 2026, <https://www.scribd.com/document/794313188/ALH-FINAL-ASSEMBLY>
 10. January, 2006 - Nocturnalknight's Lair, accessed on May 4, 2026, <https://nocturnalknight.co/2006/01/>
 11. To assess whether Indigenous capability was developed through LCA programme 3.1 Absence of Indigenisation Plan CHAPT, accessed on May 4, 2026, https://www.cag.gov.in/uploads/download_audit_report/2015/Union_Performance_Defense_Design_Manufacture_Light_Combat%20Aircraft_17_2015_chapter_6.pdf
 12. Common Causes of Gas Turbine Failure | Allied Power Group, accessed on May 4, 2026, <https://alliedpg.com/latest-articles/common-causes-gas-turbine-failure/>
 13. Summary of DRISHTI Challenges “DPSU-driven Research & Innovation for Strategic and High- impact Technology Integration” - iDEX, accessed on May 4, 2026, https://idx.gov.in/uploads/challenges/1774438199_0d2856bdda2fe13b800b.pdf
 14. AWEIL Comprehensive Policy Framework for Funding and Management of DRISHTI Challenges, accessed on May 4, 2026, <https://www.aweil.in/download/notices/idx-challenges/Guidelines-for-DRISHTI-Challenges.pdf?v=1.956>
 15. Overview of predictive maintenance based on digital twin technology - PMC, accessed on May 4, 2026, <https://pmc.ncbi.nlm.nih.gov/articles/PMC10070392/>
 16. (PDF) A Novel Method of Digital Twin-Based Manufacturing Process State Modeling and Incremental Anomaly Detection - ResearchGate, accessed on May 4, 2026, https://www.researchgate.net/publication/367346924_A_Novel_Method_of_Digital

[Twin-Based Manufacturing Process State Modeling and Incremental Anomaly Detection](#)

17. ADA/HAL LCA Tejas - Lethal-Compact-Agile - Full Afterburner, accessed on May 4, 2026,
<http://fullafterburner.weebly.com/next-gen-weapons/lca-tejas-lethal-compact-agile-part-1>
18. Design & Development Of Starter Engine Control Unit For The Fighter Aircraft, accessed on May 4, 2026,
<https://www.quickcompany.in/patents/design-development-of-starter-engine-control-unit-for-the-fighter-aircraft>
19. HAL - Hindustan Aeronautics Limited, accessed on May 4, 2026,
https://hal-india.co.in/backend/wp-content/uploads/2023/05/305_Download_HAL-R_D-Capabilities.pdf
20. Digital Twin-Based Health Management for Complex Aircraft Systems: Case Studies and Applications - CERES Research Repository, accessed on May 4, 2026,
<https://dspace.lib.cranfield.ac.uk/bitstreams/8e5942b3-c59b-48c5-9db9-65f42a89ef02/download>
21. The Most Common Turbine Engine Starting Failures - Pilots Who Ask Why, accessed on May 4, 2026,
<https://pilotswhoaskwhy.com/2022/04/03/the-most-common-turbine-engine-starting-failures/>
22. Digital Twin for Gas Turbine Performance Optimization - Oxmaint, accessed on May 4, 2026,
<https://oxmaint.com/industries/power-plant/digital-twin-gas-turbine-performance-optimization>
23. Simplified Data-Driven Models for Gas Turbine Diagnostics - MDPI, accessed on May 4, 2026, <https://www.mdpi.com/2075-1702/13/5/344>
24. Construction of Data-Driven Performance Digital Twin for a Real-World Gas Turbine Anomaly Detection Considering Uncertainty - MDPI, accessed on May 4, 2026, <https://www.mdpi.com/1424-8220/23/15/6660>
25. The development of a Novel Hybrid Gas Turbine digital twin to predict performance deterioration - Cal-Tek, accessed on May 4, 2026,
<https://www.cal-tek.eu/proceedings/i3m/2023/sesde/003/pdf.pdf>
26. Digital Twins Verification and Validation Approach through the Quintuple Helix Conceptual Framework - MDPI, accessed on May 4, 2026,
<https://www.mdpi.com/2079-9292/13/16/3303>
27. Technologies, Applications, and Challenges of Digital Twin Across Industries - IEEE Xplore, accessed on May 4, 2026,
<https://ieeexplore.ieee.org/iel8/6287639/10820123/11134372.pdf>
28. digital twins for advanced manufacturing: the standardized approach, accessed on May 4, 2026, https://tsapps.nist.gov/publication/get_pdf.cfm?pub_id=957417
29. Boruah A. Embedded Artificial Intelligence. Real-Life Apps and Case Studies 2025 - Scribd, accessed on May 4, 2026,
<https://www.scribd.com/document/840586473/Boruah-A-Embedded-Artificial-Intelligence-Real-Life-Apps-and-Case-Studies-2025>

30. Overview on Predictive Maintenance Techniques for Turbomachinery - MDPI, accessed on May 4, 2026, <https://www.mdpi.com/2075-1702/14/4/396>
31. Health Management for In-Service Gas Turbine Engines - PHM Society, accessed on May 4, 2026, https://phmsociety.org/wp-content/uploads/2009/06/FieldedSystems_Mooney.pdf
32. Digital Twin Consortium Publishes Digital Twin Research & Technology Gap Whitepaper, accessed on May 4, 2026, <https://www.digitaltwinconsortium.org/press-room/04-17-25/>
33. The Digital Twin in Aviation: A Review of Core Technologies, Lifecycle Applications, and Future Challenges - TechRxiv, accessed on May 4, 2026, <https://www.techrxiv.org/doi/pdf/10.36227/techrxiv.176524820.07513276>
34. Digital Twin Technology for Gas Turbines, accessed on May 4, 2026, <https://www.lifepredictiontech.com/digital-twin-gas-turbines>
35. Physics-Informed Machine Learning for Intelligent Gas Turbine Digital Twins: A Review, accessed on May 4, 2026, <https://www.mdpi.com/1996-1073/18/20/5523>
36. Physics-Informed Neural Networks for Industrial Gas Turbines: Recent Trends, Advancements and Challenges - arXiv, accessed on May 4, 2026, <https://arxiv.org/html/2506.19503v1>
37. GPPS-TC-2025-0001, accessed on May 4, 2026, https://gpps.global/wp-content/uploads/2025/09/GPPS-TC-2025_paper_001.pdf
38. GAS turbine sensor fault diagnostic system in a real-time executable digital-twin, accessed on May 4, 2026, <https://journal.gpps.global/GAS-turbine-sensor-fault-diagnostic-system-in-a-real-time-executable-digital-twin.159781.0.2.html>
39. View of Development of a Data-driven Model for Marine Gas Turbine (MGT) Engine Health Monitoring - PHM Papers, accessed on May 4, 2026, https://papers.phmsociety.org/index.php/phmconf/article/view/543/phmc_18_543
40. Prognostics vs Diagnostics in Gas Turbines — PatSnap Eureka, accessed on May 4, 2026, <https://www.patsnap.com/resources/blog/rd-blog/prognostics-vs-diagnostics-in-gas-turbines-patsnap-eureka/>
41. Prognostic Enhancements to Gas Turbine Diagnostic Systems - DTIC, accessed on May 4, 2026, <https://apps.dtic.mil/sti/tr/pdf/ADA457841.pdf>
42. EasyChair Preprint Development of Digital Twin Model of Gas Turbine for Performance Simulation, accessed on May 4, 2026, <https://easychair.org/publications/preprint/Wptd/open>
43. Proceedings of - Lincoln Repository, accessed on May 4, 2026, <https://repository.lincoln.ac.uk/ndownloader/files/44458733>
44. A Prognostic and Health Management Framework for Aero-Engines Based on a Dynamic Probability Model and LSTM Network - MDPI, accessed on May 4, 2026, <https://www.mdpi.com/2226-4310/9/6/316>
45. Digital Twin Architecture & Standards - Visartech Blog, accessed on May 4, 2026, <https://www.visartech.com/blog/digital-twin-architecture-guide/>
46. Development and Integration of a Digital Twin Model for a Real Hydroelectric

- Power Plant, accessed on May 4, 2026,
https://www.researchgate.net/publication/381782313_Development_and_Integration_of_a_Digital_Twin_Model_for_a_Real_Hydroelectric_Power_Plant
47. Designing a Conceptual Digital Twin Architecture for High-Temperature Heat Upgrade Systems - MDPI, accessed on May 4, 2026,
<https://www.mdpi.com/2076-3417/15/5/2350>
 48. Industrial applications of a modular software architecture for line-less assembly systems based on interoperable digital twins - Frontiers, accessed on May 4, 2026,
<https://www.frontiersin.org/journals/mechanical-engineering/articles/10.3389/fmech.2023.1113933/full>
 49. Turbine (Jet) Engine Failed Starts Explained - Pilot Institute, accessed on May 4, 2026, <https://pilotinstitute.com/turbine-engine-failed-starts-explained/>
 50. A Case for the Use of Data-driven Methods in Gas Turbine Prognostics - PHM Papers, accessed on May 4, 2026,
<https://papers.phmsociety.org/index.php/phmconf/article/view/2483>
 51. Verification and Validation of Rotating Machinery Using Digital Twin, accessed on May 4, 2026,
<https://asmedigitalcollection.asme.org/risk/article/10/1/011104/1169942/Verification-and-Validation-of-Rotating-Machinery>
 52. CEMILAC/5390/AW/01/ Directives - DRDO, accessed on May 4, 2026,
https://drdo.gov.in/drdo/sites/default/files/form_formats/AiworthinessDirective_16.pdf
 53. CEMILAC/GDA/1004 24 Aug 2011 1. An Airworthiness Directive no. 11 on Transfer of Technology (ToT) is the procedure of ToT and de - DRDO, accessed on May 4, 2026,
https://drdo.gov.in/drdo/sites/default/files/form_formats/AirworthinessDirective11.pdf
 54. SECTION : 4 (b) (iv) Norms set for the discharge of functions - dgaqa, accessed on May 4, 2026, <https://dgaeroga.gov.in/images/pdf/rti/chapter-4.pdf>
 55. DESIGN, DEVELOPMENT AND PRODUCTION OF MILITARY AIR SYSTEMS AND AIRBORNE STORES, accessed on May 4, 2026,
https://www.aemc-india.in/?smd_process_download=1&download_id=3071
 56. How to Apply -...: iDEX - Innovation for Defence Excellence :..., accessed on May 4, 2026, https://idex.gov.in/how_to_apply
 57. iDEX Open Challenge Proposal Template | PDF - Scribd, accessed on May 4, 2026,
<https://www.scribd.com/document/959989379/ab9c40fa18286f5688a6acbd0ce08e38ef9fc3bf>
 58. New HAL Aero Engine Design And Test Facility To Propel Development Of Strategic Engines For Aircraft And Drones - Swarajya, accessed on May 4, 2026,
<https://swarajyamag.com/defence/new-hal-aero-engine-design-and-test-facility-to-propel-development-of-strategic-engines-for-aircraft-and-drones>
 59. A Novel Digital Twin Framework for Aeroengine Performance Diagnosis - MDPI, accessed on May 4, 2026, <https://www.mdpi.com/2226-4310/10/9/789>
 60. An Integrated Approach to Conversion, Verification, Validation and Integrity of

- AFRL Generic Engine Model and Simulation (Postpr - DTIC, accessed on May 4, 2026, <https://apps.dtic.mil/sti/tr/pdf/ADA466221.pdf>
61. Gas Turbine Performance Digital Twin for Real-Time Embedded Systems - ResearchGate, accessed on May 4, 2026, https://www.researchgate.net/publication/344513589_Gas_Turbine_Performance_Digital_Twin_for_Real-Time_Embedded_Systems
 62. Project Proposal Format, accessed on May 4, 2026, <https://drishti.cmti.res.in/downloads/proposalformat.doc>
 63. Digital Twin in Aerospace Industry: A Gentle Introduction - CERES Research Repository, accessed on May 4, 2026, <https://dspace.lib.cranfield.ac.uk/server/api/core/bitstreams/c21397ce-42cf-4e6e-9608-2002f71d2080/content>
 64. Guidance Notes on Verification and Validation of Models, Simulations, and Digital Twins - American Bureau of Shipping (ABS), accessed on May 4, 2026, https://ww2.eagle.org/content/dam/eagle/rules-and-guides/current/design_and_analysis/348-guidance-notes-on-verification-and-validation-of-models,-simulations,-and-digital-twins-2024/348-vandv-gn-nov24.pdf
 65. Defence India Startup Challenge - IDEX, accessed on May 4, 2026, <https://idex.gov.in/challenges>
 66. Digital Twin Technology - GE Vernova, accessed on May 4, 2026, <https://www.gevernova.com/software/innovation/digital-twin-technology>
 67. aircraft fighter - Hindustan Aeronautics Limited, accessed on May 4, 2026, https://hal-india.co.in/backend/wp-content/uploads/2024/02/HAL_CO_Broucher-Full.pdf
 68. Digital Twin Frameworks for Oil and Gas Processing Plants: A Comprehensive Literature Review - MDPI, accessed on May 4, 2026, <https://www.mdpi.com/2227-9717/13/11/3488>
 69. Digital Twin in Aerospace Industry: A Gentle Introduction - White Rose Research Online, accessed on May 4, 2026, https://eprints.whiterose.ac.uk/id/eprint/226986/1/Digital_Twin_in_Aerospace_Industry_A_Gentle_Introduction.pdf