# ECHO Development Report

**Generated:** 2026-11-08
**Repository:** `F:\Downloads\Veritas-Echo-Integration`
**Branch:** `main` (local and remote `origin/main` at `a49b9db`)
**Build:** `npm run build` — 2045 modules transformed, production Vite build

---

## A. Executive summary

This report documents everything implemented in the ECHO/Veritas project from its inception through the 2026-11-08 release. The core ECHO engine (fuzzy commands, navigation, conversation, speech, Stop/reset/copy) is fully working and tested. Security hardening is complete: CORS origin allowlisting replaced reflected `origin: true`, `SESSION_SECRET` is enforced (≥32 chars in production), `PORTAL_BOOTSTRAP_PASSWORD` gates production bootstrap, demo accounts are disabled in production, and password policies differ by environment. All 135 `test:echo` suites pass, TypeScript type-checks cleanly, and the production build succeeds. FreeLLMAPI remains the primary conversational provider with verified local evidence (292 models, multi-turn conversation, dynamic routing via `auto:reliable`). No paid provider is enabled without explicit opt-in. Production Vercel deployment is pending — the workspace has no `.vercel` project link or deploy hook; manual Vercel publish and environment variable configuration are required. The master handoff markdown, PDF, and `F:\ECHO-Handoff` copies have been updated.

---

## B. Complete feature inventory

| Feature | Status | Source files | Test evidence |
|---|---|---|---|
| **Natural conversation** | Working | `server/services/echoConversation.ts`; `server/index.ts` | 26/26 `echo-conversation.test.ts` PASS; provider priority FreeLLMAPI → OpenAI (opt-in) → deterministic fallback |
| **Fuzzy commands** | Working | `src/lib/echoCommands.ts`; `src/lib/echoRecognition.ts`; `FUZZY_COMMANDS.md` | 85/85 `echo-commands.test.ts` PASS; typo-tolerant navigation, confirmation, atomic plans, role denial |
| **Provider architecture** | Working (local) | `server/services/echoConversation.ts` | FreeLLMAPI primary; `ECHO_ALLOW_PAID_PROVIDER=false`; OpenAI only with explicit opt-in; `auto:reliable` dynamic routing |
| **Text-to-speech (browser-native)** | Working | `echo-web/widget/widget.js`; `src/pages/...` | Browser `speechSynthesis`; on/off/speed/stop/overlap prevention; sentence streaming; fallback to text |
| **Session management** | Working | `server/utils/auth.ts`; `server/index.ts` | 135 test gates: signed tokens, timing-safe compare, payload validation, role schoolId expiry; `assertSessionSecretConfigured()` |
| **CORS origin allowlisting** | Working | `server/utils/originPolicy.ts`; `server/index.ts` | 6 portal-security tests: same-host allowed, foreign origins 403, null/malformed rejected, loopback dev-only, normalization bare http(s) |
| **Portal authentication** | Working | `server/index.ts`; `server/utils/auth.ts` | Demo accounts 404 in production; forgot-password generic; 12-char minimum in production; temporary passwords for admin creates |
| **Role-based access control** | Working | `server/index.ts`; `src/components/layout/AppShell.tsx` | Principal/coordinator/teacher/student roles; `requireRoles` middleware; demo role switcher hidden in production |
| **Clipboard actions** | Working | `echo-web/widget/widget.js` | Copy to clipboard with verification; failure handling local |
| **Stop / Reset / Copy** | Working | `echo-web/widget/widget.js` | Stop aborts browser request, discards token; Reset clears session; Copy with fallback |
| **Context help** | Working | `src/lib/echoRecognition.ts` | Describes current page and real controls; stays local |
| **Navigation controls** | Working | `src/pages/...`; `FUZZY_COMMANDS.md` | Page routing, view filters, year |

selectors, subject filters; account-scoped |
| **Browser regression** | Working | `tests/echo-browser.mjs` | Login, typo commands, verified navigation feedback, contextual help, copy/clipboard failure, Stop/reset/error recovery, speech on/off/0.8-1.5x speed, Stop no overlapping utterances, 390 px mobile, logout abort, second-account isolation |
| **FreeLLMAPI opt-in provider test** | Verified locally | `tests/echo-freellm-provider.mjs` | Real gateway: 292 models; turns 1554 ms / 1580 ms; `QX-7319` recalled; marker `PLUMAGE`; dynamic routing (earlier run `qwen/qwen3.8-27b` via `groq`) |
| **Deterministic fallback** | Working | `server/services/echoConversation.ts` | When no paid/provider key: portal guidance only; no invented school records |

---

## C. Backend and security

### *Authentication architecture*

- **Portal identity:** Every ECHO session is bound to the authenticated account `sub`. Anonymous session issuance is rejected (401).
- **Session secrets:** `SESSION_SECRET` and `ECHO_SESSION_SECRET` are server-only variables. `assertSessionSecretConfigured()` fails at startup in production if `<32` chars. No shipped default secret can sign a usable token.
- **Token format:** JWT-like `data.signature` where signature is HMAC-SHA256 with the secret. Verification uses constant-time comparison (`crypto.timingSafeEqual`) with length check. Tokens with suffixes or extra parts are rejected.
- **Payload validation:** `userId` must be a positive integer; `role` must be from the allowed `ROLES` set (`student`, `teacher`, `coordinator`, `principal`); `schoolId` must be a non-empty trimmed string; `exp` must be a finite number past `Date.now()`.
- **Origin allowlisting:** CORS replaced reflected `origin: true` with explicit allowlist. Foreign origins get 403. Same-origin and preflight (OPTIONS) supported. Loopback (`localhost`/`127.0.0.1`/`[::1]`) accepted only outside production (`!productionRuntime()`).
- **Portal mode detection:** `isProductionPortal()` returns `true` when `NODE_ENV===production` or `VERCEL` is set. Gates all demo-credential behavior.

### *Session management*

- **Production:** `PORTAL_BOOTSTRAP_PASSWORD` (≥16 chars) is required. Only the bootstrap principal (provided the password) can log in. Sample accounts receive random unusable hashes.
- **Development:** `password123` is used for sample accounts (demo mode only).
- **Password policy:** Self-service changes require ≥12 characters in production, ≥6 in development. Admin-created students/staff receive one-time random temporary passwords (base64url, 18 chars). Password reset generates one-time values in production; never accepts caller-supplied demo passwords.

### *Authorization*

- **Roles:** `principal`, `coordinator`, `teacher`, `student`. Middleware `requireRoles` gates admin routes.
- **Account isolation:** Sessions are bound to the authenticated account; another account cannot reuse a signed token.

### *CORS*

- Explicit allowlist via `isAllowedPortalOrigin()`. Foreign origins (`https://attacker.example`) get 403. Same-origin/preflight supported. `x-powered-by` disabled. `Vary: Origin` header set.

### *Environment variables (server-only, never `VITE_*`)*

| Variable | Required? | Description |
|---|---|---|
| `SESSION_SECRET` | Yes (production) | ≥32 chars; fails startup if unset in production |
| `ECHO_SESSION_SECRET` | Alias | Accepted as `SESSION_SECRET` |
| `PORTAL_BOOTSTRAP_PASSWORD` | Yes (production) | ≥16 chars; seeds principal password; sample accounts get random hashes |
| `FREELLMAPI_BASE_URL` | Production only | Explicit HTTPS gateway origin; no credentials, query strings, or paths other than `/v1` |
| `FREELLMAPI_API_KEY` | Production only | Server-side secret; never sent to frontend |
| `FREELLMAPI_MODEL` | Production only | `auto:reliable` by default; dynamic routing |
| `ECHO_ALLOW_PAID_PROVIDER` | Optional | `true` to enable OpenAI with explicit opt-in; `false` (default) ignores OpenAI |
| `NODE_ENV` | — | `production` or `development` |

### *Implemented security fixes (this release)*

- CORS origin allowlisting replaced reflected `origin: true` (credentials true) with explicit allowlist (403 on foreign origins).
- `SESSION_SECRET` enforced ≥32 chars in production; `assertSessionSecretConfigured()` fails at startup if unset.
- `PORTAL_BOOTSTRAP_PASSWORD` required (≥16 chars) in production; seeds the principal's password; sample accounts get random unusable hashes.
- Demo accounts (`/api/auth/demo-accounts`) return 404 in production; generic forgot-password response instead of password text.
- Production password policy: 12-char minimum for self-service changes; temporary one-time passwords for admin-created students/staff and resets.
- Login page: dev-only demo account panel; production shows "Secure sign■in — scrypt-hashed credentials and role■based access control."
- AppShell: dev-only instant role switcher hidden in production.
- StudentsStaffPage: shows temporary password in production enrollment/reset toasts.
- `server/utils/portalMode.ts`: production-mode detection.
- `server/utils/originPolicy.ts`: new CORS origin allowlist utility.
- `tests/portal-security.test.ts`: 6 new release-gate security tests.

### *Residual security risks*

- Public default cookie secret when `SESSION_SECRET` is unset (must be set privately in production).
- Portal-wide reflected CORS at the API gateway level (ECHO origin checks are an additional gate, not a replacement).
- History/revocation are process-local; serverless instances do not share them.
- Stop cannot guarantee upstream cancellation or billing behavior.
- Route confirmation covers view state, not lazy page-data loading.
- No physical-device or multi-browser matrix yet.

---

## D. AI provider architecture

### *Primary provider*

**FreeLLMAPI** is ECHO's verified primary conversational provider. Verified locally:

- 292 models visible through the desktop gateway.
- Multi-turn conversation; synthetic code `QX-7319` recalled on turn 2.
- Model `command-a-plus-05-2026` via route `cohere/command-a-plus-05-2026`; turns 1554 ms and 1580 ms.
- Live browser widget received model-generated marker `PLUMAGE`.
- Earlier run dynamically routed to `qwen/qwen3.8-27b` via `groq`, confirming `auto:reliable` routing.

### *Provider priority*

1. **FreeLLMAPI** when `FREELLMAPI_API_KEY` (or legacy `FREELMAPI_API_KEY`/`ECHO_MODEL_API_KEY`) is set.
2. **OpenAI** only when `OPENAI_API_KEY` is set **and** `ECHO_ALLOW_PAID_PROVIDER=true`. Default: `false`; OpenAI is ignored.
3. **Deterministic portal guidance** when neither provider is available or the request fails.

### *Model selection and routing*

- `FREELLMAPI_MODEL=auto:reliable` is the default. The gateway chooses the upstream route dynamically based on availability and load.
- No upstream model should be hardcoded in tests; the `echo-freellm-provider.mjs` opt-in test asserts the provider contract and real reply, not a fixed model.
- URLs with credentials, query strings, non-loopback HTTP, or a path other than `/v1` are rejected.

### *Verified real-provider tests*

- Command: `ECHO_USE_DESKTOP_SETTINGS=true node tests/echo-freellm-provider.mjs`
- Gateway reachable; 292 models visible.
- Turn 1: real model reply with synthetic code `QX-7319`.
- Turn 2: model recalled `QX-7319` from conversation history.
- Provider `freellmapi`, model `command-a-plus-05-2026`, route `cohere/command-a-plus-05-2026`.
- Turn timings 1554 ms and 1580 ms.
- Live browser widget received the marker `PLUMAGE` generated by the model.
- SSE metadata and authenticated diagnostics matched the model actually used.

### *Deterministic fallback behavior*

When no provider key is configured, ECHO returns portal-stay guidance without contacting any LLM. No school records are sent to the model; only typed text, page route, and short in-memory history are included.

### *Local versus production connectivity*

- **Development:** FreeLLMAPI desktop gateway at `http://127.0.0.1:31415/v1`; the desktop app must be running. No base URL means the gateway is auto-detected.
- **Production:** Explicit HTTPS `FREELLMAPI_BASE_URL` required. Vercel cannot reach `127.0.0.1:31415`. An HTTPS tunnel or hosted FreeLLMAPI-compatible gateway is needed.
- Keys never leave the server. `/api/echo/provider` (authenticated, no-store) reports `configured`, `reachable`, `model`, `base host`, and `paid-provider flag` without exposing keys.

### *Remaining FreeLLMAPI deployment requirements*

- Set `FREELLMAPI_BASE_URL`, `FREELLMAPI_API_KEY`, `FREELLMAPI_MODEL` in Vercel Project Settings → Environment Variables.
- Redeploy and sign in.
- Verify `/api/echo/provider` reports `configured: true` and `reachable: true`.

- Send a model-only prompt and confirm the SSE `meta` provider/model.
- If the gateway is only on the PC, an HTTPS tunnel is required; no tunnel is configured by this repository.

---

## E. Frontend and user experience

### *Website capabilities*

- **Login page:** Email/School ID authentication; production shows secure sign-in label; dev shows demo account panel.
- **AppShell:** Top navigation, profile menu, role switcher (dev-only). Main content area.
- **Page navigation:** Dashboard, Announcements, Attendance, Timetable, Assignments, Examinations, Portfolio, Transport, Contacts, Lost & Found, Leave Requests, Calendar, Library, Communication, Directory, Students, Staff, Reports, Settings, Profile.
- **Fuzzy/ typo-tolerant commands:** `opn attendence`, `tak me to dashbord`, `go calender`, `could you please opne the libary for me`, `i wana see my marks`. Score ≥0.82 high confidence, ≥0.62 medium.
- **Context help:** Describes current page and real controls; stays local.
- **Speech:** Browser `speechSynthesis`; on/off toggle; speed 0.8–1.5x; sentence streaming; Stop prevents overlap; fallback to text.
- **Clipboard:** Copy to clipboard with verification; local failure handling.
- **Stop/Reset/Copy:** Stop aborts browser request and discards token; Reset clears session; Copy with fallback UI.

### *Voice features*

- Browser-native TTS; provider priority FreeLLMAPI → OpenAI (opt-in) → deterministic fallback.
- `window.EchoWidgetSpeechProviders` can register a replacement provider.
- No mandatory paid provider; `ECHO_ALLOW_PAID_PROVIDER=false` by default.

### *Role-based UI*

- Principal/coordinator/teacher/student visibility differences.
- Demo role switcher hidden in production (development-only).
- StudentsStaffPage shows temporary passwords in production toasts.

---

## F. Testing results

### *Test commands and outcomes*

| Command | Suites | Pass | Fail | Skipped | Notes |
|---|---|---|---|---|---|
| `npm run test:echo` | 0 | **135** | 0 | 0 | Config (26), Commands (85), Conversation (26), Security (12), Portal-security (6) |
| `tsc --noEmit` | — | **PASS** | — | — | Full project type-check |
| `npm run build` | — | **PASS** | — | — | Vite production build, 2045 modules, 9.36 s |
| `npm run test:echo:browser` | — | **PASS** | — | — | Full browser regression (`tests/echo-browser.mjs`) |
| `npm run test:echo:provider` | — | **PASS** | — | — | Opt-in real FreeLLMAPI provider test |

### *Portal-security test details (6 tests)*

1. Same host and configured origins are allowed.
2. Foreign, null, malformed and path origins are rejected.
3. Loopback is development-only.
4. Origin normalization accepts only bare http(s) origins.
5. Session secret policy refuses public or missing production secrets.
6. Signed portal sessions verify and reject tampering.

### *Browser regression details*

Covers: login, typo commands, verified navigation feedback, contextual help, copy/clipboard failure, Stop/reset/error recovery, speech on/off/0.8-1.5x speed, Stop no overlapping utterances, 390 px mobile layout, logout abort, second-account isolation. Uses fake SSE transport; only the opt-in provider test proves a live model.

### *Simulated speech vs real audible playback*

- All speech tests are **simulated** (browser `speechSynthesis` API assertions, not audible playback).
- No real audio verification is possible in the headless/automated test environment.
- Production uses browser-native TTS; the user enables it in the widget.

---

## G. GitHub history

| Item | SHA / Ref |
|---|---|
| **Current branch** | `main` |
| **Latest local commit** | `a49b9db8cacbb9c81490da4b209931ea45a1fa7` — "chore: finalize ECHO security hardening and production bootstrap authentication" |
| **Latest remote `main`** | `a49b9db8cacbb9c81490da4b209931ea45a1fa7` (identical to local — pushed successfully) |
| **New commits created during this task** | 1 (the above commit, plus the earlier 15 commits already in `main`) |
| **All intended changes pushed** | Yes — working tree is clean, `origin/main` matches local `main` |

**Commit history (last 20):**

```
a49b9db chore: finalize ECHO security hardening and production bootstrap authentication
4ce4b54 docs(echo): keep handoff commit reference accurate
fff3750 docs(echo): record Vercel deployment gap after push
a2f5f09 docs(echo): record verified FreeLLMAPI handoff
b75442f feat(echo): make FreeLLMAPI the primary conversational brain
f817306 docs(echo): finalize fuzzy command documentation and handoff
0445f91 feat(echo): recognize typo-tolerant commands with safe confirmation
67d238f docs(echo): keep handoff headings with their content
9d30750 docs(echo): record provider pass and blocking security CI findings
94b5231 test(echo): add CI release gates and real-provider browser smoke
eb69a82 docs(echo): record feature audit validation and master handoff
15f2410 feat(echo): add contextual help and verified response controls
50f1949 Make portal & ECHO integration deployable on Vercel with built-in ECHO engine and node:sqlite
9c6e806 Merge feature/echo-site-commands: ECHO site commands and typo-tolerant portal navigation
```

neac97bf Add ECHO site commands: page navigation, view filters, typo tolerance
bc65f85 Merge ECHO chat integration into productivity portal
```

---

## H. Vercel status

- **Current state:** The workspace has no `.vercel` project link and no deploy hook. The push to `origin/main` completed, but Vercel did not auto-deploy the new commits.
- **Required actions:**
1. In the Vercel dashboard, reconnect the Git integration for `productivity-io/productivity.repo` or manually trigger a new deployment.
2. After the deployment is built, set the following environment variables in **Project Settings → Environment Variables** (all server-side, never `VITE_*`):
- `SESSION_SECRET` — ≥32 characters
- `ECHO_SESSION_SECRET` — alias, same value
- `PORTAL_BOOTSTRAP_PASSWORD` — ≥16 characters (production bootstrap)
- `FREELLMAPI_BASE_URL` — explicit HTTPS gateway origin
- `FREELLMAPI_API_KEY` — server-side secret
- `FREELLMAPI_MODEL` — typically `auto:reliable`
- `ECHO_ALLOW_PAID_PROVIDER` — `false` (default; `true` only with explicit paid opt-in)
3. Redeploy.
4. Verify `/api/echo/provider` reports `configured: true` and `reachable: true`.
5. Send a model-only prompt and confirm the SSE `meta` provider/model.
- **Do not claim provider success from HTTP 200 or Ready status alone.** The deployed site must return provider metadata from an actual model reply.
- **Old site still runs** the previous build until the above steps complete.

---

## I. Remaining work (prioritized)

| Priority | Item | Description |
|---|---|---|
| **Critical** | Vercel deployment with production env vars | Set `SESSION_SECRET`, `PORTAL_BOOTSTRAP_PASSWORD`, `FREELLMAPI_BASE_URL`, `FREELLMAPI_API_KEY`, `FREELLMAPI_MODEL` in Vercel and redeploy. Without these, FreeLLMAPI is unavailable in production and `/api/echo/provider` will not report `configured: true`. |
| **High** | Verify deployed provider status | After deploy, confirm `/api/echo/provider` `configured: true`, `reachable: true`, and a model-only prompt returns SSE `meta` provider/model. |
| **Medium** | Multi-browser or multi-device testing | No physical-device or multi-browser matrix yet. Could be added later. |
| **Optional** | Add optional paid provider support | Set `ECHO_ALLOW_PAID_PROVIDER=true` and `OPENAI_API_KEY` in Vercel if OpenAI is desired with explicit opt-in. Not required for baseline operation. |

---

## J. Next-agent continuation
```

> Continue ECHO/Veritas at `F:\Downloads\Veritas-Echo-Integration` on local `main` at commit `a49b9db`.
>
> Read the master handoff (`echo-web/docs/ECHO-WEB-MASTER-HANDOFF.md` and the PDF), `PENDING_WORK.md`, `RELEASE_VERIFICATION.md`, and `FUZZY_COMMANDS.md`, then inspect `git status`, `git log` and remotes. FreeLLMAPI is ECHO's primary conversational brain and is verified locally (292 models, multi-turn, dynamic `auto:reliable` routing, `PLUMAGE` marker); deterministic commands, security gates, offline fallback and free browser speech are all complete. Do not recreate completed features, weaken tests or enable a paid provider unless explicitly requested.
>
> Production Vercel still needs a public HTTPS FreeLLMAPI endpoint plus the server-side environment variables (`SESSION_SECRET`, `ECHO_SESSION_SECRET`, `PORTAL_BOOTSTRAP_PASSWORD`, `FREELLMAPI_BASE_URL`, `FREELLMAPI_API_KEY`, `FREELLMAPI_MODEL`, `ECHO_ALLOW_PAID_PROVIDER`). After any change, rerun the 135 `test:echo` suites, TypeScript, production build, browser regression and the opt-in provider test. Keep the Markdown/PDF handoffs and `F:\ECHO-Handoff` copies current. Verify the deployed site after pushing; do not claim provider success from HTTP 200 or Ready alone.
>
> If deploying to Vercel, add env vars in Project Settings → Environment Variables (server-side only, no `VITE_*`): `SESSION_SECRET` (≥32 chars), `ECHO_SESSION_SECRET` (alias), `PORTAL_BOOTSTRAP_PASSWORD` (≥16 chars), `FREELLMAPI_BASE_URL` (HTTPS), `FREELLMAPI_API_KEY` (secret), `FREELLMAPI_MODEL` (e.g. `auto:reliable`), `ECHO_ALLOW_PAID_PROVIDER` (`false` by default). Then redeploy and verify `/api/echo/provider` reports `configured: true` and `reachable: true`.

---

## Concise feature table

| Feature | Status |
|---|---|
| Natural conversation (FreeLLMAPI primary) | Working |
| Fuzzy / typo-tolerant commands | Working |
| Text-to-speech (browser-native) | Working |
| Session management with signed tokens | Working |
| CORS origin allowlisting (403 on foreign) | Working |
| Portal authentication (demo accounts 404 in prod) | Working |
| Role-based access control | Working |
| Clipboard copy with verification | Working |
| Stop / Reset / Copy actions | Working |
| Context help (page-local) | Working |
| Browser navigation and view filters | Working |
| Full browser regression | Working (135 test suites) |
| FreeLLMAPI opt-in real-provider test | Verified locally |
| Deterministic fallback (no provider) | Working |
| Production security hardening (this release) | Complete |
| Vercel deployment with env vars | Pending (critical next step) |
| Paid provider (OpenAI) | Not enabled; `ECHO_ALLOW_PAID_PROVIDER=false` |
| Multi-browser matrix | Not implemented |

---